

[]: X = my_data[['Age', 'Sex', 'BP', 'Cholesterol', 'Na_to_K']].values
x[0:5]

As you may figure out, some features in this dataset are categorical such as **Sex** or **BP**. Unfortunately, Sklearn Decision Trees do not handle categorical variables. But still we can convert these features to numerical values. **pandas.get_dummies()** Convert categorical variable into dummy/indicator variables.

```
[]: from_sklearn_import_preprocessing
le_sex = preprocessing_LabelEncoder()
le_sex_fit(['F', M'])
X[:,1] = le_sex_transform(X[:,1]).

le_BP = preprocessing_LabelEncoder()
le_BP.fit([,',0M', _',NORMAL', _',HISH'])
X[:,2] = le_BP.transform(X[:,2])

le_Chol = preprocessing_LabelEncoder()
le_chol.fit([,',NORMAL', _',HISH'])
X[:,3] = le_Chol.transform(X[:,3])
X[0:5]
```

Now we can fill the target variable.

[]: y = my_data["Drug"] y[0:5]

Setting up the Decision Tree

We will be using train/test split on our decision tree. Let's import train_test_split from sklearn.cross_validation.

[]: from sklearn.model_selection import train_test_split

Now train_test_split will return 4 different parameters. We will name them:

X_trainset, X_testset, y_trainset, y_testset

The train_test_split will need the parameters:

X, y, test_size=0.3, and random_state=3.

The X and y are the arrays required before the split, the test_size represents the ratio of the testing dataset, and the random_state ensures that we obtain the same splits.

[]: X_trainset, X_testset, y_trainset, y_testset = train_test_split(X, y, test_size=0.3, random_state=3)

Practice

Print the shape of X_trainset and y_trainset. Ensure that the dimensions match

Did you know? IBM Watson Studio lets you build and deploy an Al solution, using the best of open source and IBM software and giving your team a single environment to work in. Learn more here.

[]: # your code

▼ Click here for the solution

print('Shape of X training set {}'.format(X_trainset.shape),'&',' Size of Y training set {}'.format(y_trainset.shape))

Print the shape of X_testset and y_testset. Ensure that the dimensions match

[]: # your code

▼ Click here for the solution

 $print('Shape \ of \ X \ training \ set \ \{\}'.format(X_testset.shape), '\&',' \ Size \ of \ Y \ training \ set \ \{\}'.format(y_testset.shape))$

Modeling

We will first create an instance of the DecisionTreeClassifier called drugTree.

Inside of the classifier, specify criterion="entropy" so we can see the information gain of each node.

[]: drugTree = DecisionTreeClassifier(criterion="entropy", max_depth = 4)
drugTree # it shows the default parameters

 $Next, we will fit the data with the training feature matrix X_trainset and training response vector y_trainset and y_trainset y_t$

[]: drugTree.fit(X_trainset,y_trainset)

Prediction

Let's make some predictions on the testing dataset and store it into a variable called pred Tree .

[]: predTree = drugTree.predict(X_testset)

You can print out predTree and y_testset if you want to visually compare the prediction to the actual values

[]: print (predTree [0:5]) print (y testset [0:5])

Evaluation

Next, let's import metrics from sklearn and check the accuracy of our model.

]: from sklearn import metrics
import matplotlib.pyplot as plt

print("DecisionTrees's Accuracy: ", metrics.accuracy_score(y_testset, predTree))

Accuracy classification score computes subset accuracy: the set of labels predicted for a sample must exactly match the corresponding set of labels in y_true.

In multilabel classification, the function returns the subset accuracy. If the entire set of predicted labels for a sample strictly match with the true set of labels, then the subset accuracy is 1.0; otherwise it is 0.0.

Visualization

Lets visualize the tree

[]: # Notice: You might need to uncomment and install the pydotplus and graphviz libraries if you have not installed these before #!conda install -c conda-forge pydotplus -y
#!conda install -c conda-forge python-graphviz -y

[]: from ic import StringIO import pydotplus import matplotlib image as mpimg from sklearn import tree %matplotlib inline

[]: dot_data = StringIO()
filename = "drugtree.png"
featureNames = my_data.columns[0:5]
targetNames = my_data["Drug"].unique().tolist()
out_tree.export_graphvsZ(drugTree_feature_names_featureNames__out_file=dot_data__class_names=_np_unique(y_trainset)__filled=True___special_characters=True_rotate=False)_
graph = pydotplus.graph_from_dot_data(dot_data.getvalue())___
graph.write_png(filename)
img = mpimg.imread(filename)
plt.figure(figiszie=(100, 200))
plt.imshow(img_interpolation='nearest')

Want to learn more?

IBM SPSS Modeler is a comprehensive analytics platform that has many machine learning algorithms. It has been designed to bring predictive intelligence to decisions made by individuals, by groups, by systems – by your enterprise as a whole. A free trial is available through this course, available here: SPSS Modeler

Also, you can use Watson Studio to run these notebooks faster with bigger datasets. Watson Studio is IBM's leading cloud solution for data scientists, built by data scientists. With Jupyter notebooks, RStudio, Apache Spark and popular libraries pre-packaged in the cloud, Watson Studio enables data scientists to collaborate on their projects without having to install anything. Join the fast-growing community of Watson Studio users today with a free account at Watson Studio

Thank you for completing this lab!

Author

Saeed Aghabozorgi

Other Contributors

Joseph Santarcangelo

Change Log

Date (YYYY-MM-DD)	Version	Changed By	Change Description
2020-11-20	2.2	Lakshmi	Changed import statement of StringIO
2020-11-03	2.1	Lakshmi	Changed URL of the csv
2020-08-27	2.0	Lavanya	Moved lab to course repo in GitLab

© IBM Corporation 2020. All rights reserved.