



+ Code + Text Copy to Drive

Connect Editing

```
##@title Licensed under the Apache License, Version 2.0 (the "License");  
## you may not use this file except in compliance with the License.  
## You may obtain a copy of the License at  
##  
## https://www.apache.org/licenses/LICENSE-2.0  
##  
## Unless required by applicable law or agreed to in writing, software  
## distributed under the license is distributed on an "AS IS" BASIS,  
## WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.  
## See the License for the specific language governing permissions and  
## limitations under the License.
```

Licensed under the Apache License, Version 2.0 (the "License");

## Multiple Layer GRU

```
[ ] from __future__ import absolute_import, division, print_function, unicode_literals
```

```
import tensorflow_datasets as tfds  
import tensorflow as tf  
print(tf.__version__)
```

```
[ ] import tensorflow_datasets as tfds  
import tensorflow as tf  
print(tf.__version__)
```

```
[ ] # Get the data  
dataset, info = tfds.load('imdb_reviews/subwords8k', with_info=True, as_supervised=True)  
train_dataset, test_dataset = dataset['train'], dataset['test']
```

```
[ ] tokenizer = info.features['text'].encoder
```

```
[ ] BUFFER_SIZE = 10000  
BATCH_SIZE = 64  
  
train_dataset = train_dataset.shuffle(BUFFER_SIZE)  
train_dataset = train_dataset.padded_batch(BATCH_SIZE, train_dataset.output_shapes)  
test_dataset = test_dataset.padded_batch(BATCH_SIZE, test_dataset.output_shapes)
```

```
[ ] model = tf.keras.Sequential([  
    tf.keras.layers.Embedding(tokenizer.vocab_size, 64),  
    tf.keras.layers.Conv1D(128, 5, activation='relu'),  
    tf.keras.layers.GlobalAveragePooling1D(),  
    tf.keras.layers.Dense(64, activation='relu'),  
    tf.keras.layers.Dense(1, activation='sigmoid')  
])
```

```
[ ] model.summary()
```

```
[ ] model.compile(loss='binary_crossentropy', optimizer='adam', metrics=['accuracy'])
```

```
[ ] NUM_EPOCHS = 10  
history = model.fit(train_dataset, epochs=NUM_EPOCHS, validation_data=test_dataset)
```

```
[ ] import matplotlib.pyplot as plt
```

```
def plot_graphs(history, string):  
    plt.plot(history.history[string])  
    plt.plot(history.history['val_'+string])  
    plt.xlabel("Epochs")  
    plt.ylabel(string)  
    plt.legend([string, 'val_'+string])  
    plt.show()
```

```
[ ] plot_graphs(history, 'accuracy')
```

```
[ ] plot_graphs(history, 'loss')
```

