



20.8. Instances as Return Values

Functions and methods can return objects. This is actually nothing new since everything in Python is an object and we have been returning values for quite some time. (You can also have lists or tuples of object instances, etc.) The difference here is that we want to have the method create an object using the constructor and then return it as the value of the method.

Suppose you have a point object and wish to find the midpoint halfway between it and some other target point. We would like to write a method, let's call it `halfway`, which takes another `Point` as a parameter and returns the `Point` that is halfway between the point and the target point it accepts as input.

Save & Run

Original - 1 of 1

Show in CodeLens

```
1 class Point:
2
3     def __init__(self, initX, initY):
4
5         self.x = initX
6         self.y = initY
7
8     def getX(self):
9         return self.x
10
11    def getY(self):
12        return self.y
13
14    def distanceFromOrigin(self):
15        return ((self.x ** 2) + (self.y ** 2)) ** 0.5
```

```
x = 4.0, y = 8.0
4.0
8.0
```

Activity: 1 -- ActiveCode (chp13_classesmid1)

The resulting `Point`, `mid`, has an `x` value of 4 and a `y` value of 8. We can also use any other methods on `mid` since it is a `Point` object.

You have attempted 2 of 1 activities on this page

20.7. Converting an Object to a String">

20.9. Sorting Lists of Instances">

Converting an Object to a String">

✓ Completed, Well Done!

20.9. Sorting Lists of Instances">Next Section - 20.9. Sorting Lists of Instances