

File Edit View Run Kernel Git Tabs Settings Help

Launcher Lab1A.ipynb git Run as Pipeline R



**IBM Developer
SKILLS NETWORK**

Hands-on Lab: Lists and Data Frames in R

Table of Contents

- About the Dataset
- Lists
- Data frames

Estimated Time Needed: 15 min

About the Dataset

Imagine you got many movie recommendations from your friends and compiled all of the recommendations in a table, with specific info about each movie.

The table has one row for each movie and several columns

- name** - The name of the movie
- year** - The year the movie was released
- length_min** - The length of the movie in minutes
- genre** - The genre of the movie
- average_rating** - Average rating on Imdb
- cost_millions** - The movie's production cost in millions
- sequences** - The amount of sequences
- foreign** - Indicative of whether the movie is foreign (1) or domestic (0)
- age_restriction** - The age restriction for the movie

Part of the dataset can be seen below

name	year	length_min	genre	average_rating	cost_millions	foreign	age_restriction
Toy Story	1995	81	Animation	8.3	30	0	0
Akira	1998	125	Animation	8.1	10.4	1	14
The Breakfast Club	1985	97	Drama	7.9	1	0	14
The Artist	2011	100	Romance	8	15	1	12
Modern Times	1936	87	Comedy	8.6	1.5	0	10
Fight Club	1999	139	Drama	8.9	63	0	18
City of God	2002	130	Crime	8.7	3.3	1	18
The Untouchables	1987	119	Drama	7.9	25	0	14
Star Wars	1977	121	Action	8.7	11	0	10
American Beauty	1999	122	Drama	8.4	15	0	14
Room	2015	118	Drama	8.3	13	1	14
Dr. Strangelove	1964	94	Comedy	8.5	1.8	1	10
The Ring	1998	95	Horror	7.3	1.2	1	18
Monty Python and the Holy Grail	1975	91	Comedy	8.3	0.4	1	18
High School Musical	2006	98	Comedy	5.2	4.2	0	0
Shaun of the Dead	2004	99	Horror	8	6.1	1	18
Taxi Driver	1976	113	Crime	8.3	1.3	1	14
The Shawshank Redemption	1994	142	Crime	9.3	25	0	16
Interstellar	2014	169	Adventure	8.6	165	0	10
Casino	1995	178	Biography	8.2	50	0	18
The Goodfellas	1990	145	Biography	8.7	25	0	14
Blue is the Warmest Colour	2013	179	Romance	7.8	4.5	1	18
Black Swan	2010	108	Thriller	8	13	0	16
Back to the Future	1985	116	Sci-fi	8.5	19	0	0
The Wave	2008	107	Thriller	7.6	5.5	1	16
Whiplash	2014	106	Drama	8.5	3.3	1	12

The Grand Hotel Budapest	2014	100	Crime	8.1	25.5	0	14
Jumanji	1995	104	Fantasy	6.9	65	0	12
The Eternal Sunshine of the Spotless Mind	2004	108	Drama	8.3	20	0	14
Chicago	2002	113	Comedy	7.2	45	0	12

Lists

First of all, we're gonna take a look at lists in R. A list is a sequenced collection of different objects of R, like vectors, numbers, characters, other lists as well, and so on. You can consider a list as a container of correlated information, well structured and easy to read. A list accepts items of different types, but a vector (or a matrix, which is a multidimensional vector) doesn't. To create a list just type `list()` with your content inside the parenthesis and separated by commas. Let's try it!

```
[ ]: movie <- list("Toy Story", 1995, c("Animation", "Adventure", "Comedy"))
```

In the code above, the variable `movie` contains a list of 3 objects, which are a string, a numeric value, and a vector of strings. Easy, eh? Now let's print the content of the list. We just need to call its name.

```
[ ]: movie
```

A list has a sequence and each element of a list has a position in that sequence, which starts from 1. If you look at our previous example, you can see that each element has its position represented by double square brackets "`[[]]`".

Accessing items in a list

It is possible to retrieve only a part of a list using the **single _square** bracket operator `"[]"`. This operator can be also used to get a single element in a specific position. Take a look at the next example:

The index number 2 returns the second element of a list, if that element exists:

```
[ ]: movie[2]
```

Or you can select a part or interval of elements of a list. In our next example we are retrieving the 1st, 2nd, and 3rd elements:

```
[ ]: movie[1:3]
```

It looks a little confusing, but lists can also store names for its elements.

Named lists

The following list is a named list:

```
[ ]: movie <- list(name = "Toy Story",
                    year = 1995,
                    genre = c("Animation", "Adventure", "Comedy"))
```

Let me explain that: the list `movie` has some named objects within it. `name`, for example, is an object of type **character**, `year` is an object of type **number**, and `genre` is a vector with objects of type **character**.

Now take a look at this list. This time, it's full of information and well organized. It's clear what each element means. You can see that the elements have different types, and that's ok because it's a list.

```
[ ]: movie
```

You can also get separated information from the list. You can use `listName$selectorName * *`. The `* dollar - sign operator * **` will give you the block of data that is related to `selectorName`.

Let's get the genre part of our movies list, for example.

```
[ ]: movie$genre
```

Another way of selecting the genre column:

```
[ ]: movie["genre"]
```

You can also use numerical selectors like an array. Here we are selecting elements from 2 to 3.

```
[ ]: movie[2:3]
```

The function `class()` returns the type of a object. You can use that function to retrieve the type of specific elements of a list:

```
[ ]: class(movie$name)
      class(movie$foreign)
```

Adding, modifying, and removing items

Adding a new element is also very easy. The code below adds a new field named `age` and puts the numerical value 0 into it. In this case we use the double square brackets operator, because we are directly referencing a list member (and we want to change its content).

```
[ ]: movie[["age"]] <- 5
      movie
```

In order to modify, you just need to reference a list member that already exists, then change its content.

```
[ ]: movie[["age"]] <- 6
      # Now it's 6, not 5
      movie
```

And removing is also easy! You just put `NULL`, which means missing value/data, into it.

```
[ ]: movie[["age"]] <- NULL
      movie
```

Concatenating lists

Concatenation is the process of putting things together, in sequence. And yes, you can do it with lists. Just call the function `c()`. Take a look at the next example:

```
[ ]: # We split our previous list in two sublists
movie_part1 <- list(name = "Toy Story")
movie_part2 <- list(year = 1995, genre = c("Animation", "Adventure", "Comedy"))

# Now we call the function c() to put everything together again
movie_concatenated <- c(movie_part1, movie_part2)

# Check it out
movie_concatenated
```

Lists are really handy for organizing different types of elements in R, and also easy to use. Additionally, lists are also important since this type of data structure is essential to create data frames, our next covered topic.

Did you know? IBM Watson Studio lets you build and deploy an AI solution, using the best of open source and IBM software and giving your team a single environment to work in. [Learn more here](#).

Data Frames

Data frame is a structure that is used for storing data tables. Underneath it all, a data frame is a list of vectors of same length, exactly like a table (each vector is a column). We call a function called **data.frame()** to create a data frame and pass vector, which are our columns, as arguments. It is required to name the columns that will compose the data frame.

```
[ ]: movies <- data.frame(name = c("Toy Story", "Akira", "The Breakfast Club", "The Artist",
"Modern Times", "Fight Club", "City of God", "The Untouchables"),
year = c(1995, 1998, 1985, 2011, 1936, 1999, 2002, 1987),
stringsAsFactors=F)
```

Let's print its content of our recently created data frame:

```
[ ]: movies
```

It's very easy! You can note how it looks like a table.

We can also use the **"\$"** selector to get some type of information. This operator returns the content of a specific column of a data frame (that's why we have to choose a name for each column).

```
[ ]: movies$name
```

You retrieve data using numeric indexing, like in lists:

```
[ ]: # This returns the first (1st) column
movies[1]
```

The function called **str()** is one of most useful functions in R. With this function you can obtain textual information about an object. In this case, it delivers information about the objects whithin a data frame. Let's see what it returns:

```
[ ]: str(movies)
```

It shows this data frame has 8 observations, for 2 columns, so called **name** and **year**. The "name" column is a factor with 8 levels and "year" is a numerical column.

The **class()** function works for data frames as well. You can use it to determine the type of a column of a data frame.

```
[ ]: class(movies$year)
```

You can use numerical selectors to reach information inside the table.

```
[ ]: movies[1,2] #1-Toy Story, 2-1995
```

The **head()** function is very useful when you have a large table and you need to take a peek at the first elements. This function returns the first 6 values of a data frame (or event a list).

```
[ ]: head(movies)
```

Similar to the previous function, **tail()** returns the last 6 values of a data frame or list.

```
[ ]: tail(movies)
```

Now let's try to add a new column to our data frame with the length of each movie in minutes.

```
[ ]: movies['length'] <- c(81, 125, 97, 100, 87, 139, 130, 119)
movies
```

A new column was included into our data frame with just one line of code. We just needed to add a vector to data frame, then it will be our new column.

Now let's try to add a new movie to our data set.

```
[ ]: movies <- rbind(movies, c(name="Dr. Strangelove", year=1964, length=94))
movies
```

REMEMBER!!!! You can't add a list with more variables than the data frame, and vice-versa.

We don't need this movie anymore, let's delete it. Here we are deleting row 12

```
[ ]: movies <- movies[-12,]
movies
```

To delete a column you can just set it as **NULL**.

```
[ ]: movies[["length"]] <- NULL
movies
```

That is it! You learned a lot about data frames and how easy it is to work with them.

Authors

- Thiago Felipe Correa Borges

Changelog

Date (YYYY-MM-DD)	Version	Changed By	Change Description
2016	1.0	Thiago Felipe Correa Borges	Created initial version of the lab

Copyright © IBM Corporation 2016. All rights reserved.

Simple 0 2 R | Connecting Waiting... Mem: 2.45 / 6.00 GB

Mode: Command Ln 1, Col 1 English (American) Lab1A.ipynb