


Content of this lecture Administrative announcements Deadlock recovery Summary CS 323 - Operating Systems, Yuanyuan Zhou CS 323 - Operating Systems, Yuanyuan Zhou



Review Resource: preemptible or non-preemptible Deadlock avoidance Unsafe vs. safe state Banker algorithm Deadlock detection Wait graph CS 323 - Operating Systems, Yuanyuan Zhou

Recovery From Deadlock

OPTIONS:

- Kill deadlocked processes and release resources
- Kill one deadlocked process at a time and release its resources
- Rollback all or one of the processes to a checkpoint that occurred before they requested any resources

Note: with rollback, difficult to prevent indefinite postponement

-5

2/16/2003

CS 323 - Operating Systems, Yuanyuan Zhou

Deadlock Summary

- In general, deadlock detection or avoidance is expensive
- Must evaluate cost of deadlock against detection or avoidance costs
- Deadlock avoidance and recovery may cause indefinite postponement


CS 323 - Operating Systems 2/16/2003 Yuanyuan Zhou


Memory Management


- Storage Hierarchy
- Resident Monitor
- Fixed Partitions for Spooling and Multiprogramming
- Variable Sized Partitions
- Storage Placement Strategies
- Compaction


2/16/2003


CS 323 - Operating Systems, Yuanyuan Zhou












Fixed Partition Allocation Separate input queue for each partition Requires sorting the incoming jobs and putting them into separate queues Inefficient utilization of memory when the queue for a large partition is empty but the queue for a small partition is full. Small jobs have to wait to get into memory even though plenty of memory is free. One single input queue for all partitions. Allocate a partition where the job fits in. Best Fit Available Fit CS 323 - Operating Systems, Yuanyuan Zhou



Relocation • Correct starting address when a program should start in the Different jobs will run at different addresses When a program is linked, the linker must know at what address the program will begin in memory. Logical addresses, Virtual addresses Logical address space, range (0 to max) • Physical addresses, Physical address space range (R+0 to R+max) for base value R. • User program never sees the real physical addresses Memory-management unit (MMU) map virtual to physical addresses. relocation register Mapping requires hardware (MMU) with the base register CS 323 - Operating Systems, 2/16/2003 Yuanyuan Zhou

