NOTES:

 \overline{l}

RACK MARKS PERMISSIBLE ON I.D. SURFACE ONLY

- 2. REMOVE ALL BURRS
- 3. VINDICATES KEY FEATURES TO BE CHECKED AT INCOMING Q.C.

4


DIMENSION SHALL BE VERIFIED USING GO/NO-GO MANDRELS. PART SHALL BE CONSTRAINED TO A ROUND CONDITION DURING INSPECTION.

5. PASSIVATE PER QQ-P-35

<u></u>

DIRECTION OF GRAIN, O.D. ONLY.

- 7. FORM AND WELD ON A MANDREL.
- 8. WELD TO BE INSPECTED BY PENETRANT TECHNIQUE PER ASTM E-165.



	REV	REVISION DESCRIPTION	BY	DATE	ECO +
į	Α	INITIAL RELEASE, REPLACES 777096-177	JCW	0/24/01	BCT009695
	В	THICKNESS (.075) WAS .078 +/002; AND ADDED 14 GA. STOCK TO MATERIAL	AR	04/19/05	BCT014995

6-12-09 408

			trug, art t		
THESE DRAWINGS A AND SHALL NOT SALE OF APPAR	NO SPECIFICATIONS : BE REPRODUCED, CO NATUS WITHOUT WRITE	ARE THE PROPERTY OF BANGRO BCT IN PIED. OR USED FOR MANUFACTURE OR EX PERMISSION OF GANGRO BCT INC.	10811 Collins Avenue, Lahavood, Colorean 80215-4440 USA		
PER ANSI 1	AND SYMBOLOGY (14.5%-1982 SPECIFIED ARE	DIMENSIONS ARE IN INCHES UNLI DIMENSIONS SPECIFIED	GAMBRO, BCT		
.X1 ANGLES .XX1.O1 ± 5° .XXX1 SURF. FINISH		MATERIAL 316 STAINLESS STEEL 14 GA. STOCK	BAND, SS FILLER		
SIZE SCALE	DO THE SCALE OF SCALE	DELODEAU 11/03	PART NO. REV SHT / OF		