NOTES:

- 1 DIMENSIONS NOT SPECIFIED ON THE DRAWING ARE CONTAINED IN THE DATABASE FOR THIS PART NUMBER AND REVISION.
- 2 RAW CAST SURFACE FINISH TO BE 125 OR BETTER. CASTING TO BE FREE OF FLASH AND BURRS.

CAST SURFACE VISUAL SEVERITY LEVELS:

TYPE OF DEFECT		SIZE			
NEGATIVES		EVEL AA		EVEL A	
MAX LENGTH	• •	.020 .015		2E0.	
POSITIVES MAX LENGTH	• •	.010 .010		.025	
NONFILL		.010		.020	
MISMATCH, PARTING LINE MAX HEIGHT		.005		.010	

- WELD REPAIR: COSMETIC WELD RESTORATION IS PERMITTED IN ACCORDANCE WITH EITHER MIL-STD-2219 OR MIL-W-8604.
- 4 TOOLING CHANGES AFTER APPROVED FIRST ARTICLE INSPECTION REQUIRE APPROVAL FROM GAMBRO BCT.
- 5 V INDICATES KEY DIMENSION OR SURFACE(S) TO BE CHECKED BY INCOMING O.C..
- 6 SECONDARY SURFACE FINISH:


ALL EXTERIOR SURFACES (MARKED BY NOTE 7, 8 AND 91 TO BE POLISHED & ALUMINUM OXIDE GRIT BLASTED TO AN ACCEPTABLE (APPROVED BY GAMBRO BCT) FINISH FOR ELECTROPOLISHING.


A CAST SURFACE VISUAL SEVERITY LEVEL AA.


A CAST SURFACE VISUAL SEVERITY LEVEL A.

CAST SURFACE VISUAL SEVERITY LEVEL AA, EXCEPT NO PARTING LINES, WITNESS LINES, GRINDING MARKS OR NONUNIFORMITY IN THE SURFACE.












SECTION B-B

~	REV	REVISION DESCRIPTION	EY	DATE	ECO .
	A	INITIAL RELEASE, REPLACES 777096-452: 2X Ø .515/.505 WAS Ø .40: ADDED SECTION B-B	CH	12/8/91	5CT 003359
	6	CHANGED HORIZONTAL BORE DIAMETER FROM .505515 TO .501502 AND TO THRU BORE; VERTICAL BORE DIAMETER WAS .505515; DELETED DIM. 2X .50 AND 2X R.255 FROM SECTION B-B; REF DIM. 1.5021 WAS 1.5101 ON SECTION B-B; ADDED BOR ITEM 900; AND CHANGED COMPANY NAME ON NOTES 4 & B TO GAMBRO.	AR	1167 ₀₈	BCT01B198





CAD GENERATED DWG UG DWG



7-27-09 408

900	1	EΛ	7	77094-442	TEE	EE, CAST		
I TEM	OTY	U/M		PART NO.		DESCRIPTION		
_				BILL	\ OF	F REFERENCE		
PER D	THE CHARLES AND STELLIS AND THE CHARLES TO SHOW THE CHARLES THE CHARLES AND SHOULD SEE THE CHARLES STELLIS AND SHOULD SEE							
TO PROMETE AND STREET, DUTY PARK AND THE PROPERTY OF THE PROPE						- GAMRRO RCT		
.Za .Za	-1	[편발] #0 # #	utte	MIDNIAL 304 STAINLES	/	TEE,		
.xxxx .010 SEE NOTES		STEEL DATE		BAG HOLDER, MACHINED				
	ULL	題, 1		C HAKE	DATE THE THE PARTY OF THE PARTY			

NOTES:

- DIMENSIONS NOT SPECIFIED ON THE DRAWING ARE CONTAINED IN THE DATABASE FOR THIS PART NUMBER AND REVISION.
- 2 RAW CAST SURFACE FINISH TO BE 125 OR BETTER. CASTING TO BE FREE OF FLASH AND BURRS.


CAST SURFACE VISUAL SEVERITY LEVELS:


TYPE OF DEFECT	LEVEL AA	Œ
NEGATIVES MAX LENGTHMAX DEPTH		.035 .030
POSITIVES MAX LENGTH	010	.025 .020
NONFILL	010	.020
MISMATCH, PARTING LINE MAX HEIGHT	005	.010


- WELD REPAIR: COSMETIC WELD RESTORATION IS PERMITTED IN ACCORDANCE WITH EITHER MIL-STD-2219 OR MIL-W-8804.
- TOOLING CHANGES AFTER APPROVED FIRST ARTICLE INSPECTION REQUIRE APPROVAL FROM GAMBRO BCT.
- INDICATES KEY DIMENSION OR SURFACE(S) TO BE CHECKED BY INCOMING O.C..
- 6 SECONDARY SURFACE FINISH:


ALL EXTERIOR SURFACES (MARKED BY NOTE 7, 8 AND 91 TO BE POLISHED & ALUMINUM OXIDE GRIT BLASTED TO AN ACCEPTABLE (APPROVED BY GAMBRO BCT) FINISH FOR ELECTROPOLISHING.

- A CAST SURFACE VISUAL SEVERITY LEVEL AA.
- A CAST SURFACE VISUAL SEVERITY LEVEL A.
- CAST SURFACE VISUAL SEVERITY LEVEL AA, EXCEPT NO PARTING LINES, WITNESS LINES, GRINDING MARKS OR NONUNIFORMITY IN THE SURFACE.










SECTION B-B

REV	REVISION DESCRIPTION	BY	DATE	ECO •	
٨	INITIAL RELEASE, CREATED FROM 777096-679.	AR	11/07/08	BCTO (B) SB	



CAD GENERATED DWG

GAMBRO, BCT TEE, CAST

SEE NOTES .xxxx .0050

. .5"

. XXX. . D[O B.F. FINISH

.xx. .02

AND COMMENTS AND ADDRESS OF THE PROPERTY OF SAME AND THE PARTY OF THE

OTHER PRESIDENCES IN EN

304

STEEL

STAINLESS