




- 1. BREAK ALL SHARP EDGES AND CORNERS.
- THE UNDERCUT SHOULDERS MUST BE FREE OF BURRS RIDGES AND CHATTER MARKS.
- ESSENTIAL DIMENSIONS TO BE VERIFIED AT INCOMING O.C. ARE SHOWN ON THE FILLER ASSEMBLY DRAWING TO WHICH THIS PART IS A COMPONENT.







SECTION A - A

THE DESIGN AND PRECIFICATION AND THE PREPARTY OF CHARLESON INC. OF MANY ACTION OF MANY ACTION OF MANY ACTION OF MANY ACTIONS O

ACETAL PER ASTM D4181, POM 211, COLOR NATURAL

.z. 0.10

UNIGRAPHICS

.xx. 0.01 | ± 2"

.DE.D.DOS SET. FINISH


MONITOR AND IN HOUSE UNLESS CAPACITIES CAPACITIES AND CONTROL OF C


COLOR NATURAL


| SOCIET | STATE | STAT


FILLER, TRIMA SS

ACCEL











REV REVISION DESCRIPTION BY DATE ECO .





6-11-09 408

THE TRAINED AND PROJECTIONS ON THE PROPERTY OF DEVILORED INC. AND SOUL AND REPORTED THE PROPERTY OF DEVILORED INC. AND SOUL AND REPORTED THE PROPERTY OF DEVILORED INC. AND THE PROPERTY OF					ichii Cultira Avena Literati, Calernia ECIS-11
TILERANCES AND STREET TOY FER AND TIA 184-1852 DIRECTOR STREET TO STREET		DIFFWIE SPECIFIED		CaridianBCT 44	
.x. 0.10 .m. 0.01 .xxx.0.005	#0.E5 ± 2°	ACETAL PE ASTM 0416 POM 211, COLOR NAT	31.	FILLER,	
		DRIGHATION HAKE	DATE		
D I : I			CATE CRAGO	'''' 777098	370 B 67/5

UNIGRAPHICS

