

NOTES:

- 1. REMOVE ALL BURRS AND BREAK SHARP EDGES R.O1 OR x 45°
- 2. W INDICATES KEY DIMENSIONS TO BE CHECKED AT INCOMING O.C.
- 3. COAT WITH "NICOTEF" PROCESS .0007 WHN. THICKNESS. 10007 -10009 NIMET INDUSTRIES INC. SOUTH BEND, IN 46619 USA
- 4 ALL PART DIMENSIONS ARE TO BE ACHIEVED AFTER COATING PROCESS.


REV	REVISION DESCRIPTION	BY	DATE	ECO #
Α	INITIAL RELEASE	КМК	4/9/97	BCT 002059
В	Ø.161 +.000/005 WAS Ø.156, 1.46 WAS 1.43	КМК	8/2/87	BCT







UG DWG.



Dupl.

THE OMINES ME SPECIFICATION ME THE PROPERTY OF CONSIDERED SIG. ON USED FOR MANAGEMEN OF SALE OF APPARATES BITHOUT WITTEN PERSONS OF CONSIDERED SIG.					1081) Collins Avenue Lokesood, Colorado BO215-4440	
PER ANSI 1	NG SYMBOLDOY 14.59-1002 PECIFIED ME TYE FINISH.	DIMENSIONS ARE IN INCRES UNLESS DIMENSISE SPECIFIED		CaridianBCT	USA	
.xx 0.1 .xx 0.01 .xx 0.005	**CLES ± 2° SURT. FINISH	NATERIAL SO SS		STEM, HEX UPPER HEX		
SIZE SCALE	RIT RMS	ORIGINATOR K. KLIMEK DRAWN K. KLIMEK	DATE 1/3/ 97 DATE 1/3/97	7777000	PRO 1 1 1 1	