REVISION DESCRIPTION HOTES A INITIAL RELEASED (WAS 2826550) 1. BREAR ALL SHARP EDGES AND CORNERS 0.2 MM - 0.4 MM. 2. TO BE CHECKED AT INCOMING INSPECTION. 3. PASSIVATE PER 00-P-35. 1 DEBURE TO BE VERIFIED VISUALLY. 10.000 - A -(5.00) ⊕ Ø0.4000 A00 B C Ø0.2000 A00 Ø 8.00-5.00 15.00 SECTION A - A 10.10 A (315) Α \triangle $\boxed{}$ 19.0 8.00 -2X DEBURR ALL AROUND 0.2 - 0.6 В 32.0 DEBURR — ALL AROUND 0.2 - 0.6 SECTION B-B 90,00 DESCRIPTION OF STEPLINGS OF THE PREPART OF BROOK SET INC.

PAGE OF PROMISES STEELD WHITEH PROMISES OF PROMOS SET INC.

TO THREE OF ON STREET OF THE THREE STEELS OF THE SET INC.

TO THREE OF ON STREET OF THE THREE STEELS OF THE SET INC.

THE STREET OF THE

SECTION C-C

4X R 0.30 -

Dated Print 10-22-10

GAMBRO. BCT TOLERWICES !7-4PH, CONDITION H900, STAINLESS STEEL .41 0.04 SHAFT, HINGE - INNER LID .xx. D.008 z.zi 0.2 .xxx.0.004 x.xx.0.10 UNIIGRAPHIILES D 2/1 SHOT HONG NGLYEN OF 29/07 986301-301 A 1/1

DATE

HON 02/05/07 BCT018840

ECO •