NOTES

- 1. GENERAL SPECIFICATIONS FOR ANODIZED PART: TYPE II, CLASS 2 PER MIL-A-8625F
 - A. COLOR: BLACK.
 - B. RACKING POINTS AT DISCRETION OF ANODIZER.
 - C. DO NOT MASK HOLES.

NOTE: GAUGES TO BE USED AFTER COATING, WHETHER MASKED OR NOT. GLASS BEAD BLAST Ø.BI TO PROVIDE MATTE FINISH.

3. 1 INDICATES FEATURE/DIMENSION TO BE CHECKED AT INCOMING INSPECTION.

A	17 M25X0.5 45° 45° 45° 45° 1.00-32UN-2A	
	Ø 1.339 ±.001 Ø 1.09	
	Ø .94 Ø .23	
A	50 MIN50	
— 1.125 HEX———▶		3
	THE DIRECTION OF SECTION OF AN AN EXPONENT OF EACH OF THE MANAGEMENT OF CONTINUED THE	-44

REV

REVISION DESCRIPTION

A ORIGINAL RELEASE REPLACES 777094-231

B Note 1 bead blast diameter was .18

S DURKEE

C .50 MIN was .60 MIN

BY DATE

ECO .

мв ^{го}′го_{бт} ВСТО20785

MY ⁰¹/₂₉/₆₈ BCT021532 MY ⁰²/₆₆/₆₉ BCT024508