REVISION DESCRIPTION ECO + A INITIAL RELEASE BSE 08/00/BCT02Z49Z NOTES 1. BREAK ALL SHARP EDGES AND CORNERS. 2. TINDICATES FEATURE OR DIMENSION TO BE CHECKED AT INCOMING INSPECTION. -64.00-[2.520] 9 3.50 ±0.025 [# .025 A [0.138 ±0.001] <u></u> 3.15 [.124] - 34.00 -CHAMF. 0.2 X 45' --[0.339] [.01] [0.12] ø 2.0-**--6.**0 [:0a] [.24] [.26] -6.5 MIN. FULL THD. 3.15-[.26] [.124] z.525 -A- V .0994 .0984 MZXO.4 THREAD-[.138] SECTION A - A

7-2-08 408

	PRESENTATION AND PROCESSION OF THE PROSTED OF DEVIALENCE THE APPLICATION OF APPLICATION OF THE PROSTED OF DEVIALED OF THE PROSTED OF THE PROS			CaridianBCT
TO ENGRE	HILLIMETER TOLEWOOS	MELES	HATERIAL	tire
.X2 0.04 .XX4 0.008 .XXX4 0.004 .XXXX 0.002(x.xxx 0.10	0.8 557. FINISH	303 STAINLESS STEEL	SHAFT, ADAPTER, HSI ACTUATOR
UNIGRAPHICS	D 4:1		ELL INGBOE 07/13/07	~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~