


- 1. BREAK ALL SHARP EDGES AND CORNERS R.005-.015 (OR X 45°).
- 2. VINDICATES KEY FEATURES TO BE VERIFIED AT INCOMING INSPECTION.

6-32 UNC-2B THRU .550 .1245 THRU .25 .1240	
.02	

REV	REVISION DESCRIPTION	ÐΥ	DATE	ECO +
Α	INITIAL RELEASE	СН	5/18/97	BCT 00ZZ00
В	ADDED 6-32 TAPPED HOLE	JB	1/31/02	BCT 010058



7-30-09 408

901 1	EΑ	77	7096-641	CAS	STING, LOCK HSNG, IV POLE
I TEM OTY	U/M		PART NO.		DESCRIPTION
			BILL	MATERIAL	
THESE (PATINGS AND SALL IN SALE OF APPA	NO SPECIFIC IT BE POPPOX NATUS YITHO	CATIONS A SUCED, COT UT WHITE	HE THE PROPERTY OF Corld PICE, OF LISED FOR WALFAL OF PERMISSION OF Corlding	10511 Callins Avenue Lakerood, Calanado 60215-4440	
TOLERANCES AND SYMBOLOGY DID FER AND YIA. SH-1902 DIMERSIONS SECURIED AND AVIEW AND IT IVE PURISH.		DINERSIDE ME IN INCES UNLESS DINERSISE SPECIFIED		CaridianBCT (SA)	
.x: 0.1 .xx: 0.01	# ± ±	.E5	MATERIAL.		MACHINED, LOCK HSNG, IV POLE
SIZE SCALE 1 # 1	00	RMS	C HAKE C HAKE	DATE 3/1/97 DATE 3/1/97	

UG DWG

