## NOTES REV REVISION DESCRIPTION BY DATE 1. BREAK ALL SHARP EDGES AND CORNERS. INITIAL RELEASE DANJ 08/12/05 BCT015540 2. APPLY CHROMATE CONVERSION COATING PER MIL-DTL-REVISED NOTE 2 5541F, TYPE II (ROHS COMPLIANT, NON-HEXAVALENT), CLASS 3. CERTIFICATE OF COMPLIANCE TO BE ΕK |7/14/11| BCT031385 PROVIDED 3. DIMENSIONS ARE IN MM. 4. INDICATES FEATURE/DIMENSION TO BE CHECKED AT INCOMING INSPECTION. -2X Ø 4.40 THRU 5.0 25.40 Ø 10.0-60.0 12.362) 15.40 24.0 2X R 5.0 4X R 2.0 (.106) 15.0-

5-9-12 408

B I

10811 Collins Avenue

Lokewood, Coloredo 80215-4440

ECO #

**30.00** → (1.181)

12.7—

(1/2 INCH THICK)

TOLERANCES AND SYMBOLOGY PER ANSI Y14.5M-1882.
DIMENSIONS SPECIFIED ARE AFTER ADDITIVE FINISH.
DIMENSIONS ARE IN MILLIMETERS UNLESS OTHERWISE SPECIFIED.
DIMENSIONS IN () ARE IN INCHES. **Caridian**BCT INCH TOLERANCES MILLIMETER TOLERANCES ANGLES MATERIAL X± 0.04 X± 1.0 FORK CROSS, UPPER, ANTI-ROT 6061-T6 -XX± 0.00B x.x± 0.2 ALUMINUM .XXX± 0.004 SURF. FINISH x.xx± 0.10 MACHINE .xxxx±0.0020 x.xxx±0.050 SIZE SCALE DO THIRD AND THE AN 986100-289 DRAWN UNIGRAPHICS

DANJ