N62763 TELEDYNE POST NOTE: L. WINDICATES KEY DIMENSIONS TO INSPECTED BY INCOMING QC. **□** ₹ J m ADDED .186 + .004 DIM, .250/.230 R & MAT'L TYPE W/COLOR; .125 R WAS .06
R; TOL FOR .117 \$ .241 DIMS WAS \$ .003
.115 R \$ .010 WAS .230 TOLERANCE ON .380
MH 8/87
ADDED DIAMOND AND NOTE I

WF 7/8/8 EXPLANATION OF DIMENSIONS
TOLERANCES AND SYMBOLIZATION PER
ANSLY 14,5 1973, DIMENSONS SPECIFIED
ARE AFTER MACH. FIMSH O X QTY U/M XXXX A ±.01 DIM WAS .17 ±.01, ADDED .06 R PROJECTION PART NO. THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF COBE LABORATORIES
INC. AND SHALL NOT BE REPRODUCED, COPIED, OR USED
FOR MANUFACTURE OR SALE
OF APPARATUS WITHOUT
WRITTEN PERMISSION.
DRAWN BY PROD ENGR R & O 772647-595 COBE LABORATORIES, INC.
LAKEWOOD, COLOPADO, U.S.A. RETAINER, CARD LATEST CHANGE DATE DESCRIPTION R.X. 3/21/8 VLF 18/4 65164 YB DATE ABUSAL

22/27/27

2349

€CO

32

STATUS A

CLASS

数7°cf 2/2

180