

ODRE PQC | 14-day free trial

[Installation](#) · [Starting a Trial](#) · [Gateway integration](#) · [Paid conversion](#)

Try ODRE PQC for 14 days without buying a paid license or entering a License ID or License Key. A server-signed Trial entitlement controls the trial period.

Free download · No email required · Downloading does not start the Trial · 14 days from first successful activation · 1 Device, 1 Trial · Downloading again or reinstalling does not reset the period · Protected Routes fail closed after expiry · Convert to Paid without reinstalling.

Item	Guide baseline
Reference	Korean Installation and License Activation Guide v1.2.1
Core	0.2.9 - existing Wheel retained
Commercial	0.2.9.post4 - Wheel Trial commands and Gateway entitlement gate
Native	0.3.0-rc.2 - separate Windows / Ubuntu procedures
Platforms	Windows Server 2022 AMD64 / Ubuntu 24.04 AMD64 · CPython 3.12

Existing Client → server uses HTTPS/TLS. Gateway → Private Core is the ODRE v3 protected segment. This is not end-to-end PQC from a mobile device to the Handler.

Select your installation path on page 2. The Wheel procedure is on pages 5-27, Windows Native on pages 28-29, and Ubuntu Native on pages 30-31. Do not run installation or Trial commands from multiple paths.

This is an installation guide. Publishing it does not mean all product release checks are complete. Check the bundle's approval, signatures and integrity, and the verification scope on page 27.

Quick Start | Choose your installation path

Use only the execution path supplied in your official bundle. For an existing installation, keep the same account, identity and state path.

Supplied configuration	Start here	Valid Trial status
Wheel / Python venv	Pages 7-10 → 12-15	ACTIVE / TRIAL_VALID / INTEGRITY: PASS
Windows Native	Pages 28-29	ACTIVE / LEASE_VALID / ENTITLEMENT_KIND=TRIAL
Ubuntu Native	Pages 30-31	Check signature, device binding and Trial period in Native status

1. Verify the official Manifest signature and file SHA-256 hashes. Verify the installer, verifier and trust configuration against the same approved trust basis. (Page 7)
2. Use the installer for your selected path. Do not confuse verified Core-only installation with installation of the whole bundle. (Pages 9, 28, 30)
3. For a new Wheel installation only, run `init` → `doctor` → `verify`. Native users follow the identity procedure in their appendix.
4. Configure Gateway/Core, the entitlement gate, identity, keys, trust and protected routes. (Pages 14, 29, 31)
5. Run the Trial command for your path and check status, start time and expiry. Starting a Trial requires no payment, email or Paid Key.
6. Start the servers and verify the real Gateway → Core → Handler path. A status query alone does not prove successful integration.

Paid conversion: Wheel uses HTTPS web approval on page 25; Native uses its dedicated Paid prompt on pages 29 and 31. Do not mix the credential-entry procedures.

Contents

Procedure	Page
Free trial Quick Start	2
0. Before you begin	5
1. Trial terms and behavior	6
2. Download and integrity verification	7
3. Pre-installation checks	8
4. Windows / Ubuntu Wheel installation	9
4.1 init → doctor → verify	10
5. Diagnostics, self-test and status	11
6. Start the Trial	12
7. Check status → start the servers	13
8. Connect Gateway / Core	14
9. Verify the real integration	15

Contents (continued)

Operation / appendix	Page
10. Normal operation during the Trial	16
11. 1 Device, 1 Trial	17
12. Troubleshooting	18
13. Expiry, clock rollback and fail-closed	19
14. Updates, reinstallation and state preservation	20
15. Technical support	21
16. Handling sensitive information	22
17. Installation checklist	23
18. Glossary	24
Appendix A. Wheel Paid conversion	25
Appendix B. Prohibited actions	26
Document changes and verification scope	27
Appendix C. Windows Native installation and execution	28-29
Appendix D. Ubuntu Native installation and execution	30-31

The existing chapter order and 27-page flow are retained, with Native appendices on pages 28-31. The Wheel procedure on pages 5-27 and Native procedures on pages 28-31 are alternatives, not consecutive installation steps.

0. Before you begin

This guide is for server operators and developers starting a free trial. A payment confirmation email is not a prerequisite.

Requirement	Condition
OS / CPU	Windows Server 2022 AMD64 or Ubuntu 24.04 AMD64
Python	CPython 3.12
Permissions	Permission to install and create protected state paths. The service and CLI must access the same state path.
Network	Access to pip dependency downloads and the official HTTPS activation service
Time	Maintain a trustworthy system clock. Do not roll it back.
Backup	An approved recovery point for application code and configuration
Components	Core 0.2.9, Commercial 0.2.9.post4, and Gateway integration appropriate for the customer application

The software manages the Trial ticket, installation private key and local state. Customers are not asked to enter a paid License Key.

1. Trial terms and behavior

Free download · No email required · Downloading does not start the Trial · 14 days from the first successful activation · 1 Device, 1 Trial · Downloading again or reinstalling does not reset the period · Protected Routes fail closed after expiry · Convert to Paid without reinstalling.

Term	Behavior
Free download / no email	The Trial-start request sends no email, payment details or Paid credentials.
Not started by download	The download session is separate from Trial activation.
14 days from activation	14 days from the server's issued_at to expires_at
1 Device, 1 Trial	One Trial bound to device identity. Retries retain the existing period.
Download again / reinstall	Does not create another free period for the same device.
Expiry	Blocks new protected requests. Authorized public routes retain their existing policy.
Convert after purchase	Approve on the web using the same installation identity, then use Paid entitlement.

“Without a license” means a trial without proof of a paid purchase. The period and device binding are still verified against a server-signed Trial entitlement.

2. Download and integrity verification

Obtain the official bundle and the Manifest, signatures and installation instructions for that same release. Downloading does not consume any of the 14 days.

1. Verify the Release Manifest signature against an independent official trust anchor.
2. Compare file names, sizes and SHA-256 hashes, including installers, verifiers and trust configuration.
3. Confirm that the approved installer enforces verification before installation, then run it. Stop on any mismatch.

Check file SHA-256

```
Get-FileHash -Algorithm SHA256 -LiteralPath "<ARTIFACT_PATH>"
```

```
sha256sum -- "<ARTIFACT_PATH>"
```

<ARTIFACT_PATH> is the downloaded file path. Hash equality alone does not authenticate a publisher. Successful pip installation, ZIP readability or CRC checks do not prove integrity either.

The existing verifier on page 9 is for Core 0.2.9 only. It does not verify the complete Commercial post4, Gateway or Native bundle. Each component needs its own official Manifest and approved installation path.

This guide does not invent a final bundle hash. Do not reuse Commercial post3 hashes for post4. If the verifier or trust material is missing, obtain the correct distribution; do not bypass verification with ordinary pip.

3. Pre-installation checks

Check	PASS condition	If it fails
OS / CPU / Python	Exact supported combination	Stop installation; contact support.
System time	NTP synchronized; no significant drift	Resolve the clock issue.
HTTPS egress	Outbound 443 to the official service	Obtain approval for firewall changes.
Permissions / ACL	Administrator/root and restricted state-path permissions	Correct the permissions design.
Integrity	Manifest signature and every hash match	Discard the artifact; download again.
Backup	Application rollback point available	Back up before making changes.

A backup may include approved copies of application code and configuration. Do not clone an existing installation identity, device private key, refresh credential or Offline Lease to a new VM or container.

4. Wheel installation | Preserve verification

These are the verified Core 0.2.9-only installer commands. Put the verifier, anchor and Wheel in the same directory and complete page 7 first. These commands do not install the entire Commercial + Gateway bundle.

Windows · Use verified Python 3.12

```
$trustedPython = Read-Host 'Verified Python 3.12 executable path'
& .\Invoke-ODREV029VerifiedInstall.ps1 `
  -WheelPath .\odre_pqc-0.2.9-py3-none-any.whl `
  -TargetPath .\core-verified-new `
  -EvidencePath .\core-install-result.json `
  -PythonPath $trustedPython
```

Ubuntu · Python 3.12 isolated mode

```
python3.12 -I ./odre-v029-preinstall-verifier.pyz \
  ./odre_pqc-0.2.9-py3-none-any.whl \
  --trust-anchor ./ODRE_PQC_v0.2.9_RELEASE_TRUST_ANCHOR.json \
  --install --target ./core-verified-new \
  --json-output ./core-install-result.json
```

core-verified-new must be a new dedicated target that does not yet exist. Do not select or delete an existing installation, identity or state path. The Windows wrapper also checks the Python signature.

The installer invokes pip only after all Core checks pass and installs with `--no-index / --no-deps`. It does not configure dependencies, Commercial, Gateway, the customer venv or CLI paths.

Configure the complete bundle using its accompanying approved installation instructions. Stop here if those commands have not been supplied. Do not reinstall the Wheel using ordinary pip after verification, or invent a PYTHONPATH configuration.

Proceed to page 10 only after the official procedure has configured the venv, dependencies, Commercial post4, Gateway and CLI, and pip check and version checks pass. If you received Native, use page 28 or 30 instead.

4.1 init → doctor → verify

Continue only after the official installation procedure has prepared the complete Wheel configuration and customer .venv, with dependency and version checks complete. The Core-only installation on page 9 does not meet that condition by itself.

Windows PowerShell - new installations only

```
& .\venv\Scripts\odre-pqc.exe init  
& .\venv\Scripts\odre-pqc.exe doctor  
& .\venv\Scripts\odre-pqc.exe verify
```

Ubuntu Bash - new installations only

```
.venv/bin/odre-pqc init  
.venv/bin/odre-pqc doctor  
.venv/bin/odre-pqc verify
```

init prepares a new installation identity, configuration and state. Do not repeat init on an existing installation or update with config/keys/runtime/state. Never delete state or keys to bypass this restriction.

doctor diagnoses the installation environment; verify is an independent Core self-test, not a customer Gateway/Handler integration test. It need not be repeated after Trial activation or Gateway integration. Rerun a failed check only after correcting its cause.

5. Diagnostics, self-test and status

Command / check	Meaning
pip check	Checks for Python dependency conflicts
odre-pqc doctor	Diagnoses the installation environment before Gateway integration
odre-pqc verify	Independent Core self-test using temporary keys and a temporary DB
odre-pqc-commercial trial	Starts the device Trial; 14 days from first successful activation
Commercial status	Checks signature, device binding, Trial period and installation integrity
odre-pqc status	Checks authenticated runtime evidence from the running Core
Gateway integration test	Separately verifies the real request path to the business Handler

verify PASS does not automatically prove the state of a running server. Core status checks HMAC, nonce, freshness, and provider/key/security/worker state, among other runtime evidence.

If the server is not running or the correct authenticated target cannot be reached, the result may be Runtime UNKNOWN / PQC PROTECTION: BLOCKED. Do not substitute the healthy status of another Core for Gateway Private Core integration evidence.

6. Start the Trial - no payment or email

After the Core self-test and the Gateway entitlement gate integration on page 14, run the command for your OS under the same account and state path that the service will use.

Windows PowerShell

```
& .\.\venv\Scripts\odre-pqc-commercial.exe trial
```

Ubuntu Bash

```
./venv/bin/odre-pqc-commercial trial
```

The CLI creates and stores the installation identity and handles download/Trial tickets and the device challenge. It submits signed proof of device possession; it does not send the private key to the server. No License ID, License Key or email input is required.

Expected result: ACTIVATION: ACTIVE / LEASE: TRIAL_VALID / INTEGRITY: PASS. TRIAL_STARTED_AT and TRIAL_EXPIRES_AT define the server-issued period. Do not relabel the Wheel Trial state as Paid LEASE_VALID.

Running the same command again does not restart the period. If the server approved activation but its response was not received, recover the same Trial using the preserved identity and ticket. Do not delete existing state.

7. Check status → start servers → runtime

1) Commercial status

```
& .\venv\Scripts\odre-pqc-commercial.exe status
# Ubuntu
.venv/bin/odre-pqc-commercial status
```

For the Trial, check ACTIVE / TRIAL_VALID / INTEGRITY: PASS. After expiry, EXPIRED / TRIAL_EXPIRED is displayed. The absence of a License ID or Paid Key is normal for the Trial.

2) Start the customer server + Gateway Private Core

Use the approved start command for the customer application. Bind Private Core to loopback only and route Nginx's public paths through the Gateway. No customer module name or port is assumed here.

3) Check the running Core

```
& .\venv\Scripts\odre-pqc.exe status
# Ubuntu
.venv/bin/odre-pqc status
```

The Core status target and authentication settings must match the actual Gateway Private Core. Then verify the real business request path on page 15.

8. FastAPI / Server Gateway integration

External HTTPS Client → Nginx → FastAPI / ODRE Server Gateway → Python PQC Client → ODRE v3 → Private Core → Protected Handler

Add the following call using `host` and `private_core` returned by your existing `build_host(...)` integration. Run it once before starting the two ASGI servers.

```
from odre_pqc_commercial import install_gateway_license_gate

install_gateway_license_gate(host, private_core)
```

Integration item	Required check
host	GatewayDispatch returned by the existing <code>build_host</code> ; forwards designated protected routes to the Gateway
private_core	The actual Private Core FastAPI object for this Gateway
Entitlement gate	Checks entitlement on each new request at both Gateway and Private Core entry
identity / key / trust	Retain existing ODRE v3-specific configuration. Do not confuse Trial installation identity with cryptographic protocol keys.
Public paths	Existing host health and activation control-plane paths retain their policies.

This call does not create a Gateway or automatically protect every customer API. Your existing integration must define protected routes, prevent Handler bypass, and configure startup/shutdown.

9. Verify Gateway / Core / Handler

Check the running customer application in an isolated validation environment. This is not another run of the independent verify command.

Check	Expected behavior
Normal request	Preserves existing HTTPS API semantics and executes the Handler
v3 path	Actual Gateway handshake and encrypted requests/responses
Session reuse	Trial entitlement checked on every request, even with an existing session
Expiry	New protected requests rejected from expiry onward; no increase in Handler execution count
Private Core	Direct entry also applies the entitlement gate; never publicly exposed
Public health	Existing response retained independently of Trial expiry
Integration status	Record Core status and actual Handler verification separately

A Handler already admitted and running before expiry is not forcibly interrupted. The contract blocks new protected requests entering after expiry.

Retain existing security regressions and customer-specific business correctness checks. HTTP success counts alone do not prove load performance or coverage of every security path.

10. Normal operation during the Trial

The Trial remains valid until the absolute expiry time issued at first activation. Restarting a server or job does not create another 14 days.

Item	Operational guidance
Period	Check TRIAL_STARTED_AT / TRIAL_EXPIRES_AT in Commercial status.
Renewal	No renew operation extends the Trial period. Distinguish this from Paid renew.
Connectivity loss	Valid local signed entitlement is verified without an online call for every request.
State protection	Retain Windows DPAPI and restricted ACLs, or Linux encrypted state and restricted permissions.
Updates	Keep identity and state; verify new release hashes and dependencies.
Errors	Keep protected paths blocked while resolving the cause.

Fail-closed applies if system time is untrustworthy or entitlement, device binding or installation integrity verification fails. Adjusting the clock to extend the Trial is not supported.

11. 1 Device, 1 Trial

A Trial is bound to the server's device-identity record. Deleting an installation folder or venv does not delete that record.

Situation	Result
Retry on the same installation	Retains the original Trial start and expiry times
Download again	A new download creates no new Trial entitlement
Reinstall	Does not reset the same device's free period
Copy state to another device	Rejected because signed device/identity binding does not match
Concurrent start	No duplicate Trial issued for the same device
Run trial after expiry	Returns the existing expired/already-used state, not a new free period
Purchase	Activate separate Paid entitlement on the same installation

No claim is made of complete protection when an administrator/root attacker controls OS identity and the trust store. Do not clone devices/state or alter identifiers to bypass Trial policy.

12. Troubleshooting

Error / state	Customer action
TRIAL_ALREADY_USED	Check the device's Trial history. Do not try to reset it by downloading or installing again.
TRIAL_EXPIRED	Keep protected paths blocked; convert to Paid to continue.
CLOCK_TAMPER_DETECTED	Check time synchronization and change history. Do not delete state.
ENTITLEMENT_BINDING_INVALID	Check for mixed state from another device, identity or key.
ENTITLEMENT_SIGNATURE_INVALID	Check the official entitlement response and file integrity. Do not edit it.
RUNTIME_INTEGRITY_FAILURE	Verify the official Core and installation integrity.
AUTHORITY_UNREACHABLE	Check DNS, TLS and official-service connectivity, then retry the same command.
OPERATION_IN_PROGRESS	Complete the active activation/renewal CLI operation first.
PAID_INSTALLATION_EXISTS	Do not revert an existing Paid installation to Trial.

Do not disable the gate or expose a Handler directly to eliminate protected-path 503 responses. Retain error codes from the CLI, not secret state in support tickets.

13. Expiry, clock rollback and fail-closed

Protected Routes fail closed after Trial expiry. No new request is admitted at or after signed expires_at; there is no additional Trial grace period.

Wheel Trial verification

The signed entitlement binds device, installation identity, key, product and period. The last checked time is retained in encrypted state; a monotonic clock reference is also used while running so clock rollback cannot extend expiry.

Install the entitlement gate at both Gateway and Private Core. Even an existing session requires entitlement checks for new requests. Missing/corrupt entitlement files, time inconsistency, expiry and integrity failure are reasons to block.

Preserving existing Native protection

The Phase 3B Native EXE has a separate monotonic deadline, key removal at expiry, Named Pipe IPC and broker controls. Do not delete that EXE or replace it with the Wheel gate. Historical Native PASS results are not reused as PASS evidence for this Wheel path.

Do not fall back to plaintext/classical transport after entitlement verification fails. The customer's normal HTTPS connection is distinct from such fallback.

14. Updates, reinstallation and state

Do not rerun init on an existing installation. Preserve Core config/keys/runtime/state and the Commercial installation identity.

Operation	Precaution
Commercial update	Use the approved new Wheel; retain the protected state path.
Trial retry	Recover the existing server record with the same trial command.
App restart	No period reset. Install the gate before server startup.
Restore	Do not import another device's Trial, Lease or keys.
Paid conversion	Approve activate on the web for the same installation; no venv/Core/Gateway reinstall.
Device replacement	Not a Trial-period reissuance process; check support policy.

Deleting state files to make an error disappear is not a valid recovery procedure. Do not manually edit private keys, Trial tickets or signed entitlements.

15. Requesting technical support

Customer support and inquiries: odrai2025@gmail.com

Safe to send	Do not send
Core / Commercial / Python / OS versions	Private keys or state encryption keys
UTC time and error codes	Trial tickets; access/refresh/poll tokens
Redacted installation ID and start/expiry times	Complete local state files
Redacted doctor / verify / status results	Customer business request/response bodies
Official filenames and SHA-256 hashes	Full environment-variable, configuration or DB dumps

Starting the Trial requires no email. This address is an optional support channel if a problem occurs, not a mandatory step in Trial activation.

16. Information you must not disclose

- Actual License Keys or examples resembling real values
- Valid Refresh Tokens, Access Tokens, poll_token or Device Codes
- Instance/device private keys, state encryption keys, keystore/DPAPI exports
- Webhook secrets, provider API secrets, KMS/HSM credentials
- Complete environment-variable/configuration/DB dumps or internal administrative endpoints
- Real customer identifiers and application request/response bodies
- Internal detection thresholds and implementation details that would enable bypassing defenses

Do not send these values even to someone claiming to be support staff. Legitimate support procedures do not require raw License Keys or private keys.

17. Installation checklist

For the Wheel path. Native users follow pages 28-31; the same integrity, state-preservation and real Handler-verification principles apply.

- [] Select the bundle's installation path; verify Manifest signatures and SHA-256 hashes
- [] Use the approved installer to configure Core, Commercial, Gateway, dependencies and CLI
- [] Do not mistake successful Core-only installation for complete bundle installation
- [] Complete pip check and version checks; run init once for new installations only
- [] doctor → verify succeeds; distinguish self-tests from business integration tests
- [] Connect entitlement gates to Gateway host and Private Core
- [] Commercial trial: check ACTIVE / TRIAL_VALID / INTEGRITY: PASS
- [] Retries do not reset start or expiry times
- [] Start the customer server and Private Core; check the actual runtime target
- [] Verify Gateway → v3 → Private Core → Handler
- [] In isolation, confirm zero new Handler executions after expiry and preserved public routes
- [] Preserve existing identity and state during updates and Paid conversion

18. Glossary

Term	Meaning
Trial	14-day evaluation from first successful activation without buying a paid license
Device	Installation device bound to the server-side Trial-use history
Trial entitlement	Signed authorization containing device, installation, product and period
TRIAL_VALID / TRIAL_EXPIRED	Actual display values for a valid/expired Trial
installation identity	Installation identifier linked to a local private key; retained when converting to Paid
Gateway / Private Core	Server layer connecting the external HTTPS API with the ODRE v3 protected boundary
Paid entitlement / Lease	Signed authorization used by an approved installation after purchase
Fail-closed	Reject protected requests if entitlement or protection conditions cannot be proven
Native Phase 3B	Separate Rust EXE and broker protection path; distinct from Wheel Trial

Appendix A. Convert to Paid without reinstalling

To continue using the product, complete the official purchase process, then activate Paid under the same installation and service account used for the Trial. This step is not needed to start the Trial.

Windows PowerShell

```
& .\.\venv\Scripts\odre-pqc-commercial.exe activate  
& .\.\venv\Scripts\odre-pqc-commercial.exe status
```

Ubuntu Bash

```
.venv/bin/odre-pqc-commercial activate  
.venv/bin/odre-pqc-commercial status
```

On the official HTTPS page indicated by activate, approve the purchased License ID and License Key together with the CLI device registration code. Do not put purchase credentials in the CLI, source code or logs.

On success, the same installation identity becomes ACTIVE / LEASE_VALID. No venv/Core/Gateway reinstall or init is needed. The gate reads Paid entitlement on the next request. A pending or failed approval alone does not consume or reset an otherwise valid Trial period.

Once Paid state is applied, Paid expiry or deactivation does not automatically revert to the old Trial. Purchase and completion of Paid activation on the installation are separate steps.

Appendix B. Prohibited customer actions

- Run an artifact whose hash or Manifest signature does not match
- Open protected traffic despite doctor/verify failure
- Roll back system time or bypass time checks
- Clone Offline Leases, Commercial state, refresh credentials or instance keys
- Reuse an existing Lease after cloning a VM
- Store a License Key in source, command lines, environment variables or logs
- Execute a raw Wheel directly or use an unofficial mirror artifact
- Bypass the license gate or local-state verification
- Connect a protected route to classical/plaintext fallback
- Force execution on an unofficial OS/runtime and describe it as supported

If any of these occur, close traffic, return to the last verified deployment state and investigate the cause.

Document changes and verification scope

Location	RC2 document changes
Pages 2, 4	Path selection and Windows/Ubuntu Native contents entries
Pages 7, 9, 10	Pre-install verification; distinguish Core-only and whole-bundle installation
Pages 12, 13, 25	Retain Wheel status labels and web approval
Pages 28-31	Separate Native 0.3.0-rc.2 execution, status and Paid prompts
Existing assets	Retain Core 0.2.9, existing identity and original Phase 3B evidence

The baseline RC2 material records Wheel Trial and Commercial regressions in isolated Windows/Ubuntu 24.04 VMs. Paid conversion used actual service code with an isolated DB and test signer, not production payment or issuance.

The Wheel path uses ASGI TestClient; Windows/Ubuntu Native use isolated HTTPS → Nginx → Gateway → Core → Handler and session reuse. Lease expiry during execution, retained public routes and Paid conversion are separate checks.

This editing and translation work does not rerun product tests. It does not establish production Native Live activation, performance/load validation, official publisher signing or final bundle approval. Check the release's RELEASE_GATE.json and approved evidence for actual deployment status.

Applies to Commercial post4 and server releases supporting its Trial responses. post3 has no trial command. The Core-only verifier described here does not guarantee Commercial/Gateway installation.

Appendix C. Windows Native installation

Native 0.3.0-rc.2 is a separate Windows Server 2022 execution configuration. Do not also start the Wheel Trial on pages 9-25. Creating another identity on a device that has used its Trial does not reset the period.

First obtain approved authority trust configuration and its SHA-256 separately. It includes the issuer's HTTPS address, public CA information, issuance-signing public key and actual Native EXE hash. Do not invent trust values in source code.

1. Create identity - does not start the Trial

```
Set-Location .\native\windows
py -3.12 .\odre-native.py identity
```

Rerunning identity verifies and preserves the existing identity. Do not delete device.json or native-state.dpapi, or generate a new identity, during an update.

2. First Trial activation and status

```
$trustConfig = Read-Host 'Approved trust config path'
$trustPin = Read-Host 'Approved trust SHA-256'
py -3.12 .\odre-native.py trial `
  --trust-config $trustConfig --trust-pin $trustPin
py -3.12 .\odre-native.py status `
  --trust-config $trustConfig --trust-pin $trustPin
```

Native status: ACTIVATION=ACTIVE, LEASE=LEASE_VALID, ENTITLEMENT_KIND=TRIAL. This differs from the Wheel TRIAL_VALID label on page 12. LEASE_VALID alone does not mean Paid. No email or Paid License Key is needed; the 14 days begin at first successful activation. If a response is delayed, retain the Trial and confirm a new lease before running.

Appendix C. Run Native and convert to Paid

3. Connect the reviewed backend and Gateway, then run

```
$backend = Read-Host 'Reviewed backend.py path'
$backendPython = Read-Host 'Customer venv Python path'
py -3.12 .\odre-native.py run `
  --trust-config $trustConfig --trust-pin $trustPin `
  --backend-script $backend --backend-python $backendPython
```

run starts the Native gate, Private Core and 10 backend workers. Default ports are 29380 for Native and 29400-29409 for backends, all on loopback. Do not replace or reuse occupied ports. Connect Gateway/Nginx separately for the customer's configuration.

Install business dependencies in the separate venv selected by --backend-python. Do not install packages or add files in the signed Native Core runtime.

The reviewed /secure/ path runs through Gateway → Native gate → Core. Only canonical paths without escapes or dot segments are supported. Never expose backend ports externally. Verify the real Handler integration.

Signed leases renew automatically during normal execution. Protected paths may return 503 while renewal or conversion is prepared. Failed renewal never extends expiry; expired protected requests are rejected. Public paths remain available.

4. Convert with the same identity - Native only

```
py -3.12 .\odre-native.py paid `
  --trust-config $trustConfig --trust-pin $trustPin
py -3.12 .\odre-native.py status `
  --trust-config $trustConfig --trust-pin $trustPin
```

Enter the purchased License ID and License Key only in this Native paid prompt. The Key goes through stdin, not arguments, environment variables or files. This differs from Wheel HTTPS web approval on page 25. Success sets ENTITLEMENT_KIND=PAID; no reinstall or identity regeneration is needed.

For Ubuntu, use pages 30-31. Never copy state or identity between OSes. Check the applicable RELEASE_GATE.json for official publisher approval and deployment status.

Appendix D. Ubuntu Native installation

Native 0.3.0-rc.2 for Ubuntu 24.04 AMD64 / Python 3.12. Do not start a second Trial through the Wheel path. Check publisher approval and artifact integrity first. A test signature does not substitute for official publisher signing approval.

1. Install the public runtime - no identity or Trial creation

```
read -r -p "Verified inventory SHA-256: " inventory_sha
sudo python3.12 native/ubuntu/install-native-ubuntu.py \
  --source native/ubuntu \
  --inventory-sha256 "$inventory_sha"
```

The default path is /opt/odre-pqc-native; existing paths are not overwritten. The runtime must be root-owned and not writable by the service account. Do not add business dependencies to it with pip.

2. Create identity and start Trial as the service account

```
cd /opt/odre-pqc-native
python3.12 odre-native-ubuntu.py identity
read -r -p "Approved trust config: " trust_config
read -r -p "Approved trust SHA-256: " trust_pin
python3.12 odre-native-ubuntu.py trial \
  --trust-config "$trust_config" --trust-pin "$trust_pin"
python3.12 odre-native-ubuntu.py status \
  --trust-config "$trust_config" --trust-pin "$trust_pin"
```

Do not run the service as root. The default state path is ~/.local/state/odre-pqc/native-commercial under the service account. Keep the same account and path. identity preserves existing identity and does not start the Trial.

Parent directories of the state path must not be writable by group or other users. Core state is created with owner-only permissions; unsafe parent paths are rejected. Check signature, device binding and Trial period in status; do not substitute Wheel status labels.

Appendix D. Run Ubuntu and convert to Paid

3. Run with the customer venv and reviewed backend

```
read -r -p "Reviewed backend.py: " backend
read -r -p "Customer venv Python: " backend_python
python3.12 odre-native-ubuntu.py run \
  --trust-config "$trust_config" --trust-pin "$trust_pin" \
  --backend-script "$backend" --backend-python "$backend_python"
```

Install business dependencies in a backend-specific venv. Native retains that Python invocation path; Core uses a separately signature-verified embedded runtime. Ports 29380 and 29400-29409 are loopback-only. Connect Gateway/Nginx and verify the real Handler response.

Core startup wait defaults to 25 seconds. For slower environments, use `--core-startup-seconds 120` (range 1-300 seconds). This changes startup wait only, not Lease validity.

Linux protects state with service-UID permissions and local AES-GCM files; IPC uses Unix socket PID/UID checks and authenticated frames. This is not the Windows DPAPI/Named Pipe implementation. Never copy state to another account or device.

Preserve Gateway PQC Client keys across restarts and Paid conversion. Arbitrarily regenerating keys for the same Client causes rejection by Core's key-change protection.

4. Convert the same installation to Paid - Native only

```
python3.12 odre-native-ubuntu.py paid \
  --trust-config "$trust_config" --trust-pin "$trust_pin"
python3.12 odre-native-ubuntu.py status \
  --trust-config "$trust_config" --trust-pin "$trust_pin"
```

Enter License ID and License Key only in the Native paid prompt; Trial needs neither. The Key is passed through stdin, unlike Wheel web approval on page 25. Never put it in arguments, environment variables, files or logs. Convert the same identity; no init, identity regeneration or Core reinstall is needed.

Failed renewal does not extend expiry. Expired protected requests are rejected; public paths remain available. Paid conversion and expiry blocking are isolated-test coverage. Official production publisher approval, Native Live E2E and load validation require separate confirmation.