DEV 140 · DISCUSSION 3 · CSS BASICS

Style Your Page with CSS

Linking a stylesheet, selectors, and changing colors, fonts, and sizes

Link a separate CSS file in the <head>

index.html

```
<head>
  <title>Sourdough 101</title>
  <link rel="stylesheet" href="style.css">
</head>
```

Two files, two jobs

`index.html`
The content: headings, paragraphs, images

`style.css`
The look: colors, fonts, sizes, spacing

`rel` says the file is a stylesheet. `href` says which file to load. Without this one line, the browser never reads your CSS.

CSS BASICS · 2 OF 4

Every CSS rule has the same three parts

```
h1 { color: #8b5a2b; }
```

selector
which elements

property
what to change

value
what to change it to

style.css

```
h1 {
  color: #8b5a2b;
  font-size: 2.5rem;
}
```

The browser shows



Sourdough 101

CSS BASICS · 3 OF 4

Selectors choose which elements get styled

TYPE

```
p { }
```

Every <p> on the page

Matches this HTML

```
<p>Hello</p>
```

CLASS

```
.card { }
```

Every element with that class. Reuse it as often as you like.

Matches this HTML

```
<article class="card">
```

ID

```
#method { }
```

The one element with that id. Only one per page.

Matches this HTML

```
<section id="method">
```

The `.` and `#` only go in the CSS. In the HTML you just write the name.

CSS BASICS · 4 OF 4

Change colors, fonts, and sizes

style.css

```css
body {
  background-color: #fdf6ec;
  color: #3b2a1a;
  font-family: Arial, sans-serif;
}
h1 { font-size: 2.5rem; }
p { font-size: 1.125rem; }
```

The browser shows

Sourdough 101

Bread made from flour, water, and salt.

Colors

`background-color` fills the box. `color` sets the text.

Fonts

`font-family` lists fonts in order. The browser uses the first one it has.

What's a rem?

`1rem` = the browser's default text size, usually 16px. So 2rem = 32px.