

Creating mqtt on docker

Tuesday, September 23, 2025 11:20 PM

Step 1: Create a folder for Mosquitto

Pick a place on your PC, e.g., C:\docker\mosquitto. Inside that folder, create a subfolder config:

```
mkdir C:\docker\mosquitto\config
```

Step 2: Create mosquitto.conf

Open Notepad and save this as:

```
C:\docker\mosquitto\config\mosquitto.conf
persistence true
persistence_location /mosquitto/data/
log_dest file /mosquitto/log/mosquitto.log
allow_anonymous true
listener 1883
listener 9001
protocol websockets
```

Step 3: Run the Docker container

Open **PowerShell** and run:

```
docker run -d --name mosquitto `
-p 1883:1883 `
-p 9001:9001 `
-v C:\docker\mosquitto\config:/mosquitto/config `
-v C:\docker\mosquitto\data:/mosquitto/data `
-v C:\docker\mosquitto\log:/mosquitto/log `
eclipse-mosquitto:2
```

Step 4: Verify it's running

```
docker ps
```

You should see mosquitto up and running with 0.0.0.0:1883->1883/tcp.

Great! Let's test your MQTT broker before connecting Hubitat.

Step 1: Subscribe to all topics

Open **PowerShell** and run: `docker exec -it mosquitto mosquitto_sub -h localhost -t "#" -v`

Step 2: Publish a test message

Open another PowerShell window and run: `docker exec -it mosquitto mosquitto_pub -h localhost -t "test/topic" -m "Hello Hubitat!"`

Step 3: Verify

- The first terminal (subscriber) should immediately show:

```
bash  
  
test/topic Hello Hubitat!
```

If you see that, your MQTT broker is working perfectly 

Set the restart policy without recreating:

`docker update --restart unless-stopped mosquitto`

☒ **Check current restart policy:** `docker inspect -f "{{.HostConfig.RestartPolicy.Name}}" mosquitto`