

Exercises week 2

Last update: 2022/09/08

Exercise 2.1 Consider the Readers and Writers problem we saw in class. As a reminder, here is the specification of the problem:

- Several reader and writer threads want to access a shared resource.
- Many readers may access the resource at the same time as long as there are no writers.
- At most one writer may access the resource if and only if there are no readers.

Mandatory

1. Use Java Intrinsic Locks (i.e., `synchronized`) to implement a monitor ensuring that the access to the shared resource by reader and writer threads is according to the specification above. You may use the code in the lectures and Chapter 8 of Herlihy as inspiration, but do not feel obliged copy that structure.
2. Is your solution fair towards writer threads? In other words, does your solution ensure that if a writer thread wants to write, then it will eventually do so? If so, explain why. If not, modify part 1. so that your implementation satisfies this fairness requirement, and then explain why your new solution satisfies the requirement.

Challenging

3. What type of fairness does your solution enforce? Hint: Consider the two types of fairness we discussed in class, see lecture slides.
4. Is it possible to ensure strong fairness using `ReentrantLock` or intrinsic java locks (`synchronized`)? Explain why.

Exercise 2.2 Consider the lecture's example in file `TestMutableInteger.java`, which contains this definition of class `MutableInteger`:

```
// WARNING: Not ready for usage by concurrent programs
class MutableInteger {
    private int value = 0;
    public void set(int value) {
        this.value = value;
    }
    public int get() {
        return value;
    }
}
```

For instance, as mentioned in Goetz, this class cannot be used to reliably communicate an integer from one thread to another, as attempted here:

```
final MutableInteger mi = new MutableInteger();
Thread t = new Thread(() -> {
    while (mi.get() == 0)          // Loop while zero
    { /* Do nothing*/ }
    System.out.println("I completed, mi = " + mi.get());
});
t.start();
try { Thread.sleep(500); } catch (InterruptedException e) {
    e.printStackTrace(); }
```

```
mi.set(42);
System.out.println("mi set to 42, waiting for thread ...");
try { t.join(); } catch (InterruptedException e) { e.printStackTrace(); }
System.out.println("Thread t completed, and so does main");
```

Mandatory

1. Compile and run the example as is. Do you observe the "main" thread's write to `mi.value` remains invisible to the `t` thread, so that it loops forever? Independently of your observation, is it possible that the program loops forever? Explain your answer.
2. Use Java Intrinsic Locks (`synchronized`) on the methods of the `MutableInteger` to ensure that thread `t` always terminates. Explain why your solution prevents thread `t` from running forever.
3. Would thread `t` always terminate if `get()` is not defined as `synchronized`? Explain your answer.
4. Remove all the locks in the program, and define `value` in `MutableInteger` as a `volatile` variable. Does thread `t` always terminate in this case? Explain your answer.

Challenging

5. Explain parts 3. and 4. in terms of the *happens-before* relation.

Exercise 2.3 Consider the small artificial program in file `TestLocking0.java`. In class `Mystery`, the single mutable field `sum` is `private`, and all methods are `synchronized`, so superficially the class seems that no concurrent sequence of method calls can lead to race conditions.

Mandatory

1. Compile the program and run it several times. Show the results you get. Are there any race conditions?
2. Explain why race conditions appear when `t1` and `t2` use the `Mystery` object. Hint: Consider (a) what it means for an instance method to be `synchronized`, and (b) what it means for a static method to be `synchronized`.
3. Implement a new version of the class `Mystery` so that the execution of `t1` and `t2` does not produce race conditions, *without* changing the modifiers of the field and methods in the `Mystery` class. That is, you should not make any static field into an instance field (or vice versa), and you should not make any static method into an instance method (or vice versa).

Explain why your new implementation does not have race conditions.