

No-bulge model

The figure displays 12 plots arranged in a 6x2 grid. The left column is labeled 'bt10_re03', 'bt10_re06', 'bt25_re03', 'bt25_re06', 'bt50_re03', and 'bt50_re06' from top to bottom. The right column is labeled 'bt00'. Each plot shows 'Circular velocity [km/s]' on the y-axis (ranging from 0 to 600) versus 'Radius [kpc]' on the x-axis (ranging from 0 to 5). The plots compare four components: 'total' (black solid line), 'disk' (blue solid line), 'bulge' (orange solid line), and 'halo' (green solid line). Shaded regions around the solid lines represent uncertainty or confidence intervals. Dashed lines of the same color represent alternative model components. The 'total' velocity is the sum of the other components. The 'bulge' component is only present in the 'bt00' model, where it is a constant low value. In the other models, the bulge component is more complex, often peaking at small radii. The 'disk' component is the dominant contributor to the total velocity in most models, peaking around 2-3 kpc. The 'halo' component is generally the least significant, increasing slowly with radius. The 'bt00' model shows a much lower total velocity compared to the other models, peaking around 400 km/s. The 'bt10' and 'bt25' models show higher total velocities, peaking around 400-500 km/s. The 'bt50' models show the highest total velocities, peaking around 550-600 km/s.