

## TECHNICAL CHARACTERISTICS

MATERIAL  
INSULATOR: PA 66  
FLAMMABILITY RATING: UL94-V0  
COLOR: GREEN  
CONTACT: BRASS  
SOLDER TAIL PLATING: TIN

ENVIRONMENTAL  
OPERATING TEMPERATURE: -40 UP TO 105°C  
COMPLIANCE: LEAD FREE AND ROHS

ELECTRICAL	cULus	VDE
CURRENT RATING:	10 A	10.5 A
WORKING VOLTAGE:	300 VAC	300 VAC
WITHSTANDING VOLTAGE:	1.6 kV	2.5 kV
CONTACT RESISTANCE:	20 mOhm max	

STANDARD  
c<sup>9</sup>us CERTIFIED E315414  
VSE CERTIFIED 40023195



MECHANICAL  
PITCH: 3.5MM

## SOLDERING

### JEDEC LEAD FREE WAVE SOLDERING PROCESS

PACKAGING  
BOX

DIMENSION  
A = (NB. PINS -1) x PITCH  
B = ((NB. PINS -1) x PITCH) +4,9

RoHS Compliant				PROJECTION: 	GENERAL TOLERANCE $.X = \begin{smallmatrix} + \\ - \end{smallmatrix} 0.2$ $.XX = \begin{smallmatrix} + \\ - \end{smallmatrix} 0.15$		DESCRIPTION: SERIE 3211 - 3.50MM VERTICAL PCB HEADER WR-TBL WERI PART NO: 691 321 100 0xx	SIZE <b>A4</b>
G								
F								
E								
D								
C	04-APR-16	DRAWING	AK	APPROVAL: FBr	UNIT: MM			
B	12-OCT-09	STANDARD	JP		SCALE:			
A	31-OCT-08	PDF	JP		SHEET: 1/2			
REV	DATE	FILE	BY		DRAW: MARVIN			



# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Wurth Elektronik:](#)

[691321100006](#)