



a Screened observation contracts

encoding	label in b-f	serialized example	feature encoded	bins	precision	value convention
24 intervals, 6 decimals (fixed baseline)	baseline		interval edges + mass	24	6 decimals	fractions, $\Sigma = 1$
24 bin centers	centers 24		bin center + mass	24	6 decimals	fractions, $\Sigma = 1$
24 bin centers, half-bin origin shift	centers 1/2-shift		bin center + mass	24	6 decimals	fractions, $\Sigma = 1$
12 intervals	intervals 12		interval edges + mass	12	6 decimals	fractions, $\Sigma = 1$
48 intervals	intervals 48		interval edges + mass	48	6 decimals	fractions, $\Sigma = 1$
24 intervals, 4 decimals	intervals d4		interval edges + mass	24	4 decimals	fractions, $\Sigma = 1$
24 integer counts, fixed total	counts 100		interval edges + count	24	6 decimals	integers, $\Sigma = 100$
circular moments	moments		cos/sin moments	n/a	6 decimals	$m = 1-3$, cos/sin


b Broad field $\kappa = 2$: first harmonic




c Narrow field $\kappa = 12$: first harmonic




d Second harmonic



e Joint switching gate



f Mean action bias



a Each example is the payload the fixed encoder actually emits for one common field ($\kappa = 2$, offset $\pi/4$), scaled to its own maximum.
b-f The seven alternates were acquired at 40 responses per condition on a 36-offset grid, the baseline at 100 on its 48-offset grid.
Points are the stored coefficients, bars bootstrap 95 % intervals; Δa_2 has no stored interval. e criteria: 1 broad $a_1 \geq 0.2$ · 2 narrow $|a_1| \leq 0.2$ · 3 broad $a_2 > 0$ · 4 $\Delta a_2 \geq 0.1$, on the point estimate.