

a Full original prompt (16 lines, verbatim)

```
mrc_replay_f00 · sha256 255de816dde8... · 789 chars · 16 lines · task-relevant block = lines 11–16

1 You are an interaction operator for a phase on a circle.
2 The values are the first three normalized circular moments of the distribution of other phases relative to you.
3 Negative relative phase is behind you; positive relative phase is ahead of you.
4 Choose one social correction in response to this distribution:
5 - "advance": move in the positive phase direction
6 - "stay": apply no social correction
7 - "retard": move in the negative phase direction
8 Use only the relative distribution below. Return exactly one JSON object and no other text.
9 Required schema: {"social_action": "advance|stay|retard"}
10 Relative phase distribution as circular moments:
11 moment_1_cos: -0.101643
12 moment_1_sin: -0.045362
13 moment_2_cos: -0.056036
14 moment_2_sin: -0.097057
15 moment_3_cos: +0.278805
16 moment_3_sin: +0.115485
```

Lines 1 and 3–9 (the action contract) are byte-identical in all three variants; only line 2 and the payload block below it change. The six signed six-decimal moment components in lines 11–16 are the whole of the task-relevant information.

b Full reformatted prompt (15 lines; the 7 that differ from a)

```
mrc_replay_f00 · sha256 1e793d84f314... · 823 chars · 15 lines · task-relevant block = lines 11–15

lines 1, 3–9 byte-identical to a (not reprinted)
2 The table lists the first three normalized circular moments of the distribution of other phases relative to you (identical
information to the line-list moments encoding).
10 Relative phase distribution as circular moments (table):
11 harmonic | cos | sin
12 ---|---|---
13 1 | -0.101643 | -0.045362
14 2 | -0.056036 | -0.097057
15 3 | +0.278805 | +0.115485
```

The same six values in the same order, retyped as a markdown table: one row per harmonic, cos before sin. Nothing numerical is added or removed; the prompt grows by 34 characters of table scaffolding and the wording of line 2.


c Full length-matched prompt (24 lines; values and appended padding)

```
mrc_replay_f00 · sha256 2d4b913c490b... · 1496 chars · 24 lines · task-relevant block = lines 11–16


lines 1–10 byte-identical to a (not reprinted)
11 moment_1_cos: -0.101643
12 moment_1_sin: -0.045362
13 moment_2_cos: -0.056036
14 moment_2_sin: -0.097057
15 moment_3_cos: +0.278805
16 moment_3_sin: +0.115485
17 Note: length-matching placeholder only; ignore this line; it carries no phase information.
lines 18–23: six further byte-identical copies of line 17
24 Note: length-matching placeholder only; ignore this line; it carries
```

The padded prompt is the complete original prompt followed by 707 characters of neutral filler (8 lines; the last is cut mid-sentence by the deterministic 1496-character target). The filler carries no phase information, but it is neither empty nor inert: it is eight further instruction-shaped sentences appended after the values.


d Value identity audit



e Prompt size per variant



f Position of the task-relevant values



Claim boundary

The padded condition is not a length-only intervention. Relative to the original it changes prompt length (789 → 1496 characters), context volume (16 → 24 lines of instruction-shaped text) and the position of the task-relevant block (message-final → mid-message) simultaneously. Any difference it produces is attributable to that bundle, not to prompt length alone.