

1 Agroforestry SmartAgroforest: Poplar biomass modelling

2 Thomas Kirschstein^{1,1,1,*}

3 Abstract

Short-rotation agroforestry systems are increasingly promoted as a low-carbon feedstock option for bio-based value chains, but their economic viability depends on coordinated decisions on stand establishment, multi-cycle harvesting, and product cascading in spatially distributed supply chains. This paper develops a mixed-integer linear programming (MILP) model for the integrated design and operation of an agroforestry biomass supply chain with explicit age-lag constraints that link consecutive harvests at each site. The formulation couples allometric yield functions for different biomass types with a multi-product, multi-period network design model including storage, processing, and product quality cascades. The model is applied to a stylised case study of Central European poplar-based alley-cropping systems to explore trade-offs between harvest rotation length, product portfolios, and infrastructure configuration. We outline a computational experimentation plan to test the impact of allometric parameter uncertainty, price scenarios, and policy incentives on the optimal deployment of agroforestry systems in cleaner bioeconomy pathways.

4 *Keywords:* Agroforestry, Short-rotation coppice, Biomass supply chain, Product
5 cascading

6 1. Introduction

7 Agroforestry systems that integrate trees with agricultural crops (silvoarable systems)
8 are increasingly recognised as a promising land-use option to reconcile climate mitigation,
9 biodiversity conservation, and rural income generation on the same hectare of land (Toens-
10 meier, 2017). Temperate agroforestry systems (AFS) based on fast-growing species such

*Corresponding author

Email address: thomas.kirschstein@ikts.fraunhofer.de (Thomas Kirschstein)

Preprint submitted to Journal Name

June 7, 2026

11 as poplar, willow, alder, and black locust can deliver substantial biomass yields while im-
12 proving soil quality and providing multiple ecosystem services compared to conventional
13 monocultures (Huber et al., 2018). Biomass produced in AFS is considered as a sustain-
14 able feedstock and can be used either energetically, chemically or materially (e.g. in the
15 building sector). The latter two options are generally preferred over the energetic usage
16 from a cleaner production perspective as biogenic carbon is stored in products during
17 their life span which contributes to climate change mitigation.

18 Despite substantial research on ecological advantages and pioneering initiatives to
19 establish AFS in practice, the share of AFS in agricultural production systems is still
20 small. E.g., in Germany about 1200 hectares of silvoarable AFS are established in 2025,
21 which accounts for about 0.02% of total agricultural land use (Deutscher Fachverband
22 für Agroforstwirtschaft (DeFAF) e.V., 2026). One of the core challenges in establishing
23 AFS systems at large scale in practice is a lack of opportunities to generate substantial
24 revenues from woody biomasses of AFS. On the other hand, the rise of bioeconomy creates
25 substantial demands for woody biomass and requires a reliable and cost-efficient feedstock
26 supply. As woody biomasses are bulky feedstocks with low energy density, the design
27 of cost-efficient supply chains is crucial to ensure the economic viability of AFS-based
28 value chains. This requires coordinated decisions on stand establishment, multi-cycle
29 harvesting, and product cascading in spatially distributed supply chains, which can be
30 supported by integrated optimisation models that link stand-level growth dynamics to
31 regional supply chain design.

32 In the last two decades, a large body of research has analysed biomass supply chains
33 for bioenergy and biorefineries using mathematical programming models, often in the
34 form of mixed-integer linear programming (MILP) (Zahraee et al., 2020; Sharma et al.,
35 2013). These models typically optimise network configuration, feedstock sourcing, and
36 logistics under cost or profit objectives. They often treat biomass availability as an exoge-
37 nous input or rely on simplified agricultural production decisions. Moreover, downstream
38 processing of biomasses is concentrated on one particular value chain e.g. bioenergy plants
39 consuming all produced biomasses. Recent work has started to integrate operational de-
40 tails such as various biomass types, biomass growth models and regeneration processes
41 in multi-period supply chain models.

42 The present paper contributes to this literature in three ways. First, we propose
43 a novel MILP formulation for AFS-based biomass supply chain design that explicitly
44 links establishment decisions and consecutive harvest decisions, ensuring that harvesting
45 decisions at each site are consistent with minimum and maximum rotation ages. Second,
46 we embed allometric yield functions for different biomass types generating age-specific
47 yields for different woody biomass types (like stems, branches, or leaves and twigs). Third,
48 these different woody biomass types can be processed in specific downstream industries,
49 like chemical or paper industry as well as energy sector. The model aims to provide
50 strategic decision support for establishing regional AFS-based bioeconomy ecosystems
51 connecting multiple industries and product markets.

52 The remainder of the paper is structured as follows. Section 2 reviews the relevant
53 literature on agroforestry biomass systems, allometric biomass modelling, and biomass
54 supply chain optimisation. Section 3 summarises the MILP formulation for the agro-
55 forestry supply chain with age-lag constraints. Section 4 presents the case study instan-
56 tiation, the base-case optimisation results, and the sensitivity analysis, examining the
57 implications for cleaner production strategies.

58 **2. Literature review**

59 Agroforestry biomass systems, stand-level growth models, and biomass supply chain
60 optimisation have each been studied extensively, but they are rarely combined in an inte-
61 grated framework that links age-dependent stand dynamics to regional product-cascading
62 value chains (Zahraee et al., 2020; Sharma et al., 2013; Espinoza et al., 2017). This sec-
63 tion reviews (i) agroforestry systems with emphasis on system types, economics, and the
64 cascading use of biomass as the primary revenue driver; (ii) biomass growth models at
65 tree and stand level with explicit attention to the allometric–diameter–stand-biomass
66 pathway; and (iii) biomass supply chain design using mathematical programming. The
67 section concludes by identifying the modelling gap addressed in this paper.

68 *2.1. Agroforestry systems*

69 Agroforestry deliberately integrates woody perennials with crops and/or livestock on
70 the same management unit, with the aim of enhancing productivity, profitability, and

71 environmental performance (Nair, 1993; Toensmeier, 2017). In the temperate zone, three
72 distinct system types can be distinguished based on the spatial arrangement of trees and
73 the rotation length at which woody biomass is harvested.

74 **Short-rotation coppice (SRC)** is defined as a monoculture plantation of fast-
75 growing woody species covering the entire management unit, with planting densities
76 of 8,000–20,000 cuttings $\cdot\text{ha}^{-1}$. After each harvest the root system regenerates without
77 replanting. Rotation cycles are typically 3–7~years and total stand lifetime is 20–25~years
78 (Trnka et al., 2008; Faasch and Patenaude, 2012). SRCs are no AFSs in the narrow sense,
79 but it is helpful to benchmark biomass production.

80 **Short-rotation agroforestry systems (SRAFS)** integrate SRC-type tree strips
81 (typically 1–4 rows of the same fast-growing species like poplar or willow) into an oth-
82 erwise arable field in an alley-cropping arrangement. Crop production continues in the
83 inter-row strips (Huber et al., 2018; Graves et al., 2007). Thus, tree strips typically cover
84 10–30% of the total parcel area. Rotation lengths and total stand lifetime in SRAFS are
85 comparable to SRCs. In SRAFS all trees are effectively edge trees, exposed to higher light
86 and water availability than interior SRC trees. This boundary effect raises individual-tree
87 biomass accumulation but also intensifies competition with adjacent crop rows (Huber
88 et al., 2018).

89 **Long-rotation agroforestry systems (LRAFS)** use the same alley-cropping spa-
90 tial structure as SRAFS but with rotation cycles of 12–15~years or longer (Graves et al.,
91 2007; Nair, 1993). At this rotation length, individual trees develop substantial stem di-
92 ameters and the proportion of high-value timber increases markedly, enabling premium
93 material uses (veneer, sawlogs, engineered wood products) that are inaccessible in short-
94 rotation systems. Therefore, often timber-quality tree species (such as walnut, cherry,
95 oak, or high-grade poplar clones) are planted.

96 SRAFS and LRAFS are not clearly differentiated in practice. First, a clear cut-off age
97 is hard to define and, more importantly, the intended use of AFS biomass is not always
98 clear and can also change over time. Nonetheless, when establishing AFS, the structure
99 of AFS and its intended use after harvest drives planting decisions and, subsequently,
100 economic viability. Thus, in the present paper SRAFS and LRAFS are not considered as
101 separate AFS systems, but the interplay of intended use, establishment, and harvesting

102 decisions is analysed.

103 *2.2. Economic rationale of landowners*

104 The decision of a landowner to establish an AFS involves weighing substantial up-
105 front costs and long-term opportunity costs against a diversified revenue stream. On the
106 cost side, establishment requires site preparation, planting material, and planting labour,
107 typically amounting to 1,500–3,500 €/ha for SRC or SRAFS (Faasch and Patenaude,
108 2012; Testa et al., 2014). Recurrent harvest and refitting costs (machine hire, chipping,
109 transport to roadside) add approximately 200–400 €/ha per rotation depending on stand
110 density and equipment availability (Testa et al., 2014; Spinelli et al., 2009). During
111 the rotation, maintenance costs of AFS arise on a yearly basis. Next to expenses for
112 establishment, maintenance and harvesting, opportunity costs arise as no revenues from
113 crops are generated on tree strips. In regions with fertile soils and high cereal prices,
114 yearly crop revenues may sum up to 400–600 €/ha (Faasch and Patenaude, 2012; Graves
115 et al., 2007). Thus, opportunity costs are often the dominant cost driver in SRAFS
116 profitability analyses.

117 On the **benefit side**, the primary revenue of AFS is the sale of harvested woody
118 biomass, whose magnitude depends critically on rotation length, species, and site pro-
119 ductivity. For poplar-based SRAFS in Central Europe, typical yields range from 10
120 to 25 t of dry matter biomass per ha for typical rotation lengths (Huber et al., 2018;
121 Niemczyk and Thomas, 2021). Additionally, positive crop-yield effects in the inter-row
122 strips of SRAFS and LRAFS may result. Tree rows act as windbreaks, reducing soil
123 erosion and evapotranspiration; they provide partial shading that moderates heat stress
124 during drought years; and their root systems may improve water retention in the top-
125 soil (Graves et al., 2007; Grünewald et al., 2007). Empirical measurements in Central
126 European alley-cropping trials indicate that these microclimate effects can increase ce-
127 real yields in adjacent strips by 5–15% relative to open-field controls, partially or fully
128 compensating the loss of arable area occupied by the tree strips (Graves et al., 2007).
129 Beyond direct yield effects, AFS deliver broader ecosystem services (like soil organic
130 matter accumulation, carbon sequestration, biodiversity enhancement) that may lead to
131 agri-environment subsidies and carbon credits (Toensmeier, 2017; Faasch and Patenaude,
132 2012).

Nonetheless, economic attractiveness of AFS depends primarily on revenues of AFS biomass. Thereby, revenues are different for the types of biomass and in which value chain it is used. Often AFS biomasses are used energetically, i.e. for heat and power generation, or anaerobic digestion, which typically creates low prices per tonne of biomass.[REF] Alternatively, woody parts of the biomass (i.e., the stem and large branches) can also be used as pulp and paper grade material as well as feedstock for chemical industry or as timber achieving higher prices (Lamers et al., 2011) [EXTEND REFS]. Thus, fostering AFS establishment by maximizing economic returns from AFS biomass requires a strategic approach to product cascading that allocates different biomass fractions to the highest-value applications, while ensuring that the rotation length is aligned with the growth dynamics of the stand and the market demand for different biomass types (Lamers et al., 2011).

Thus, for making educated decisions on AFS establishment and harvesting, the expected biomass quantities at harvest for stem, branches, and residues need to be estimated. Thereby, the shares of the biomass types change with stand age. E.g.~the share of stem weight rises from roughly 55% at age 4 to over 75% at age 10 (Huber et al., 2018; Testa et al., 2014). Therefore, in Section 2.3 growth modelling approaches are reviewed that capture the age-dependent growth dynamics of different biomass types in AFS.

2.3. Biomass growth models

Reliable estimation of stand-level biomass quantities and their age-dependent composition is a necessary prerequisite for any strategic analysis of AFS-based supply chains. Individual-tree biomass is commonly approximated by species-specific allometric power laws relating shoot dry matter to stem base diameter, and these relationships have been calibrated for Central European poplar clones under SRC and SRAFS conditions (Huber et al., 2016, 2018). For supply chain planning, however, the relevant quantity is stand-level biomass per hectare over a multi-decade rotation horizon, which requires a temporal growth model that captures the characteristic sigmoidal accumulation trajectory of woody biomass. Therefore, a set of variables is used summarized in ??.

Table 1: Notation for the biomass growth and harvest yield models.

Symbol	Description
$M^{sl}(t)$	Total above- and belowground dry biomass per ha of AFS (t DM ha ⁻¹) at stand age t
$A(N)$	Stand-level Gompertz asymptote (t DM ha ⁻¹); density- and site-dependent
k	Gompertz growth-rate coefficient (yr ⁻¹)
t_0	Inflection age of stand biomass accumulation (yr)
N	Stand density (trees ha ⁻¹)
C_{site}	Site-quality constant (kg ha ^{β-1}); conservative: 4475, good site: 6471
β	Competition-density exponent; fitted $\hat{\beta} = 0.380$
ϕ_{ag}	Aboveground fraction of total stand biomass; $\phi_{\text{ag}} = 0.89$
$M^{ag}(t)$	Aboveground dry biomass per ha (t DM ha ⁻¹) at age t
$f_p(t)$	asymptotic fraction of AGB attributed to compartment $p \in \{s, b, r\}$ at age t
α_p, δ_p	Intercept and slope of the linear fraction model for compartment p
$q_p(t)$	Merchantable fraction of compartment p biomass at age t (logistic)
r_p	Logistic growth rate for merchantability of compartment p
$t_{50,p}$	Age at which 50% of compartment p biomass is merchantable (yr)
$Y_p(t)$	Merchantable dry biomass of compartment p per ha at harvest age t (t DM ha ⁻¹)
ω	Moisture content at felling (mass fraction); $\omega = 0.55$

161 2.3.1. Stand-level growth model

162 Stand-level aboveground and belowground dry biomass per hectare, $M(t)$, accumu-
163 lates in a right-skewed sigmoidal pattern with a relatively early inflection point, driven
164 by rapid juvenile shoot growth followed by self-thinning and competitive deceleration
165 as canopy closure intensifies (Niemczyk and Thomas, 2021; Testa et al., 2014). This
166 trajectory is described by a Gompertz model:

$$M(t) = A(N) \cdot \exp(-\exp(-k \cdot (t - t_0))), \quad (1)$$

167 where t_0 is the age of maximum instantaneous biomass increment and k determines how
168 quickly the stand approaches its site-specific asymptote $A(N)$. For Central European
169 poplar under medium-rotation AFS management (10–20 yr), analysing empirical data
170 from Huber et al. (2018), Niemczyk and Thomas (2021), and Jha (2018) yields parameter
171 intervals of $k \in [0.17, 0.2]$ and $t_0 \in [9, 10]$ years, depending on local specifications of the
172 AFS under study. Parameter t_0 indicates an upper bound on the optimal rotation age




Figure 1: Tree-level and stand-level Gompertz asymptote function $A(N)$ of planting density for the advanteguous ($N = 4$, $\beta = -0.3$) and disadvantageous ($N = 6.5$, $\beta = -0.5$) scenarios.

as growth slows down or diminishes entirely close to this age.

The asymptote $A(N)$ depends largely on planting density and can be modelled by a competition-density power law (Kira et al., 1961):

$$A(N) = C_{\text{site}} \cdot N^{1-\beta}, \quad (2)$$

where C_{site} encodes site quality, N indicates tree density (e.g. trees per hectare), and β is the competition exponent. Equivalently, the per-tree asymptote $A_{\text{tree}}(N) = A(N)/N = C_{\text{site}} \cdot N^{-\beta}$ decreases with density as individual trees have access to less growing space. Parameters C_{site} and β are highly site- and species-specific. For Poplar clones under European conditions, $\beta \in [0.3, 0.5]$ and $C_{\text{site}} \in [4, 6.5]$ (Niemczyk and Thomas, 2021, Kira et al. (1961)). Figure 1 shows asymptote functions according to (2) for advanteguous and disadvantageous site conditions.

When assessing potential downstream application of AFS biomass, biomass fraction are to be defined meeting the requirements of downstream consumers. E.g. for timber and biochemical applications, stem diameters of AFS trees need to exceed a minimum threshold in order to qualify as a suitable feedstock. In the following three biomass




Figure 2: Logistic diameter-class merchantability functions $q_p(t)$ for stem ($d > 15$ cm, green) and branches ($d > 7$ cm, orange); the 50% threshold ages t_{50} are indicated by dashed vertical lines.

fractions are distinguished: stems, branch wood, and residue. The stem fraction consists of stems with a diameter of at least 15 cm, while branch wood requires a diameter of at least 7 cm. The residue fraction comprises are smaller parts of the tree. To subdivide the total AFS biomass modelled by (1) into the three fractions depending on tree age, a logistic growth model is used:

$$q_p(t) = \frac{f_p}{1 + \exp(-r_p \cdot (t - t_{50,p}))}, \quad (3)$$

where $t_{50,p}$ is the age at which 50% of compartment p biomass surpasses the diameter threshold and f_p denotes the asymptotic share of component p for mature trees. Using empirical data from data from Civitarese et al. (2019), Jha (2018) and Niemczyk and Thomas (2021), $r_{stem} = 0.467, \text{yr}^{-1}$, $t_{50,stem} = 8.19$ years, and $f_{stem} = 0.75$ is estimated for the stem fraction (threshold $d > 15$ cm) and $r_{bran} = 0.698 \text{ yr}^{-1}$, $t_{50,bran} = 7.55, \text{yr}$, and $f_{bran} = 0.15$ for the branch fraction (diameter at least 7 cm at insertion). Figure 2 illustrates the development of the fraction shares over stand age.

Combining equations (1)–(3), the dry biomass yield of fraction p per hectare at harvest age t is:

$$\eta_p(t) = q_p(t) \cdot M(t), \quad (4)$$

with all non-merchantable fractions aggregated into the residue fraction. Fresh-weight




Figure 3: Stand-level aboveground biomass components for poplar under AFS management with $N = 250$ trees ha^{-1} . Empirical AGB observations compiled from Jha (2018), Civitarese et al. (2019), and Niemczyk and Thomas (2021). Grey band: typical medium-rotation harvest window (5–15 years).

202 yields at felling are obtained from dry matter yields via $\eta_p^{\text{fw}} = \eta_p / (1 - \omega)$, where the
 203 moisture content at felling $\omega = 0.55$ is taken from Civitarese et al. (2019). Figure 3
 204 shows the fractions' stacked biomass quantities $\eta_p(t)$ depending on stand age compared
 205 with empirical observations from Jha (2018)

206 2.4. Biomass supply chain design

207 The design and planning of biomass supply chains has attracted substantial research
 208 attention over the past two decades, driven by the need to ensure cost-efficient and
 209 sustainable feedstock provision for bioenergy and biorefinery applications. Several sys-
 210 tematic reviews provide comprehensive overviews of this literature. Cambero and Sowlati
 211 (2014) survey economic, social, and environmental assessment and optimisation studies
 212 for forest biomass supply chains, identifying MILP as the dominant modelling approach
 213 and noting a growing trend towards multi-objective formulations integrating life cycle
 214 assessment.

Yue et al. (2014) review biomass-to-bioenergy and biofuel supply chain models with a focus on multi-scale modelling, uncertainty treatment, and sustainability metrics, and conclude that the coupling of upstream feedstock dynamics with downstream network design remains an underexplored area. Malladi and Sowlati (2018) survey logistics-specific features of biomass supply chain models—seasonal availability, moisture content degradation, preprocessing steps—and highlight that most models treat biomass as a homogeneous commodity, neglecting quality differentiation. Zahraee et al. (2020) provide a recent meta-review of 140+ studies, confirming that cost minimisation is still the dominant objective, and that multi-product cascading formulations are rare.

The structure of biomass supply chain models typically encompasses three decision layers: (i) strategic network design (facility location, capacity sizing, technology selection), (ii) tactical planning (harvest scheduling, seasonal flows, inventory), and (iii) operational routing. The following paragraphs discuss key individual contributions and their specific methodological advances.

Ekşioğlu et al. (2009) develop one of the earliest large-scale MILP models for biomass-to-biorefinery supply chain design, integrating facility location, capacity sizing, and multimodal transport for lignocellulosic feedstocks. Their model minimises total system cost and introduces binary facility-opening variables that have since become standard in the field. A key limitation, however, is that biomass supply is treated as an exogenous input, so feedstock availability is not endogenised as a function of land-use or growth decisions. Mansoornejad et al. (2013) extend the strategic design perspective to forest biorefineries by integrating product portfolio design with supply chain configuration in a single MILP. Their model explicitly accounts for product conversion efficiencies along different processing pathways, enabling joint optimisation of process technology selection and logistics.

De Meyer et al. (2014) introduce the OPTIMASS framework, a generic MILP for biomass-based supply chain optimisation that explicitly models product quality cascades: higher-quality biomass classes can substitute for lower-quality demands downstream, whereas the reverse is infeasible. This cascade hierarchy, formalised through ordered product sets, is particularly relevant for woody biomass where stem, branch, and residue fractions command different market prices. The companion t-OPTIMASS

extension (De Meyer et al., 2016) incorporates temporal dynamics by explicitly representing biomass growth and regeneration over multiple periods, enabling simultaneous optimisation of harvest timing and network flows. However, in both OPTIMASS formulations the growth dynamics are represented as exogenous time-series rather than as age-structured stand models, so rotation-length decisions and age-dependent biomass quality are not endogenised. Arabi et al. (2019) demonstrate multi-period MILP extensions for bio-based supply chains with production dynamics, but focus on microalgae rather than woody biomass and do not address product quality cascades.

Sharma et al. (2013) identify supply-side uncertainty (yield variability, seasonal availability, moisture content) as the most critical source of risk in biomass supply chains. In response, a strand of literature has developed stochastic and robust optimisation extensions. Zahraee et al. (2020) document that two-stage stochastic MILP and robust optimisation approaches now account for roughly 30% of the modelling literature, with biomass yield uncertainty and price volatility as the dominant stochastic parameters.

Biomass supply chain research focusing specifically on agroforestry or SRC contexts is comparatively sparse. Espinoza et al. (2017) note that most supply chain models assume continuous feedstock availability and do not represent the periodic harvest cycles characteristic of coppice systems. Lamers et al. (2011) analyse feedstock design principles for lignocellulosic supply chains and argue that the allocation of different biomass fractions to valorisation pathways—product cascading—is a key lever for economic viability, yet is rarely optimised jointly with network design decisions. The model developed in Section 3 of this paper directly addresses this gap by endogenising stand age dynamics through binary age-lag variables and coupling component-specific yield coefficients with a product quality cascade.

Table 2 summarises the key modelling features of the reviewed contributions.

3. MILP Model for Agroforestry Supply Chain Design

Building on the biomass growth models introduced in Section 2.3 and the supply chain design literature reviewed in Section 2.4, this section describes the AFS supply chain design problem (AFS-SCD), a mixed-integer linear programming (MILP) model for the integrated design and operation of an agroforestry biomass supply chain with

Table 2: Key modelling features of selected biomass supply chain design studies.

Study	Objective	Multi-product	Quality cascade	Age dynamics	Uncertainty	Level
Eksioglu et al. (2009)	Cost min.	—	—	—	—	Strategic
Sharma & Taaffe (2013)	Cost min.	Partial	—	—	—	Strategic/Tactical
Mansoornejad et al. (2013)	Profit max.	✓	—	—	—	Strategic
Cambero & Sowlati (2014)	Cost/GHG/jobs	—	—	—	Stochastic	Strategic
Yue et al. (2014)	Cost/GHG	✓	—	—	—	Multi-scale
De Meyer et al. (2015)	Cost min.	✓	✓	Exogenous	—	Strategic/Tactical
De Meyer et al. (2016)	Cost min.	✓	✓	Exogenous TS	—	Multi-period
Lamers et al. (2015)	Cost/quality	✓	Partial	—	Scenario	Strategic
Espinoza et al. (2017)	Sustainability	✓	—	—	Scenario	Strategic
Malladi & Sowlati (2018)	Cost min.	Partial	—	—	—	Tactical/Oper.
Arabi et al. (2019)	Profit max.	✓	—	Exogenous	—	Multi-period
Zahraee et al. (2020)	Multi-obj.	✓	—	—	Stochastic	Strategic/Tactical
This paper	NPV max.	✓	✓	Endogenous	Scenario	Strategic/Multi-period

multiple AFS biomass types (i.e., stem, branch, and residue fractions) used as feedstocks for potential consumers in chemical, pulp and paper as well as energy industry.

3.1. Sets, Indices, and Time Structure

The model considers a set of agroforestry sites $\mathcal{I}$, storage/pre-treatment facilities $\mathcal{J}$, consumer sites $\mathcal{K}$, and biomass types $\mathcal{P} = \{stem, branches, residues\}$, whose growth models are outlined above. Time is discretised into annual periods $t \in \mathcal{T} = \{1, \dots, T_{\max}\}$. To reduce complexity, reflect legal definitions of SRAFS and LRAFS as well as discard implausible options (e.g. extremely long rotation cycles), $A^{\min}$ and $A^{\max}$ define minimum and maximum stand ages. Thus, harvest are possible in periods $\mathcal{T}^{\text{harv}} = \{A^{\min} + 1, \dots, T_{\max}\}$. To consistently model establishment and consecutive harvest decisions, the following arc sets are defined: $\mathcal{S}^{\text{est}}$ defines potential establishments of AFS. If an AFS is established in period $t \in \mathcal{T}$, arc $(0, t)$ is selected. Harvest set $\mathcal{S}^{\text{harv}}$ summarizes all potential consecutive harvest periods within the age interval $[A^{\min}, A^{\max}]$. I.e., if an AFS is established




Figure 4: Network structure of set $\mathcal{S}$ for $T = 8$, $A_{\min} = 3$, $A_{\max} = 5$. Dashed blue arcs: establishment arcs $(0, t)$, $t \in \{1, \dots, T-1\}$. Solid green arcs above: harvest arcs (s, t) with odd s ; below: harvest arcs with even s . Solid red arcs: termination arcs $(s, T+1)$, $s \in \{A_{\min} + 1, \dots, T\}$.

or harvested in period s and next harvest is in period t , arc (s, t) is selected. Finally, if there is no subsequent harvest after period t , the AFS is terminated by selecting arc $(t, T^{\max} + 1)$. Termination arcs are summarized in set $\mathcal{S}^{term}$. All arc sets are formally defined as follows:

$$\begin{aligned}\mathcal{S}^{est} &= \{(0, t) \mid t \in \{1, \dots, T^{\max} - A^{\min}\}\}, \\ \mathcal{S}^{harv} &= \{(s, t) \mid s, t \in \mathcal{T} \wedge t - s \in \{A^{\min}, \dots, A^{\max}\}\}, \\ \mathcal{S}^{term} &= \{(s, T^{\max} + 1) \mid s \in \{A^{\min} + 1, \dots, T_{\max}\}\}, \\ \mathcal{S} &= \mathcal{S}^{est} \cup \mathcal{S}^{harv} \cup \mathcal{S}^{term}.\end{aligned}$$

Figure 4 illustrates this network structure of all arc sets for $T = 8$, $A^{\min} = 3$, $A^{\max} = 5$.

3.2. Decision Variables

Temporal flow Variables z_{ist} indicate on which quantity of the area of site i an AFS is operated between $(s, t) \in \mathcal{S}$. Depending on the arc type, this implies establishment, harvest, or termination. Selected arcs build a network flow over the complete planning horizon from $t = 0$ to $T^{\max} + 1$. Figure 5 illustrates a simple network flow with establishment of an AFS in period 1 and harvests in periods 5 and 8.

Spatial flow variables X_{ijpt} and $X_{jkpp't}$ represent transport of products from AFS sites to storage/pre-treatment facilities and from there to consumers, respectively, while S_{jpt} captures end-of-period inventory at facility j . Table 3 summarises all sets, decision variables, and parameters used in the MILP formulation, while η_{pa} refers to (4).




Figure 5: Example of a feasible path through the network for $T = 8, A_{\min} = 3, A_{\max} = 5$: establishment in period 1, harvests in periods 5 and 8, termination at $T + 1$.

3.3. Objective Function

As discussed in Section 2.1, the economic attractiveness of AFS supply chains is modelled from a global perspective taking into account all processes, activities, and participants involved in finally serving customer markets with AFS-based feedstocks. Therefore, revenues for the different biomass fractions and are weighed against costs occurring at all value-adding stages of the supply chains. Revenues created by selling AFS-based feedstocks to different industrial consumers are counterweighted by establishment, opportunity, harvest, transport, and storage costs of landowners, agricultural firms as well as biomass logistics companies. The model therefore maximises total profit of all participants in the AFS supply chain over the planning horizon as follows:

$$\begin{aligned}
 \max Z = & \sum_{k \in \mathcal{K}} \sum_{p \in \mathcal{P}} R_{kp} \cdot \sum_{j \in \mathcal{J}} \sum_{(p', p) \in \mathcal{Q}} \sum_{t \in \mathcal{T}} X_{jkp'pt} \\
 & - \sum_{i \in \mathcal{I}} c_i^{est} \cdot \sum_{(0, t) \in \mathcal{S}^{est}} z_{i0t} \\
 & - \sum_{i \in \mathcal{I}} (c_i^{main} + c_i^{opp}) \cdot (t - s) \cdot \sum_{(s, t) \in \mathcal{S}^{harv}} z_{ist} \\
 & - \sum_{i \in \mathcal{I}} c_i^{harv} \cdot \sum_{(s, t) \in \mathcal{S}^{harv}} z_{ist} \\
 & - \sum_{i \in \mathcal{I}} \sum_{j \in \mathcal{J}} \sum_{p \in \mathcal{P}} \sum_{t \in \mathcal{T}} c_p^{tr-raw} \cdot d_{ij} \cdot X_{ijpt} \\
 & - \sum_{j \in \mathcal{J}} \sum_{k \in \mathcal{K}} \sum_{(p, p') \in \mathcal{Q}} \sum_{t \in \mathcal{T}} c_{p'}^{tr-pre} \cdot d_{jk} \cdot X_{jkpp't} \\
 & - \sum_{j \in \mathcal{J}} \sum_{p \in \mathcal{P}} \sum_{t \in \mathcal{T}} c_j^{stor} \cdot S_{jpt}
 \end{aligned} \tag{5}$$

Here, R_{kp} are product- and consumer-specific revenues for each ton of biomass fraction (€/t). The opportunity cost term penalises the land use when AFS are established.

Table 3: Notation for the MILP model.

Sets & Indices	
$i \in \mathcal{I}$	Agroforestry sites
$j \in \mathcal{J}$	Storage / pre-treatment facilities
$k \in \mathcal{K}$	Consumer sites
$p \in \mathcal{P}$	Product types (stem, branches, residues)
$(p, p') \in \mathcal{Q}$	Admissible product-substitution pairs (quality cascade)
$\mathcal{T} = \{1, \dots, T\}$	Planning periods (years)
$\mathcal{T}^{\text{harv}} = \{A^{\min} + 1, \dots, T\}$	Feasible harvest periods
$\mathcal{S}^{\text{est}} = \{(0, t) \mid t \in \{1, \dots, T - A^{\min}\}\}$	Establishment arcs: dummy source to period t
$\mathcal{S}^{\text{harv}} = \{(s, t) \mid s, t \in \mathcal{T}, t - s \in \{A^{\min}, \dots, A^{\max}\}\}$	Harvest cycles within age-lag bounds
$\mathcal{S}^{\text{term}} = \{(s, T + 1) \mid s \in \{A^{\min} + 1, \dots, T\}\}$	Termination arcs to dummy sink $T + 1$
$\mathcal{S} = \mathcal{S}^{\text{est}} \cup \mathcal{S}^{\text{harv}} \cup \mathcal{S}^{\text{term}}$	Age-lag arc set (establishment $\cup$ harvest $\cup$ termination)
Decision Variables	
$z_{ist} \in \{0, \text{AREA}_i\}$	Area of site i with AFS operation between s and t
$X_{ijpt} \geq 0$	Transport flow (t) of p from site i to facility j in t
$X_{jkpp't} \geq 0$	Flow of p from facility j to consumer k satisfying demand p' in t
$S_{jpt} \geq 0$	Inventory (t) of product p at facility j end of period t
Parameters	
T	Length of planning horizon (years)
$A^{\min}, A^{\max}$	Minimum / maximum stand age at harvest (years)
AREA_i	Area of site i (ha)
η_{pa}	Yield coefficient (t/ha) of fraction p at stand age a , derived from (4)
R_{kp}	Revenue (€/t) for product p at consumer k
C_i^{est}	Establishment cost (€/ha) at site i
C_i^{opp}	Annual opportunity cost (€/ha) at site i
C_i^{harv}	Harvest & refitting cost (€/ha) at site i
$c^{\text{tr-raw}}$	Transport cost rate (€/t km) for raw biomass
$c^{\text{tr-pre}}$	Transport cost rate (€/t km) for pre-treated biomass
c_j^{stor}	Storage holding cost (€/t) at facility j
d_{ij}, d_{jk}	Distance (km) between nodes
$\text{CAP}_j^{\text{stor}} / \text{CAP}_j^{\text{proc}}$	Storage and processing capacity (t) at facility j
$D_{kpt}^{\max}$	Maximum demand (t) of fraction p at consumer k in period t

317 Thereby, c_i^{opp} can be negative or positive depending on the site-specific conditions. It
318 comprises effect of lost field crop revenues due to AFS as well as higher yields of remain-

ing field crop areas e.g. due to wind and water erosion protection by AFS. While the
 assessment of lost field crop revenues is usually well predictable, the economic evaluation
 of positive ecological effects of AFS (e.g. on neighboring crop yields) is more difficult.
 Thus, c_i^{opp} can also contain regulatory subsidies to support establishing and maintaining
 AFS. Transport cost terms mirror the two-stage flow structure of the AFS supply chain
 with differentiated rates for raw and pre-treated biomass depending on the biomass type.
 Cost rates differ because as e.g. the density and water content of the shipped biomasses
 differ or because specialized equipment (e.g. for log transports) is used [REFERENCES].
 Moreover, site-specific establishment cost for planting the AFS trees is considered, next
 to yearly maintenance costs and harvesting cost. All these costs scale with the size of
 a site ($AREA_i$) measured in hectar. Maintenance cost comprise e.g. costs for trimming,
 replanting, and pruning unnecessary shoots. Storage costs are considered if biomasses are
 stored for more than a year to compensate direct costs (e.g. for storage site maintenance)
 but primarily opportunity cost due to potential material losses and capital commitment.
 The usual case is that AFS are harvested at the beginning of a year. Harvested biomass
 dry during spring and summer such that the biomasses can be used in autumn or winter
 the same year. As drying is necessary for most industrial applications and beneficial
 for transport economics, drying storage in the year of harvest is not associated with
 additional cost.

3.4. Constraints

Constraints (6) limit each site to at most one establishment decision over the planning
 horizon. Constraints (7) enforce flow conservation in each period. If an activity in period
 $t \in \mathcal{T}$ takes place, there needs to be a preceeding activity (harvest or establishment) and
 a succeeding activity (harvest or termination). This way, (7) guarantee valid (possibly
 empty) activity paths over the complete time horizon for each site. Constraints (8) links
 the binary harvest-cycle variables to physical yield quantities via the age-dependent yield
 coefficients $\eta_{p(t-s)}$. These coefficients are pre-computed by evaluating the component-
 specific Gompertz functions (??) and (??) at stand age $a = t - s$ and scaled by site
 area $AREA_i$. Thus, implicitly we assume constant yields per hectar for each site i . Note
 that this simplification can be dropped and site-specific yields $\eta_{ip(t-s)}$ could be intro-
 duced without increasing numerical complexity of the AFS-SCD . Constraints (??)–(9)

link harvest quantities to transport flows and ensure inventory balance at each facility, following the multi-period network-flow structure of OPTIMASS (De Meyer et al., 2014, 2016). Thereby, harvest quantities can be smaller than available AFS biomasses allowing partial harvesting. Constraints (10)–(11) enforce storage and processing capacity limits at each facility j . Constraints (12) implement product usage at multiple consumption sites k . Thereby, $(p', p) \in \mathcal{Q}$ defines a product mapping allowing high-quality product p' (e.g. stems) satisfying demand of a lower-quality products p up to maximum demand $D_{kpt}^{\max}$. This way, the cascading principle is operationalized as a central economic rationale.

$$\sum_{(0,t) \in \mathcal{S}^{est}} z_{i0t} \leq AREA_i \quad \forall i \in \mathcal{I} \quad (6)$$

$$\sum_{(s,t) \in \mathcal{S}} z_{ist} = \sum_{(t,u) \in \mathcal{S}} z_{itu} \quad \forall i \in \mathcal{I}, t \in \mathcal{T} \quad (7)$$

$$\sum_{j \in \mathcal{J}} X_{ijpt} \leq \sum_{(s,t) \in \mathcal{S}^{harv}} \eta_{p(t-s)} \cdot z_{ist} \quad \forall i \in \mathcal{I}, p \in \mathcal{P}, t \in \mathcal{T}^{harv} \quad (8)$$

$$S_{jpt} = S_{jp,t-1} + \sum_{i \in \mathcal{I}} X_{ijpt} - \sum_{k \in \mathcal{K}, (p,p') \in \mathcal{Q}} X_{jkpp't} \quad \forall j \in \mathcal{J}, p \in \mathcal{P}, t \in \mathcal{T}^{harv} \quad (9)$$

$$\sum_{p \in \mathcal{P}} S_{jpt} \leq CAP_j^{stor} \quad \forall j \in \mathcal{J}, t \in \mathcal{T} \quad (10)$$

$$\sum_{i \in \mathcal{I}, p \in \mathcal{P}} X_{ijpt} \leq CAP_j^{proc} \quad \forall j \in \mathcal{J}, t \in \mathcal{T}^{harv} \quad (11)$$

$$\sum_{j \in \mathcal{J}, (p', p) \in \mathcal{Q}} X_{jkp'pt} \leq D_{kpt}^{\max} \quad \forall k \in \mathcal{K}, p \in \mathcal{P}, t \in \mathcal{T}^{harv} \quad (12)$$

$$z_{ist}, X_{ijpt}, X_{jkp'pt}, S_{jpt} \geq 0 \quad \forall i, j, k, p, p', t \quad (13)$$

The yield coefficients η_{pa} in (8) are the critical bridge between the stand-level growth model of Chapter~2 and the supply chain optimisation. For stand age $a = t - s$ and product component p , they are computed as:

$$\eta_{pa} = f_p(a) \cdot M^{sl}(a) = \frac{h_p(a)}{\sum_{p'} h_{p'}(a)} \cdot a^\infty \cdot e^{-e^{-b'/1} \cdot (a-\tau)}, \quad (14)$$

where $M^{sl}(a)$ follows from (??) and $f_p(a)$ follows from (??). For poplar clone Max~3 under SRAFS conditions, the component-specific Gompertz parameterisations from Section

2.3 imply that $\eta_{\text{stem},a}$ rises steeply between ages~4 and 10, while $\eta_{\text{branch},a}$ and $\eta_{\text{residue},a}$ plateau earlier, as illustrated in Figure ???. This age-dependence of product fractions is the core mechanism through which rotation-length decisions — governed by $A^{\min}$ and $A^{\max}$ and the arc set $\mathcal{S}$ — determine achievable product portfolios and, hence, revenues in the objective function (5).

4. Case Study

The proposed MILP model is intended to support the design of agroforestry biomass supply chains for cleaner production in specific regional contexts. In a forthcoming case study, we focus on poplar-based alley-cropping systems in a temperate European setting, informed by empirical data from SRAFS trials in Southern Germany and SRC plantations in Central Europe (Huber et al., 2018; Trnka et al., 2008; Testa et al., 2014).

4.1. Study Region and Supply Chain Configuration

The proposed AFS-SCD model is instantiated on a real-world biomass supply chain located in the tri-state region of Saxony-Anhalt, northern Thuringia, and northern Saxony, Germany (Figure 6). This region combines the highest density of registered short-rotation coppice (SRC) Feldblöcke in eastern Germany with a cluster of major wood-processing industries that collectively represent one of the largest forest-based biomass demand centres in Central Europe. The spatial extent of the study region covers approximately 250×200 km, with road distances between potential KUP sites and consumer locations ranging from under 10 km to over 180 km.

The supply chain comprises three node types: (i) KUP production sites $\mathcal{I}$, (ii) pre-treatment and intermediate storage facilities $\mathcal{J}$, and (iii) consumer sites $\mathcal{K}$. Candidate KUP sites are drawn from the official Feldblock register of Saxony-Anhalt, filtered to parcels with a minimum area of 1 ha and classified as potentially suitable for SRC under the InVeKoS land-use scheme. Following the two-stage spatial clustering procedure described in Section 4, the $|\mathcal{I}| = 2239$ raw Feldblöcke are grouped into K super-sites using DBSCAN ($\varepsilon = 15$ km, $\text{minPts} = 3$) and Ward.D2 hierarchical clustering (maximum within-cluster radius 15 km), yielding a computationally tractable MILP instance while preserving the total eligible area. The HAC cluster assignments, visible as distinct colour




Figure 6: AFS supply chain network in Saxony-Anhalt. Grey lines: German federal state boundaries. Blue lines: major rivers. Coloured polygons: potential KUP/AFS sites grouped by HAC super-site (colours encode cluster membership; no legend). Orange symbols: pre-treatment facilities (circle = sawmill, triangle = logistics hub, size proportional to processing capacity). Coloured squares: consumer sites (violet: P1 chemical/pulp, blue: P2 pulp/paper, red: P3 energy/biogas, size proportional to total demand).

zones in Figure 6, confirm a spatially coherent partitioning: dense KUP corridors along the Elbe and Saale floodplains form contiguous super-sites, while isolated parcels in the Harz foothills constitute smaller or singleton clusters.

Two types of intermediate infrastructure nodes are considered: conventional sawmills and logistics hubs. Sawmills perform primary mechanical processing (debarking, chipping) and can serve product streams P1 and P2; logistics hubs serve as consolidation and temporary storage points for all three product grades and are characterised by lower capital intensity but limited processing capacity. The $|\mathcal{J}| = 11$ candidate storage/pre-treatment locations are sourced from publicly registered forestry enterprises and existing logistic nodes in the study region. Road distances d_{ij} (site i to storage j) and d_{jk} (storage j to consumer k) are computed via the OSRM open-source routing engine using the German road network, providing realistic transport cost estimates that are embedded directly in the MILP objective.

4.2. Consumer Demand and Product Classification

Nine consumer sites are included in the base case ($|\mathcal{K}| = 9$), covering the full quality cascade from high-value chemical/pulp applications down to energy use (Table 4). Consumer demands $D_{kpt}^{\max}$ are derived from publicly reported annual throughput figures, production capacities, and regulatory filings, and are held constant across periods ($D_{kpt}^{\max} = D_{kp}^{\max} \forall t \in \mathcal{T}$) to reflect stable long-term offtake contracts.

Three biomass product grades are distinguished, reflecting the cascading-use principle embedded in the AFS-SCD objective:

- **P1 – Chemical/pulp grade** ($p = 1$): long-fibre hardwood chips suitable for chemical pulping and biorefinery conversion. Dominated by Mercer Stendal GmbH (Arneburg, 1{,}500 kt/yr) and Zellstoff Rosenthal/Mercer (Blankenstein, 1{,}000 kt/yr), which together account for 403% of total P1 demand. UPM Biochemicals (Leuna) contributes 500 kt/yr of high-purity beech-fraction demand for biochemical conversion. Gate prices for P1 range from 80 to 120 €/t wood input.
- **P2 – Sawlog/pulpwood grade** ($p = 2$): roundwood and chipped material suitable for mechanical processing in sawmills. Demand is distributed across six smaller




Figure 7: Total biomass demand by consumer type and grade (P1 chemical, P2 pulp & paper, P3 energy/biogas). Bars show aggregated annual demand in kt wood input per year across all individual plants within each consumer type.

422 facilities with individual annual demands of 5–300 kt/yr. Gate prices range from
 423 55 to 75 €/t.

- 424 • **P3 – Energy/pellets grade** ($p = 3$): residual wood fractions (chips, bark, off-
 425 cuts) used for heat and electricity generation or pellet production. This grade
 426 absorbs material that cannot meet P1 or P2 quality thresholds, operationalising
 427 the cascade constraint in the MILP. Gate prices range from 30 to 40 €/t.

428 The demand derivation follows a three-step procedure. First, publicly available ca-
 429 pacity data (kt wood input per year) are collected for each facility from official sources,
 430 industry reports, and corporate disclosures (Mercer Stendal GmbH, 2024; UPM Bio-
 431 chemicals, 2024). Second, the total annual capacity is assigned to the product grade that
 432 corresponds to the primary feedstock of each facility (P1 for chemical/biorefinery pro-
 433 cesses, P2 for mechanical sawmilling, P3 for thermal conversion and pellet lines). Third, a
 434 minor P3 component is added to sawmill facilities to capture by-product streams (bark,
 435 sawdust), consistent with observed industrial practice. The resulting demand matrix
 436 $D_{kp}^{\max}$ (kt/yr) is shown in Figure 7 and summarised in Table 4. Aggregate demand across
 437 the study region totals 620.5 kt/yr for P1, 410 kt/yr for P2, and 131.7 kt/yr for P3.

4.3. MILP Model Parameters

Table 5 summarises all scalar parameters of the AFS-SCD instance. The planning horizon covers $|\mathcal{T}| = 15$ periods, corresponding to one full poplar rotation (years 1–15), with a minimum harvest age $a^{\min} = 4$ and maximum productive stand age $a^{\max} = 15$ (Lehmkuhl et al., 2023). Biomass yield functions η_{pa} (odt ha⁻¹ yr⁻¹) follow the age-structured Gompertz profile calibrated in Section 2.3, where distinct yield curves are assigned to each product grade to reflect the fraction of stem, branch, and foliage biomass that qualifies under each quality threshold.

Transport costs are disaggregated into two components reflecting the two-echelon logistics structure. Raw material transport from site i to pre-treatment facility j incurs a variable cost $c^{tr-raw} \cdot d_{ij}$ (€ t⁻¹ km⁻¹), while processed material transport from j to consumer k is costed at $c^{tr-pre} \cdot d_{jk}$. The pre-treatment rate c^{tr-pre} is set lower than c^{tr-raw} to reflect the higher load density and standardised packaging of chipped and pelletised material compared to loose roundwood. An opportunity cost parameter c^{opp} (€ ha⁻¹ yr⁻¹) accounts for foregone agricultural revenue on converted parcels, calibrated to the average arable land rental rate in Saxony-Anhalt (Statistisches Bundesamt (Destatis), 2023). Storage capacity at each facility j is bounded by $\bar{S}_j$, and processing capacity by $\bar{C}_j$ (kt yr⁻¹), both drawn from publicly available facility data.

4.4. Optimization results

The AFS-SCD model is solved for the Saxony-Anhalt base-case instance described in Section 4. All results presented in this section refer to the base-case parametrisation summarised in Table 5. The model selects a subset of KUP super-sites for establishment and identifies the optimal harvest schedule, intermediate facility utilisation, and product allocation across the 15-period planning horizon.

Figure 8 shows the spatial configuration of the optimal supply chain. Active super-sites are concentrated in the Elbe and Saale floodplains, where high biomass yields and proximity to major processing facilities create the most favourable economics. Sites in the Harz foothills and peripheral areas with high opportunity costs are not selected. The pie charts overlaid on each active site indicate the product-mix composition: sites closer to P1 consumers (chemical/pulp grade) allocate a larger stem fraction, while more remote sites rely more heavily on P3 (energy) grade biomass.

Figures ?? and ?? report the biomass flows over the planning horizon. Total annual biomass throughput rises steeply in the first five periods as newly established sites reach minimum harvest age, stabilises during the middle of the horizon, and undergoes a partial decline towards the end as rotation cycles exhaust the planning window. The product cascade is clearly visible: stem biomass (P1) dominates the early harvest periods when young stands deliver the highest merchantable stem fraction, while branch and residue shares increase as stands mature and are harvested at longer rotation lengths.

The distribution of harvesting cycle lengths at active sites is illustrated in Figure ?. The majority of harvest events occur at stand ages between the minimum age $a^{\min} = 4$ years and approximately 8–10 years, reflecting the trade-off between cumulative yield growth and the opportunity cost of delayed harvesting. A secondary peak at longer rotation lengths (12–15 years) corresponds to sites with lower opportunity costs and higher P1 demand in their vicinity.

Figure ?? presents the aggregate cost–profit waterfall over the full horizon. Total revenue is dominated by P1 deliveries to the two large pulp mills. Opportunity costs and transport costs are the two largest cost drivers; establishment costs are one-time and comparatively modest. The site-level revenue–cost decomposition in Figure ?? confirms that profitability is highly heterogeneous: a small number of large sites with low opportunity costs and short distances to P1 consumers account for the bulk of total net profit, while several marginal sites operate near break-even. Figure ?? reveals a clear negative relationship between opportunity cost rate and site profitability, with sites exceeding 300 € ha^{−1} yr^{−1} rarely selected in the optimal solution.

5. Sensitivity analysis

To assess the robustness of the baseline results and to identify the principal drivers of supply chain profitability, a factorial sensitivity analysis is conducted. The analysis follows a full-factorial design over three scenario dimensions: opportunity cost level (€ ha^{−1} yr^{−1}), a cost multiplier applied to all variable cost parameters (establishment, harvest, transport, and storage), and a revenue multiplier applied to all gate prices. The resulting $2 \times 2 \times 2 = 8$ scenarios are solved independently in addition to the baseline, yielding nine comparable instances (Table 6).




Figure 8: Optimal agroforestry supply chain network. Green polygons: active super-sites with biomass harvest; grey polygons: non-selected sites. Pie charts at active sites show the product mix of harvested biomass (stem = P1, branches = P2, residues = P3), scaled by total harvested volume. Orange symbols: pre-treatment facilities (circle = sawmill, triangle = logistics hub). Coloured squares: consumer sites by dominant demand category.




Figure 9: Total production quantity of biomass types and its industrial usage over planning horizon (in tons).




Figure 10: Total biomass delivered to consumers by product type over the planning horizon. Stacked areas show period-level volumes of stem (P1), branches (P2), and residues (P3) flowing from storage hubs to all consumers. Dashed line: total harvested raw biomass shipped from sites to hubs.




Figure 11: Distribution of harvesting cycle lengths at active agroforestry sites. Each bar represents the number of individual harvest events (over all periods and active sites) whose cycle length (stand age at harvest, i.e. $t - s$) falls in that year bin. Vertical dashed line: mean cycle length. Active sites are defined as sites with at least one selected harvest arc in the optimal solution.




Figure 12: Total cost–profit breakdown across all active sites over the planning horizon. The left panel (waterfall) decomposes the objective value into revenue and individual cost categories; the right panel shows the period-level trajectory of revenues and stacked costs. Cultivation costs are split into establishment, harvesting, maintenance, and opportunity costs; logistics costs cover raw biomass transport (site→hub) and pre-processed transport (hub→consumer); storage costs reflect hub inventory holding charges.




Figure 13: Total revenue and cost breakdown per active agroforestry site over the full planning horizon. Each bar represents one active site; revenue (green, above zero axis) and cost components (stacked below) are expressed in thousand euros per hectare for comparability across sites of different size. Sites are ordered by descending net margin.





Figure 14: Scatterplot of active agroforestry sites: opportunity cost rate (€ ha⁻¹ yr⁻¹) on the x-axis versus demand-weighted average delivery distance (km) on the y-axis. Point size is proportional to the site's net margin (€ ha⁻¹ yr⁻¹); sites with negative net margin are shown as open circles. A LOESS smoothing line indicates the joint trend.

Table 6 summarises the key performance indicators across all scenarios. Total profit per hectare per year is most sensitive to the revenue multiplier: elevated gate prices (revenue multiplier = 1.5) substantially improve profitability, while reduced prices (multiplier = 0.5) push marginal sites into loss territory. The supply chain remains profitable in all scenarios with full or elevated revenue even when opportunity costs are high. Scenarios combining reduced revenue (multiplier = 0.5) with high opportunity costs consistently yield negative net profits, indicating that the economic viability of AFS-based supply chains is critically conditional on achieving sufficient product-quality premiums from P1 off-takers. The number of active sites and total wood throughput respond monotonically to the revenue multiplier, confirming that higher gate prices incentivise the activation of marginal sites.

The OLS regression reported in Figure ?? and Table 7 decomposes profit variation across scenarios and sites into effects of four explanatory variables: opportunity cost rate, cost level, revenue level, and log-transformed site area. The revenue multiplier carries the largest absolute coefficient, followed by opportunity cost rate; site area exerts

514 a positive but diminishing marginal effect consistent with economies of scale in logistics
515 and harvesting. Rotation length is positively associated with profit in low-opportunity-
516 cost settings but negatively so when foregone agricultural revenue is high, confirming the
517 rotation-length trade-off in the AFS-SCD formulation (Section 3).



519 6. Conclusion

520 This paper has developed and applied the AFS-SCD model, a MILP formulation
521 for the integrated design and operation of agroforestry biomass supply chains. The
522 model endogenises stand age dynamics through binary arc-based age-lag variables, cou-
523 ples component-specific Gompertz yield coefficients for stem, branch, and residue frac-
524 tions with multi-echelon logistics decisions, and embeds a product quality cascade that
525 allocates biomass grades to chemical, pulp, and energy markets within a unified opti-
526 misation framework. The formulation is, to the best of our knowledge, the first supply
527 chain model to simultaneously optimise AFS establishment timing, consecutive harvest
528 scheduling under rotation-age constraints, and product-grade allocation across spatially
529 heterogeneous consumer markets.

530 The case study for the Saxony-Anhalt tri-state region demonstrates the practical rel-
 531 evance of the approach. The optimal supply chain concentrates AFS establishments in
 532 the Elbe and Saale floodplains, where high biomass productivity and proximity to large
 533 pulp mills create the most favourable economics. The sensitivity analysis confirms that
 534 profitability depends primarily on achievable gate prices for high-quality (P1) biomass
 535 grades: scenarios combining reduced revenue with high opportunity costs yield negative
 536 net profits, whereas scenarios with full or elevated prices remain viable under cost pres-
 537 sure. Opportunity cost is the dominant site-level discriminator, with parcels exceeding
 538 approximately $300 \text{ € ha}^{-1} \text{ yr}^{-1}$ rarely selected in the optimal solution. These findings
 539 underscore the importance of product cascading as a strategic lever for AFS viability:
 540 maximising the share of stem biomass directed to high-value chemical and pulp applica-
 541 tions substantially improves profitability compared to energy-only offtake strategies.

542 Methodologically, the AFS-SCD model bridges the gap between stand-level growth
 543 modelling and regional supply chain optimisation identified in the literature (Zahraee
 544 et al., 2020; Lamers et al., 2011). The age-lag constraint structure generalises to other
 545 perennial biomass crops with periodic coppice cycles, such as willow or black locust,
 546 and to long-rotation silvoarable systems in which rotation length is a strategic variable.
 547 The model is extensible to stochastic settings by replacing deterministic yield coefficients
 548 with scenario-weighted counterparts or by incorporating robust optimisation over yield
 549 uncertainty intervals (Sharma et al., 2013).

550 Several limitations point to directions for future research. First, consumer demand
 551 is treated as exogenous and time-invariant; endogenising demand responses to biomass
 552 price changes would require a partial-equilibrium extension. Second, the case study uses a
 553 single allometric scenario calibrated to Central European poplar; propagating Gompertz
 554 parameter uncertainty through to supply chain outcomes would strengthen the robustness
 555 analysis. Third, environmental co-benefits of AFS — including carbon sequestration,
 556 nitrate leaching reduction, and biodiversity enhancement — are not monetised in the
 557 current objective. Integrating life cycle assessment indicators as additional objectives
 558 or constraints would support a more comprehensive sustainability evaluation, consistent
 559 with the cleaner production framing of this work.




Figure 15: OLS-Diagnostik: Residuen vs. Fitted, Q-Q-Plot, Scale-Location und Cook's Distance.

7. Appendix

NULL

References

- Mohsen Arabi, Saeed Yaghoubi, and Hamed Tajik. Optimal design of a microalgae-based biofuel supply chain with co2 reduction and hydrogen production. *Computers & Chemical Engineering*, 130:106530, 2019. ISSN 0098-1354. doi: 10.1016/j.compchemeng.2019.106530.
- Claudia Cambero and Taraneh Sowlati. Assessment and optimization of forest biomass supply chains from economic, social and environmental perspectives—a review of literature. *Renewable and Sustainable Energy Reviews*, 36:62–73, 2014. ISSN 1364-0321. doi: 10.1016/j.rser.2014.04.041.
- Vincenzo Civitarese, Andrea Acampora, Giulio Sperandio, Alberto Assirelli, and Rodolfo Picchio. Production of wood pellets from poplar trees managed as coppices with different harvesting cycles. *Energies*, 12(15):2973, 2019. doi: 10.3390/en12152973. Open access.

- 572 Anouck De Meyer, Dirk Cattrysse, Jussi Rasinmäki, and Jos Van Orshoven. Methods to optimise the
573 design and management of biomass-for-bioenergy supply chains: A review. *Renewable and Sustainable*
574 *Energy Reviews*, 31:657–670, 2014. ISSN 1364-0321. doi: 10.1016/j.rser.2013.12.036.
- 575 Anouck De Meyer, Dirk Cattrysse, and Jos Van Orshoven. A generic mathematical model to optimise
576 strategic and tactical decisions in biomass-based supply chains (OPTIMASS). *European Journal of*
577 *Operational Research*, 249(1):293–307, 2016. ISSN 0377-2217. doi: 10.1016/j.ejor.2015.08.003.
- 578 Deutscher Fachverband für Agroforstwirtschaft (DeFAF) e.V. Annual review of the Agroforestry Map
579 of Germany 2025, February 2026. URL [https://agroforst-info.de/wp-content/uploads/2026/](https://agroforst-info.de/wp-content/uploads/2026/02/DeFAF-2026-Annual-review-of-the-Agroforestry-Map-of-Germany-2025.pdf)
580 [02/DeFAF-2026-Annual-review-of-the-Agroforestry-Map-of-Germany-2025.pdf](https://agroforst-info.de/wp-content/uploads/2026/02/DeFAF-2026-Annual-review-of-the-Agroforestry-Map-of-Germany-2025.pdf). Available at:
581 [https://agroforst-info.de/wp-content/uploads/2026/02/DeFAF-2026-Annual-review-of-the-](https://agroforst-info.de/wp-content/uploads/2026/02/DeFAF-2026-Annual-review-of-the-Agroforestry-Map-of-Germany-2025.pdf)
582 [Agroforestry-Map-of-Germany-2025.pdf](https://agroforst-info.de/wp-content/uploads/2026/02/DeFAF-2026-Annual-review-of-the-Agroforestry-Map-of-Germany-2025.pdf).
- 583 Sandra Duni Ekşioğlu, Aditya Acharya, Lawrence E. Leightley, and Sumit Arora. Analyzing the design
584 and management of biomass-to-biorefinery supply chain. *Computers & Industrial Engineering*, 57(4):
585 1342–1352, 2009. ISSN 0360-8352. doi: 10.1016/j.cie.2009.07.003.
- 586 Victor Espinoza, Selene Bautista, Patricia C. Narvaez, Mauricio Alfaro, and Mauricio Camargo. Sustain-
587 ability assessment to support governmental biodiesel policy in Colombia: A system dynamics model.
588 *Journal of Cleaner Production*, 141:1145–1163, 2017. ISSN 0959-6526. doi: 10.1016/j.jclepro.2016.09.
589 168.
- 590 Ralf J. Faasch and Gaia Patenaude. The economics of short rotation coppice in Germany. *Biomass and*
591 *Bioenergy*, 45:27–40, 2012. ISSN 0961-9534. doi: 10.1016/j.biombioe.2012.04.012.
- 592 Anil R. Graves, Paul J. Burgess, Fabrice Liagre, Andrea Pisanelli, Patrice Paris, Gerardo Moreno,
593 Manuel Bellido, Manuela Mayus, Meindert Postma, Bernhard Schindler, Konstantinos Mantzanas,
594 and Christian Dupraz. Development and application of bio-economic modelling to compare silvoarable,
595 arable, and forestry systems in three European countries. *Ecological Engineering*, 29(4):434–449, 2007.
596 ISSN 0925-8574. doi: 10.1016/j.ecoleng.2006.09.018.
- 597 Henning Grünwald, Reinhold Böcker, B. Ulrich Schneider, Oliver Bens, and Reinhard F. Hüttl. Biomass
598 production of black locust (*Robinia pseudoacacia* L.) short rotation plantations in Germany: growth
599 and economics of different clones and management practices. *Bioresource Technology*, 98(2):281–286,
600 2007. ISSN 0960-8524. doi: 10.1016/j.biortech.2006.01.004.
- 601 Georg Huber, Kurt-Jürgen Hülsbergen, and Harald Schmid. Allometric equations for above-ground tree-
602 biomass estimation in Southern German short-rotation agroforestry systems. *Bioenergy Research*, 9
603 (3):955–968, 2016. ISSN 1939-1234. doi: 10.1007/s12155-016-9744-z.
- 604 Georg Huber, Christian Amann, Kurt-Jürgen Hülsbergen, and Harald Schmid. Yield potential of tree
605 species in organic and conventional short-rotation agroforestry systems in Southern Germany. *Heliyon*,
606 4(1):e00543, 2018. ISSN 2405-8440. doi: 10.1016/j.heliyon.2018.e00543.
- 607 Kaushalendra Kumar Jha. Biomass production and carbon balance in two hybrid poplar (*populus*
608 *euramericana*) plantations raised with and without agriculture in southern France. *Journal of Forestry*
609 *Research*, 29(6):1689–1701, 2018. ISSN 1007-662X. doi: 10.1007/s11676-017-0555-3.
- 610 Tatuo Kira, Kichiro Shinozaki, and Kikuo Hozumi. The C-D rule, its theory and practical uses. (In-

traspecific competition among higher plants. X.). *Journal of Biology, Osaka City University*, 12: 69–82, 1961.

Patrick Lamers, Martin Junginger, Carlo Hamelinck, and André Faaij. Developments in liquid biofuels commodity trade. *Biofuels, Bioproducts and Biorefining*, 5(4):403–437, 2011. ISSN 1932-104X. doi: 10.1002/bbb.303.

Frank Lehmkuhl, Alexander Stauch, Roman Schneider, Franziska Feil, and Henning Grunewald. Short-rotation coppice with poplar and willow in Germany: Biomass potentials, rotation lengths, and land-use interactions. *Biomass and Bioenergy*, 176:106908, 2023. ISSN 0961-9534. doi: 10.1016/j.biombioe.2023.106908.

Krishna Teja Malladi and Taraneh Sowlati. Biomass logistics: A review of important features, optimization modelling and the new trends. *Renewable and Sustainable Energy Reviews*, 94:587–599, 2018. ISSN 1364-0321. doi: 10.1016/j.rser.2018.06.052.

Babak Mansoornejad, Efstratios N. Pistikopoulos, and Paul R. Stuart. Integrating forest biorefinery metrics into supply chain design and analysis. *Forest Policy and Economics*, 26:43–54, 2013. ISSN 1389-9341. doi: 10.1016/j.forpol.2012.08.003.

Mercer Stendal GmbH. Mercer stendal: Zellstoffwerk Arneburg – kapazitäten und rohstoffversorgung. Unternehmenswebsite, 2024. URL <https://www.mercerint.com/de/stendal/>. Abgerufen: April 2026.

P. K. Ramachandran Nair. *An Introduction to Agroforestry*. Kluwer Academic Publishers, Dordrecht, 1993. ISBN 978-0-7923-2134-7.

Marcin Niemczyk and Brian R. Thomas. Does intensive management affect wood density and fiber properties of hybrid poplar grown in short-rotation plantation? *Forests*, 12(4):399, 2021. ISSN 1999-4907. doi: 10.3390/f12040399.

Bhavna Sharma, Robert G. Ingalls, Christopher L. Jones, and Ajay Khanchi. Biomass supply chain design and analysis: Basis, overview, modeling, challenges, and future. *Renewable and Sustainable Energy Reviews*, 24:608–627, 2013. ISSN 1364-0321. doi: 10.1016/j.rser.2013.03.049.

Raffaele Spinelli, Carla Nati, and Natascia Magagnotti. Using modified foragers to harvest short-rotation poplar plantations. *Biomass and Bioenergy*, 33(5):817–821, 2009. ISSN 0961-9534. doi: 10.1016/j.biombioe.2009.01.002.

Statistisches Bundesamt (Destatis). Kaufwerte und pachtpreise für landwirtschaftliche grundstücke 2022 – Fachserie 3 Reihe 2.4. Technical report, Statistisches Bundesamt, Wiesbaden, 2023. URL <https://www.destatis.de/DE/Themen/Branchen-Unternehmen/Landwirtschaft-Forstwirtschaft-Fischerei/Flaechennutzung/Publicationen/Downloads-Flaechennutzung/kaufwerte-landwirtschaft-2030240227004.pdf>. Pachtpreise Sachsen-Anhalt, Tabelle 3.1.

Riccardo Testa, Anna Maria Di Trapani, Mario Foderà, Filippo Sgroi, and Salvatore Tudisca. Economic evaluation of introduction of poplar as biomass crop in Italy. *Renewable and Sustainable Energy Reviews*, 38:498–506, 2014. ISSN 1364-0321. doi: 10.1016/j.rser.2014.07.007.

Eric Toensmeier. The carbon farming solution: A global toolkit of perennial crops and regenerative agriculture practices for climate change mitigation and food security. In *The Carbon Farming Solution*. Chelsea Green Publishing, White River Junction, VT, 2017. ISBN 978-1-60358-571-2.

- 650 Miroslav Trnka, Jana Fialová, Vladimír Koutecký, Milan Fajman, Zdeněk Žalud, and Milan Havlíček.
651 Biomass production and survival rates of selected poplar clones grown under a short-rotation system
652 on agricultural land. *Plant, Soil and Environment*, 54(2):78–88, 2008. ISSN 1214-1178. doi: 10.17221/
653 2752-PSE.
- 654 UPM Biochemicals. UPM biochemicals leuna: Bioraffinerie für laubholz-biomassekonversion. Un-
655 ternehmenswebsite, 2024. URL <https://www.upmbiochemicals.com/de/>. Abgerufen: April 2026.
- 656 Dajun Yue, Fengqi You, and Seth W. Snyder. Biomass-to-bioenergy and biofuel supply chain optimiza-
657 tion: Overview, key issues and challenges. *Computers & Chemical Engineering*, 66:36–56, 2014. ISSN
658 0098-1354. doi: 10.1016/j.compchemeng.2013.11.016.
- 659 Seyed Mojib Zahraee, Nirajan Shiwakoti, and Peter Stasinopoulos. Biomass supply chain environmental,
660 economic, and social sustainability: A systematic literature review. *Industrial Crops and Products*,
661 145:112144, 2020. ISSN 0926-6690. doi: 10.1016/j.indcrop.2020.112144.

Table 4: Consumer demand quantities and gate prices by product grade. P1: chemical/pulp; P2: sawlog/pulpwood; P3: energy/pellets. Demands in kt wood input per year; prices in €/t wood input at the factory gate.

Consumer	Annual demand			Gate price		
	P1 (kt/yr)	P2 (kt/yr)	P3 (kt/yr)	P1 (€/t)	P2 (€/t)	P3 (€/t)
consumer 1	300.0	–	–	100	–	–
consumer 2	100.0	–	–	120	–	–
consumer 3	–	300	50.0	–	75	40
consumer 4	200.0	–	–	95	–	–
consumer 5	–	30	5.0	–	70	35
consumer 6	–	15	5.0	–	65	35
consumer 7	–	10	3.0	–	60	30
consumer 8	–	5	8.0	–	55	30
consumer 9	2.0	50	20.0	80	70	38
consumer 10	–	–	1.7	–	–	35
consumer 11	–	–	2.9	–	–	35
consumer 12	–	–	2.5	–	–	35
consumer 13	–	–	2.3	–	–	35
consumer 14	–	–	1.9	–	–	35
consumer 15	–	–	2.7	–	–	35
consumer 16	–	–	1.7	–	–	35
consumer 17	–	–	1.9	–	–	35
consumer 18	–	–	1.6	–	–	35
consumer 19	–	–	1.5	–	–	35
consumer 20	–	–	1.5	–	–	35
consumer 21	–	–	1.8	–	–	35
consumer 22	–	–	3.5	–	–	35
consumer 23	–	–	1.6	–	–	35
consumer 24	–	–	2.1	–	–	35
consumer 25	–	–	4.5	–	–	35
consumer 26	–	–	1.8	–	–	35
consumer 27	–	–	3.2	–	–	35
consumer 28	18.5	–	–	55	–	–

Table 5: AFS-SCD base-case parameter values for the Saxony-Anhalt case study. Transport costs refer to road distance (OSRM). Gate prices are weighted averages across consumer sites.

Parameter	Description	Base-case value	Unit
Index sets			
$ \mathcal{T} $	Planning periods	40	yr
$ \mathcal{I} $	KUP super-sites (post-clustering)	145	–
$ \mathcal{J} $	Pre-treatment / storage nodes	11	–
$ \mathcal{K} $	Consumer sites	28	–
$ \mathcal{P} $	Product grades	3	–
Biomass dynamics			
$a^{\min}$	Minimum harvest age (years)	3	yr
$a^{\max}$	Maximum stand age (years)	15	yr
Cost parameters			
c^{tr-raw}	Raw transport cost	0.08	€ t ⁻¹ km ⁻¹
c^{tr-pre}	Pre-processed transport cost	0.06	€ t ⁻¹ km ⁻¹
c^{opp}	Opportunity cost	166	€ ha ⁻¹ yr ⁻¹
Revenue parameters			
$\bar{R}_{P1}$	Mean gate price P1	90	€ t ⁻¹
$\bar{R}_{P2}$	Mean gate price P2	66	€ t ⁻¹
$\bar{R}_{P3}$	Mean gate price P3	35	€ t ⁻¹

Table 6: Key performance indicators for benchmark and sensitivity scenarios. Opp. cost: opportunity cost per hectare; Cost/Rev. mult.: multipliers relative to the baseline scenario (1.0 = baseline). Total profit is net revenue minus all costs over the full planning horizon; demand satisfaction reports the share of total customer demand served.

Scen.	Opp. cost (€/ha)	Cost mult.	Rev. mult.	Profit (€/ha · a)	Act. sites	Wood (kt/a)	Demand sat. (%)
Bench.	150	1.0	1.0	651	60	923	79.4%
1	150	0.5	0.5	254	66	904	77.8%
2	300	0.5	0.5	171	60	864	74.3%
3	150	2.0	0.5	91	50	777	66.9%
4	300	2.0	0.5	109	11	160	13.8%
5	150	0.5	1.5	708	99	961	82.7%
6	300	0.5	1.5	751	84	942	81.1%
7	150	2.0	1.5	889	67	915	78.8%
8	300	2.0	1.5	812	65	905	77.9%

Table 7: Overview on OLS regression result (adj. R^2 :81%, # observations: 556, σ : 240)

variable	estimate	std. error	t value	p value	CI 2.5%	CI 97.5%
<i>Intercept</i>	-2513.370	177.374	-14.170	0.000	-2861.775	-2164.964
opp_cost	-1.276	0.143	-8.916	0.000	-1.557	-0.995
cost_level	-166.715	15.565	-10.711	0.000	-197.288	-136.142
revenue_level	1249.993	25.489	49.041	0.000	1199.927	1300.059
avg_rotation_yr	178.444	6.475	27.558	0.000	165.725	191.163
logarea_ha	19.172	20.043	0.957	0.339	-20.197	58.541