

n8n M-Pesa Mastery

Build STK Push Payment Workflows — No Code

n8n M-Pesa Mastery : Course Handbook

This Markdown file is the master draft. Export to PDF via **Pandoc** or **Typora**:

```
pandoc docs/handbook.md -o docs/handbook.pdf --pdf-engine=xelatex --toc -V
geometry:margin=1in
```

Table of Contents

- 0. Welcome
 - 1. Introduction to n8n
 - 2. Understanding the Daraja API
 - 3. OAuth in n8n
 - 4. Building the STK Push Workflow
 - 5. Handling the Callback
 - 6. Status Query & Reconciliation
 - 7. Production Hardening
 - 8. Real-World Use Cases
 - 9. Beyond STK Push
 - 10. Selling Your Skill
 - 11. Appendix: Troubleshooting
-

Welcome

What you'll build: a production-ready M-Pesa STK Push integration using n8n — no backend microservice required. By the end of this course you'll have:

- A self-hosted n8n instance behind HTTPS
- 4 core workflows (auth, STK push, callback, reconciliation)
- A Postgres database tracking every transaction
- 5 real-world use-case templates (e-commerce, SaaS, school fees, donations, WhatsApp)
- The skills to sell this as a service to Kenyan businesses

Prerequisites:

- Comfort with the command line
 - A credit card for a \$6/month VPS (optional for local dev)
 - A Safaricom Developer account (free)
 - 6–8 hours of focused time
-

Module 1 : Introduction to n8n

1.1 What is n8n?

n8n (pronounced *n-eight-n*) is an open-source workflow automation tool. Think Zapier or Make, but:

- **Self-hostable** — no per-task fees
- **Code-friendly** — drop into JavaScript when you need to
- **400+ integrations** out of the box
- **Fair-code licensed** — free for internal use, paid for embedding in products

1.2 Why n8n for M-Pesa?

The traditional approach to M-Pesa integration is a Spring Boot / Node.js / Django service that:

1. Fetches an OAuth token
2. Builds the STK push payload (timestamp + password)
3. POSTs to Daraja
4. Exposes a `/callback` endpoint
5. Writes to a DB
6. Notifies the customer

That's 300+ lines of code, a Dockerfile, a CI pipeline, and a server to maintain. n8n does the same with 4 visual workflows you can modify in-browser.

1.3 Installing n8n locally

```
cd docker/  
cp .env.example .env  
# edit .env  
docker compose up -d  
open http://localhost:5678
```

Log in with the basic-auth credentials from your `.env`.

1.4 The n8n UI

- **Workflows** — your automations (one per use case)
- **Executions** — history of every run (success / fail / running)
- **Credentials** — encrypted secrets (DB passwords, API keys)
- **Variables** — plaintext globals (shortcodes, URLs)

1.5 Your first workflow : "Hello Webhook"

1. Click **New Workflow**
2. Add a **Webhook** node → path = `hello` , method = `POST`
3. Add a **Set** node → add a field `message` = `Hello {{$json.body.name}}`
4. Click **Execute Workflow**, then POST to the test URL


```
curl -X POST http://localhost:5678/webhook-test/hello -d '{"name":"Titus"}' -H 'Content-Type: application/json'
```

Congratulations — you just built your first n8n API. The M-Pesa workflow is the same pattern, scaled up.

Module 2 : Understanding the Daraja API

See [daraja-cheatsheet.md](#) for the one-page reference. Key points:

- **Sandbox vs Production** — different base URLs, different credentials. Switch via `MPESA_ENV` .
- **OAuth lifecycle** — Basic Auth with Consumer Key/Secret → Bearer token (3599s TTL).
Cache it.
- **STK Push sequence:**



Module 3 : OAuth in n8n

Import `workflows/01-mpesa-auth.json` . Walkthrough:

1. **Trigger** — "When called by another workflow" makes this a reusable sub-workflow.
2. **Code node — Build Basic Auth** — reads env vars and base64-encodes `key:secret` .
3. **HTTP Request** — GET `/oauth/v1/generate` with `Authorization: Basic ...` .
4. **Code node — Return Token** — returns `{ access_token, expires_in, expires_at }` .

Caching strategy (optional upgrade)

Store the token in n8n's **Workflow Static Data**:

```

const data = $getWorkflowStaticData('global');
if (data.token && new Date(data.expires_at) > new Date(Date.now() + 60_000)) {
  return [{ json: { access_token: data.token, cached: true } }];
}

```

Only hit `/oauth/v1/generate` on cache miss. Saves ~200ms per transaction and avoids rate limits.

Module 4 : Building the STK Push Workflow

Import `workflows/02-stk-push.json` . The flow:

1. **Webhook** receives `{ phone, amount, reference, description }`
2. **Validate Input** normalises phone & checks amount
3. **Execute Workflow** → **01-mpesa-auth** gets a Bearer token
4. **Build STK Payload** computes timestamp + password
5. **HTTP Request** POSTs to `/mpesa/stkpush/v1/processrequest`
6. **Postgres** saves a pending row
7. **Build API Response** returns the result to the caller

Test it

```
curl -X POST http://localhost:5678/webhook/mpesa/stk-push \
-H 'Content-Type: application/json' \
-d '{"phone":"254708374149","amount":1,"reference":"ORDER-1"}'
```

You should see the STK prompt on the test phone (sandbox: any Safaricom number returns a mock prompt).

Module 5 : Handling the Callback

Import `workflows/03-stk-callback.json` .

CRITICAL: Respond `200 OK` **immediately**. Safaricom does not retry callbacks, but a slow response can cause them to mark your endpoint as unhealthy.

The workflow:

1. **Webhook** on `/mpesa/stk-callback` , response mode = **On Received** (returns ACK before processing)
2. **Parse Callback** flattens the nested `Body.stkCallback.CallbackMetadata.Item[]` into clean fields
3. **Update Transaction** sets `status` , `mpesa_receipt_number` , etc. by `CheckoutRequestID`

4. **IF branch** — on success → build confirmation; on failure → log

Exposing locally with ngrok

```
docker compose --profile tunnel up -d
docker compose logs ngrok | grep 'url='
# -> https://xxxx-xxx.ngrok-free.app
```

Put that URL in `.env` as `MPESA_CALLBACK_BASE_URL` and restart n8n.

Module 6 : Status Query & Reconciliation

Callbacks sometimes don't arrive (user ignored the prompt, network blip, your server was down). Workflow `04-reconciliation.json` fixes this.

- Runs every 5 minutes
- Finds `pending` transactions older than 2 minutes
- Calls `stkpushquery/v1/query` to get the real status
- Updates the DB

This single workflow is what separates "hobby demo" from "production payment system".

Module 7 : Production Hardening

Deploy to a VPS

```
ssh root@your-server
curl -fsSL https://raw.githubusercontent.com/<you>/n8n-mpesa-course/main/deploy/vps-
setup.sh \
  | bash -s -- api.yourdomain.co.ke you@email.com
```

The script installs Docker, Nginx, Let's Encrypt, and clones this repo.

Security checklist

- Change `N8N_BASIC_AUTH_PASSWORD` and `N8N_ENCRYPTION_KEY`
- Firewall: only 22, 80, 443 open
- DB backups via `pg_dump` cron
- Rotate Daraja Consumer Secret quarterly

- Monitor failed-login attempts via `fail2ban`

Rate limiting

Add this to `nginx.conf` :

```
limit_req_zone $binary_remote_addr zone=stk:10m rate=5r/s;
location /webhook/mpesa/stk-push { limit_req zone=stk burst=10; proxy_pass
http://127.0.0.1:5678; }
```

Module 8 : Real-World Use Cases

Each JSON in `workflows/use-cases/` is a working template. Customise and deploy:

File	Scenario
<code>ecommerce.json</code>	WooCommerce order → STK push → mark paid
<code>saas-billing.json</code>	Monthly subscription with retries
<code>school-fees.json</code>	Google Form → STK → PDF receipt via email
<code>donations.json</code>	Bubble.io form → STK → thank-you WhatsApp
<code>whatsapp-bot.json</code>	WhatsApp message triggers STK push

Module 9 : Beyond STK Push

Teasers for a future course:

- **B2C** — paying salaries, refunds, winnings
- **C2B Register URL** — merchant till notifications
- **Account Balance** — automated float checks
- **Reversal** — refund within 7 days

Same patterns, different endpoints. The `01-mpesa-auth` workflow is reusable for all of them.

Module 10 : Selling Your Skill (*Agency tier*)

Pricing templates (KES)

Package	Price	Deliverables
Starter	25,000	Deploy n8n + STK push + callback for one shortcode
Standard	75,000	+ Reconciliation + DB + 1 integration (Sheets/WhatsApp)
Premium	200,000	+ Multi-tenant, dashboard, 3-month support

Client onboarding checklist

1. Get their Daraja production credentials (NDA first)
2. Get domain + VPS access (or provision your own)
3. Deliver the 4 workflows + Postman collection
4. Train one of their devs for 2 hours
5. 30-day warranty

Appendix : Troubleshooting

Symptom	Likely cause	Fix
Invalid Access Token	Expired or wrong env	Re-run auth workflow; verify <code>MPESA_BASE_URL</code> matches env
Bad Request – Invalid Timestamp	Server clock drift	<code>timedatectl set-ntp true</code>
Callback never arrives	URL not public / HTTPS invalid	Test with <code>curl</code> from an external machine
The initiator information is invalid	Wrong Passkey	Copy-paste from Daraja portal exactly
STK push succeeds but no row in DB	Postgres credential wrong in n8n	Re-select the credential in the workflow node
ResultCode 1037	User didn't enter PIN in 60s	Reconciliation workflow will mark it timeout

End of handbook. Last updated: October 2026.