

Test system `testecalj`

(2025-10-8).

Our new test system is made from two files

```
SRC/exec
├─ comp.py      utilities (functions to show difference of files) called
from testecalj
└─ testecalj    main program for test
```

- Install test described in `InstallAll.py` is performed at `ecalj/Samples/TestInstall`.
- We can run `testecalj` as `>testecalj foobar`, where `foobar/` is the name of a test directory. `testecalj` creates `foobar_work/` directory and do test in it.
- `foobar/` should contain initial settings such as `ctrl`, `GWinput` and files to be compared. In addition, we have to write `test.py` which describe schedules to run programs and to compare files. `ecalj/Samples/TestInstall/foobar` contains samples of test directories.
- For any test directories `foobar`, we can perform test by `testecalj foobar`. In fact, we can run test of `Fe_magnon` at `ecalj/Samples/Magnon` since we added `ecalj/Samples/Magnon/test.py`.
- We can write your own `test.py` easily.
- `testecalj` use binaries such as `lmfa`, `lmf`, `qg4gw...` in the directory containing the `testecalj`.
- We can do only numerical comparison of files by

```
from comp import test2_check
testdir= "/home/takao/ecalj/Samples/Magnon/Ni_magnon/"
workdir= "/home/takao/ecalj/Samples/Magnon/Ni_magnon_work/"
dat='wan_ChIPMz.mat.sym11'
tall=test2_check(testdir+'/'+dat, workdir+'/'+dat,tol=0.01)
```

where, we need to import `ecalj/SRC/exec/comp.py`.

- `Samples/TestInstall`にテストを移した。`InstallAll.py`を実行するとテストではそこへ飛びます。個別実行も`Samples/TestInstall`で行います。どんなところにある`foobar/`に対してもその横に`foobar_work/`をつかってそこでテストするようにしました。`foobar/`には`test.py`をいれること
- `testecalj`というコマンドを作った。51行の短いプログラム。これはバイナリのあるディレクトリ `BINDIR`に入ります。使うバイナリはその同じディレクトリにあるものです。

たとえばSamples/AHC/xxxにでもtest.pyをおけばテストできるはず。