

Recommended Windows Event IDs

The following list provides Brady's general recommendation of Windows Event IDs that should be configured for logging within each host's Group Policy settings. This is a general list of known IDs that may be beneficial for security or forensic auditing and should not be considered a complete or exhaustive list of security Event IDs. For Microsoft's recommended best practices, please refer to [Microsoft's official documentation](#).

EventCode	Description
1102	The audit log was cleared
4103	A PowerShell script was executed
4104	A remote PowerShell command was executed
4624	An account was successfully logged on
4625	An account failed to log on
4648	A logon was attempted using explicit credentials
4657	A registry value was modified
4663	An attempt was made to access an object
4670	Permissions on an object were changed
4672	Special privileges assigned to new logon
4673	A privileged service was called
4688	A new process has been created
4697	A service was installed in the system
4698	A scheduled task was created
4699	A scheduled task was deleted
4720	A user account was created
4722	A user account was enabled
4723	An attempt was made to change an account's password
4724	An attempt was made to reset an accounts password
4725	A user account was disabled
4726	A user account was deleted
4727	A security-enabled global group was created
4728	A member was added to a security-enabled global group
4729	A member was removed from a security-enabled global group
4730	A security-enabled global group was deleted
4731	A security-enabled local group was created
4732	A member was added to a security-enabled local group
4733	A member was removed from a security-enabled local group
4734	A security-enabled local group was deleted
4735	A security-enabled local group was changed
4737	A security-enabled global group was changed
4738	A user account was changed
4739	Domain Policy was changed
4740	A user account was locked out
4741	A computer account was created
4743	A computer account was deleted
4767	A user account was unlocked
4769	A Kerberos service ticket was requested
4771	Kerberos pre-authentication failed
4776	The domain controller attempted to validate the credentials for an account

4780	The ACL was set on accounts which are members of administrators groups
4782	The password hash an account was accessed
4950	A Windows Firewall setting has changed
5025	The Windows Firewall Service has been stopped
5140	A network share object was accessed
6416	A new external device was recognized by the system.

Recommended *Nix File Paths

The following list provides Brady's general recommendation of Linux/Unix logging file paths that should be monitored for SIEM ingestion. This is a general list of known file paths for a variety of *nix flavors and may not be completely applicable to every environment. These were chosen as they may be beneficial for security or forensic auditing and should not be considered a complete or exhaustive list of security Event IDs. For SANS recommended best practices, please refer to this [SANS Unix Logging post from 2010](#).

File Path	Description
/var/log/messages	This log file contains generic system activity logs. Here you can track non-kernel boot errors, application-related service errors and the messages that are logged during system startup
/var/log/auth.log	All authentication related events in Debian and Ubuntu server are logged here.
/var/log/secure	It stores all security related messages including authentication failures. It also tracks sudo logins, SSH logins and other errors logged by system security services daemon.
/var/log/boot.log	The system initialization script, /etc/init.d/bootmisc.sh, sends all bootup messages to this log file
/var/log/kern.log	Perfect for troubleshooting kernel related errors and warnings.
/var/log/faillog	This file contains information on failed login attempts.
/var/log/cron	This log file records information on cron jobs.
/var/log/yum.log	It contains the information that is logged when a new package is installed using the yum command.
/var/log/audit/audit.log	Default logging location for the audit daemon built into Linux systems. Helps you track all activity in Linux systems, and can even provide commands ran by users before and after entering sudo.
var/log/httpd/	Error and access logs in this directory are critical to monitor on web servers as it will have your HTTP status response codes. Logs the IP address and user ID of all clients that make connection requests to the server.