



LIFTING YOU SINCE '62

STANMORE LIFT EQUIPMENT LTD.

BRAND STANDARDS

Rules for applying the Stanmore identity across print collateral, vehicle and equipment decals, and trade show graphics. Written for internal staff and for the print vendors producing the work.

ONTARIO, CANADA 1 855-955-LIFT CONCEPT 03 – AUGUST 2026

01 THE MARKS

02 CLEAR SPACE & SIZE

03 MISUSE

04 COLOUR

05 TYPOGRAPHY

06 LOGO IN USE

07 APPLICATIONS

08 VENDOR CHECKLIST

01

THE MARKS

The wordmark is the mark. It is drawn artwork — white letterforms with a black keyline — and one file covers white, black and Stanmore Red grounds, so there is no separate reverse version to manage. A tagline lockup and two one-colour versions cover what the primary file cannot. Legacy artwork stays in circulation on existing stock and equipment until it is replaced, but never appears alongside the new mark in a single piece.



PRIMARY

The wordmark on a light ground. This is the mark for covers, cards, flyers and spec sheets — the standard in every case where nothing forces otherwise.



ON DARK AND RED GROUNDS

The same file, unchanged. The white letterforms carry the mark and the black keyline reads as depth instead of disappearing, so black, Stanmore Red and dark photography all take the primary artwork.

TAGLINE LOCKUP

Optional, and supplied as drawn artwork in a version for light grounds and one for dark. Never re-set the tagline as live type.



The tagline is locked to the wordmark in the supplied file — the maple leaf, the spacing and the cap height are all fixed. Scale the lockup proportionally as a single object; never move, re-space or redraw any part of it, never separate the leaf from the tagline, and never rebuild it by setting the tagline under the plain wordmark.

Take the light-ground version on white, and the dark-ground version on black or over dark photography — the tagline is solid, so unlike the wordmark it does need the matching file. Use the lockup on covers, vehicles, booth panels and the back of the business card — anywhere it sits on a face of its own. Keep it off faces carrying contact information, where it competes for attention. Where the tagline is not wanted, take the plain wordmark rather than deleting the tagline from this artwork.

ONE-COLOUR

For single-ink print, cut vinyl, embroidery, engraving and any process that cannot hold two colours. Never substitute a one-colour version where the full mark will reproduce.



BLACK

Solid black, no keyline. Invoices, forms, single-ink print and any black-only run.



WHITE

Solid white, no keyline. Embroidery, cut vinyl and engraving on dark material – anywhere the process cannot hold the keyline.

CLEAR SPACE & MINIMUM SIZE



Clear space on all four sides equals half the wordmark's overall height. Nothing enters that zone — no type, no rule, no photo edge, no fold or trim.

BUSINESS CARD, LETTERHEAD	32 mm / 1.25 in wide min.
FLYER, BROCHURE, QUOTE FORM	50 mm / 2 in wide min.
EQUIPMENT DECAL	300 mm / 12 in wide min.
VEHICLE DOOR	450 mm / 18 in wide min.
BOOTH BANNER, TOWER	One third of panel width

Below these sizes the black keyline starts to fill in and the counters close up. If the space will not hold the minimum, move to a larger format or drop the mark from the piece — never shrink it past this.

03

MISUSE

- ✗

Never re-set the wordmark in another typeface. It is drawn artwork, not live type.
- ✗

Never recolour. Red, black and white only – no gradients, no metallics, no brand-partner colours.
- ✗

Never place the mark on a mid-tone ground or a busy photograph. It needs white, black or Stanmore Red behind it – anything between kills either the white letterforms or the black keyline.
- ✗

Never rotate. The only exception is a deliberate vertical spine on a narrow format.
- ✗

Never stretch, condense or re-slant. Scale proportionally only.
- ✗

Never add drop shadows, bevels, extra outlines or outer glows. The black keyline is part of the drawn artwork; nothing else goes on top of it.
- ✗

Never lock partner logos into the Stanmore mark. Run them as a separate row, equal height, outside its clear space.
- ✗

Never rebuild the mark from a screenshot or a JPG. Always start from the supplied vector.



✗

RED-FILLED WORDMARK

Red against the black outline is too low in contrast to read at distance. Keep the white fill.

04

COLOUR

Three core colours carry the brand. Red is the accent and the attention-getter, never the reading surface. Two neutrals exist only to support layout — rules, panels, secondary type.




STANMORE RED

HEX ED1C24 · RGB 237 28 36



EQUIPMENT BLACK

HEX 111111 · RGB 17 17 17




WHITE

HEX FFFFFFF · Unprinted stock



STEEL

6E7175 · secondary type, rules



FOG

E4E2E0 · panels, table fills

PRODUCTION VALUES

COLOUR	COATED STOCK	SPOT	CUT VINYL
Stanmore Red	C0 M95 Y100 K0	PMS 485 C	3M 3630-53 / ORACAL 751-031
Equipment Black	K100 · rich C60 M40 Y40 K100 over 50 mm	PMS Black C	3M 3630-22 / ORACAL 751-070
White	Knockout, no ink	—	3M 3630-20 / ORACAL 751-010

Red is the one colour worth a press check. Match to PMS 485 C on every process, and hold the same red across print and vinyl so a card and a truck door read as the same company.

05

TYPOGRAPHY

The wordmark is a heavy slanted condensed grotesque. The brand pairing extends that logic rather than competing with it: a condensed face for headlines and equipment labels, its normal-width sibling for body copy. Both are free, licensed for print and embedding, and installable on any staff machine.

BRAND TYPEFACE

BARLOW CONDENSED + BARLOW

ROUGH
TERRAIN

1056-G REACH

HEADLINES · LABELS · NUMBERS

Stanmore has been lifting you since '62. Rough terrain forklifts, telehandlers, scissor lifts, scaffolding and mortar mixers, rented and sold across Ontario.

BODY · CAPTIONS · SPECS

PRINT HEADLINE	24 pt and up, condensed, uppercase
SUBHEAD	14–18 pt, condensed, tracking 60
BODY	10–12 pt / 15 pt leading, never below 9 pt
DECAL COPY	75 mm / 3 in cap height min. on equipment
OFFICE FALLBACK	Arial Narrow / Arial where Barlow is unavailable

06

LOGO IN USE

The wordmark carries every piece on its own. Give it a clean ground — white, black, or a solid red panel — size it to the format, and keep everything else outside its clear space.



Vehicle wrap. A red panel carries the wordmark across the cargo side, reversed out so the white letterforms and the black keyline both hold against the red. The tagline sits in black on the white below the panel with the crest to its right. Red stripes sweep up off the front fender and run the length of the body, passing below the panel rather than across it. The rear doors take the same panel at a smaller scale.



THE CREST

A secondary mark for occasional use. It supports the wordmark and never stands in for it — no piece is identified by the crest alone. Approved use today is the vehicle wrap only, where it sits on the white below the red panel, clear of the wordmark.

Keep it reading as a stamp rather than a second logo: no wider than a third of the wordmark it accompanies, and never locked into the mark or inside its clear space. Never recolour it, never separate the leaf from the ring. Anything beyond the vans goes past the marketing contact first.



BUSINESS CARD

Front runs white and carries contact only — first name in red, surname in black, role in letterspaced caps below it, then email, and the company name and address at the foot. Phone numbers align right and a QR code sits in the top corner. No mark on this face.

Back is white and carries the tagline lockup centred, and nothing else — no contact type, no partner marks. The two faces split the work: contact on the front, identity on the back. Where partner marks are needed, they run on the piece that calls for them, as a single row at equal height, never on the card.



WORKWEAR

Charcoal polo carrying the wordmark on the left chest — roughly 90 mm / 3.5 in wide, centred between the placket and the sleeve seam and level with the second button.

Embroidery closes fine detail, so apparel takes the one-colour white artwork rather than the keyline mark. Charcoal, black and white garments only — never a red garment, where the mark loses its ground.

07

APPLICATIONS

BUSINESS CARD

3.5 × 2 IN · 16 PT MATTE · 1/8 IN BLEED

Front runs white and carries contact only: name, role, email and address set left, phone numbers right, QR code in the top corner, no mark. Back is white with the tagline lockup centred and nothing else. First name in red, surname in black.

EQUIPMENT & VEHICLE DECAL

CAST VINYL · 5 YR OUTDOOR · CONTOUR CUT

Existing stacked decal artwork, phone number always present. Keep the decal off panel seams, hinges and rivets, and match the same red on every unit in the fleet.

FLYER & SPEC SHEET

8.5 × 11 IN · 0.5 IN MARGINS

Mark top left, red band at the foot with phone and web. Equipment photography sits full-bleed or on white — never on a red field, which fights the machines.

TRADE SHOW

READ AT 20 FT · ONE MESSAGE PER PANEL

Black ground, white type, red accent. Mark in the top third of each panel above sightline. Partner brands run as a single row along the base, equal height, on white.



EXISTING DECAL ARTWORK

Stays in service on the fleet and on equipment. Runs on its own — never alongside the new wordmark in a single panel.

08

VENDOR CHECKLIST

- 01

Vector artwork only: EPS or PDF for print, SVG for screen.
No PNG or JPG logos.
- 02

All type converted to outlines before release.
- 03

CMYK for process print, spot for two-colour jobs, RGB
never sent to press.
- 04

1/8 in bleed and a 1/8 in safety margin on every trimmed
piece.
- 05

Raster images 300 dpi at final size; large-format banners
100 dpi at final size.
- 06

Hard-copy or drawdown proof on the first run of any new
red application.
- 07

Tagline lockup placed from the supplied vector file,
never re-set as live type: LIFTING YOU SINCE '62.
- 08

Barlow Condensed and Barlow supplied with the artwork
package; do not substitute.

Questions on any application, or a format not covered here, go to the
marketing contact before the job goes to press.

STANMORE