THALES

Applying TLA+ in a Safety-Critical Railway Project

Stefan Resch
Dependable Systems Architect, Thales




This project has received funding from the ECSEL Joint Undertaking under grant agreement No 692455. This Joint Undertaking receives support from the European Union's Horizon 2020 research and innovation program and Austria, Denmark, Germany, Finland, Czech Republic, Italy, Spain, Portugal, Poland, Ireland, Belgium, France, Netherlands, United Kingdom, Slovakia, Norway.



www.thalesgroup.com

OPEN

- Safety approval according to CENELEC 50129 SIL 4
- Safety layer
 - > Fault tolerance
 - Health monitoring
 - Various redundancy architectures
- Board support package
 - Communications interfaces / drivers
 - Some are very specific
- Based on COTS hardware / operating system
- Support 25 years of application business logic (with changing underlying hardware and software)




TAS Control Platform in about 70% of new safety-critical products in Thales Ground Transportation

THALES

Formal Modelling Objectives

- New Redundancy Architecture
- Gain confidence in design
 - Relevant results/insights
- Feasible
 - > Time and effort
- Close representation to implementation
 - Reduce bugs introduced between model and coding
 - Get feedback from experienced experts in team





Some time later ...




- Formal model in TLA+ and PlusCal
 - ➤ Algorithm specification in C-like language
 - Linear temporal logic formulas
 - ➤ Model checking with TLC
- Efficient model checking through a good level of abstraction
 - > Prerequisite for design process
- Property-driven design
 - Process that provides confidence in model
- C code generation from model
 - > Close gap between model and implementation



Algorithm defined in PlusCal

- **Environment in TLA+**
 - ≥ 3 classes of events
 - Progress
 - Upper Layer
 - Fault
- Properties
 - Invariants: e.g. no two masters
 - Liveness: e.g. all nodes eventually get a correct view of the system
- I TLC model checker






So we found a model checker ...



Analogous to test driven development

Gain confidence in model


- Observe many traces of model
- Check that properties capture intended behaviour
- Fast feedback to design decisions
- Feedback from increasing size of state space






Recap test driven development

- > Write new test
- > Execute test → fail
- Write implementation
- ➤ Execute all tests → pass
- > Refactor







- > Define property
- > Enhance environment
- Adapt algorithm
- Cross check with negation of property




- Define property
- > Enhance environment
- Adapt algorithm
- Cross check with negation of property




- Define property
- > Enhance environment
- ➤ Adapt algorithm
- Cross check with negation of property



- Define property
- > Enhance environment
- Adapt algorithm
- Cross check with negation of property




- Define property
- > Enhance environment
- Adapt algorithm
- Cross check with negation of property



Track size of state space between model checker runs

- ➤ Constant size but algorithm got more complex
 - Most likely added dead code

- > Sudden increase of size
 - Most likely a bug in specification





How properties drive the process

Invariants

- Help detecting "bugs"

> Liveness

- Force enhancement of algorithm



Instant feedback supports design decisions

Many traces build confidence in model

- Unanticipated scenarios were found
 - ➤ Longest trace consisted of more than 30 steps

Major drawback is time necessary for modelling

PlusCal

```
\* initialization
procedure node_init () {
init:
  state[self] := STATE_START;
  \* set all but own state to off
  reset node view(NO NODE);
  \* start a timeout to send
  \* ping for the first time
  start_timeout(TO PING,
    TO_PING_STARTUP_TIME);
```

C

```
// initialization
void node init (void) {
  state = STATE START;
  // set all but own state to off
  reset node view(NO NODE);
  // start a timeout to send ping
  // for the first time
  start_timeout(TO_PING,
    TO_PING_STARTUP_TIME);
```




Defining Different Modules

Specific environment definition necessary

- Avoid state space explosion
- > Substantial effort

Strategy for interfaces is essential

Layering seems to be the simplest approach



Potential Improvements

Readable Traces

Animation

Faster check of liveness properties

```
_ | X
File Edit Tools Syntax Buffers Window Help
        ( 0 :> "__unused_init_value" @@
1 :> "__unused_init_value" @@
                                2 :> "_unused_init_value" )
35 + /\ msg_to_send = [no_message |-> ""]
36 + // event = (0 :> defaultInitValue @@ 1 :> defaultInitValue @@ 2 :> defaultInitValue)
37 + /\ timeout_request_del = [type |-> "__notimeout"]
38 + /\ stack = (0 :> <>> (0 1 :> <<>> (0 2 :> <<>>)
40 step 2: <Action line 434, col 5 to line 439, col 22 of module pingpong_env>
            /\ timeouts = ( 0 :>
                         ( 0 :> [type |-> "__notimeout"] (0
1 :> [type |-> "__notimeout"] (0
2 :> [type |-> "__notimeout"] ) (0
                        ( 0 :> [type |-> "__notimeout"] @@
1 :> [type |-> "__notimeout"] @@
2 :> [type |-> "__notimeout"] ) @@
                         ( 0 :> [type |-> "__notimeout"] (()
1 :> [type |-> "__notimeout"] (()
2 :> [type |-> "__notimeout"] ) )
            /\ messages = ( 0 :> (0 :> <>> 00 1 :> <>> 00 2 :> <<>>) 00 1 :> <<>> 00 2 :> <<>>) 00 1 :> <<>> 00 2 :> <<>>) 00 2 :> <<>>) 00 2 :> <<>>) 00 2 :> <<>>) 00 2 :> <<>>) 00 2 :> <<>>) 00 2 :> <<>>) 00 2 :> <<>>) 00 2 :> <<>>) 00 2 :> <<>>) 00 2 :> <<>>) 00 2 :> <<>>) 00 2 :> <<>>) 00 2 :> <<>>) 00 2 :> <<>>) 00 2 :> <<>>) 00 2 :> <<>>) 00 2 :> <<>>) 00 2 :> <<>>) 00 2 :> <<>>) 00 2 :> <<>>) 00 2 :> <<>>) 00 2 :> <<>>) 00 2 :> <<>>) 00 2 :> <<>>) 00 2 :> <<>>) 00 2 :> <<>>) 00 2 :> <<>>) 00 2 :> <<>>) 00 2 :> <<>>) 00 2 :> <<>>) 00 2 :> <<>>) 00 2 :> <<>>) 00 2 :> <<>>) 00 2 :> <<>>) 00 2 :> <<>>) 00 2 :> <<>>) 00 2 :> <<>>) 00 2 :> <<>>) 00 2 :> <<>>) 00 2 :> <<>>) 00 2 :> <<>>) 00 2 :> <<>>) 00 2 :> <<>>) 00 2 :> <<>>) 00 2 :> <<>>) 00 2 :> <<>>) 00 2 :> <<>>> 00 2 :> <<>>) 00 2 :> <<>>> 00 2 :> <<>>> 00 2 :> <<>>> 00 2 :> <<>>> 00 2 :> <<>>> 00 2 :> <<>>> 00 2 :> <<>>> 00 2 :> <<>>> <<>>> 00 2 :> <<>>> 00 2 :> <<>>> 00 2 :> <<>>> 00 2 :> <<>>> <<>>> 00 2 :> <<>>> 00 2 :> <<>>> 00 2 :> <<>>> 00 2 :> <<>>> 00 2 :> <<>>> 00 2 :> <<>>> 00 2 :> <<>>> 00 2 :> <<>>> 00 2 :> <<>>> 00 2 :> <<>>> 00 2 :> <<>>> 00 2 :> <<>>> 00 2 :> <<>>> 00 2 :> <<>>> 00 2 :> <<>>> 00 2 :> <<>>> 00 2 :> <<>>> 00 2 :> <<>>> 00 2 :> <<>>> 00 2 :> <<>>> 00 2 :> <<>>> 00 2 :> <<>>> 00 2 :> <<>>> 00 2 :> <<>>> 00 2 :> <<>>> 00 2 :> <<>>> 00 2 :> <<>>> <</>>>>>> 00 2 :> <<<>>> 00 2 :> <<<>>> 00 2 :> <<<>>> 00 2 :> <<<>>> 00 2 :> <<<>>> 00 2 :> <<<>>> 00 2 :> <<<>>> 00 2 :> <<<>>> 00 2 :> <<<>>> 00 2 :> <<<>>> 00 2 :> <<<>>> 00 2 :> <<<>>> 00 2 :> <<<>>> 00 2 :> <<<>>> 00 2 :> <<<>>> 00 2 :> <<<>>> 00 2 :> <<<>>> 00 2 :> <<<>>> 00 2 :> <<<>>> 00 2 :> <<<>>> 00 2 :> <<<>>> 00 2 :> <<<>>> 00 2 :> <<<>>> 00 2 :> <<<>>> 00 2 :> <<<>>> 00 2 :> <<<>>> 00 2 :> <<<>>> 00 2 :> <<<>>> 00 2 :> <<<>>> 00 2 :> <<<>>> 00 2 :> <<<>>> 00 2 :> <<<>>> 00 2 :> <<<>>> 00 2 :> <<<>>> 00 2 :> <<<>>> 00 2 :> <<<>>> 00 2 :> <<<>>> 00 2 :> <<<>>> 00 2 :> <<<>>> 00 2 :> <<<>>> 00 2 :> <<<>>>> 00 2 :> <<<>>> 00 2 :> <<<>>> 00 2 :> <<<>>> 00 2 :> <<<>>> 00 2 :> <<<>>> 00 2
                2:>(0:><>> 001:><>> 001:><>> 001:><>> 001:><>>> 001:><>>> 001:><>>> 001:><>>> 001:><>>> 001:><>>> 001:><>>> 001:><>>> 001:><>>> 001:></
              /\ seqnr = (0 :> 0 @@ 1 :> 0 @@ 2 :> 0)
57 + /\ pc = (0 :> "init" (0 1 :> "off" (0 2 :> "off")
             /\ state = ( 0 :> " unused init value" 88
               1 :> "_unused_init_value" (0
2 :> " unused_init_value")
              /\ timeout_request_add = [type |-> "__notimeout"]
                          ( 0 :> "__unused_init_value" @@
1 :> "__unused_init_value" @@
                                 2 :> "_unused_init_value" ) @@
                         ( 0 :> "__unused_init_value" @@
                                1 :> "_unused_init_value" @@
                                 2 :> "_unused_init_value" ) )
               /\ msq to send = [no message |-> ""]
              /\ event = (0 :> defaultInitValue @@ 1 :> defaultInitValue @@ 2 :> defaultInitValue)
              /\ timeout_request_del = [type |-> "__notimeout"]
/\ stack = (0 :> <<>> (0 1 :> <<>> (0 2 :> <<>>)
              /\ timeouts = ( 0 :>
                           ( 0 :> [type |-> " notimeout"] @@
                               1 :> [type |-> "_notimeout"] @@
2 :> [type |-> "_notimeout"] ) @@
                          ( 0 :> [type |-> "__notimeout"] @@
1 :> [type |-> "__notimeout"] @@
2 :> [type |-> "__notimeout"] ) @@
                          ( 0 :> [type |-> "__notimeout"] (0
                                1 :> [type |-> "__notimeout"] @@
            2 :> [type |-> "_notineout"] ) )

/ messages = ( 0 :> (0 :> <<>> 88 1 :> <<>> 86 2 :> <<>>) 88
                  1 :> (0 :> <<>> @ 1 :> <<>> @ 2 :> <<>>) @@
               2:>(0:><>>001:><>>000)
97 + /\ pc = (0 :> "Error" (0 1 :> "off" (0 2 :> "off")
99 + // state = (0 :> "state_start" (0 1 :> "_unused_init_value" (0 2 :> "_unused_init_value")
```

Lessons Learnt

Valuable insights to system design

Justifiable overhead

Very close to implementation

Further Material

This document may not be reproduced, modified, adapted, published, translated, in any way, in whole or in part or disclosed to a third party without the prior written consent of Thales - © Thales 2018 All rights reserved

- **Environment with example algorithm**
 - https://github.com/stresch/pingpong