

PB4 Aluminium Pad Mount Motors - Performance Data

2 - 6 pole Motors - 50Hz Supply

IEC Rating	Output	Frame Size	Type	Speed	Pole	Current at 400 V	FLT	Efficiency (%)			Power Factor			D.O.L			Motor
	kW		PB3/PB4*	r/min		A	Nm	4/4	3/4	1/2	4/4	3/4	1/2	Starting Torque	pu Current	BDT	Mass
	0.37	71	070	2740	2	0.94	1.3	70.0	68.9	66.2	0.81	0.75	0.63	2.2	6.1	2.2	8
	0.55	71	073	2740	2	1.33	1.9	73.0	70.2	67.4	0.82	0.77	0.64	2.2	6.1	2.2	9
	0.75	80	080	2855	2	1.64	2.5	80.7	80.7	79.1	0.82	0.77	0.64	2.3	7	2.3	10
	1.1	80	083	2855	2	2.31	3.7	82.7	82.7	81.0	0.83	0.81	0.70	2.2	7.6	2.3	13
	1.5	90S	090	2880	2	3.06	5.0	84.2	84.2	82.5	0.84	0.77	0.65	2.2	7.9	2.3	15
	2.2	90L	093	2880	2	4.35	7.3	85.9	85.9	84.2	0.85	0.82	0.71	2.2	7.9	2.3	18
	3	100L	101	2890	2	5.7	9.9	87.1	87.1	85.4	0.87	0.85	0.77	2.2	8.5	2.3	24
	4	112M	112	2905	2	7.4	13.1	88.1	88.1	86.3	0.88	0.87	0.80	2.2	8.5	2.3	32
	5.5	132S	130	2920	2	10.1	18.0	89.2	89.2	87.4	0.88	0.87	0.81	2	8.5	2.3	47
	7.5	132S	131	2915	2	13.7	24.6	90.1	90.1	88.3	0.88	0.87	0.82	2	8.5	2.3	51
	9.2	132M	133	2920	2	16.7	30.1	90.4	90.4	88.5	0.88	0.88	0.83	2	8.5	2.3	56

0.25	71	071	1330	4	0.8	1.8	65.0	62.1	60.9	0.74	0.66	0.54	2.1	4.4	2.1	8
0.37	71	073	1330	4	1.1	2.7	67.0	64.9	62.1	0.75	0.67	0.55	2.1	5.2	2.1	8
0.55	80	080	1420	4	1.3	3.7	80.8	80.8	79.2	0.75	0.67	0.55	2.4	6.6	2.3	10
0.75	80	083	1420	4	1.7	5.0	82.5	82.5	80.9	0.75	0.72	0.59	2.3	6.6	2.3	12
1.1	90S	090	1425	4	2.5	7.4	84.1	84.1	82.4	0.76	0.69	0.56	2.3	6.8	2.3	16
1.5	90L	093	1430	4	3.3	10.0	85.3	85.3	83.6	0.77	0.71	0.58	2.3	7	2.3	19
2.2	100L	101	1440	4	4.5	14.6	86.7	86.7	85.0	0.81	0.75	0.63	2.3	7.6	2.3	26
3	100L	102	1440	4	6.0	19.9	87.7	87.7	85.9	0.82	0.78	0.66	2.3	7.6	2.3	30
4	112M	112	1445	4	7.95	26.4	88.6	88.6	86.8	0.82	0.79	0.68	2.2	7.8	2.3	37
5.5	132S	130	1460	4	10.67	36.0	89.6	89.6	87.8	0.83	0.80	0.68	2	7.9	2.3	47
7.5	132M	133	1460	4	14.26	49.1	90.4	90.4	88.6	0.84	0.80	0.69	2	7.5	2.3	59
9.2	132M	135	1460	4	17.43	60.2	90.7	90.7	88.8	0.84	0.81	0.71	2.2	7.7	2.3	64

0.37	80	080	930	6	1.04	3.8	73.5	73.5	72.0	0.70	0.60	0.47	1.9	6	2	10
0.55	80	083	930	6	1.43	5.6	77.2	77.2	75.7	0.72	0.62	0.50	1.9	6	2.1	13
0.75	90S	090	940	6	1.93	7.6	78.9	78.9	77.3	0.71	0.62	0.48	2	6	2.1	16
1.1	90L	093	940	6	2.69	11.2	81.0	81.0	79.4	0.73	0.64	0.50	2	6	2.1	21
1.5	100L	102	950	6	3.59	15.1	82.5	82.5	80.9	0.73	0.65	0.51	2	6.5	2.1	23
2.2	112M	112	950	6	5.09	22.1	84.3	84.3	82.6	0.74	0.68	0.55	2	6.6	2.1	33
3	132S	130	975	6	6.84	29.4	85.6	85.6	83.9	0.74	0.68	0.54	2	6.8	2.1	39
4	132M	133	975	6	8.99	39.2	86.8	86.8	85.1	0.74	0.67	0.54	2	6.8	2.1	48
5.5	132M	134	975	6	12.03	53.9	88.0	88.0	86.2	0.75	0.69	0.55	2	7	2.1	57

AIR OVER RATING		
Output	Current at 400 V	Required Air Flow
kW	A	m/s
0.4	1.02	12.0
0.65	1.57	12.0
0.85	1.85	12.0
1.3	2.73	12.0
1.8	3.67	14.5
2.6	5.14	14.5
3.5	6.67	19.5
4.7	8.75	19.5
6	11.0	26.0
8.6	15.7	26.0
10.6	19.2	26.0

0.28	0.84	7.0
0.4	1.15	7.0
0.65	1.55	7.5
0.85	1.98	7.5
1.3	2.94	9.0
1.8	3.96	9.0
2.6	5.34	11.0
3.5	7.03	11.0
4.7	9.34	12.0
6	11.6	16.0
8.6	16.3	16.0
10.6	20.1	16.0

0.4	1.12	6.5
0.65	1.69	6.5
0.85	2.19	7.5
1.3	3.17	7.5
1.8	4.31	8.0
2.6	6.02	9.0
3.4	7.75	11.0
4.5	10.1	11.0
6	13.1	11.0

* PB3 range for frame size 71. PB4 range for frames 80 to 132

Values indicated are subject to change without prior notice. To obtain guaranteed values, please contact and AEM motor outlet.

All values are subject to IEC tolerances. Values are given for a 50Hz supply.

Locked Rotor Ratios - Pu Value
 Power Factor - Power Factor under different conditions
 Output - Rated Output (kW)
 Speed - Motor Rated speed (r/min)
 Frame - IEC Frame Size

FLT - Full Load torque (Nm)
 Type - Range Type
 Efficiency - Efficiency at full load