

Package ‘myFun’

November 13, 2023

Type Package

Title myFun is a collection of my favorite R functions, packaged for simplicity

Version 1.0.6

Date 2023-11-13

Author Tom Lesluyes [aut, cre]

Maintainer Tom Lesluyes <lesluyes.tom@iuct-oncopole.fr>

Description My utility functions for R.

URL <https://github.com/tlesluyes/myFun>

BugReports <https://github.com/tlesluyes/myFun/issues>

License GPL-3 + file LICENSE

Encoding UTF-8

LazyData true

Depends R (>= 3.4.0)

Imports GenomicRanges,
IRanges,
doParallel,
foreach

Roxygen list(markdown = TRUE)

RoxygenNote 7.2.3

R topics documented:

adjustPositions	2
checkGRlist	3
computeBAF	4
computeFit	5
computeISA	6
computeISA_batch	7
computeLogR	8
computeMD	9

computeMD_batch	10
generate_cytoband_and_CHRsize	11
harmonizeGRanges	12
load_CHRsize	13
load_cytoband	13
occurrenceGRanges	14
reestimate_ploidy	15
reestimate_purity	16
splitDF	17
summarise_segmetation	18

Index	19
--------------	-----------

adjustPositions	<i>adjustPositions</i>
-----------------	------------------------

Description

Adjust genomic positions

Usage

```
adjustPositions(  
  DF,  
  CHRsize,  
  chr_column = "chr",  
  start_column = "start",  
  end_column = "end",  
  suffix = "_adj"  
)
```

Arguments

DF	a data.frame
CHRsize	a data.frame from the load_CHRsize function
chr_column	a column name with chromosome information (default: "chr")
start_column	a column name with start position (default: "start")
end_column	a column name with end position (default: "end")
suffix	a suffix for the adjusted positions (default: "_adj")

Details

This function adjusts genomic positions according to the chromosome sizes. The first nucleotide of chromosome 2 corresponds to the size of the chromosome 1 + 1bp and so on.

Value

A data.frame with adjusted genomic positions

Author(s)

tlesluyes

Examples

```
DF=data.frame(chr=c(1:3), start=rep(1e6, 3), end=rep(125e6, 3))
load_CHRsize("hg19")
adjustPositions(DF, CHRsize)
```

checkGRlist*checkGRlist*

Description

Check that the given object is a list of GRanges objects

Usage

```
checkGRlist(myGRList)
```

Arguments

myGRList a list of GRanges objects

Details

This function checks that the given object is a list of GRanges objects.

Value

TRUE if the input is a list of GRanges objects

Author(s)

tlesluyes

Examples

```
require("GenomicRanges")
GR1=GRanges(seqnames="1", ranges=IRanges(start=1, end=1000))
GR2=GRanges(seqnames="1", ranges=IRanges(start=10, end=2000))
checkGRlist(list(GR1, GR2))
```

`computeBAF`*computeBAF*

Description

Compute the theoretical BAF values for a given segment

Usage

```
computeBAF(nMajor, nMinor, purity, digits = 4)
```

Arguments

nMajor	the number of copies of the major allele
nMinor	the number of copies of the minor allele
purity	the purity estimate of the tumour
digits	a numeric, the number of digits to round to (default: 4)

Details

This function computes the theoretical BAF values for a given segment (from nMajor, nMinor and purity values).

Value

A vector of two numbers representing the BAF values

Author(s)

tlesluyes

See Also

<https://doi.org/10.1038/s41592-020-01013-2>

Examples

```
# A 2+1 state in a tumour with 90% purity
computeBAF(2, 1, 0.9)
# A 1+0 state in a tumour with 60% purity
computeBAF(1, 0, 0.6)
```

`computeFit`*computeFit*

Description

Compute the purity/ploidy fit for a given segment

Usage

```
computeFit(logR, BAF, nMajor, nMinor, gamma, digits = 4)
```

Arguments

logR	the logR value of the segment
BAF	the BAF value of the segment (upper band only so the value should be in the 0.5-1 space)
nMajor	the number of copies of the major allele
nMinor	the number of copies of the minor allele
gamma	the gamma parameter is platform-dependent and represents the expected logR decrease in a diploid sample where one copy is lost (should be 1 for HTS data and 0.55 for SNP arrays)
digits	a numeric, the number of digits to round to (default: 4)

Details

This function computes the purity/ploidy fit (rho, psi and psit) for a given segment (from logR, BAF, proposed nMajor and proposed nMinor).

Value

A list with the rho (=purity), psi (=total ploidy) and psit (=tumour ploidy) values

Author(s)

tlesluyes

See Also

<https://doi.org/10.1038/s41592-020-01013-2>

Examples

```
# A segment has logR=0.5361 and BAF=0.3448/0.6552
# What is the purity/ploidy fit if I believe that the segment is 2+1?
computeFit(0.5361, 0.6552, 2, 1, 1) # purity=90%; ploidy=2
```

computeISA

computeISA

Description

Compute the inter-sample agreement (ISA)

Usage

```
computeISA(GR1, GR2, CNstatus = "CNstatus")
```

Arguments

GR1	a GRanges object corresponding to a single CNA profile
GR2	a GRanges object corresponding to a single CNA profile
CNstatus	a metadata column name for the copy-number status (default: "CNstatus"). Can be total (e.g. "3") or allele-specific (e.g. "2+1")

Details

This function computes the inter-sample agreement (ISA) between two profiles (as GRanges objects). This corresponds to the fraction of the genome (%) with the same CN status.

Value

A percentage representing the ISA

Author(s)

tlesluyes

Examples

```
require("GenomicRanges")
GR1=GRanges(seqnames=rep("1", 3),
             ranges=IRanges(start=c(1, 1001, 10001),end=c(1000, 10000, 20000)),
             CNstatus=c("1+1", "2+1", "1+1"))
GR2=GRanges(seqnames=rep("1", 2),
             ranges=IRanges(start=c(500, 10001),end=c(10000, 25000)),
             CNstatus=c("2+1", "1+1"))

# in this example:
#   Region 500-1000 (size=501) is 1+1 for GR1 and 2+1 for GR2
#   Region 1001-20000 (size=19000) is identical between GR1 and GR2 (both 2+1 and 1+1)
#   ISA is: 19000/19501 = 97.43%
computeISA(GR1, GR2)
```

computeISA_batch	<i>computeISA_batch</i>
------------------	-------------------------

Description

Compute the inter-sample agreement (ISA) for a batch of samples

Usage

```
computeISA_batch(myGRList, cores = 1, min_seg_size = 0, CNstatus = "CNstatus")
```

Arguments

myGRList	a list of GRanges objects, each object should correspond to one CNA profile
cores	a numeric, the number of cores to use (default: 1)
min_seg_size	a numeric, the minimum segment size (in bp) to consider (default: 0)
CNstatus	a metadata column name for the copy-number status (default: "CNstatus"). Can be total (e.g. "3") or allele-specific (e.g. "2+1")

Details

This function computes the inter-sample agreement (ISA) between multiple profiles (as a list of GRanges objects).

Value

A matrix of ISA values

Author(s)

tlesluyes

Examples

```
require("GenomicRanges")
GR1=GRanges(seqnames=rep("1", 3),
             ranges=IRanges(start=c(1, 1001, 10001), end=c(1000, 10000, 20000)),
             CNstatus=c("1+1", "2+1", "1+1"))
GR2=GRanges(seqnames=rep("1", 2),
             ranges=IRanges(start=c(500, 10001), end=c(10000, 25000)),
             CNstatus=c("2+1", "1+1"))
GR3=GRanges(seqnames="1",
             ranges=IRanges(start=500, end=25000),
             CNstatus="1+1")
myGRList=list(GR1, GR2, GR3)
names(myGRList)=c("GR1", "GR2", "GR3")
computeISA_batch(myGRList)
```

`computeLogR`*computeLogR*

Description

Compute the theoretical logR value for a given segment

Usage

```
computeLogR(nMajor, nMinor, purity, ploidy, digits = 4)
```

Arguments

nMajor	the number of copies of the major allele
nMinor	the number of copies of the minor allele
purity	the purity estimate of the tumour
ploidy	the ploidy estimate of the tumour
digits	a numeric, the number of digits to round to (default: 4)

Details

This function computes the theoretical logR value for a given segment (from nMajor, nMinor, purity and ploidy values). Since logR isn't allele-specific, ntot can be used instead of nMajor (and nMinor should set to 0).

Value

A number representing the logR value

Author(s)

tleluyes

See Also

<https://doi.org/10.1038/s41592-020-01013-2>

Examples

```
# A 2+1 state in a diploid tumour with 90% purity
computeLogR(2, 1, 0.9, 2)
# A loss of 1 copy (2+1) in a pseudo-tetraploid tumour with 60% purity
computeLogR(2, 1, 0.6, 3.5)
```

computeMD	<i>computeMD</i>
-----------	------------------

Description

Compute the Manhattan distance (MD)

Usage

```
computeMD(GR1, GR2, nMajor = "nMajor", nMinor = "nMinor", convertMb = FALSE)
```

Arguments

GR1	a GRanges object corresponding to a single CNA profile
GR2	a GRanges object corresponding to a single CNA profile
nMajor	a metadata column name for the major allele (default: "nMajor")
nMinor	a metadata column name for the minor allele (default: "nMinor")
convertMb	a boolean, the MD will be converted to megabases if set to TRUE (default: FALSE)

Details

This function computes the Manhattan distance (MD) between two profiles (as GRanges objects).

Value

A numeric value representing the MD

Author(s)

tlesluyes

Examples

```
require("GenomicRanges")
GR1=GRanges(seqnames=rep("1", 3),
             ranges=IRanges(start=c(1, 1001, 10001), end=c(1000, 10000, 20000)),
             nMajor=c(1, 2, 1),
             nMinor=c(1, 1, 1))
GR2=GRanges(seqnames=rep("1", 2),
             ranges=IRanges(start=c(500, 10001), end=c(10000, 25000)),
             nMajor=c(2, 1),
             nMinor=c(1, 1))

# in this example:
#   Region 500-1000 (size=501) is 1+1 for GR1 and 2+1 for GR2
#   Region 1001-20000 (size=19000) is identical between GR1 and GR2 (both 2+1 and 1+1)
#   MD is: (abs(2-1)+abs(1-1))*501 = 501
computeMD(GR1, GR2)
```

computeMD_batch	<i>computeMD_batch</i>
-----------------	------------------------

Description

Compute the Manhattan distance (MD) for a batch of samples

Usage

```
computeMD_batch(  
  myGRList,  
  cores = 1,  
  min_seg_size = 0,  
  nMajor = "nMajor",  
  nMinor = "nMinor",  
  convertMb = FALSE  
)
```

Arguments

myGRList	a list of GRanges objects, each object should correspond to one CNA profile
cores	a numeric, the number of cores to use (default: 1)
min_seg_size	a numeric, the minimum segment size (in bp) to consider (default: 0)
nMajor	a metadata column name for the major allele (default: "nMajor")
nMinor	a metadata column name for the minor allele (default: "nMinor")
convertMb	a boolean, the MD will be converted to megabases if set to TRUE (default: FALSE)

Details

This function computes the Manhattan distance (MD) between multiple profiles (as a list of GRanges objects).

Value

A matrix of MD values

Author(s)

tlesluyes

Examples

```
require("GenomicRanges")
GR1=GRanges(seqnames=rep("1", 3),
             ranges=IRanges(start=c(1, 1001, 10001), end=c(1000, 10000, 20000)),
             nMajor=c(1, 2, 1),
             nMinor=c(1, 1, 1))
GR2=GRanges(seqnames=rep("1", 2),
             ranges=IRanges(start=c(500, 10001), end=c(10000, 25000)),
             nMajor=c(2, 1),
             nMinor=c(1, 1))
GR3=GRanges(seqnames="1",
             ranges=IRanges(start=500, end=25000),
             nMajor=1,
             nMinor=1)
myGRList=list(GR1, GR2, GR3)
names(myGRList)=c("GR1", "GR2", "GR3")
computeMD_batch(myGRList)
```

```
generate_cytoband_and_CHRsize
```

```
generate_cytoband_and_CHRsize
```

Description

Generate cytoband and CHRsize information

Usage

```
generate_cytoband_and_CHRsize(cytoband_file)
```

Arguments

cytoband_file a cytoband file

Details

This function generates cytoband and CHRsize information from a cytoband file. This can be obtained from the UCSC table browser -> select a genome/assembly -> "Mapping and Sequencing" -> "Chromosome Band" (not the ideogram version!) -> "get output" -> Remove the first "#" character (keep the header!).

Value

A list with both the cytoband and CHRsize information

Author(s)

tlesluyes

See Also

```
load_CHRsize("hg38"); load_cytoband("hg38")
```

harmonizeGRanges	<i>harmonizeGRanges</i>
------------------	-------------------------

Description

Harmonize GRanges objects

Usage

```
harmonizeGRanges(myGRList, cores = 1)
```

Arguments

myGRList	a list of GRanges objects, each object should correspond to one CNA profile
cores	a numeric, the number of cores to use (default: 1)

Details

This function harmonizes GRanges objects by keeping only regions covered by all samples.

Value

A list of harmonized GRanges objects

Author(s)

tleluyes

Examples

```
require("GenomicRanges")
GR1=GRanges(seqnames="1", ranges=IRanges(start=1, end=1000), nMajor=1, nMinor=1)
GR2=GRanges(seqnames="1", ranges=IRanges(start=10, end=2000), nMajor=2, nMinor=1)
harmonizeGRanges(list(GR1, GR2))
```

load_CHRsize	<i>load_CHRsize</i>
--------------	---------------------

Description

Load CHRsize information

Usage

```
load_CHRsize(assembly)
```

Arguments

assembly an assembly (hg19 or hg38)

Details

This function loads CHRsize information for a given assembly. It is then available as a data.frame called CHRsize in the environment.

Value

A data.frame with the CHRsize information

Author(s)

tlesluyes

Examples

```
load_CHRsize("hg38"); head(CHRsize)
```

load_cytoband	<i>load_cytoband</i>
---------------	----------------------

Description

Load cytoband information

Usage

```
load_cytoband(assembly)
```

Arguments

assembly an assembly (hg19 or hg38)

Details

This function loads cytoband information for a given assembly. It is then available as a data.frame called cytoband in the environment.

Value

A data.frame with the cytoband information

Author(s)

tlesluyes

Examples

```
load_cytoband("hg38"); head(cytoband)
```

occurrenceGRanges	<i>occurrenceGRanges</i>
-------------------	--------------------------

Description

Get the occurrence of events

Usage

```
occurrenceGRanges(myGRList, myMetadata)
```

Arguments

myGRList	a list of GRanges objects, each object should correspond to one CNA profile
myMetadata	a vector of metadata to consider

Details

This function gets the occurrence of events in a list of GRanges objects. All objects must have the same metadata columns and metadata must be TRUE/FALSE.

Value

A GRanges object with nSamples as the total number of samples and metadata columns with the occurrence of events

Author(s)

tlesluyes

Examples

```
require("GenomicRanges")
GR1=GRanges(seqnames="1", ranges=IRanges(start=1, end=1000), Gain=TRUE, Loss=FALSE)
GR2=GRanges(seqnames="1", ranges=IRanges(start=10, end=2000), Gain=FALSE, Loss=TRUE)
occurrenceGRanges(list(GR1, GR2), c("Gain", "Loss"))
```

reestimate_ploidy	<i>reestimate_ploidy</i>
-------------------	--------------------------

Description

Compute the re-estimated ploidy for a given sample

Usage

```
reestimate_ploidy(rho.old, psit.old, rho.new, WGD, digits = 4)
```

Arguments

<code>rho.old</code>	old purity estimate
<code>psit.old</code>	old ploidy estimate
<code>rho.new</code>	new purity estimate
<code>WGD</code>	number of WGD events (0 if there is no WGD)
<code>digits</code>	a numeric, the number of digits to round to (default: 4)

Details

This function computes the re-estimated ploidy for a given sample (from its old purity/ploidy fit and the re-estimated purity).

Value

A number representing the re-estimated ploidy

Author(s)

tlesluyes

Examples

```
# A pseudo-diploid sample has purity=74% and ploidy=2.4
# What is the re-estimated ploidy if I believe that the sample has purity=61%?
reestimate_ploidy(0.74, 2.4, 0.61, 0)
```

reestimate_purity	<i>reestimate_purity</i>
-------------------	--------------------------

Description

Compute the re-estimated purity for a given sample

Usage

```
reestimate_purity(rho.old, psit.old, switch, digits = 4)
```

Arguments

rho.old	old purity estimate
psit.old	old ploidy estimate
switch	a character ("double" or "halve") indicating whether the ploidy should be doubled or halved
digits	a numeric, the number of digits to round to (default: 4)

Details

This function computes the re-estimated purity for a given sample in the context of a jump in ploidy (so the matched ploidy needs to be doubled or halved).

Value

A number representing the re-estimated purity

Author(s)

tlesluyes

Examples

```
# A sample has purity=74% and ploidy=2.4 but the CNA profile needs to be doubled
# What is the re-estimated purity?
reestimate_purity(0.74, 2.4, "double")
```

`splitDF`*splitDF*

Description

Split a data.frame

Usage

```
splitDF(DF, chunks, shuffle = FALSE, seed = 1234)
```

Arguments

DF	a data.frame to split
chunks	a number of chunks to obtain
shuffle	a boolean, whether to shuffle the data.frame before splitting (default: FALSE)
seed	a number, the seed for the random number generator (default: 1234)

Details

This function splits a data.frame into a list of data.frames.

Value

A list of data.frames

Author(s)

tlesluyes

Examples

```
DF=data.frame(a=1:26, b=letters)
splitDF(DF, 3)
```

summarise_segmetation *summarise_segmetation*

Description

Summarise segmentation data

Usage

```
summarise_segmetation(DF, col_chr, col_start, col_end, col_values)
```

Arguments

DF	a data.frame with segmentation data
col_chr	a string, the name of the column containing the chromosome
col_start	a string, the name of the column containing the start position
col_end	a string, the name of the column containing the end position (can be the same as col_start for SNP-based segmentation where start=end)
col_values	a vector of strings, the names of the columns containing the values of interest (logR, BAF, etc.)

Details

This function summarises segmentation data, typically logR and/or BAF values for individual SNPs or loci.

Value

A named list with segments being a data.frame with the summarised information and IDs being a list of SNPs/loci associated with the different segments

Author(s)

tlesluyes

Examples

```
DF=data.frame(chr=c(rep("chr1", 10),rep("chr2", 6)),
              pos=c(1:10*1e3, 1:6*1e3),
              logR=c(rep(0, 4), rep(0.54, 3), rep(0, 3), rep(-0.86, 3), rep(0, 3)),
              BAF=c(rep(0.5, 4), rep(0.34, 3), rep(0.5, 3), rep(0.09, 3), rep(0.5, 3)),
              row.names=paste0("SNP_", 1:16))

DF
summarise_segmetation(DF, "chr", "pos", "pos", c("logR", "BAF"))
```

Index

`adjustPositions`, [2](#)

`checkGRlist`, [3](#)
`computeBAF`, [4](#)
`computeFit`, [5](#)
`computeISA`, [6](#)
`computeISA_batch`, [7](#)
`computeLogR`, [8](#)
`computeMD`, [9](#)
`computeMD_batch`, [10](#)

`generate_cytoband_and_CHRsize`, [11](#)

`harmonizeGRanges`, [12](#)

`load_CHRsize`, [13](#)
`load_cytoband`, [13](#)

`occurrenceGRanges`, [14](#)

`reestimate_ploidy`, [15](#)
`reestimate_purity`, [16](#)

`splitDF`, [17](#)
`summarise_segmetation`, [18](#)