





NEW ORLEANS, LA


HOUSTON, TX


OF 6

VICINITY MAP











CONSULTING ENGINEERS INCORPORATED

NEW ORLEANS, LA

BEAUMONT, TX

LOUISIANA

PERMIT DRAWING GRETNA DOCK FACILITY - DOCK UPGRADE NEW 42'Ø CAPTURE PILE


DATE_OCT. '11 DESIGN TMO DRAWN BSB CHECK JEJ CONTRACT 8591 SHEET No.

5 _{OF} 6

NOTES:



- SIZE OF RIPRAP TO VARY BETWEEN 6 POUNDS AND 125 POUNDS WITH 40% TO 60% OF THE STONE WITHIN THE RANGE OF 25 POUNDS TO 75 POUNDS.
- 2. WHEN PENETRATING UPPER BANK PAVING IN A WHEN FENE IRATING OPPER BANK PAVING IN A
 REVETMENT AREA WITH PILES, CAISSONS AND/OR PILE
 CLUSTERS, A 10 INCH THICKNESS OF RIPRAP STONE
 SHALL BE PLACED OVER ALL AREAS WHERE BANK
 PAVING IS DISTURBED BY DRIVING OPERATIONS.
- 3. VOLUME OF RIPRAP 46 CUBIC YARDS.



BEPTH OF WATER IN FEET AT POINT OF PENETRATION AT TIME OF STONE PLACEMENT	DIMENSIONS IN FEET FOR PROTECTION AREA REQUIRED							
	PILE		CAISSON		SPUD PILE W/ ANCHOR CHAIN & BUOY		PILE CLUSTER	
	Х	Υ	Х	Υ	Χ	Υ	X	Υ
1 TO 10	3	1 1/2	5	2			3	1
11 TO 40	5	2	8	3	7	3	6	2
41 TO 60	8	3	12	4	12	4	10	3

REVETMENT REPAIR DETAIL

8591-P6 DATE <u>OCT.</u> '11

TMO

DESIGN



LANIER & ASSOCIATES

CONSULTING ENGINEERS INCORPORATED

NEW ORLEANS, LA

BEAUMONT, TX

GRETNA

IMIT LOUISIANA

DRAWN BSB CHECK<u>JEJ</u> CONTRACT<u>8591</u> SHEET No.

6 _{OF} 6

PERMIT DRAWING GRETNA DOCK FACILITY - DOCK UPGRADE REVETMENT REPAIR DETAIL