


BULKHEADS WILL BE INSTALLED ALONG THE CANAL BANKS EXCEPT FOR THE CANAL THROUGH THE WETLANDS AND ALONG THE CANAL BANK THAT IS ADJACENT TO THE WETLANDS

# PROPOSED TYPICAL SECTION

SECTION "A-A"

N.T.S.






### PROPOSED TYPICAL SECTION

SECTION "B-B"

BULKHEADS WILL BE INSTALLED ALONG THE CANAL BANKS EXCEPT FOR THE CANAL THROUGH THE WETLANDS AND ALONG THE CANAL BANK THAT IS ADJACENT TO THE WETLANDS






BULKHEADS WILL BE INSTALLED ALONG THE CANAL BANKS EXCEPT FOR THE CANAL THROUGH THE WETLANDS AND ALONG THE CANAL BANK THAT IS ADJACENT TO THE WETLANDS

PROPOSED SECTION "C-C"

N.T.S.






PROPOSED TYPICAL SECTION

SECTION "D-D"

BULKHEADS WILL BE INSTALLED ALONG THE CANAL BANKS EXCEPT FOR THE CANAL THROUGH THE WETLANDS AND ALONG THE CANAL BANK THAT IS ADJACENT TO THE WETLANDS






## PROPOSED TYPICAL SECTION

SECTION "E-E"

N.T.S.

BULKHEADS WILL BE INSTALLED ALONG THE CANAL BANKS EXCEPT FOR THE CANAL THROUGH THE WETLANDS AND ALONG THE CANAL BANK THAT IS ADJACENT TO THE WETLANDS






BULKHEADS WILL BE INSTALLED ALONG THE CANAL BANKS EXCEPT FOR THE CANAL THROUGH THE WETLANDS AND ALONG THE CANAL BANK THAT IS ADJACENT TO THE WETLANDS




27343 FROST ROAD LIVINGSTON, LA. 70754 (225)686-1444



BULKHEADS WILL BE INSTALLED ALONG THE CANAL BANKS
EXCEPT FOR THE CANAL THROUGH THE WETLANDS AND ALONG
THE CANAL BANK THAT IS ADJACENT TO THE WETLANDS





TYPICAL ROADWAY SECTION

#### LEGEND: FOR ASPHALT PAVING

- 3" THICK (MIN.) ASPHALT PAVEMENT (2-13" LIFTS). (TYPE 3 WEARING COURSE MARSHALL MIX DESIGN PER LOUISIANA STANDARD SPECIFICATIONS FOR ROADS AND SRIDGES 2006 EDITION).
- ② 10" (MIN.) BABE TO BE TREATED WITH 10% (BY VOLUME) TYPE 0 LIME TREATMENT AND TREATED WITH 10% (BY VOLUME) TYPE 1 PORTLAND DEMENT TREATMENT BOTH PER LOUISIANA STANDARD SPECIFICATION FOR ROADS AND SRIDGES 2006 EDITION OR AS REGO PROM TESTING LAS RESULTS.
- (3) EXISTING GROUND.

#### BASE PREPARATION AND PAVING NOTES:

- 1. ALL WORK AND MATERIAL TO BE IN
  COMPLIANCE WITH LOUISIANA DEPARTMENT OF
  TRANSPORTATION STANDARD SPECIFICATIONS
  FOR ROADS AND SRIDGES, LATEST EDITION,
  UNLESS OTHERWISE NOTED.
- 2. EXISTING TOP SOIL IN PROPOSED ROAD BED TO BE EXCAVATED AND REMOVED AS NECESSARY FOR FINAL GRADE.
- 3. GRUB REMAINING BASE MATERIAL TO A DEPTH OF 12" BEFORE TREATING WITH LIME/CEMENT.
- 4. ROADWAY BASE AND SUB-BASE SHALL HAVE PLASTICITY INDEX OF 15 OR LESS UNDISTURBED AND SHALL BE COMPACTED TO 95% STANDARD

