

Inheritance

Tiziana Ligorio
tligorio@hunter.cuny.edu

Today's Plan



Inheritance Recap
Polymorphism

Announcements and Syllabus Check

Q: Why use dynamic memory allocation?

Q: Is while loop condition in `toVector()` redundant?

Forum: on Blackboard. Get it started, soon I will discontinue
csci235.help@gmail.com

Slight modifications to Project 3:

Changed wording of copy constructor paragraph to be more clear (might have been misleading)

Added some checks to the main function

Inheritance Recap

Basic Inheritance

```
class Printer
{
public:
    //Constructor, destructor


    void setPaperSize(const int size);
    void setOrientation(const string& orientation);
    void changeCartridge();
    void printDocument(const string& document);
private:
    // stuff here
}; //end Printer

class BatchPrinter: public Printer // inherit from printer
{
public:
    //Constructor, destructor
    void addDocument(const string& document);
    void printAllDocuments();
private:
    vector<string> documents; //Document queue
}; //end BatchPrinter
```

```
class GraphicsPrinter: public Printer // inherit from printer
{
public:
    //Constructor, destructor
    void changeCartridge();
    void printDocument(const Picture& picture);

private:
    //stuff here
}; //end GraphicsPrinter
```

Basic Inheritance



```
void initializePrinter(Printer& p)
BatchPrinter batch;
initizlizePrinter(batch); //legal because batch is-a printer
```

Think of argument types as specifying *minimum requirements*

Problem

```
class BatchPrinter: public Printer // inherit from printer
{
public:
    //Constructor, destructor
    void addDocument(const string& document);
    void printAllDocuments();
private:
    vector<string> documents; //Document queue
}; //end BatchPrinter
```

**We would like to print all kinds of documents not just text
documents should be able to store different types of documents**


Generalized Document

Whatever the type of document, a printer ultimately prints a grid of pixels

Generalized Document should know how to convert itself into a printable format

We want Document to be an *interface* => not concerned with implementation details

printAllDocuments()



A red arrow pointing downwards from the row of Document objects to the code block below.

```
Document::convertToPixelArray()  
printPixelArray()
```

Polymorphism

```
class BatchPrinter: public Printer // inherit from printer
{
public:
    //Constructor, destructor
    void addDocument(const Document* document);
    void printAllDocuments();
private:
    vector<Document*> documents; //Document queue
}; //end BatchPrinter
```

Abstract Class!

```
class Document:
{
public:
    //Constructor, destructor
    virtual void convertToPixelArray() const = 0;
    virtual int getPriority() const = 0;
private:
    //stuff here
}; //end Document
```

This function has no implementation**




I'll explain this next

**odd syntax due to historical/political reasons, explained in quote later

```
class TextDocument: public Document // inherit from Document
{
public:
    //Constructor, destructor
    virtual void convertToPixelArray() const override;
    virtual int getPriority() const override;

    void setFont(const string& font); //text-specific formatting
    void setSize(int size);

private:
    //stuff here
}; //end TextDocument
```




Have implementation

```
class TextDocument: public Document
```

```
class GraphicsDocument: public Document
```

```
class PortableFormatDocument: public Document
```

```
class SpreadsheetDocument: public Document
```



But how does compiler know whose
`convertToPixelArray()` to call?

`TextDocument::convertToPixelArray?`

`GraphicsDocument::convertToPixelArray?`


Where are we going?

I want to store all kinds of documents in my
`BatchPrinter` queue

I want to access the correct `convertToPixelArray()`
method specific to each document type

main()

TextDocument **is-a** Document
GraphicsDocument **is-a** Document
We can point to objects of derived class
using pointers to base class



```
BatchPrinter myBatchPrinter;
```

```
Document* myTextDocument = new TextDocument;
```

```
Document* myGraphicsDocument = new GraphicsDocument;
```

```
//do stuff
```

We store in printer queue pointers to Document
but really can access any derived class document



```
myBatchPrinter.addDocument(myTextDocument)
```

```
myBatchPrinter.addDocument(myGraphicsDocument)
```

```
myBatchPrinter.printAllDocuments();
```

```
myTextDocument->convertToPixelArray();  
myGraphicsDocument->convertToPixelArray();
```

convertToPixelArray
is marked **virtual** so
the appropriate function call
is **determined at runtime**



Late Binding via Virtual Functions

Avoid statically binding function calls at compile time

Must declare functions as **virtual** for **late binding**

Polymorphism

We just saw an example of *polymorphism* (literally *many forms*)

With *virtual* functions the outcome of an operation is determined at execution time

With basic inheritance we were just saving ourselves the trouble of re-writing code

Abstract Class

Pure virtual function (=0) has no implementation in its own class

Abstract class

- Has at least one *pure virtual function*
- Cannot be instantiated because does not have implementation for some/all its member functions

```
Document myDocument;           //Error!
```

```
Document* myDocument;          //Error!
```

"The curious `=0` syntax was chosen over the obvious alternative of introducing a new keyword `pure` or `abstract` because at the time I saw no chance of getting a new keyword accepted. Had I suggested `pure`, Release 2.0 would have shipped without abstract classes, I chose `abstract classes`. Rather than risking delay and incurring the certain fights over `pure`, I used the traditional C and C++ convention of using 0 to represent 'not there' "

Bjarne Stroustrup

Polymorphism without abstraction

Superclass **need not** be abstract

Virtual functions in superclass **need not** be pure
virtual

Polymorphism without Abstract Classes

```
class RollerBlader()  
{  
public:  
    //constructor, destructor  
    virtual void slowDown();  
    //virtual, not pure  
virtual  
private:  
    //stuff here  
}; //end RollerBlader
```

```
void RollerBlader::slowDown()  
{  
    applyBreaks();  
} //end slowDown
```

```
class InexperiencedRollerBlader:  
    public RollerBlader  
{  
public:  
    //constructor, destructor  
    virtual void slowDown() override;  
private:  
    //stuff here  
}; //end InexperiencedRollerBlader
```

```
void InexperiencedRollerBlader  
    ::slowDown()  
{  
    fallDown();  
} //end slowDown
```

implementation does not
have **virtual** or
override keyword

Polymorphism without Abstract Classes

main()

```
RollerBlader* firstBlader = new RollerBlader;  
firstBlader->slowDown();    // applyBreaks()
```

```
RollerBlader* secondBlader = new InexperiencedRollerBlader;  
secondBlader->slowDown();    // falDown()
```

Polymorphism without Abstract Classes

Need not override **non-pure virtual** functions

```
class StuntRollerBlader: public RollerBlader
{
public:
    //constructor, destructor - note no mention of slowDown
    void frontFlip();
    void backFlip();
private:
    //stuff here
}; //end StuntRollerBlader
```

```
// stuff here
```

```
RollerBlader* blader = new StuntRollerBlader;
blader->slowDown();    // applyBreaks()
```

Warning

```
class NotVirtual
{
public:
    void notAVirtualFunction();
}; //end NotVirtual
```

```
class NotVirtualDerived: public NotVirtual
{
public:
    void notAVirtualFunction();
}; //end NotVirtualDerived
```

```
NotVirtual* nv = new NotVirtualDerived;
nv->notAVirtualFunction(); // OUCH!!! calls NotVirtual's member
                           // instead of NotVirtualDerived's member
```

When using pointers to base class, to let derived classes override functions in base class **must** make the base class's function **virtual**

More design considerations

Back to Document class


Assume we realize all types of documents have **width** and **height** data members

Makes sense to move them into base class

Don't want client to have direct access to data members

```
class Document:
{
public:
    //Constructor, destructor
    virtual void convertToPixelArray() const = 0;
    virtual int getPriority() const = 0;

private:
    int width, height; //Problem!!!
    //stuff here
}; //end Document
```



protected Access Specifier

```
class Document:
{
public:
    //Constructor, destructor
    virtual void convertToPixelArray() const = 0;
    virtual int getPriority() const = 0;

protected:
    int width, height;
    //stuff here

private:
    //stuff here
}; //end Document
```

Access Specifiers

public

accessible by everyone

private

accessible within class and by friends

protected

accessible within class, by friends and by **derived classes**

Inheritance accessibility

Access in Base Class	Inheritance Method	Access in Derived Class
public	public <i>is-a</i>	public
protected		protected
private		no access
public	protected <i>is-implemented-and-inherited-as</i>	protected
protected		protected
private		no access
public	private <i>is-implemented-as</i>	private
protected		private
private		no access

We will not discuss the details of protected and private inheritance in this course

override specifier


Explicitly tell compiler you mean to override a function

Compiler will check!

Also self-documenting

```
class BaseClass
{
    virtual void f(int);
};

class DerivedClass: public BaseClass
{
    virtual void f(float) override; //Compile-time error
};
```



final specifier

- Prevents inheritance
- Prevents deriving classes from overriding methods

```
class A
{
    virtual void f();
};
```

```
class B : public A
{
    void f() final override; //cannot override f()
};
```

```
class C: public B final //cannot inherit from C
{
    void f() override; //Error, f is final! ←
```

```
class D: public C{} //Error C is final! ←
```



Programming Practice

Write `BaseClass` and `DerivedClass` and inspect behavior with different configurations

- when do you get expected behavior?
- when do you get errors?

Abstract `BaseClass` vs Non-abstract `BaseClass`

Understand use of `virtual`, `final` and `override` specifiers, what they mean and when appropriate together

Investigate constructor and destructor behavior (discussed next)

Recap

Polymorphism -> virtual functions

Pure vs non-pure virtual functions

Polymorphism with or without abstract classes

`override` and `final`

Need to pay **extra** attention to **destructors** when
pointing to objects!!

```
class BaseClass()  
{  
public:  
    BaseClass();  
    ~BaseClass();  
}; //end BaseClass
```

```
class DerivedClass:  
    public BaseClass  
{  
public:  
    DerivedClass();  
    ~DerivedClass();
```


```
private:  
    char* myString;  
}; //end DerivedClass
```

```
DerivedClass::DerivedClass()  
{  
    //allocate some memory  
    myString = new char[128];  
}  
  
DerivedClass::~~DerivedClass()  
{  
    //deallocate memory  
    delete[] myString;  
}
```

```
main()
```

```
BaseClass* myClass = new DerivedClass;  
delete myClass; //PROBLEM!!! ←
```

**BaseClass destructor is invoked.
Need to allow late binding for destructor!!!**

Fix 

```

class BaseClass()
{
public:
    BaseClass();
    virtual ~BaseClass();

}; //end BaseClass

class DerivedClass:
    public BaseClass
{
public:
    DerivedClass();
    ~DerivedClass();

private:
    char* myString;
}; //end DerivedClass

```

```

DerivedClass::DerivedClass()
{
    //allocate some memory
    myString = new char[128];
}

DerivedClass::~~DerivedClass()
{
    //deallocate memory
    delete[] myString;
}

```

```

main()
BaseClass* myClass = new DerivedClass;
delete myClass; // both destructors
                //invoked

```

Problem fixed! BOTH destructors invoked

Virtual Functions in Constructors and Destructors

Recall

- **BaseClass** constructor invoked before **DerivedClass**'
- **DerivedClass** destructor invoked before **BaseClass**'

If **virtual function** in **constructor/destructor** is called polymorphically could try to access **uninitialized/deallocated** data

C++ prevents this by calling virtual functions in **constructors/destructors non-polymorphically**

```

class BaseClass()
{
public:
    BaseClass()
    {
        someVirtualFunction();
    }
    virtual void someVirtualFunction()
    {
        cout << "Base" << endl;
    }
}; //end BaseClass

```

```

class DerivedClass: public BaseClass
{
public:

```

```

    virtual void someVirtualFunction()
    {
        cout << "Derived" << endl;
    }

```

```

}; //end DerivedClass

```

```
main()
```

```
DerivedClass myDerivedClass;
```

Standard output:

Base



Runtime Costs of Virtual Functions

Function call overhead

- C++ maintains **virtual function tables** that store pointers to each virtual function
- Determine which function to call at execution time by looking-up **v-table** of object being pointed to


Clever! But still

Slower

Extra space for v-tables

Overhead -> mark individual functions **virtual** to take advantage of polymorphism only when appropriate

Fully polymorphic inheritance would be overkill in most cases



Invoking Virtual Members Non-Virtually

Sometimes may need to call the `BaseClass` version of a virtual function from a `DerivedClass`

```
void DerivedClass::someFunction()  
{  
    BaseClass::someVirtualFunction(); // no polymorphism  
    //do more stuff  
}
```

Copy Constructors and Assignment Operators with Inheritance

Can become complicated beasts with inheritance!!!

Must **always call explicitly** BaseClass within
DerivedClass

```

class Base()
{
public:
    Base();
    Base(const Base& other);
    Base& operator=(const Base& other);
    virtual ~Base();
    //other public and protected members here that will be inherited

}; //end BaseClass

```

```

class Derived: public Base
{
public:
    Derived();
    Derived(const Derived& other);
    Derived& operator=(const Derived& other);
    virtual ~Derived();
private:
    char* theString; //a C string
    //generic helper functions
    void copyOther(const Derived& other);
    void clear();
}; //end DerivedClass

```

Derived Implementation

```
//generic "copy other" private member function
void Derived::copyOther(const Derived& other)
{
    theString = new char[strlen(other.theString)+1];
    strcpy(theString, other.theString);
}

// clear out private member function
void Derived::clear()
{
    delete[] theString; //deallocate memory
    theString = NULL;   //avoid dangling pointer
}
```

Derived Incorrect Implementation

```
//copy constructor
```

```
Derived::Derived(const Derived& other)
{
    copyOther(other);
}
```

```
//assignment operator
```

```
Derived& Derived::operator=(const Derived& other)
{
    if(this != other)
    {
        clear();
        copyOther(other);
    }
    return *this;
}
```


Derived Incorrect Implementation

//copy constructor

```
Derived::Derived(const Derived& other)
{
    copyOther(other);
}
```

//WRONG!!!




//assignment operator

```
Derived& Derived::operator=(const Derived& other)
{
    if(this != other)
    {
        clear();
        copyOther(other);
    }
    return *this;
}
```


//WRONG!!!





After invoking copy constructor
or assignment operator


PROBLEM!!!



Derived Correct Implementation

```
//copy constructor
Derived::Derived(const Derived& other): Base(other) //CORRECT!!!
{
    copyOther(other);
}

//assignment operator
Derived& Derived::operator=(const Derived& other)
{
    if(this != other)
    {
        clear();
        Base::operator= (other); //CORRECT!!!Invoke Base operator=
        // explicitly
        copyOther(other);
    }
    return *this;
}
```



Slicing

Copy ONLY BaseClass portion of object

Opposite of previous case


```
Base* ptr1;  
Base* ptr2 = new Derived; // pointer of type Base that points to type Derived  
  
//do stuff  
  
*ptr1 = *ptr2; //copy value pointed to by ptr2 into variable pointed to by  
ptr1
```

Note potential problem!!!

The above expands into

```
ptr1->operator= (*ptr2);
```

Invoking the `operator=` of the Base **loosing** all data of `Derived` portion



Slicing via Copy Constructor

```
void doSomething(Base baseObject)
{
    //do something
}
```


```
Derived myDerived;
doSomething(myDerived);
```

PROBLEM!!! Parameter baseObject will be initialized using Base copy constructor

Slicing

Ever more insidiously!!!

```
vector<Base> myBaseVector;  
Base* myBasePtr = someFunction(); //pointer to Base  
//ATTENTION myBasePtr could point to Derived object  
myBaseVector.push_back(*myBasePtr);
```



If someFunction returns a pointer to an object of type Derived
calling push_back on object of type Derived will likely **slice** the
object storing only its Base data

Possible solution: store pointers in myBaseVector instead of objects

Casting

Forcing one datatype to be converted into another

Up-casting (Derived to Base) automatically available through inheritance

```
Base* basePtr;  
Derived* derivedPtr;  
//do stuff  
basePtr = derivedPtr; //automatic conversion Derived is-a Base
```


Down-casting (Base to Derived)

```
Base* basePtr = new Derived; // pointer of type Base points to  
Derived  
//do stuff  
Derived* derivedPtr = (Derived*) basePtr;
```



Casting

Classic C++ cast too powerful => no checks.
Could write something totally nonsensical

```
Base* basePtr;  
vector<double>* myVectorPtr = (vector<double>*) basePtr;  
//PROBLEM!! Makes no sense, no compiler error
```

A red arrow points from the right side of the slide to the cast expression `(vector<double>*)` in the second line of code.

```
const Base* basePtr = new Derived;  
// do stuff  
Derived* derivedPtr = (Derived*) basePtr;  
//PROBLEM!!! Lost constness of Base object  
//derivedPtr is now free to modify it
```

A red arrow points from the right side of the slide to the cast expression `(Derived*)` in the fourth line of code.

static_cast

static_cast checks at compile time that cast "makes sense"

Allows:

- Converting between **primitive types** (e.g. int to float)
- Converting pointers or references of **Derived** type to pointers or references of **Base** type (e.g. **Derived*** to **Base***) where target is at least as **const** as the source
- Converting pointers or references of **Base** type to pointers or references of **Derived** type (e.g. **Base*** to **Derived***) where target is at least as **const** as the source

```
Base* basePtr = new Derived;  
// do stuff  
Derived* derivedPtr = static_cast<Derived*>(basePtr);
```


dynamic_cast

If `Base*` did not point to `Derived` object, `static_cast` would succeed

=> runtime problems

e.g. access `Derived` data members not present in `Base`

```
Base* basePtr = new Base;  
Derived* derivedPtr1 = (Derived*)basePtr; //BAD!!!  
Derived* derivedPtr2 = static_cast<Derived*>(basePtr); //BAD!!!  
Derived* derivedPtr3 = dynamic_cast<Derived*>(basePtr); //GOOD!!!
```



Will return a NULL pointer



Conclusion

Polymorphism is easy, Just put **virtual** everywhere and the compiler will take care of the rest!

Conclusion

Polymorphism is easy, Just put **virtual** everywhere and the compiler will take care of the rest!



Conclusion

Overhead! Use it only when useful/necessary

Carefully craft constructors

Make destructor virtual

Beware of Slicing (in all its forms)

**Beware of casting and use level most appropriate
and safe for your situation**

For Project 3

- No polymorphism (if we were, which functions should we have marked virtual? In which class?)
- Pay attention to copy constructor



```
public:

    LinkedSet();           // Default constructor

    LinkedSet(const LinkedSet<ItemType>& a_set); // Copy constructor

    virtual ~LinkedSet();  // Destructor should be virtual

    int getCurrentSize() const;

    bool isEmpty() const;

    bool add(const ItemType& new_entry);

    bool remove(const ItemType& an_entry);

    void clear();

    bool contains(const ItemType& an_entry) const;

    std::vector<ItemType> toVector() const;
```