WAVE SDK Version 1007 Release Notes

1. Provide a new mechanism “uCoupler” to replace “OSLink”. The content includes following:

   a. Configuration files for 2 OBU-201U units (sender & receiver) in following folder

      `/app/uCoupler/config_files`

   b. Customize firmware for uCopuler in following folder

      `/app/uCoupler/fw`

   c. Example codes to be executed on PC (Linux) for UDP and UART in following folder

      `/app/uCoupler/example`

   See “User-Guide-for-uCoupler.pdf” for more detail

2. An example code which demonstrates the usage of UART0 interface has been added in following folder

   `/example/uart-echo`

WAVE SDK Version 978-rev3 Release Notes

1. This version of SDK supports OSLink mechanism based on IEEE 1609.3 (2016 specification). To understand OSLink mechanism and usage, pls refer to OSLink user guide. Related example code can be found in sdk-us-978-rev3/example/oslink folder.

WAVE SDK Version 978 Release Notes

1. SDK has been reorganized. A simple application which constantly transmits & receives BSMs using real/correct GPS information has been added in "example/bsm" folder. Other example codes have been moved under “example/test” folder. **Note:** BSMs are sent as per J2945/1 (March 2016) specification following Minimum criteria for BSM transmission (section 6.3.5)

2. The way to do memory management in the examples of previous version of SDKs is changed. Users are suggested to utilize the ThreadX APIs to fully control the memory management, but not rely on the ones used in the example of previous version of SDK. Those APIs will be deprecated in the future. For ease of use, a simple malloc implementation is provided in “sdk/example/bsm” folder. As the new way, the size and behaviors can be fully controlled by users.

3. There is a change in bsm_decode API. Pls check section 5.3.2, page 110 in WAVE SDK version 978 API guide.