



US009686216B2

(12) **United States Patent**
Hammer et al.

(10) **Patent No.:** **US 9,686,216 B2**
(45) **Date of Patent:** **Jun. 20, 2017**

(54) **SERVER SIDE EMAIL CONTENT
MODIFICATION TO SELECTED EMAIL
RECIPIENTS**

7,290,035 B2 10/2007 Mattathil
7,844,671 B1 * 11/2010 Lawler G06F 15/16
709/204
7,877,454 B1 * 1/2011 Hunter G06Q 10/107
709/206

(71) Applicant: **SNAP INC.**, Venice, CA (US)

(72) Inventors: **Mette F. M. Hammer**, Dublin (IE);
Liam Harpur, Dublin (IE); **Joseph M.
Jaquinta**, Medford, MA (US); **Pauli P.
O. Nurmenkari**, Dublin (IE)

9,092,759 B2 7/2015 Hammer et al.
2003/0061289 A1 3/2003 Clissold et al.
(Continued)

(73) Assignee: **SNAP INC.**, Venice, CA (US)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 0 days.

OTHER PUBLICATIONS
“eCipher, Secure Email Made Simple—Email Encryption and Digital Rights Management,” [online] Essential Security Software, 2009, [retrieved Jun. 29, 2010] retrieved from the Internet: <<http://www.essentialsecurity.com/products.html>>.
(Continued)

(21) Appl. No.: **14/704,018**

(22) Filed: **May 5, 2015**

Primary Examiner — Angela Nguyen

(65) **Prior Publication Data**

US 2015/0236995 A1 Aug. 20, 2015

(74) Attorney, Agent, or Firm — Schwegman Lundberg & Woessner, P.A.

Related U.S. Application Data

(63) Continuation of application No. 12/825,962, filed on
Jun. 29, 2010, now Pat. No. 9,092,759.

(51) **Int. Cl.**
H04L 12/58 (2006.01)

(52) **U.S. Cl.**
CPC **H04L 51/12** (2013.01); **H04L 51/28**
(2013.01); **H04L 51/32** (2013.01)

(58) **Field of Classification Search**
None
See application file for complete search history.

(56) **References Cited**


U.S. PATENT DOCUMENTS

6,609,196 B1 8/2003 Dickinson, III et al.
7,139,802 B2 11/2006 Keohane et al.

(57) **ABSTRACT**

A method for prohibiting email content propagation that receives, at a server, an email message. At the server, at least one email address associated with the email message which is designated not to receive a content of the email message is identified. At the server, the email message is modified by selectively removing a content of the email message to be conveyed to the at least one email address. The server conveys the modified email message to the at least one email address. The server conveys the email message to one or more recipient email addresses except the at least one email address. Consequently, the server has sent a submitted message to multiple email addresses, while modifying the content sent to a subset of the addresses that received the email message.

20 Claims, 5 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

2003/0233410	A1 *	12/2003	Gusler	G06Q 10/107 709/206
2004/0010552	A1 *	1/2004	Keohane	G06Q 10/107 709/206
2004/0172252	A1 *	9/2004	Aoki	H04M 3/564 704/270
2007/0005717	A1	1/2007	LeVasseur et al.	
2008/0104712	A1 *	5/2008	Oliver	G06F 21/6227 726/27
2009/0031393	A1	1/2009	Denner et al.	
2009/0037546	A1	2/2009	Kirsch	
2009/0157650	A1	6/2009	Chow et al.	

OTHER PUBLICATIONS

“Network Box Anti-Spam Technology Briefing: Network Box Email Envelope Pre-Scan,” [online] Network Box UK, 2003-2009 [retrieved Jun. 29, 2010] retrieved from the Internet: <<http://www.network-box.co.uk/files/uploads/NetworkBox-PreEnvelopeSystemOverview.pdf>>.

“Prevent E-mail Message Recipients from using Reply All or Forward,” [online] Microsoft Corporation 2010, [retrieved Jun. 29, 2010] retrieved from the Internet: <<http://office.microsoft.com/en-us/outlook/HA011142241033.aspx>>.

“About Information Rights Management,” Microsoft Corporation 2010, [retrieved Jun. 29, 2010] retrieved from the Internet: <<http://office.microsoft.com/en-us/help/HP062208591033.aspx>>.

“Microsoft Windows Rights Management Services Client with Service Pack 2—x86,” [online] Microsoft Corporation 2010, [retrieved Jun. 29, 2010] retrieved from the Internet: <<http://www.microsoft.com/downloads/details.aspx?FamilyId=02DA5107-2919-414B-A5A3-3102C7447838&displaylang=en>>.

“Postini: Google Message Encryption,” [online] Google, 2010, [retrieved Jun. 29, 2010] retrieved from the Internet: <<http://www.google.com/postini/encryption.html>>.

“U.S. Appl. No. 12/825,962, Final Office Action mailed Sep. 21, 2012”, 25 pgs.

“U.S. Appl. No. 12/825,962, Non Final Office Action mailed May 25, 2012”, 21 pgs.

“U.S. Appl. No. 12/825,962, Non Final Office Action mailed Jun. 19, 2014”, 11 pgs.

“U.S. Appl. No. 12/825,962, Notice of Allowance mailed Feb. 6, 2015”, 9 pgs.

“U.S. Appl. No. 12/825,962, Response filed Jun. 11, 2012 to Non Final Office Action mailed May 25, 2012”, 21 pgs.

“U.S. Appl. No. 12/825,962, Response filed Jul. 1, 2014 to Non Final Office Action mailed Jun. 19, 2014”, 6 pgs.

“U.S. Appl. No. 12/825,962, Response filed Dec. 19, 2012 to Final Office Action mailed Sep. 21, 2012”, 19 pgs.

* cited by examiner






FIG. 1

**FIG. 2**

300

Social Network 342

Node	Email Address	Ties	Relationship
Alice	alice@ibm.com	Joc, Fred	Marketing
Joc	joe@ibm.com	Ted, Sam	Co-workers
Fred	fred@ibm.com	Suc, Bob	Dev Team

350

Email 331

Msg ID	Policy ID	Contents
Msg A	Policy_A	Project A...
Msg B	Policy_B	Project B...
Msg C	Policy_B	Project A...



352

Policy 336

Policy ID	Policy
Policy_A	Fred's Network
Policy_B	Distance=2
Policy_C	Marketing

354

FIG. 3


400**FIG. 4**

300

E-mail Interface 505 □ □ ×

To:

Not To:

Distance: 


Cc:

Bcc:

Subject:

Project A is on schedule, here's the rundown for the next meeting:

- Address bugs
- Status of Widget A
- Code review
- Review timelines






FIG. 5

1

SERVER SIDE EMAIL CONTENT MODIFICATION TO SELECTED EMAIL RECIPIENTS

CROSS-REFERENCE TO RELATED APPLICATIONS

This application is a continuation of U.S. patent application Ser. No. 12/825,962, filed Jun. 29, 2010 (pending), which is incorporated herein in its entirety.

BACKGROUND

The present invention relates to the field of email distribution and, more particularly, to controlling email propagation within a social network utilizing proximity restrictions.

Electronic mail (email) has become an integral part of communications for many industries and enterprises. As such, email content protection is often the center of much concern within organizations. One aspect of content protection that continues to plague email users is control over which parties can receive an email once it is sent by a sender. For example, a recipient of an email can forward the email to any party which they choose. That is, the sender loses control over the email once it is communicated to recipients. As such, this can be a compromise of email conveyed content and/or security for companies and individuals. For example, an employee can accidentally forward a sensitive company email to a family member. Further, many integrity issues for individuals have arisen as a result of this problem.

These problems are further compounded when emails are communicated within a social network. In a social network, each member of the social network can be potentially connected to many other members. Currently, email solutions do not consider relationships between a sender and a recipient when conveying an email to a recipient. In many instances, email is intended for a select group of individuals which are often the recipients within the email sender's social network. Frequently, individuals outside the sender's social network are not aware of secure communication occurring within the social network. For instance, when a party not within the same social network receives an email, information within the email can often pose potential security problems for the sender and individuals within the social network. As such, it would be beneficial if email distribution can be controlled within a social network after it is sent.

BRIEF SUMMARY

One aspect of the disclosure discloses a system, method, and computer program product that receives, at a server, an email message. At the server, at least one email address associated with the email message which is designated not to receive a content of the email message is identified. At the server, the email message is modified by selectively removing a content of the email message to be conveyed to the at least one email address. The server conveys the modified email message to the at least one email address. The server conveys the email message to one or more recipient email addresses except the at least one email address. Consequently, the server has sent a submitted message to multiple email addresses, while modifying the content sent to a subset of the addresses that received the email message.

Another aspect of the disclosure is for a method, computer program product, and system for controlling email propagation within a social network utilizing proximity restrictions. A message header of an email message can be identified.

2

The message header can comprise of an exemption field which specifies one or more email addresses that is prohibited from receiving the email message. The sending email address can be associated with a sender node and the one or more email addresses is associated with a prohibited node. The sender node and the prohibited node can be arbitrarily linked within a network that is a social structure comprising of one or more individuals and organizations which can be connected by one or more specific type of interdependency. The network can be modeled as a graph which can be a mathematical structure modeling pairwise relations between nodes and edges. The email message can be conveyed to multiple email addresses except the one or more email address associated with the exemption field.

Another aspect of the disclosure is for a system, method, and computer program product for prohibiting email propagation based on proximity comprising of a processor, a volatile memory, a bus connecting said processor, non-volatile memory, and volatile memory to each other, wherein the volatile memory comprises computer usable program code executable by the processor. The computer usable program code can comprise of an email message. The email message can include a message header including an exemption field which is associated with one or more email addresses prohibited from receiving the email message. The one or more email addresses can be associated with a prohibited node which can be a component of a network. The network can be modeled as a graph which can be a mathematical structure modeling pairwise relations between nodes and edges. A proximity engine can be configured to determine a distance metric between a sender node and a recipient node of a network, compare the distance metric to a threshold value, and perform a programmatic action in response to the comparing. A notification engine can convey a notification to a sender node and another node responsive to a communication action performed on the email message, where the communication action violates a policy setting associated with a policy. A policy can be configured to identify one or more nodes prohibited from receiving the email message and one prohibited communication action associated with the one or more nodes based on the proximity from the sender node.

BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWINGS

FIG. 1 is a flowchart illustrating a method for controlling email propagation within a social network utilizing proximity restrictions in accordance with an embodiment of inventive arrangements disclosed herein.

FIG. 2 is a flowchart illustrating a method for controlling email propagation within a social network utilizing server-based proximity restrictions in accordance with an embodiment of inventive arrangements disclosed herein.

FIG. 3 is a schematic diagram illustrating a system for prohibiting email propagation within a social network based on proximity restrictions in accordance with an embodiment of inventive arrangements disclosed herein.

FIG. 4 is a schematic diagram illustrating an email header for prohibiting email propagation within a social network based on proximity restrictions in accordance with an embodiment of inventive arrangements disclosed herein.

FIG. 5 is a schematic diagram illustrating an interface for prohibiting email propagation within a social network

based on proximity restrictions in accordance with an embodiment of inventive arrangements disclosed herein.

DETAILED DESCRIPTION

The present disclosure is a solution for controlling email propagation within a social network utilizing proximity restrictions. In the solution, a proximity policy can be associated with an email message enabling the email to remain under the control of the sender after it is conveyed. The proximity policy can specify the nodes (e.g., members) within a social network that the email message is allowed to be communicated. For instance, a user can prohibit an email message from being forwarded to someone outside their immediate social network (e.g., one degree of separation). Further, the proximity policy can be utilized to notify a sender if the policy was violated, enabling the sender to maintain control and awareness of the email after it is sent.

The terminology used herein is for the purpose of describing particular embodiments only and is not intended to be limiting of the invention. As used herein, the singular forms “a”, “an” and “the” are intended to include the plural forms as well, unless the context clearly indicates otherwise. It will be further understood that the terms “comprises” and/or “comprising,” when used in this specification, specify the presence of stated features, integers, steps, operations, elements, and/or components, but do not preclude the presence or addition of one or more other features, integers, steps, operations, elements, components, and/or groups thereof.

The corresponding structures, materials, acts, and equivalents of all means or step plus function elements in the claims below are intended to include any structure, material, or act for performing the function in combination with other claimed elements as specifically claimed. The description of the present invention has been presented for purposes of illustration and description, but is not intended to be exhaustive or limited to the invention in the form disclosed. Many modifications and variations will be apparent to those of ordinary skill in the art without departing from the scope and spirit of the invention. The embodiment was chosen and described in order to best explain the principles of the invention and the practical application, and to enable others of ordinary skill in the art to understand the invention for various embodiments with various modifications as are suited to the particular use contemplated.

As will be appreciated by one skilled in the art, the present invention may be embodied as a system, method or computer program product. Accordingly, the present invention may take the form of an entirely hardware embodiment, an entirely software embodiment (including firmware, resident software, micro-code, etc.) or an embodiment combining software and hardware aspects that may all generally be referred to herein as a “circuit,” “module” or “system.” Furthermore, the present invention may take the form of a computer program product embodied in any tangible medium of expression having computer usable program code embodied in the medium.

Any combination of one or more computer usable or computer readable medium(s) may be utilized. The computer-usable or computer-readable medium may be, for example but not limited to, an electronic, magnetic, optical, electromagnetic, infrared, or semiconductor system, apparatus, device, or propagation medium. More specific examples (a non-exhaustive list) of the computer-readable medium would include the following: an electrical connection having one or more wires, a portable computer diskette, a hard disk, a random access memory (RAM), a read-only

memory (ROM), an erasable programmable read-only memory (EPROM or Flash memory), an optical fiber, a portable compact disc read-only memory (CDROM), an optical storage device, a transmission media such as those supporting the Internet or an intranet, or a magnetic storage device. Note that the computer-usable or computer-readable medium could even be paper or another suitable medium upon which the program is printed, as the program can be electronically captured, for instance, via optical scanning of the paper or other medium, then compiled, interpreted, or otherwise processed in a suitable manner, if necessary, and then stored in a computer memory. In the context of this document, a computer-usable or computer-readable medium may be any medium that can contain, store, communicate, propagate, or transport the program for use by or in connection with the instruction execution system, apparatus, or device. The computer-usable medium may include a propagated data signal with the computer-usable program code embodied therewith, either in baseband or as part of a carrier wave. The computer usable program code may be transmitted using any appropriate medium, including but not limited to wireless, wireline, optical fiber cable, RF, etc.

Computer program code for carrying out operations of the present invention may be written in any combination of one or more programming languages, including an object oriented programming language such as Java, Smalltalk, C++ or the like and conventional procedural programming languages, such as the “C” programming language or similar programming languages. The program code may execute entirely on the user’s computer, partly on the user’s computer, as a stand-alone software package, partly on the user’s computer and partly on a remote computer or entirely on the remote computer or server. In the latter scenario, the remote computer may be connected to the user’s computer through any type of network, including a local area network (LAN) or a wide area network (WAN), or the connection may be made to an external computer (for example, through the Internet using an Internet Service Provider).

The present invention is described below with reference to flowchart illustrations and/or block diagrams of methods, apparatus (systems) and computer program products according to embodiments of the invention. It will be understood that each block of the flowchart illustrations and/or block diagrams, and combinations of blocks in the flowchart illustrations and/or block diagrams, can be implemented by computer program instructions. These computer program instructions may be provided to a processor of a general purpose computer, special purpose computer, or other programmable data processing apparatus to produce a machine, such that the instructions, which execute via the processor of the computer or other programmable data processing apparatus, create means for implementing the functions/acts specified in the flowchart and/or block diagram block or blocks.

These computer program instructions may also be stored in a computer-readable medium that can direct a computer or other programmable data processing apparatus to function in a particular manner, such that the instructions stored in the computer-readable medium produce an article of manufacture including instruction means which implement the function/act specified in the flowchart and/or block diagram block or blocks.

The computer program instructions may also be loaded onto a computer or other programmable data processing apparatus to cause a series of operational steps to be performed on the computer or other programmable apparatus to produce a computer implemented process such that the

5

instructions which execute on the computer or other programmable apparatus provide processes for implementing the functions/acts specified in the flowchart and/or block diagram block or blocks.

FIG. 1 is a flowchart illustrating a method 100 for controlling email propagation within a social network utilizing proximity restrictions in accordance with an embodiment of inventive arrangements disclosed herein. In method 100, an email within a social network can be identified which can be selectively conveyed to recipients based on the proximity. Proximity can include, but is not limited to, betweenness, centrality, closeness, cohesion, degree, density, eigenvector centrality, path length, and the like. For example, an email can be limited to only three degrees of separation within a social network. That is, recipients greater than three degrees away from a sender of an email can be prohibited from receiving the email.

In step 105, an email within a social network can be identified. Identification of the email can be automatically performed and/or manually performed. In step 110, a proximity policy associated with the email can be determined. The proximity policy can be determined utilizing one or more mechanisms including manual identification and automated identification processes. In one embodiment, header control information can be used to indicate a proximity policy associated with the email. For instance, the header control information can include a "Not To" field which can indicate the location of one or more appropriate proximity policy. In one instance, tags associated with an email can be utilized to programmatically identify one or more appropriate policies.

In step 115, a recipient of the email is selected. The recipient can be selected from one or more fields including, but not limited to, the "to" field, the "cc" field, the "bcc" field, and the like. That is, the recipient email address can be identified through analysis of the header control information within the email. The email address can be used to identify a recipient within the social network. In one embodiment, the email address can be used to determine uniquely identifiable information (e.g., user id) of a recipient to establish the recipient position within a social network. In step 120, the recipient centrality within the network is determined. The centrality can be determined utilizing one or more client-side and/or server-side functionality. Centrality can be determined using a brute-force algorithm, path determination algorithms, and the like. In step 125, the recipient centrality is compared with a centrality value associated with the proximity profile. Comparison can include, direct comparison of centrality values, threshold value approximation, and the like. For instance, if the centrality value of the recipient is less than the centrality value of the proximity profile, the email can be permitted to be communicated to the recipient.

In step 130, if the recipient is prohibited from receiving the email based on the comparing step, the method can continue to step 135, else proceed to step 155. In step 135, the recipient can be omitted. In one instance, the recipient can be removed from the email prior to communication of the email. For instance, the email address of the recipient can be removed from the email header. In step 140, the sender of the email can be optionally notified of recipient omission. In step 145, the sender can optionally perform a responsive action to the recipient omission. In step 150, if there are more recipients associated with the email, the method can proceed to step 115, else proceed to step 160. In step 155, the email can be conveyed to appropriate recipients who do not

6

violate the proximity policy associated with the email. In step 160, the method can end.

Drawings presented herein are for illustrative purposes only and should not be construed to limit the invention in any regard. Social network can refer to a social structure comprising of individuals and/or organizations (e.g., nodes), which are connected by one or more specific types of interdependency, including, but not limited to, friendship, kinship, common interest, financial exchange, likes, dislikes, relationships of beliefs, knowledge, prestige, and the like. In one embodiment, the social network can be represented within a computing network as a graph, wherein the graph is a mathematical structure modeling pairwise relations between nodes (e.g., members) and edges (interdependency). Social network can include internal social network, external social network, and the like. For instance, social network can be a network of employees within a corporation. Social network can include, but is not limited to, LINKEDIN, FACEBOOK, MYSPACE, ORKUT, FRIENDSTER, TWITTER, and the like. It should be appreciated, method 100 can be performed in real-time or near real-time.

FIG. 2 is a flowchart illustrating a method 200 for controlling email propagation within a social network utilizing server-based proximity restrictions in accordance with an embodiment of inventive arrangements disclosed herein. Method 200 presents one scenario for managing email distribution via proximity policies. In method 200, an email from a sender node (e.g., member) within a social network can retain control of the email distribution once the email has been communicated to recipient nodes (e.g., connected members). That is, a member of social network can restrict which members within the social network can participate in an email dialogue. As such, the proximity policy can govern an email exposure throughout the lifespan of the email. The email can be associated with a proximity policy which can enable a sender node to control which recipient nodes within the social network can receive the email. For instance, Alice can assign a proximity policy to her email to Bob, who can be prohibited from forwarding the email to anyone outside Alice's social network. The proximity policy can be user-defined or automatically established based on historic data, organizational policy and/or email distribution configuration settings.

In step 205, an email can be received by an email server from a sender node within a social network. In step 210, a proximity policy associated with the email can be identified. In step 215, prohibited nodes within the network which are disallowed from receiving the email can be determined based on the proximity policy. In one embodiment, the proximity policy can define which nodes (e.g., prohibited nodes) and/or group of nodes (e.g., prohibited social networks) can be blacklisted from receiving the email. In another embodiment, the proximity policy can establish centrality values for limiting email exposure. For instance, the policy can permit an email to be delivered to anyone not close to the sales department. In step 220, the email can be conveyed to recipient nodes within the network according to the proximity policy. That is, the email can be conveyed to recipient nodes and prohibited nodes can remain unaware of the email.

In step 225, if a communication action is performed by a recipient node on the email which violates the proximity policy, the method can continue to step 230, else return to step 210. The communication action can include, but is not limited to, forwarding, reply to all, sending, and the like. For example, if Bob attempts to send a carbon copy of Alice's email to Fred, who is outside of Alice's social network, a

proximity policy violation can be triggered. In step **230**, the communication action can be disallowed. In one instance, the communication action can be logged within an auditing system. In step **235**, a notification policy violation can be presented to the recipient node performing the communication action. The notification can be presented within a user interface such as an email application. For instance, a graphical user interface can present a dialog indicating that the communication action associated with a prohibited node is prohibited.

In step **240**, a policy violation notification can be communicated to the sender node. In one instance, the policy violation notification can be communicated comprising of information including, but not limited to, timestamp associated with the attempt, the communication action performed by the node, and the like. In step **245**, the sender node can optionally perform a responsive action to the policy violation. In one instance, the responsive action can be initiating contact with the recipient node which violated the proximity policy. In step **250**, the method can end.

Drawings presented herein are for illustrative purposes only and should not be construed to limit the invention in any regard. Method **200** can be performed within the context of system **300**. Steps **205-245** can repeat for each instance of an email that is communicated throughout a social network.

FIG. 3 is a schematic diagram illustrating a system **300** for prohibiting email propagation within a social network based on proximity restrictions in accordance with an embodiment of inventive arrangements disclosed herein. System **300** can be present within the context of method **100** and **200**. In system **300**, proximity policy **336** can permit distribution control of email **318**, **331** to one or more clients **310** based on proximity settings associated with the proximity policy **336**. Email **318**, **331** can be communicated to email server **330** which can be utilized to propagate email based on proximity policy **336**. Turning to FIG. 4, in one embodiment **474**, proximity policy **336** can be stored within server **330** which can be indicated using a Uniform Resource Locator (URI) **486** associated with header information **482**. For instance, URL **486** can identify policy **354** associated with email **352**. In another instance **472** proximity policy **336** can be stored within header information **480** of the email message as one or more email addresses **482**.

Email **318**, **331** can be a message associated with the Simple Mail Transfer Protocol (SMTP), Post Office Protocol (POP), Internet Message Access Protocol (IMAP), Hypertext Transport Protocol (HTTP), and the like. Email **318**, **331** can be stored within a data store including but not limited to, hard drive, network attached storage (NAS), storage attached network (SAN), and the like. In one instance, email **318**, **331** can be stored within an mbox file format. Email **318**, **331** can be a user and/or automatically generated message comprising of a message header and a message body. In one embodiment, the message header can be associated with exemption field **314** which can be used to prohibit one or more nodes within network **342** from receiving email **318**, **331**. Message header can include control information including, but not limited to, one or more prohibited address (e.g., **482**), an originator's email address, one or more recipient addresses, subject information, message id, and the like. Email body can include plain text and/or Hypertext Markup Language (HTML) content. Email **318**, **331** can include multi-media content attachments (e.g., multipurpose internet mail extensions).

As used herein, client **310** can be a computing device able to send and receive email **331**. Client **310** can be mapped to

a node within a social network **342** (e.g., network **370**) such that client **310** can be a sender node, recipient node, or a prohibited node. Client **310** can include, but is not limited to, desktop computer, laptop, mobile phone, portable digital assistant, multimedia device, and the like. Client **310** can be communicatively linked to email server **330** via network **370**. In one instance, client **310** can be associated with an interface **312**.

Interface **312** can be a user interface able to permit composition and/or presentation of email **331** (e.g., mail user agent). Interface **312** can be a screen from a client-side email application such as an email client. Interface **312** can be a component of MOZILLA THUNDERBIRD, MUTT, and the like. In one instance, interface **312** can be component of a Web-based email application. In another instance, interface **312** can be a remotely executing application. Interface **312** can comprise of exemption field **314** which can permit distribution control of emails (e.g., email **318**) sent from interface **312**.

Exemption field **314** can be associated with proximity policy **336** which can be used to specify which clients **310** (e.g., nodes) within social network **342** can receive email **318**. In one embodiment, exemption field **314** can present one or more existing proximity policies which can be applied to email **318**. In another instance exemption field **314** can permit a user to create policies to be applied to email **318**.

Email server **330** can be one or more hardware/software components able to prohibit communication of an email **318**, **331** to a prohibited node. Email server **330** can be a mail submission agent, mail transfer agent, mail delivery agent, mail exchange, and the like. For example, email server can be a software email server application such as POSTFIX. Email server **330** can comprise of, but is not limited to, email **331**, proximity engine **332**, notification engine **334**, proximity policy **336**, configuration settings **338**, and data store **340**. Email server **330** can be associated with one or more entities including, but not limited to, an internet service provider (ISP), a corporation, and the like. In one instance, email server **330** can be an IBM LOTUS DOMINO server. In another instance, email server **330** can be an SENDMAIL SMTP server.

Proximity engine **332** can be one or more hardware/software components for determining the proximity of two or more nodes within a social network **342**. Engine **332** can establish proximity metrics including, but not limited to, betweenness, centrality, closeness, cohesion, degree, density, eigenvector centrality, path length, and the like. Proximity metrics established by the engine can be used to generate proximity policies, validate proximity policies, and/or resolve proximity conflicts. Proximity engine **332** can utilize network **342** data to determine proximity between nodes. For instance, relationship data **350** can be used to determine Alice is connected to Joe and Fred through a marketing department relationship. In one embodiment, proximity engine **332** can respond to real-time changes within a social network. For instance, if Fred joins Alice's social network, Fred can participate in an email which was previously prohibited to Fred. In one configuration of the embodiment, engine **332** can retroactively apply proximity policy **336** when a change in a social network occurs.

In one embodiment, proximity engine **332** can use presence information to prohibit communication of an email to a recipient. In the embodiment, location information (e.g., global positioning system data) of a node (e.g., user) can be used to dynamically restrict email messages from being conveyed to the node.

Notification engine **334** can be one or more hardware/software components able to generate a notification **360** responsive to a proximity policy violation. Engine **334** can convey notification **360** when proximity policy **336** is violated by a node (e.g., client **310**). In one embodiment, engine **334** can store policy violations which can be accessed during auditing processes. In one instance, notification engine **334** can operate in real-time to generate policy violation warnings to users of interface **312**.

Notification **360** can be a message identifying one or more proximity policy violations associated with an email **318**, **331**. Notification **360** can be an email, Short Message Service (SMS) message, voice message, instant message (IM) and the like. Notification **360** can be customized via proximity profile **336** and/or configuration settings **338**. For instance, notification **360** can generate an email notification to all participants of an email conversation when the proximity policy of the email is violated.

Proximity policy **336** can be one or more rulesets for establishing prohibited nodes within a social network **342** which are disallowed from receiving email **318**, **331**. Proximity policy **336** can be applied arbitrarily to any portion of a social network. For instance, policy **336** can be applied to subgroups (e.g., cliques) within a social network. In one embodiment, proximity policy **336** can be associated with metrics for limiting email communication. For example, a forwarding threshold value can be utilized to restrict the number of times an email can be forwarded. In one embodiment, policy **336** can be associated with an expiration value which can enable the policy **336** to be enforced for a set period of time. For example, a policy can restrict emails from being forwarded outside of a development team's social network prior to a product release date. Further, proximity policy **336** can be associated with administrative settings permitting authorized parties to view and/or modify policy **336**.

In one instance, proximity policy **336** can be used to selectively expose content of an email based on the proximity of a recipient node from a sender node. In one configuration of the instance, attachments can be selectively removed based on policy settings. For example, when the email **331** is delivered to a recipient outside of a sender's social network, image attachments associated with the email **331** can be removed. In another configuration of the instance, portions of the message body of the email **331** can be omitted when the email **331** is communicated to selected recipients.

Configuration settings **338** can be one or more local and/or global email settings for enabling system **300** functionality. Configuration settings **338** can include, but are not limited to, permitted proximity values, administrative settings, and the like. In one instance, settings **338** can allow customize proximity values to be used. For instance, settings **338** can allow physical proximity values to be used to control email propagation. In another instance, settings **338** can permit organizational proximity policies to override individual defined proximity policies.

Social network **342** can be one or more social structures associated with system **300**. Social network **342** information can be stored within data store **340**. In one instance social network **342** can be associated with a directory service. For instance, social network **342** can be associated with an IBM TIVOLI DIRECTORY SERVER. In the instance, network **342** information can be queried to determine proximity information for establishing node proximity.

In one instance, data store **340** can be a relational database including, but not limited to, relational database manage-

ment system (RDBMS), object database management system (ODBMS), and the like. In another instance, data store **340** can be a NAS, SAN, and the like.

Drawings presented herein are for illustrative purposes only and should not be construed to limit the invention in any regard. System **300** functionality can be encapsulated within a middleware software including, but not limited to, IBM WEBSPPHERE. System **300** can be one or more components of a distributed computing system, network computing system, and the like. In one instance, system **300** functionality can be accessible through a Web-based service. In one embodiment, components **332-338** can be integrated with a client-side email application. Email **318**, **331** can be stored within client **310** and/or within server **330**. In one embodiment, system **300** functionality can be a component of a client-side email application.

FIG. **5** is a schematic diagram illustrating an interface **505** for prohibiting email propagation within a social network based on proximity restrictions in accordance with an embodiment of inventive arrangements disclosed herein. In interface **505**, a user can specify one or more nodes (e.g., members) of a social network which can be prohibited from receiving an email based on a distance metric setting associated with the email **510**. Prohibited nodes can be user specified or automatically determined as shown in section **510** and suggestion **522**. Interface **505** can be one or more screens of an email application. In one instance, the application can be a client-side application permitting selective control of email distribution within a social network. For example, interface **505** can be a screen from an IBM LOTUS NOTES application.

In section **510**, a user can utilize an exemption field **512** and/or a slider element **514** to specify prohibited nodes within a social network. Section **510** can be used to establish a proximity policy for an email associated with the interface **505**. For instance, a user can establish a proximity policy for an email by utilizing field **512** and/or element **514**. In one instance, exemption field **512** and slider element **514** can be linked. In one configuration of the embodiment, manipulation of the slider element **514** can automatically populate field **512**. In another configuration of the embodiment, exemption field **512** can be used to set which nodes can be prohibited while slider element **514** can be used to specify additional prohibited nodes based on a distance from a sender node. In one embodiment, field **512** and element **514** can be used in a mutually exclusive fashion.

Exemption field **512** can be a user interface element permitting user established control of an email via user input. Exemption field **512** can be a text field used for identifying prohibited nodes within the social network. Field **512** can accept a variety of user input including, canonical names, usernames, email addresses, keywords, relationship information and the like.

Slider element **514** can be utilized to specify a distance metric from a sender node to which the email cannot be delivered. Element **514** can include a range from one degree of separation (e.g., friend of a friend) to six degrees of separation (e.g., everyone in the social network). In one instance, element **514** can be automatically positioned based on input within exemption field **512**. Element **514** can be used to specify a maximum and/or minimum distance that the email can be propagated. In another instance, the slider can be used to specify the "levels" of forwarding or "reply to all" which are allowed.

In one embodiment, prohibited nodes can be automatically determined based on content of an email within interface **505**. Based on a previously established proximity

11

policy, text 520 can trigger pop-up 522 to be presented. Pop-up 522 can present a user with an option to automatically prohibit appropriate nodes from receiving the email based on the text 520. For example, when text 520 comprises of the keyword “Widget A”, John Soft can be automatically identified as a candidate who cannot receive the email. In one instance, pop-up 522 can be used to automatically add a prohibited node to exemption field 512. For instance, when a user selects “Yes”, the pop-up 522 can trigger John Soft to be programmatically removed from the “To” field and placed within the “Not To” field 512.

Drawings presented herein are for illustrative purposes only and should not be construed to limit the invention in any regard. Interface 505 can be a component of a graphical user interface (GUI), voice user interface (VUI), mixed-mode interface, and the like. Interface elements within interface 505 can include, but are not limited to, text field, sliders, drop down boxes, radio buttons, checkboxes, and the like. In one instance, section 510 can graphically present a list of each node associated with a sender node which can be excluded. In the instance, each node can be associated with a checkbox for selecting the node to exclude. For instance, a checkbox can be presented next to a profile picture of a member within a social network that can be disallowed from receiving an email composed within interface 505.

The flowchart and block diagrams in the FIGS. 1-3 illustrate the architecture, functionality, and operation of possible implementations of systems, methods and computer program products according to various embodiments of the present invention. In this regard, each block in the flowchart or block diagrams may represent a module, segment, or portion of code, which comprises one or more executable instructions for implementing the specified logical function(s). It should also be noted that, in some alternative implementations, the functions noted in the block may occur out of the order noted in the figures. For example, two blocks shown in succession may, in fact, be executed substantially concurrently, or the blocks may sometimes be executed in the reverse order, depending upon the functionality involved. It will also be noted that each block of the block diagrams and/or flowchart illustration, and combinations of blocks in the block diagrams and/or flowchart illustration, can be implemented by special purpose hardware-based systems that perform the specified functions or acts, or combinations of special purpose hardware and computer instructions.

What is claimed is:

1. A method for prohibiting electronic mail content propagation comprising:

receiving, at a server, an electronic mail message;
identifying, at the server, a recipient electronic mail addresses and a proximity policy in the electronic mail message, the proximity policy indicating nodes associated with a prohibited node that are prohibited from receiving content of the electronic mail message;
using the proximity policy to identify a network of nodes in a social network data structure of a social network, the network of nodes being nodes that are grouped with the prohibited node in the social network data structure, the network of nodes corresponding to a plurality of prohibited electronic mail addresses designated to not receive content of the electronic mail message;
modifying, at the server, the electronic mail message by selectively removing content of the electronic mail message; and

12

conveying, by the server, the modified electronic mail message to the plurality of prohibited electronic mail addresses; and

conveying, by the server, the electronic mail message to the recipient electronic mail addresses.

2. The method of claim 1, wherein a sender electronic mail message address for the electronic mail message is associated with a sender node, wherein the sender node and the prohibited node that corresponds to the prohibited electronic mail address are communicatively linked to each other through the social network.

3. The method of claim 2, wherein the network of nodes includes a first node that corresponds to an individual user and a second node that corresponds to an organization, the first node and the second node connected by at least one type of interdependency in the social network data structure.

4. The method of claim 2, wherein the proximity policy determines whether a node of a plurality of nodes in the social network data structure is one of the network of nodes using a physical proximity value of the sender node.

5. The method of claim 2, wherein the social network data structure corresponds to a social network and the electronic mail message and the modified electronic mail message are conveyed over a computer network.

6. The method of claim 2, wherein the network of nodes are identified based on their closeness with the prohibited node within the social network data structure.

7. The method of claim 2, wherein the plurality of prohibited nodes correspond to a clique of nodes within the social network data structure.

8. The method of claim 2, further comprising:

conveying a notification to the sender electronic mail address when a node within the social network data structure performs a communication action on the electronic mail message, wherein the communication action is associated with a prohibited node; and prohibiting the communication action on the electronic mail message associated with the prohibited node.

9. The method of claim 3, wherein the social network data structure is modeled as a graph comprising the network of nodes and edges, the graph being a mathematical structure that models pairwise relations between the network of nodes using the edges.

10. The method of claim 4, wherein the physical proximity value is a physical distance metric between the sender node and the node, wherein the sender node and the node are at least one of a computing device and a human agent.

11. The method of claim 8, wherein the notification comprises a timestamp associated with the communication action, the prohibited node associated with the communication action, and the communication action performed by the node.

12. A system for prohibiting electronic mail content propagation comprising:

one or more non-transitory storage mediums storing program instructions;

one or more processors executing the program instructions;

a server, comprising the one or more processors executing the program instructions to:

receive, at a server, an electronic mail message;
identify, at the server, a recipient electronic mail addresses and a proximity policy in the electronic mail message, the proximity policy indicating nodes associated with a prohibited node that are prohibited from receiving content of the electronic mail message;

13

use the proximity policy to identify a network of nodes in a social network data structure of a social network, the network of nodes being nodes that are grouped with the prohibited node in the social network data structure, the network of nodes corresponding to a plurality of prohibited electronic mail addresses designated to not receive content of the electronic mail message;
 5 modify, at the server, the electronic mail message by selectively removing content of the electronic mail message; and
 10 convey, by the server, the modified electronic mail message to the plurality of prohibited electronic mail addresses; and
 15 convey, by the server, the electronic mail message to the recipient electronic mail addresses.

13. The system of claim **12**, wherein a sender electronic mail address for the electronic mail message is associated with a sender node, wherein the sender node and the prohibited node that corresponds to the prohibited electronic mail address are communicatively linked to each other through the social network.

14. The system of claim **13**, wherein the network of nodes includes a first node that corresponds to an individual user and a second node that corresponds to an organization, the first node and the second node connected by at least one type of interdependency in the social network data structure.

15. The system of claim **13**, wherein the proximity policy determines whether a node of a plurality of nodes in the social network data structure is one of the network of nodes using a physical proximity value of the sender node.

16. The system of claim **14**, wherein the social network data structure is modeled as a graph comprising the network of nodes and edges, the graph being a mathematical structure that models pairwise relations between the network of nodes using the edges.

17. A non-transitory machine-readable storage medium embodying instructions that, when executed by a machine, cause the machine to perform operations comprising:
 receive, at a server, an electronic mail message;
 identify, at the server,

14

a recipient electronic mail addresses and a proximity policy in the electronic mail message, the proximity policy indicating nodes associated with a prohibited node that are prohibited from receiving content of the electronic mail message;

use the proximity policy to identify a network of nodes in a social network data structure of a social network, the network of nodes being nodes that are grouped with the prohibited node in the social network data structure, the network of nodes corresponding to a plurality of prohibited electronic mail addresses designated to not receive content of the electronic mail message;

modify, at the server, the electronic mail message by selectively removing content of the electronic mail message; and

convey, by the server, the modified electronic mail message to the plurality of prohibited electronic mail addresses; and

convey, by the server, the electronic mail message to the recipient electronic mail addresses.

18. The non-transitory machine-readable storage medium of claim **17**, wherein a sender electronic mail address for the electronic mail message is associated with a sender node, wherein the sender node and the prohibited node that corresponds to the prohibited electronic mail address are communicatively linked to each other through the social network.

19. The non-transitory machine-readable storage medium of claim **18**, wherein the plurality network of nodes includes a first node that corresponds to an individual user and a second node that corresponds to an organization, the first node and the second node connected by at least one type of interdependency in the social network data structure.

20. The non-transitory machine-readable storage medium of claim **19**, wherein the social network data structure is modeled as a graph comprising the network of nodes and edges, the graph being a mathematical structure that models pairwise relations between the network of nodes using the edges.

* * * * *