

The diagram illustrates a 3D convolutional neural network (3D-CNN) architecture for video classification. The input is a video volume with dimensions (B, C, L_1, L_2, L_3) . This input is processed by three parallel 3D convolutional layers, each with kernel size $1 \times 1 \times 1$ and stride 1. The output of the first convolution is reshaped into a vector (indicated by a circle with a dot) and then passed through a SoftMax layer to produce a classification result $(B \times L_1 \times L_2, L_3, C)$. The output of the second convolution is also reshaped into a vector and then passed through a SoftMax layer to produce a classification result $(B \times L_1 \times L_2, L_3, C)$. The output of the third convolution is reshaped into a vector and then passed through a SoftMax layer to produce a classification result $(B \times L_1 \times L_2, L_3, C)$. The outputs of the three SoftMax layers are combined (indicated by a circle with a dot) and then passed through a Reshape layer to produce the final output (B, C, L_1, L_2, L_3) .

中文题目: HCMA-UNet: 一种结合 CNN 和曼巴 UNet 的混合网络, 具有跨切片自注意力机制, 用于高效的乳腺癌分割

github: https://anonymous.4open.science/r/ICME2025_HCMA-UNet/README.md

所属机构：清华大学深圳国际研究生院生物制药与健康工程研究所，浙江省医学影像与介入治疗重点实验室，浙江省介入医学工程与生物技术创新研究中心，温州医科大学附属第五医院， 广东工业大学自动化学院

核心速览：本文提出了一种名为 HCMA-UNet 的新型混合卷积神经网络（CNN）-Mamba UNet，该网络结合了跨切片自注意力机制，用于高效地进行乳腺癌的分割。

跨切片自注意力（ISSA）：通过学习不同切片之间的关系来保留关键的解剖学相关性，从而实现有效的跨切片特征整合。这种机制有助于模型捕捉到 3D 数据中每个体素与其所有空间方向上邻居的自然空间关系，克服了将体积数据强制展平为序列时引入的非因果性限制。ISSA 有助于模型更准确地学习 3D 结构，从而提高分割精度。

```
InterSliceSelfAttention(  
  (query_conv): Conv3d(32, 16, kernel_size=(1, 1, 1), stride=(1, 1, 1))  
  (key_conv): Conv3d(32, 16, kernel_size=(1, 1, 1), stride=(1, 1, 1))  
  (value_conv): Conv3d(32, 32, kernel_size=(1, 1, 1), stride=(1, 1, 1))  
  (softmax): Softmax(dim=-1)  
)  
输入张量形状: torch.Size([1, 32, 64, 64, 64])  
输出张量形状: torch.Size([1, 32, 64, 64, 64])
```