

➤ **Vendor: LPI**

➤ **Exam Code: 304-200**

➤ **Exam Name: LPIC-3 Exam 304: Virtualization**

➤ **Question 101 -- End**

[Visit PassLeader and Download Full Version 304-200 Exam Dumps](#)

QUESTION 101

Which of the following commands boots a KVM virtual machine using Debian GNU/Linux?

- A. `qemu -create -drive file=debian.img -cdrom debian.iso -m 1024 -boot d`
- B. `qemu-kvm -drive file=debian.img -cdrom debian.iso -m 1024 -boot d`
- C. `kvm -create -drive file=debian.img -cdrom debian.iso -m 1024 -boot d`
- D. `kvm -qemu -drive file=debian.img -cdrom debian.iso -m 1024 -boot d`

Answer: B

QUESTION 102

Which of the following are tools or services that manage a Linux Virtual Server (LVS) setup? (Choose TWO correct answers.)

- A. keepalived
- B. ldirectord
- C. lvsproxy
- D. roundrobin
- E. vserverd

Answer: AB

QUESTION 103

In the command:

```
crm configure ____ http-after-ipv4 Mandatory: VHost1IPv4 HTTPD
```

Which missing word is required in order to ensure that the service HTTPD is always started after the service VHost1IP?

Answer: order, ORDER

QUESTION 104

[304-200 Exam Dumps](#) [304-200 Exam Questions](#) [304-200 VCE Dumps](#) [304-200 PDF Dumps](#)

<http://www.passleader.com/304-200.html>

Which of the following statements is true regarding the quorum in a two node Pacemaker cluster?

- A. Clusters with one or two nodes cannot have a quorum and require no quorum configuration.
- B. In a two node cluster, quorum can be determined and handled just as in a cluster with a higher number of nodes.
- C. In a two node cluster the quorum is always held by the node that first started the cluster software.
- D. The default quorum policy in a two node cluster must be set to ignore in order to configure a working cluster.

Answer: D

QUESTION 105

Which of the following technologies are part of the Red Hat Enterprise Linux High Availability Add-On? (Choose THREE correct answers.)

- A. DRBD
- B. LVS
- C. cLVM
- D. Pacemaker
- E. OCFS2

Answer: BCD

QUESTION 106

In keepalived, what is configured by the configuration option `sorry_server`?

- A. The addresses of backend servers that were overloaded in the past and should be scheduled with a reduced priority.
- B. The hostnames of the servers that, despite the remaining configuration, should always be scheduled by the Serial Operation Round Robin algorithm.
- C. The addresses of backend servers that should not get assigned any new connections.
- D. The default virtual host that is assigned to incoming HTTP requests missing a Host: header before forwarding them to a backend server.
- E. The address of a server to which requests are redirected in case no real server is available.

Answer: E

QUESTION 107

Using Linux Virtual Server (LVS) without any additional tools provides which of the following features?

- A. Balancing network connections across several backend servers.
- B. Automatically taking over the services of failed nodes.
- C. Restarting failed services on the backend servers.
- D. Checking the integrity of services on backend servers.
- E. Starting and stopping backend servers as needed.

Answer: A

QUESTION 108

Which of the following commands can be used to safely test and preview Pacemaker configuration changes? (Choose TWO correct answers.)

- A. `crm_test`

- B. crm_simulate
- C. crm_dryrun
- D. crm_lab
- E. crm_shadow

Answer: BE

QUESTION 109

Which of the following describes a split brain situation in a high availability cluster?

- A. Several cluster nodes access a shared resource without coordination.
- B. Several cluster nodes run different instances of the same services.
- C. Incoming network connections are accidentally forwarded to more than one backend server.
- D. Instead of shared storage, each node uses local storage managed by itself and replicates with other nodes.
- E. In addition to shared storage, each node has local storage that is not shared with other nodes.

Answer:

[**Visit PassLeader and Download Full Version 304-200 Exam Dumps**](#)