➢ Vendor: LPI

➢ Exam Code: 101-400

➢ Exam Name: LPIC-1 Exam 101

➢ Question 121 -- End

Visit PassLeader and Download Full Version 101-400 Exam Dumps

QUESTION 121
Which of the following commands will load a kernel module along with any required dependency modules?

A. depmod
B. insmod
C. modprobe
D. module_install
E. loadmod

Answer: C

QUESTION 122
You are having some trouble with a disk partition and you need to do maintenance on this partition but your users home directories are on it and several are logged in. Which command would disconnect the users and allow you to safely execute maintenance tasks?

A. telinit 1
B. shutdown -r now
C. killall -9 inetd
D. /bin/netstop --maint
E. /etc/rc.d/init.d/network stop

Answer: A

QUESTION 123
During a system boot cycle, what is the program that is run after the BIOS completes its tasks?

A. The bootloader
B. The inetd program
C. The init program
D. The kernel

Answer: A

QUESTION 124
The message "Hard Disk Error" is displayed on the screen during Stage 1 of the GRUB boot process. What does this indicate?

A. The kernel was unable to execute /bin/init
B. The next Stage cannot be read from the hard disk because GRUB was unable to determine the size and geometry of the disk
C. One or more of the filesystems on the hard disk has errors and a filesystem check should be run
D. The BIOS was unable to read the necessary data from the Master Boot Record to begin the boot process

Answer: B

QUESTION 125
Which configuration file should be modified to disable the ctrl-alt-delete key combination?

A. /etc/keys
B. /proc/keys
C. /etc/inittab
D. /proc/inittab
E. /etc/reboot

Answer: C

QUESTION 126
The system is having trouble and the engineer wants to bypass the usual /sbin/init start up and run /bin/sh. What is the usual way to pass this change to the kernel from your boot loader?

A. Start in runlevel 1.
B. Pass init=/bin/sh on the kernel parameter line.
C. Pass /bin/sh on the kernel parameter line.
D. Pass start=/bin/sh on the kernel parameter line.

Answer: B

QUESTION 127
You want to preview where the package file, apache-xml.i386.rpm, will install its files before installing it. What command do you issue?

A. rpm -qp apache-xml.i386.rpm
B. rpm -qv apache-xml.i386.rpm
C. rpm -ql apache-xml.i386.rpm
D. rpm -qpl apache-xml.i386.rpm

Answer: D

QUESTION 128
Which RPM command will output the name of the package which installed the file /etc/exports?

A. rpm -F /etc/exports
B. rpm -qf /etc/exports
C. rpm -Kl /etc/exports
D. rpm -qp /etc/exports
E. rpm -qi /etc/exports

Answer: B

QUESTION 129
Which of the following commands can be used to enable a file for paging and swapping?

A. mkswap
B. swapon
C. inswap
D. modswap

Answer: B

QUESTION 130
What command will uninstall a package but leave its configuration files in case a package is re-installed?

A. none, no command will do this
B. dpkg -s pkgname
C. dpkg -L pkgname
D. dpkg -P pkgname
E. dpkg -r pkgname

Answer: E

QUESTION 131
Which command is used to query information about the available packages on a Debian system?

A. apt-cache
B. apt-get
C. apt-search
D. dpkg
E. dpkg-search

Answer: A

QUESTION 132
The GRUB_TIMEOUT parameter specifies a timeout period when booting in what unit of time?

A. milliseconds
B. tenths of seconds
C. seconds

D. minutes

Answer: C

QUESTION 133
Which of the following apt-get commands will install the newest versions of all currently installed packages without removing any packages or installing new packages that are not already installed?

A. auto-update
B. upgrade
C. dist-upgrade
D. install
E. update

Answer: B

QUESTION 134
Which of the following commands will change all CR-LF pairs in an imported text file, userlist.txt, to Linux standard LF characters and store it as newlist.txt?

A. tr '\r\n' '' < userlist.txt > newlist.txt
B. tr -c '\n\r' '' < newlist.txt > userlist.txt
C. tr -d '\r' < userlist.txt > newlist.txt
D. tr '\r' '\n' userlist.txt newlist.txt
E. tr -s '^M' '^J' userlist.txt newlist.txt

Answer: C

QUESTION 135
When should grep -F or the fgrep command be used to search the content of text files?

A. When files need to be searched that contain non-ASCII text.
B. When only the presence of the search pattern needs to be reported and not every line that matches the search.
C. When the text being searched for does not contain any regular expression patterns.
D. When the text files will be searched multiple times. Subsequent calls to fgrep will run faster.

Answer: ......

Visit PassLeader and Download Full Version 101-400 Exam Dumps