

➤ **Vendor: LPI**

➤ **Exam Code: 304-200**

➤ **Exam Name: LPIC-3 Exam 304: Virtualization**

➤ **Question 81 -- Question 100**

[Visit PassLeader and Download Full Version 304-200 Exam Dumps](#)

QUESTION 81

Which of the following Messaging Layers are supported by Pacemaker? (Choose TWO correct answers.)

- A. Heartbeat
- B. OpenAIS
- C. DRBD
- D. SCMP
- E. Slurm

Answer: AB

QUESTION 82

Which of the following configuration settings specify that keepalived is to use the round robin algorithm?

- A. lb_mode rr
- B. lb_algo rr
- C. loadbalancer_mode=rr
- D. algorithm=round robin
- E. lb_algorithm=rr

Answer: B

QUESTION 83

How can the state of the backing storage disks of a DRBD device be checked? (Choose TWO correct answers.)

- A. cat /proc/drdb/status
- B. cat /proc/drdb

- C. drbdadm dstate all
- D. drbdadm diskstatus all
- E. drbdadm state --disk all

Answer: BC

QUESTION 84

Which one of the following is NOT a required component for running an OCFS2 filesystem resource in a Pacemaker cluster?

- A. A clone resource for the OCFS2 file system.
- B. A shared storage device accessible by all nodes using the OCFS2 filesystem.
- C. The distributed lock manager (DLM).
- D. The cluster logical volume manager (CLVM).
- E. The O2CB service.

Answer: D

QUESTION 85

Which O2CB mode should be used for OCFS2 integration with heartbeat?

- A. user
- B. dlm
- C. heartbeat
- D. kernel

Answer: A

QUESTION 86

Which of the following statements are true regarding OCFS2? (Choose TWO correct answers.)

- A. OCFS2 is an integral part of Pacemaker and relies on Pacemaker services for functionality.
- B. To avoid the need for shared storage, OCFS2 can replicate the content of its filesystems via the network.
- C. When using OCFS2 with additional cluster software, OCFS2 must be integrated into the overall cluster manager to ensure consistent cluster behaviour.
- D. OCFS2 can be used without any additional software as it contains its own cluster manager, O2CB.
- E. In addition to filesystems, OCFS2 can handle other cluster services such as IP addresses and server daemons.

Answer: CD

QUESTION 87

Which kernel module must be loaded to initiate a RAID-1 like copy of data on two separate storage devices for a clustered storage solution?

- A. rsyncd
- B. drbd
- C. clraid
- D. clmirror

Answer: B

QUESTION 88

What is the name and path of the configuration file for the O2CB cluster that coordinates the nodes using OCFS2 filesystems?

- A. /etc/ocfs2/cluster.conf
- B. /etc/ocfs/cluster.conf
- C. /etc/ocfs2.conf
- D. /etc/cluster.conf

Answer: A

QUESTION 89

Which parameter of vgchange controls whether a volume group is shared within a shared storage cluster? (Specify ONLY the option name without any values or parameters.)

Answer: -c, c, clustered, --clustered

QUESTION 90

Which of the following commands can be used to change properties such as the number of node slots or the label of an existing OCFS2 filesystem?

- A. ocfs2.setprops
- B. ocfs2tool
- C. crm_edit
- D. tuneefs.ocfs2
- E. o2cbtool

Answer: D

QUESTION 91

Which of the following statements is true regarding journals of a GFS2 filesystem?

- A. Each GFS2 filesystem has exactly one journal.
- B. Once a GFS2 filesystem is created, the number of journals cannot be changed.
- C. Every node that simultaneously mounts the filesystem requires its own GFS2 journal.
- D. Journals were heavily used in GFS and are deprecated and optional in GFS2.
- E. The GFS Cluster Journal Daemon, GCJD, handles the journaling in a GFS2 cluster.

Answer: C

QUESTION 92

What is the task of the Cluster Logical Volume Manager, CLVM?

- A. It segments the cluster nodes into several logical groups that are always fenced together.
- B. It balances incoming TCP connections to a logical service to several backend nodes.
- C. It makes logical volumes on shared storage available to all cluster nodes.
- D. It allows several nodes to share file system locks in order to access the same files simultaneously.

Answer: C

QUESTION 93

When using DRBD in a Pacemaker cluster, which configuration objects must be managed in order

to use the DRBD device as storage for other cluster services? (Choose TWO correct answers.)

- A. A security resource in order to permit other cluster services to access the data on the DRBD device.
- B. A health resource in order to check the integrity of the file system.
- C. A file system resource to mount the device.
- D. A replication resource that synchronizes the DRBD device's data to all nodes that may take over the device after a failover.
- E. A constraint to ensure the device is mounted before the dependent services are started.

Answer: CE

QUESTION 94

Which of the following can be used as a low level device for DRBD? (Choose TWO correct answers.)

- A. A LVM logical volume
- B. A physical hard disk
- C. A rewritable CD
- D. A virtual tape library
- E. A tape streamer

Answer: AB

QUESTION 95

When using direct Linux booting to start Linux within a KVM virtual machine, which KVM parameter is used to specify parameters for the Linux Kernel? (Specify ONLY the option name without any values or parameters.)

Answer: append, -append

QUESTION 96

Which command in the KVM monitor restores a snapshot? (Specify ONLY the command without any path or parameters.)

Answer: loadvm

QUESTION 97

Which sub-command of xl lists the block devices that are currently attached to a Xen guest domain? (Specify ONLY the sub-command without any path or parameters.)

Answer: block-list, xl block-list

QUESTION 98

What is libvirt?

- A. An identity manager used to provide Single-Sign-On for different operating systems.
- B. A driver package used to support 3D printers.
- C. A cluster manager used to handle node access to shared storage.
- D. A combined interface to several virtualization products.
- E. A Linux-based virtualization hypervisor.

Answer: D

QUESTION 99

Which of the following products use container-based virtualization? (Choose THREE correct answers.)

- A. KVM
- B. Linux VServer
- C. LXC
- D. OpenVZ
- E. Xen

Answer: BCD

QUESTION 100

What is the usual way to gain command line access to computing instances in an IaaS cloud?

- A. By providing a public SSH key to the cloud management system and using the matching private SSH key to log into the instances.
- B. Usually computing instances are accessed through a web frontend and do not allow command line access.
- C. By either telnet or SSH using the credentials of the cloud management system account with administrative privileges.
- D. By using a telnet session with the credentials set and publicized by the creator of the computing instance's system image.
- E. By using a VNC console which does not require authentication when it is invoked via the cloud management system.

Answer: A

[**Visit PassLeader and Download Full Version 304-200 Exam Dumps**](#)