



Casino API



I already filtered the required API to be used on our app with provided example

Base Url



<https://bridge.747lc.com>



Deposit of chips for a player with a username of wakay with an amount of 10 php is shown on the API doc below.



Note that the API for deposit and withdraw is the same, only the key "amount" value will determine if deposit (value= positive #) or withdraw (value= negative #). Eg. 10, -10



method: **POST**



Endpoint: **/Default/Transfer**

Curl Example

```

curl -X 'POST' \
'https://bridge.747lc.com/Default/Transfer' \
-H 'accept: text/plain' \
-H 'Content-Type: application/json' \
-d '{
  "authToken": "e5aeeb98-d795-4410-89e8-297ad2810852",
  "platform": 1,
  "amount": 10,
  "toAgent": false,
  "currency": "php",
  "nonce": "ref_id:12345",
  "username": "wakay",
  "comment": "test"
}'

```

Request URL



<https://bridge.747lc.com/Default/Transfer>

Server response

Code	Details
200	<p>Response bodyDownload</p> <pre>{ "status": 0, "message": "ok" }</pre> <p>Response headers</p> <pre>access-control-allow-origin: * alt-svc: h3=":443"; ma=86400 cf-cache-status: DYNAMIC cf-ray: 7f0db05b4ea4bc4f-MNL content-encoding: gzip date: Mon, 20 Mar 2023 09:56:09 GMT nel: {"success_fraction":0,"report_to":"cf-nel","max_age":604800} report-to: {"endpoints":[{"url":"https://a.nel.cloudflare.com/sv%2F32ypdCclqa%2FDRkvjg8%2B7i4lvQQy%2FOSa6MnkGBGDwXD950pLYL6urBY4ILwRTLZqMcEgqVz3NjtBh7spUCNMVP565MFSQnei","max_age":604800}} server: cloudflare x-powered-by: ASP.NET</pre>

Note:



The key "toAgent" value should be dynamically set where if the user is an agent then the value shall be set as true, else the value be set to false if the user is player. So we can pre set this on the user database to set during the sign up process.



The key "nonce" shall be dynamically set and i strongly suggest to use the actual Reference ID which is also one of the key recommendation by the payment gateway provider "Gocashflex" which we need to integrate also on the app as our primary external payment gateway.



I recommend to use the name of the duty admin to be dynamically assigned in the "comment" key



GET/Default/GetHierarchy

Parameters

Name	Description
usernamestring(query)	
isAgentboolean(query)	--truefalse

Curl



```
curl -X 'GET' \
'https://bridge.747lc.com/Default/GetHierarchy?username=Wakay&isAgent=false' \
-H 'accept: text/plain'
```

Request URL



```
https://bridge.747lc.com/Default/GetHierarchy?username=Wakay&isAgent=false
```

Server response

Code	Details
200	<p>Response bodyDownload</p> <pre>{ "hierarchy": [{ "id": 1506, "clientId": 454867, "username": "Info@747.live", "parentClientId": null }, { "id": 17, "clientId": 457252, "username": "michaelpesigan08@gmail.com", "parentClientId": 454867 }, { "id": 53, "clientId": 458663, "username": "MarcThePogi", "parentClientId": 457252 }, { "id": 5793, "clientId": 459391, "username": "platilyn@gmail.com", "parentClientId": 458663 }, { "id": 53185, "clientId": 329777805, "username": "Wakay", "parentClientId": 459391 }] }</pre>

```

"user": {
"id": 53185,
"clientId": 329777805,
"username": "Wakay",
"parentClientId": 459391
},
"status": 0,
"message": "454867 Info@747.live→457252 michaelpesigan08@gmail.com→458663 MarcThePogi→459391 platalyn@gmail.com"
}

```

Response headers

```

alt-svc: h3=":443"; ma=86400 cf-cache-status: DYNAMIC cf-ray: 7d0ea126effbb47f-DXB content-encoding: br content-type: application
GMT nel: {"success_fraction":0,"report_to":"cf-nel","max_age":604800} report-to: {"endpoints":[{"url":"https://a.nel.cloudflare.com/n
s=7tR19He14QRI1YhutgSYCP9jJFS4BuaL0Tl2R2orr5f8lo3mZyw6bRu7dYO%2F%2B3AfMTaoEzDEunx0vqT3Ehy%2B6nNIGoTBitFu71r%2B
nel","max_age":604800} server: cloudflare x-powered-by: ASP.NET

```

Responses

Code	Description	Links
200	<p>SuccessMedia typetext/plainapplication/jsoncontext/jsonControls Accept header.</p> <ul style="list-style-type: none"> • <p>Example Value</p> <ul style="list-style-type: none"> • <p>Schema</p> <pre>{ "status": 0, "message": "string", "hierarchy": [{ "id": 0, "clientId": 0, "username": "string", "parentClientId": 0 }], "user": { "id": 0, "clientId": 0, "username": "string", "parentClientId": 0 } }</pre>	No links

GET/Default/GetTurnover

Parameters

Try it out

Name	Description
StartTimeLocalstring(\$date-time)(query)	
EndTimeLocalstring(\$date-time)(query)	
ClientIdstring(query)	
IsTeststring(query)	

Responses

Code	Description	Links
200	<p>SuccessMedia typetext/plainapplication/jsoncontext/jsonControls Accept header.</p> <ul style="list-style-type: none"> • <p>Example Value</p>	No links

- Schema

```
{  
  "alertMessage": "string",  
  "alertType": "string",  
  "hasError": true  
}
```