

TECHNICAL DATABASE REPORT

Comprehensive Database Summary

Setu_Odisha

Schema, relationships, database objects, record counts, column dictionary and data-quality analysis

Profile generated 24 July 2026, 22:03 India Standard Time

Read-only catalog and aggregate-data analysis; sensitive values masked

Detailed Summary of Overall Database

Database Overview

`Setu\_Odisha` is an online, multi-user Microsoft SQL Server database hosted on ACER-LP01-MR-CC. It was created on 2026-07-20T12:01:06, uses compatibility level 140, collation SQL_Latin1_General_CP1_CI_AS, and the FULL recovery model. The database is writable and has 144.00 MB allocated.

Purpose (confirmed from the application query paths and schema): it supports the Odisha population-based cancer registry portal, including patient, tumour, source, file, duplicate-review, geographic, classification and user-account data.

Evidence boundary: Catalog facts, exact record counts and aggregate checks are confirmed directly from the database. Business descriptions without database extended properties are explicitly labeled as inferred from names, columns or application use. No patient/user-identifiable sample values are reproduced.

Database Statistics

Metric	Confirmed value
Database	Setu_Odisha
Base tables	56
Total exact records	61,266
Total columns	344
Populated / empty tables	31 / 25
Tables with a primary key	25
Indexes	33 (including PK and unique indexes)
Enforced foreign keys	6
CHECK / DEFAULT constraints	0 / 0
Views / stored procedures	0 / 15
Functions / triggers	1 / 0
Allocated size	144.00 MB

Data-Type Distribution

Data type	Columns	Share
nvarchar	291	84.6%

Data type	Columns	Share
int	30	8.7%
datetime2	11	3.2%
bit	5	1.5%
float	3	0.9%
datetimeoffset	1	0.3%
bigint	1	0.3%
sysname	1	0.3%
varbinary	1	0.3%

Confirmed profile: 291 of 344 columns are nvarchar, and 271 are nvarchar(max). This schema is strongly text-oriented.

Database Architecture

The database is a single-schema (`dbo`) relational design with four functional layers:

- Core registry transactions: PatientTable, TumourTable, SourceTable, PatientFile and PossibleDuplicates.
- Reference/master data: geography, centres, cancer classifications, clinical codes and other Code/Value lookup tables.
- Archive/audit data: DeletedPatientTable, DeletedTumourTable and DeletedSourceTable.
- Platform/security data: ASP.NET Core Identity tables, Entity Framework migration history and SQL Server diagram metadata.

Core data flow (validated): PatientTable.REGNO -> TumourTable.PATIENTIDTUMOURTABLE -> SourceTable.TUMOURIDSOURCETABLE, with PatientFile.TumourId also pointing logically to TumourTable.TUMOURID. All current rows in those four logical child links matched a parent. These relationships are not enforced by database foreign keys.

Tables and Their Roles

Table	Role	Rows	Purpose
dbo.__EFMigrationsHistory	Platform / administration	13	Records applied Entity Framework Core migrations for application schema versioning.
dbo.AreaList	Reference / classification	3	Code/value or geographic reference data for area.
dbo.AspNetRoleClaims	Security / identity	0	Standard ASP.NET Core Identity table for role claims data.
dbo.AspNetRoles	Security / identity	0	Standard ASP.NET Core Identity table for roles data.

Table	Role	Rows	Purpose
dbo.AspNetUserClaims	Security / identity	0	Standard ASP.NET Core Identity table for user claims data.
dbo.AspNetUserLogins	Security / identity	0	Standard ASP.NET Core Identity table for user logins data.
dbo.AspNetUserRoles	Security / identity	0	Standard ASP.NET Core Identity table for user roles data.
dbo.AspNetUsers	Security / identity	154	Standard ASP.NET Core Identity table for users data.
dbo.AspNetUserTokens	Security / identity	0	Standard ASP.NET Core Identity table for user tokens data.
dbo.BasisOfDiagnosisList	Reference / classification	8	Code/value or geographic reference data for basis of diagnosis.
dbo.BehaviourList	Reference / classification	4	Code/value or geographic reference data for behaviour.
dbo.BlockList	Reference / classification	317	Block-level geographic master keyed to state and district codes.
dbo.CauseOfDeathList	Reference / classification	3	Code/value or geographic reference data for cause of death.
dbo.Centres	Operational master	31	Master list of participating centres and their geographic codes.
dbo.CentreTypeList	Reference / classification	3	Code/value or geographic reference data for centre type.
dbo.ClinicalStageList	Reference / classification	8	Code/value or geographic reference data for clinical stage.
dbo.DeletedPatientTable	Archive / deletion audit	25	Archives deleted patient rows together with deletion and audit metadata.
dbo.DeletedSourceTable	Archive / deletion audit	25	Archives deleted source rows together with deletion and audit metadata.
dbo.DeletedTumourTable	Archive / deletion audit	25	Archives deleted tumour rows together with deletion and audit metadata.
dbo.DiagnosisAtRegistrationList	Reference / classification	0	Code/value or geographic reference data for diagnosis at registration.
dbo.DistrictList	Reference / classification	30	District-level geographic master keyed to state codes.
dbo.DurationDateOfDiagnosisToDateOfDeathList	Reference / classification	0	Code/value or geographic reference data for duration date of diagnosis to date of death.
dbo.EthnicGroupList	Reference / classification	0	Code/value or geographic reference data for ethnic group.
dbo.FamilyHistoryOfCancerList	Reference / classification	0	Code/value or geographic reference data for family history of cancer.
dbo.GradeList	Reference / classification	9	Code/value or geographic reference data for grade.
dbo.HistologyList	Reference / classification	557	Code/value or geographic reference data for histology.
dbo.ICCCMaster	Reference / classification	0	Intended International Classification of Childhood Cancer reference structure; currently empty.
dbo.ICD10Group	Reference / classification	87	Maps normalized ICD-10 codes to grouped cancer-site labels used by incidence and mortality queries.

Table	Role	Rows	Purpose
dbo.LateralityList	Reference / classification	0	Code/value or geographic reference data for laterality.
dbo.Lymph_Leuk	Reference / classification	0	Intended lymphoma/leukaemia classification lookup; currently empty.
dbo.MaritalStatusList	Reference / classification	0	Code/value or geographic reference data for marital status.
dbo.Meso_Mela	Reference / classification	0	Intended mesothelioma/melanoma classification lookup; currently empty.
dbo.MList	Reference / classification	0	Code/value or geographic reference data for m.
dbo.NList	Reference / classification	0	Code/value or geographic reference data for n.
dbo.OccupationList	Reference / classification	0	Code/value or geographic reference data for occupation.
dbo.PatientFile	Core / transactional	1,349	Stores file metadata for documents attached logically to tumour records; file contents are not stored in this table.
dbo.PatientTable	Core / transactional	1,450	Stores the active patient-level cancer registry record and demographic/vital-status attributes.
dbo.PossibleDuplicates	Core / transactional	37	Tracks suspected duplicate record pairs, match scores, decisions and review workflow metadata.
dbo.PrimarySiteList	Reference / classification	401	Code/value or geographic reference data for primary site.
dbo.ReligionList	Reference / classification	0	Code/value or geographic reference data for religion.
dbo.SEERList	Reference / classification	0	Code/value or geographic reference data for seer.
dbo.SexList	Reference / classification	2	Code/value or geographic reference data for sex.
dbo.SourceCentreList	Reference / classification	0	Code/value or geographic reference data for source centre.
dbo.SourceTable	Core / transactional	1,455	Stores source-of-information records linked logically to a tumour and patient.
dbo.StaffDetails	Operational master	0	Intended to store staff master and contact/assignment metadata; currently empty.
dbo.StateList	Reference / classification	1	State-level geographic master.
dbo.sysdiagrams	Platform / administration	0	SQL Server Management Studio database-diagram metadata table.
dbo.TList	Reference / classification	0	Code/value or geographic reference data for t.
dbo.TreatmentList	Reference / classification	19	Code/value or geographic reference data for treatment.
dbo.TreatmentStatusList	Reference / classification	4	Code/value or geographic reference data for treatment status.

Table	Role	Rows	Purpose
dbo.TumourTable	Core / transactional	1,455	Stores tumour/case attributes linked logically to a patient, including diagnosis, site, histology and treatment coding.
dbo.TypeOfSourceList	Reference / classification	3	Code/value or geographic reference data for type of source.
dbo.Unknown	Reference / classification	0	Generic code/value placeholder reference table; currently empty.
dbo.VillageList	Reference / classification	53,782	Village-level geographic master keyed to state, district and block codes.
dbo.VitalStatusList	Reference / classification	3	Code/value or geographic reference data for vital status.
dbo.YesNoList	Reference / classification	3	Code/value or geographic reference data for yes no.

Relationships and Dependencies

Enforced foreign keys

Constraint	Child	Parent	Delete	Status
FK_AspNetRoleClaims_AspNetRoles_RoleId	AspNetRoleClaims.RoleId	AspNetRoles.Id	CASCADE	Trusted
FK_AspNetUserClaims_AspNetUsers_UserId	AspNetUserClaims.UserId	AspNetUsers.Id	CASCADE	Trusted
FK_AspNetUserLogins_AspNetUsers_UserId	AspNetUserLogins.UserId	AspNetUsers.Id	CASCADE	Trusted
FK_AspNetUserRoles_AspNetRoles_RoleId	AspNetUserRoles.RoleId	AspNetRoles.Id	CASCADE	Trusted
FK_AspNetUserRoles_AspNetUsers_UserId	AspNetUserRoles.UserId	AspNetUsers.Id	CASCADE	Trusted
FK_AspNetUserTokens_AspNetUsers_UserId	AspNetUserTokens.UserId	AspNetUsers.Id	CASCADE	Trusted

Confirmed: all six enforced foreign keys belong to the ASP.NET Identity subsystem. No cancer-registry, file, centre, geography or clinical lookup relationship is enforced by an FK.

Validated logical relationships

Logical relationship	Child rows	Matched	Orphans
TumourTable.PATIENTIDTUMOURTABLE -> PatientTable.REGNO	1,455	1,455	0
TumourTable.REGNO -> PatientTable.REGNO	1,455	1,455	0
SourceTable.TUMOURIDSOURCETABLE -> TumourTable.TUMOURID	1,455	1,455	0
SourceTable.REGNO -> PatientTable.REGNO	1,455	1,455	0
PatientFile.TumourId -> TumourTable.TUMOURID	1,349	1,349	0

Observed cardinality

Relationship	Parents	No child	One	Many	Max
PatientTable -> TumourTable	1,450	1	1,443	6	2
TumourTable -> SourceTable	1,455	0	1,455	0	1
TumourTable -> PatientFile	1,455	310	1,009	136	9

Keys, Constraints, and Indexes

The catalog contains 33 indexes across 25 tables. 25 tables have primary keys; 31 do not. There are no user-defined CHECK constraints, no column DEFAULT constraints and no computed columns.

Table	Index	Type	Columns
__EFMigrationsHistory	PK__EFMigrationsHistory	PK	[MigrationId] ASC
AspNetRoleClaims	PK_AspNetRoleClaims	PK	[Id] ASC
AspNetRoleClaims	IX_AspNetRoleClaims_RoleId	Nonunique	[RoleId] ASC
AspNetRoles	PK_AspNetRoles	PK	[Id] ASC
AspNetRoles	RoleNameIndex	Unique	[NormalizedName] ASC
AspNetUserClaims	PK_AspNetUserClaims	PK	[Id] ASC
AspNetUserClaims	IX_AspNetUserClaims_UserId	Nonunique	[UserId] ASC
AspNetUserLogins	PK_AspNetUserLogins	PK	[LoginProvider] ASC, [ProviderKey] ASC
AspNetUserLogins	IX_AspNetUserLogins_UserId	Nonunique	[UserId] ASC
AspNetUserRoles	PK_AspNetUserRoles	PK	[UserId] ASC, [RoleId] ASC
AspNetUserRoles	IX_AspNetUserRoles_RoleId	Nonunique	[RoleId] ASC
AspNetUsers	PK_AspNetUsers	PK	[Id] ASC
AspNetUsers	UserNameIndex	Unique	[NormalizedUserName] ASC
AspNetUsers	EmailIndex	Nonunique	[NormalizedEmail] ASC
AspNetUserTokens	PK_AspNetUserTokens	PK	[UserId] ASC, [LoginProvider] ASC, [Name] ASC
BlockList	PK_BlockList	PK	[Id] ASC
Centres	PK_Centres	PK	[Id] ASC
DeletedPatientTable	PK_DeletedPatientTable	PK	[Id] ASC
DeletedSourceTable	PK_DeletedSourceTable	PK	[Id] ASC
DeletedTumourTable	PK_DeletedTumourTable	PK	[Id] ASC
DistrictList	PK_DistrictList	PK	[Id] ASC
ICCCMaster	PK_ICCCMaster	PK	[Id] ASC
PatientFile	PK_PatientFile	PK	[Id] ASC

Table	Index	Type	Columns
PatientTable	PK_PatientTable	PK	[Id] ASC
PossibleDuplicates	PK_PossibleDuplicates	PK	[Id] ASC
SourceCentreList	PK_SourceCentreList	PK	[Id] ASC
SourceTable	PK_SourceTable	PK	[Id] ASC
StaffDetails	PK_StaffDetails	PK	[Id] ASC
StateList	PK_StateList	PK	[Id] ASC
sysdiagrams	PK__sysdiagr__C2B05B61DAFDC6EC	PK	[diagram_id] ASC
sysdiagrams	UK_principal_name	Unique	[principal_id] ASC, [name] ASC
TumourTable	PK_TumourTable	PK	[Id] ASC
VillageList	PK_VillageList	PK	[Id] ASC

Views, Stored Procedures, Functions, and Triggers

Confirmed catalog totals: 0 views; 15 stored procedures; 1 function; 0 triggers.

Type	Object	Parameters	Dependencies	Purpose
Scalar Function	dbo.fn_diagramobjects	int	None recorded	SQL Server diagram-management support object.
Stored Procedure	dbo.sp_alterdiagram	@diagramname sysname, @owner_id int, @version int, @definition varbinary	dbo.sysdiagrams	SQL Server diagram-management support object.
Stored Procedure	dbo.sp_creatediagram	@diagramname sysname, @owner_id int, @version int, @definition varbinary	dbo.sysdiagrams	SQL Server diagram-management support object.
Stored Procedure	dbo.sp_dropdiagram	@diagramname sysname, @owner_id int	dbo.sysdiagrams	SQL Server diagram-management support object.
Stored Procedure	dbo.SP_GET_NIRMITI_INCI_MORT_FORMAT	@clauses varchar	None recorded	Application export/report procedure; purpose inferred from object name.
Stored Procedure	dbo.SP_GET_NIRMITI_PAEDIATRIC_FORMAT	@clauses varchar	None recorded	Application export/report procedure; purpose inferred from object name.
Stored Procedure	dbo.SP_GET_PATIENT_DATA_CANREG5_FORMAT	@clauses varchar	None recorded	Application export/report procedure; purpose inferred from object name.
Stored Procedure	dbo.SP_GET_PATIENTTUMOUR_DATA_CANREG5_FORMAT	@clauses varchar	None recorded	Application export/report procedure; purpose inferred from object name.
Stored Procedure	dbo.SP_GET_PATIENTTUMOURSOURCEDATA_CANREG5_FORMAT	@clauses varchar	None recorded	Application export/report procedure; purpose inferred from object name.
Stored Procedure	dbo.SP_GET_SOURCE_DATA_CANREG5_FORMAT	@clauses varchar	None recorded	Application export/report procedure; purpose inferred from object name.
Stored Procedure	dbo.SP_GET_TUMOUR_DATA_CANREG5_FORMAT	@clauses varchar	None recorded	Application export/report procedure; purpose inferred from object name.

Type	Object	Parameters	Dependencies	Purpose
Stored Procedure	dbo.SP_GET_TUMOURSOURCE_DATA_CANREG5_FORMAT	@clauses varchar	None recorded	Application export/report procedure; purpose inferred from object name.
Stored Procedure	dbo.sp_helpdiagramdefinition	@diagramname sysname, @owner_id int	dbo.sysdiagrams	SQL Server diagram-management support object.
Stored Procedure	dbo.sp_helpdiagrams	@diagramname sysname, @owner_id int	sysdiagrams	SQL Server diagram-management support object.
Stored Procedure	dbo.sp_renamediagram	@diagramname sysname, @owner_id int, @new_diagramname sysname	dbo.sysdiagrams	SQL Server diagram-management support object.
Stored Procedure	dbo.sp_upgraddiagrams	None	dbo.dproperties, dbo.sysdiagrams	SQL Server diagram-management support object.

Data Quality and Integrity Analysis

- Core logical integrity is currently strong: all 1,455 tumour-to-patient, 1,455 source-to-tumour, 1,455 source-to-patient and 1,349 file-to-tumour links matched.
- Business identifiers REGNO, TUMOURID and SOURCEID have no duplicate groups in current data, but uniqueness is not enforced.
- VillageList contains 66 duplicate Villageld groups (66 excess rows) and 310 rows whose BlockId is absent from BlockList.
- TumourTable.ICD10 has 2 populated values outside the expected normalized Cnn pattern and 11 populated values not mapped by ICD10Group.
- PossibleDuplicates contains 37 decisions; ReviewedBy is missing in all 37 rows.
- 25 of 56 tables are empty, including several classification/reference tables and all standard Identity role/claim/link tables.
- 286 of 344 columns are nullable; 271 are nvarchar(max).
- No user-defined CHECK constraints or DEFAULT constraints exist.
- All populated DateOfBirth, DateOfDeath and DateOfDiagnosis values converted successfully in the current read-only check; the fields remain stored as text.

Important Findings and Recommendations

Priority	Recommendation
High	Repair the 310 VillageList rows with unknown BlockId and resolve the 66 duplicate Villageld groups before introducing constraints.
High	Add staged UNIQUE constraints for PatientTable.REGNO, TumourTable.TUMOURID and SourceTable.SOURCEID after regression testing.
High	Add staged FKs for the validated patient-tumour-source-file chain and geographic hierarchy; use WITH CHECK so trust is verified.

Priority	Recommendation
High	Remediate the 2 malformed and 11 unmapped ICD10 values, then enforce normalized code validation or a controlled lookup.
Medium	Migrate date strings to date/datetime2 columns and ContactNumber away from float; preserve source text during a controlled transition.
Medium	Replace unnecessary nvarchar(max) columns with bounded lengths derived from real maxima, prioritizing keys and frequently filtered fields.
Medium	Add CHECK/default rules for status flags, required workflow fields and audit timestamps; define nullability from business rules.
Medium	Require reviewer identity for duplicate decisions or explicitly record an automated decision source.
Medium	Review the 24 empty tables and retire, populate or document them so inactive schema does not obscure intended functionality.
Security	Verify the intended authorization model: 154 AspNetUsers rows exist while role/claim membership tables are empty and the web app also uses Windows authentication.

Detailed Summary of Individual Tables

Each section below reports the exact record count, catalog metadata, every column, enforced and logical relationships, aggregate profile facts and privacy-safe representative values. Descriptions prefixed “Inferred” are observations, not catalog documentation.

1. dbo.__EFMigrationsHistory

Table Overview

Confirmed by schema/application use. Records applied Entity Framework Core migrations for application schema versioning.

Role classification: Platform / administration.

Table Statistics

Measure	Value
Total records	13
Columns	2
Primary key	MigrationId
Enforced foreign-key columns	0
Created	2025-09-15T10:48:17
Last schema modification	2025-09-15T10:48:17

Column Details

Column Name	Data Type	Nullable	Key / Constraint	Default	Description
MigrationId	nvarchar(150)	No	PK#1	None	Entity Framework migration identifier. Representative values masked (sensitive or identifying field).
ProductVersion	nvarchar(32)	No	None	None	Entity Framework product version used for the migration. Profile: 1 distinct non-null values. Representative values: 6.0.1 (13).

Relationships

- No enforced or validated logical relationships were identified for this table.

Data Analysis

Business-critical or frequently joined/filterable columns: MigrationId.

- No null or blank values were found in profiled columns.

- The primary key prevents duplicate full rows and duplicate key values.

Data Quality Observations

2 of 2 columns have no null/blank values in the current data. Representative values in the column table are frequency-based and masked for sensitive fields.

Important Findings

- Application-level relationships exist without FK enforcement.

2. dbo.AreaList

Table Overview

Purpose inferred from table and column names. Code/value or geographic reference data for area.

Role classification: Reference / classification.

Table Statistics

Measure	Value
Total records	3
Columns	2
Primary key	None
Enforced foreign-key columns	0
Created	2025-09-16T13:05:09
Last schema modification	2025-09-16T13:05:09

Column Details

Column Name	Data Type	Nullable	Key / Constraint	Default	Description
Code	nvarchar(max)	Yes	None	None	Stored category or classification code. Profile: 3 distinct non-null values. Representative values: 1 (1); 2 (1); 3 (1).
Value	nvarchar(max)	Yes	None	None	Display label or decoded meaning for the associated code. Profile: 3 distinct non-null values. Representative values: Rural (1); Tribal (1); Urban (1).

Relationships

- Probable semantic code/value lookup for PatientTable.Area, based on matching domain names; not enforced by a foreign key.

Data Analysis

Business-critical or frequently joined/filterable columns: Code.

- No null or blank values were found in profiled columns.
- Code values are unique in the current data, but no PK/UNIQUE constraint enforces that condition.
- 2 column(s) use nvarchar(max), limiting type precision and potentially increasing storage/indexing cost.

Data Quality Observations

2 of 2 columns have no null/blank values in the current data. Representative values in the column table are frequency-based and masked for sensitive fields.

Important Findings

- No primary key is defined.
- Application-level relationships exist without FK enforcement.

3. dbo.AspNetRoleClaims

Table Overview

Confirmed standard framework schema. Standard ASP.NET Core Identity table for role claims data.

Role classification: Security / identity.

Table Statistics

Measure	Value
Total records	0
Columns	4
Primary key	Id
Enforced foreign-key columns	1
Created	2025-09-15T10:48:33
Last schema modification	2025-09-15T10:48:36

Column Details

Column Name	Data Type	Nullable	Key / Constraint	Default	Description
Id	int	No	PK#1; IDENTITY(1,1)	None	Internal row identifier.
RoleId	nvarchar(450)	No	FK -> dbo.AspNetRoles.Id	None	Inferred: stores role id data.
ClaimType	nvarchar(max)	Yes	None	None	Inferred: stores claim type data.

Column Name	Data Type	Nullable	Key / Constraint	Default	Description
ClaimValue	nvarchar(max)	Yes	None	None	Inferred: stores claim value data.

Relationships

- Enforced many-to-one: dbo.AspNetRoleClaims.RoleId -> dbo.AspNetRoles.Id (ON DELETE CASCADE; ON UPDATE NO_ACTION).

Data Analysis

Business-critical or frequently joined/filterable columns: Id, RoleId.

- The table is empty at the profiling timestamp; value distributions and duplicates cannot be assessed.
- The primary key prevents duplicate full rows and duplicate key values.
- 2 column(s) use nvarchar(max), limiting type precision and potentially increasing storage/indexing cost.

Data Quality Observations

Confirmed: no rows are present; completeness, consistency and representative-value checks are not applicable.

Important Findings

- The table is inactive/empty at the profiling timestamp; confirm whether it is planned, legacy or awaiting data.

4. dbo.AspNetRoles

Table Overview

Confirmed standard framework schema. Standard ASP.NET Core Identity table for roles data.

Role classification: Security / identity.

Table Statistics

Measure	Value
Total records	0
Columns	4
Primary key	Id
Enforced foreign-key columns	0
Created	2025-09-15T10:48:17

Measure	Value
Last schema modification	2025-09-15T10:48:36

Column Details

Column Name	Data Type	Nullable	Key / Constraint	Default	Description
Id	nvarchar(450)	No	PK#1	None	Internal row identifier.
Name	nvarchar(256)	Yes	None	None	Inferred: stores name data.
NormalizedName	nvarchar(256)	Yes	UNIQUE INDEX	None	Inferred: stores normalized name data.
ConcurrencyStamp	nvarchar(max)	Yes	None	None	Inferred: stores concurrency stamp data. Representative values masked (sensitive or identifying field).

Relationships

- Enforced one-to-many parent for dbo.AspNetRoleClaims through FK_AspNetRoleClaims_AspNetRoles_RoleId.
- Enforced one-to-many parent for dbo.AspNetUserRoles through FK_AspNetUserRoles_AspNetRoles_RoleId.

Data Analysis

Business-critical or frequently joined/filterable columns: Id.

- The table is empty at the profiling timestamp; value distributions and duplicates cannot be assessed.
- The primary key prevents duplicate full rows and duplicate key values.
- 1 column(s) use nvarchar(max), limiting type precision and potentially increasing storage/indexing cost.

Data Quality Observations

Confirmed: no rows are present; completeness, consistency and representative-value checks are not applicable.

Important Findings

- The table is inactive/empty at the profiling timestamp; confirm whether it is planned, legacy or awaiting data.

5. dbo.AspNetUserClaims

Table Overview

Confirmed standard framework schema. Standard ASP.NET Core Identity table for user claims data.

Role classification: Security / identity.

Table Statistics

Measure	Value
Total records	0
Columns	4
Primary key	Id
Enforced foreign-key columns	1
Created	2025-09-15T10:48:33
Last schema modification	2025-09-15T10:48:36

Column Details

Column Name	Data Type	Nullable	Key / Constraint	Default	Description
Id	int	No	PK#1; IDENTITY(1,1)	None	Internal row identifier.
UserId	nvarchar(450)	No	FK -> dbo.AspNetUsers.Id	None	Inferred: stores user id data.
ClaimType	nvarchar(max)	Yes	None	None	Inferred: stores claim type data.
ClaimValue	nvarchar(max)	Yes	None	None	Inferred: stores claim value data.

Relationships

- Enforced many-to-one: dbo.AspNetUserClaims.UserId -> dbo.AspNetUsers.Id (ON DELETE CASCADE; ON UPDATE NO_ACTION).

Data Analysis

Business-critical or frequently joined/filterable columns: Id, UserId.

- The table is empty at the profiling timestamp; value distributions and duplicates cannot be assessed.
- The primary key prevents duplicate full rows and duplicate key values.
- 2 column(s) use nvarchar(max), limiting type precision and potentially increasing storage/indexing cost.

Data Quality Observations

Confirmed: no rows are present; completeness, consistency and representative-value checks are not applicable.

Important Findings

- The table is inactive/empty at the profiling timestamp; confirm whether it is planned, legacy or awaiting data.

6. dbo.AspNetUserLogins

Table Overview

Confirmed standard framework schema. Standard ASP.NET Core Identity table for user logins data.

Role classification: Security / identity.

Table Statistics

Measure	Value
Total records	0
Columns	4
Primary key	LoginProvider, ProviderKey
Enforced foreign-key columns	1
Created	2025-09-15T10:48:33
Last schema modification	2025-09-15T10:48:37

Column Details

Column Name	Data Type	Nullable	Key / Constraint	Default	Description
LoginProvider	nvarchar(450)	No	PK#1	None	Inferred: stores login provider data.
ProviderKey	nvarchar(450)	No	PK#2	None	Inferred: stores provider key data.
ProviderDisplayName	nvarchar(max)	Yes	None	None	Inferred: stores provider display name data.
UserId	nvarchar(450)	No	FK -> dbo.AspNetUsers.Id	None	Inferred: stores user id data.

Relationships

- Enforced many-to-one: dbo.AspNetUserLogins.UserId -> dbo.AspNetUsers.Id (ON DELETE CASCADE; ON UPDATE NO_ACTION).

Data Analysis

Business-critical or frequently joined/filterable columns: LoginProvider, ProviderKey, UserId.

- The table is empty at the profiling timestamp; value distributions and duplicates cannot be assessed.
- The primary key prevents duplicate full rows and duplicate key values.
- 1 column(s) use nvarchar(max), limiting type precision and potentially increasing storage/indexing cost.

Data Quality Observations

Confirmed: no rows are present; completeness, consistency and representative-value checks are not applicable.

Important Findings

- The table is inactive/empty at the profiling timestamp; confirm whether it is planned, legacy or awaiting data.

7. dbo.AspNetUserRoles

Table Overview

Confirmed standard framework schema. Standard ASP.NET Core Identity table for user roles data.

Role classification: Security / identity.

Table Statistics

Measure	Value
Total records	0
Columns	2
Primary key	UserId, RoleId
Enforced foreign-key columns	2
Created	2025-09-15T10:48:35
Last schema modification	2025-09-15T10:48:37

Column Details

Column Name	Data Type	Nullable	Key / Constraint	Default	Description
UserId	nvarchar(450)	No	PK#1; FK -> dbo.AspNetUsers.Id	None	Inferred: stores user id data.

Column Name	Data Type	Nullable	Key / Constraint	Default	Description
RoleId	nvarchar(450)	No	PK#2; FK -> dbo.AspNetRoles.Id	None	Inferred: stores role id data.

Relationships

- Enforced many-to-one: dbo.AspNetUserRoles.RoleId -> dbo.AspNetRoles.Id (ON DELETE CASCADE; ON UPDATE NO_ACTION).
- Enforced many-to-one: dbo.AspNetUserRoles.UserId -> dbo.AspNetUsers.Id (ON DELETE CASCADE; ON UPDATE NO_ACTION).

Data Analysis

Business-critical or frequently joined/filterable columns: UserId, RoleId.

- The table is empty at the profiling timestamp; value distributions and duplicates cannot be assessed.
- The primary key prevents duplicate full rows and duplicate key values.

Data Quality Observations

Confirmed: no rows are present; completeness, consistency and representative-value checks are not applicable.

Important Findings

- The table is inactive/empty at the profiling timestamp; confirm whether it is planned, legacy or awaiting data.

8. dbo.AspNetUsers

Table Overview

Confirmed standard framework schema. Standard ASP.NET Core Identity table for users data.

Role classification: Security / identity.

Table Statistics

Measure	Value
Total records	154
Columns	19
Primary key	Id
Enforced foreign-key columns	0

Measure	Value
Created	2025-09-15T10:48:17
Last schema modification	2025-09-15T10:48:37

Column Details

Column Name	Data Type	Nullable	Key / Constraint	Default	Description
Id	nvarchar(450)	No	PK#1	None	Internal row identifier. Representative values masked (sensitive or identifying field).
PersonName	nvarchar(max)	No	None	None	Inferred: stores person name data. Representative values masked (sensitive or identifying field).
UserType	int	No	None	None	Inferred: stores user type data. Profile: 3 distinct non-null values; range 1 to 3. Representative values: 3 (85); 1 (66); 2 (3).
CentreCode	nvarchar(max)	No	None	None	Code identifying the participating registry centre. Profile: 31 distinct non-null values. Representative values: C023 (9); C002 (7); C017 (7).
IsActive	bit	No	None	None	Inferred: stores is active data. Profile: 2 distinct non-null values. Representative values: 1 (151); 0 (3).
UserName	nvarchar(256)	Yes	None	None	Inferred: stores user name data. Representative values masked (sensitive or identifying field).
NormalizedUserName	nvarchar(256)	Yes	UNIQUE INDEX	None	Inferred: stores normalized user name data. Representative values masked (sensitive or identifying field).
Email	nvarchar(256)	Yes	None	None	Inferred: stores email data. Representative values masked (sensitive or identifying field).
NormalizedEmail	nvarchar(256)	Yes	None	None	Inferred: stores normalized email data. Representative values masked (sensitive or identifying field).
EmailConfirmed	bit	No	None	None	Inferred: stores email confirmed data. Representative values masked (sensitive or identifying field).
PasswordHash	nvarchar(max)	Yes	None	None	Inferred: stores password hash data. Representative values masked (sensitive or identifying field).
SecurityStamp	nvarchar(max)	Yes	None	None	Inferred: stores security stamp data. Representative values masked (sensitive or identifying field).
ConcurrencyStamp	nvarchar(max)	Yes	None	None	Inferred: stores concurrency stamp data. Representative values masked (sensitive or identifying field).
PhoneNumber	nvarchar(max)	Yes	None	None	Inferred: stores phone number data. Profile: 154/154 rows are null or blank. Representative values masked (sensitive or identifying field).
PhoneNumberConfirmed	bit	No	None	None	Inferred: stores phone number confirmed data. Representative values masked (sensitive or identifying field).
TwoFactorEnabled	bit	No	None	None	Inferred: stores two factor enabled data. Profile: 1 distinct non-null values. Representative values: 0 (154).
LockoutEnd	datetimeoffset(7)	Yes	None	None	Inferred: stores lockout end data. Profile: 154/154 rows are null or blank; 0 distinct non-null values.

Column Name	Data Type	Nullable	Key / Constraint	Default	Description
LockoutEnabled	bit	No	None	None	Inferred: stores lockout enabled data. Profile: 1 distinct non-null values. Representative values: 1 (154).
AccessFailedCount	int	No	None	None	Inferred: stores access failed count data. Profile: 1 distinct non-null values; range 0 to 0. Representative values: 0 (154).

Relationships

- Enforced one-to-many parent for dbo.AspNetUserClaims through FK_AspNetUserClaims_AspNetUsers_UserId.
- Enforced one-to-many parent for dbo.AspNetUserLogins through FK_AspNetUserLogins_AspNetUsers_UserId.
- Enforced one-to-many parent for dbo.AspNetUserRoles through FK_AspNetUserRoles_AspNetUsers_UserId.
- Enforced one-to-many parent for dbo.AspNetUserTokens through FK_AspNetUserTokens_AspNetUsers_UserId.

Data Analysis

Business-critical or frequently joined/filterable columns: Id, CentreCode.

- Highest null/blank counts: PhoneNumber 154/154, LockoutEnd 154/154.
- The primary key prevents duplicate full rows and duplicate key values.
- 154 users exist while the standard role, role-claim, user-role, user-claim, login and token tables are empty.
- Authorization appears to rely on the custom UserType/CentreCode fields or external Windows authentication; verify intended policy.
- 6 column(s) use nvarchar(max), limiting type precision and potentially increasing storage/indexing cost.

Data Quality Observations

17 of 19 columns have no null/blank values in the current data. Representative values in the column table are frequency-based and masked for sensitive fields.

Important Findings

- No additional table-specific structural risk was identified beyond the database-wide recommendations.

9. dbo.AspNetUserTokens

Table Overview

Confirmed standard framework schema. Standard ASP.NET Core Identity table for user tokens data.

Role classification: Security / identity.

Table Statistics

Measure	Value
Total records	0
Columns	4
Primary key	UserId, LoginProvider, Name
Enforced foreign-key columns	1
Created	2025-09-15T10:48:35
Last schema modification	2025-09-15T10:48:35

Column Details

Column Name	Data Type	Nullable	Key / Constraint	Default	Description
UserId	nvarchar(450)	No	PK#1; FK -> dbo.AspNetUsers.Id	None	Inferred: stores user id data.
LoginProvider	nvarchar(450)	No	PK#2	None	Inferred: stores login provider data.
Name	nvarchar(450)	No	PK#3	None	Inferred: stores name data.
Value	nvarchar(max)	Yes	None	None	Display label or decoded meaning for the associated code.

Relationships

- Enforced many-to-one: dbo.AspNetUserTokens.UserId -> dbo.AspNetUsers.Id (ON DELETE CASCADE; ON UPDATE NO_ACTION).

Data Analysis

Business-critical or frequently joined/filterable columns: UserId, LoginProvider, Name.

- The table is empty at the profiling timestamp; value distributions and duplicates cannot be assessed.
- The primary key prevents duplicate full rows and duplicate key values.
- 1 column(s) use nvarchar(max), limiting type precision and potentially increasing storage/indexing cost.

Data Quality Observations

Confirmed: no rows are present; completeness, consistency and representative-value checks are not applicable.

Important Findings

- The table is inactive/empty at the profiling timestamp; confirm whether it is planned, legacy or awaiting data.

10. dbo.BasisOfDiagnosisList

Table Overview

Purpose inferred from table and column names. Code/value or geographic reference data for basis of diagnosis.

Role classification: Reference / classification.

Table Statistics

Measure	Value
Total records	8
Columns	2
Primary key	None
Enforced foreign-key columns	0
Created	2025-09-15T10:48:17
Last schema modification	2025-09-15T10:48:17

Column Details

Column Name	Data Type	Nullable	Key / Constraint	Default	Description
Code	nvarchar(max)	Yes	None	None	Stored category or classification code. Profile: 8 distinct non-null values. Representative values: 0 (1); 1 (1); 2 (1).
Value	nvarchar(max)	Yes	None	None	Display label or decoded meaning for the associated code. Profile: 8 distinct non-null values. Representative values: Clinical (1); Cytology (Peripheral blood/Bone marrow (1); Death Certificate only (1).

Relationships

- Probable semantic code/value lookup for TumourTable.BasisOfDiagnosis, based on matching domain names; not enforced by a foreign key.

Data Analysis

Business-critical or frequently joined/filterable columns: Code.

- No null or blank values were found in profiled columns.
- Code values are unique in the current data, but no PK/UNIQUE constraint enforces that condition.
- 2 column(s) use nvarchar(max), limiting type precision and potentially increasing storage/indexing cost.

Data Quality Observations

2 of 2 columns have no null/blank values in the current data. Representative values in the column table are frequency-based and masked for sensitive fields.

Important Findings

- No primary key is defined.
- Application-level relationships exist without FK enforcement.

11. dbo.BehaviourList

Table Overview

Purpose inferred from table and column names. Code/value or geographic reference data for behaviour.

Role classification: Reference / classification.

Table Statistics

Measure	Value
Total records	4
Columns	2
Primary key	None
Enforced foreign-key columns	0
Created	2025-09-15T10:48:17
Last schema modification	2025-09-15T10:48:17

Column Details

Column Name	Data Type	Nullable	Key / Constraint	Default	Description
Code	nvarchar(max)	Yes	None	None	Stored category or classification code. Profile: 4 distinct non-null values. Representative values: 0 (1); 1 (1); 2 (1).

Column Name	Data Type	Nullable	Key / Constraint	Default	Description
Value	nvarchar(max)	Yes	None	None	Display label or decoded meaning for the associated code. Profile: 4 distinct non-null values. Representative values: Benign (1); In situ (1); Malignant (1).

Relationships

- Probable semantic code/value lookup for TumourTable.Behaviour, based on matching domain names; not enforced by a foreign key.

Data Analysis

Business-critical or frequently joined/filterable columns: Code.

- No null or blank values were found in profiled columns.
- Code values are unique in the current data, but no PK/UNIQUE constraint enforces that condition.
- 2 column(s) use nvarchar(max), limiting type precision and potentially increasing storage/indexing cost.

Data Quality Observations

2 of 2 columns have no null/blank values in the current data. Representative values in the column table are frequency-based and masked for sensitive fields.

Important Findings

- No primary key is defined.
- Application-level relationships exist without FK enforcement.

12. dbo.BlockList

Table Overview

Purpose inferred from table and column names. Block-level geographic master keyed to state and district codes.

Role classification: Reference / classification.

Table Statistics

Measure	Value
Total records	317
Columns	5
Primary key	Id

Measure	Value
Enforced foreign-key columns	0
Created	2025-09-15T10:48:17
Last schema modification	2025-09-15T10:48:17

Column Details

Column Name	Data Type	Nullable	Key / Constraint	Default	Description
Id	int	No	PK#1; IDENTITY(1,1)	None	Internal row identifier. Profile: 317 distinct non-null values; range 4 to 320. Representative values: 10 (1); 100 (1); 101 (1).
StateId	nvarchar(max)	Yes	None	None	State master code. Profile: 1 distinct non-null values. Representative values: 1 (317).
DistrictId	nvarchar(max)	Yes	None	None	District master code. Profile: 30 distinct non-null values. Representative values: 122 (26); 110 (23); 130 (18).
BlockId	nvarchar(max)	Yes	None	None	Block master code. Profile: 317 distinct non-null values. Representative values: 10101 (1); 10102 (1); 10103 (1).
BlockName	nvarchar(max)	Yes	None	None	Inferred: stores block name data. Profile: 317 distinct non-null values. Representative values: Aali (1); Agalpur (1); Ambabhona (1).

Relationships

- Logical child of DistrictList and parent of VillageList; 310 VillageList rows reference a BlockId absent from BlockList.

Data Analysis

Business-critical or frequently joined/filterable columns: Id, StateId, DistrictId, BlockId.

- No null or blank values were found in profiled columns.
- The primary key prevents duplicate full rows and duplicate key values.
- 4 column(s) use nvarchar(max), limiting type precision and potentially increasing storage/indexing cost.

Data Quality Observations

5 of 5 columns have no null/blank values in the current data. Representative values in the column table are frequency-based and masked for sensitive fields.

Important Findings

- Application-level relationships exist without FK enforcement.

13. dbo.CauseOfDeathList

Table Overview

Purpose inferred from table and column names. Code/value or geographic reference data for cause of death.

Role classification: Reference / classification.

Table Statistics

Measure	Value
Total records	3
Columns	2
Primary key	None
Enforced foreign-key columns	0
Created	2025-09-15T10:48:18
Last schema modification	2025-09-15T10:48:18

Column Details

Column Name	Data Type	Nullable	Key / Constraint	Default	Description
Code	nvarchar(max)	Yes	None	None	Stored category or classification code. Profile: 3 distinct non-null values. Representative values: 1 (1); 2 (1); 4 (1).
Value	nvarchar(max)	Yes	None	None	Display label or decoded meaning for the associated code. Profile: 3 distinct non-null values. Representative values: Cancer (1); Others (1); Unknown (1).

Relationships

- Probable semantic code/value lookup for PatientTable.CauseOfDeath, based on matching domain names; not enforced by a foreign key.

Data Analysis

Business-critical or frequently joined/filterable columns: Code.

- No null or blank values were found in profiled columns.
- Code values are unique in the current data, but no PK/UNIQUE constraint enforces that condition.
- 2 column(s) use nvarchar(max), limiting type precision and potentially increasing storage/indexing cost.

Data Quality Observations

2 of 2 columns have no null/blank values in the current data. Representative values in the column table are frequency-based and masked for sensitive fields.

Important Findings

- No primary key is defined.
- Application-level relationships exist without FK enforcement.

14. dbo.Centres

Table Overview

Purpose inferred from table and column names. Master list of participating centres and their geographic codes.

Role classification: Operational master.

Table Statistics

Measure	Value
Total records	31
Columns	8
Primary key	Id
Enforced foreign-key columns	0
Created	2025-09-15T10:48:18
Last schema modification	2025-09-15T10:48:18

Column Details

Column Name	Data Type	Nullable	Key / Constraint	Default	Description
Id	int	No	PK#1; IDENTITY(1,1)	None	Internal row identifier. Profile: 31 distinct non-null values; range 1 to 73. Representative values: 1 (1); 44 (1); 45 (1).
CentreCode	nvarchar(max)	Yes	None	None	Code identifying the participating registry centre. Profile: 31 distinct non-null values. Representative values: C000 (1); C001 (1); C002 (1).
CentreName	nvarchar(max)	Yes	None	None	Inferred: stores centre name data. Profile: 31 distinct non-null values. Representative values: DHH Angul (1); DHH Balangir (1); DHH Balasore (1).
CentreType	nvarchar(max)	Yes	None	None	Inferred: stores centre type data. Profile: 1 distinct non-null values. Representative values: HOSPITAL (31).

Column Name	Data Type	Nullable	Key / Constraint	Default	Description
StateId	nvarchar(max)	Yes	None	None	State master code. Profile: 1/31 rows are null or blank; 1 distinct non-null values. Representative values: 1 (30).
DistrictId	nvarchar(max)	Yes	None	None	District master code. Profile: 1/31 rows are null or blank; 30 distinct non-null values. Representative values: 101 (1); 102 (1); 103 (1).
BlockId	nvarchar(max)	Yes	None	None	Block master code. Profile: 1/31 rows are null or blank; 30 distinct non-null values. Representative values: 10101 (1); 10201 (1); 10302 (1).
VillageId	nvarchar(max)	Yes	None	None	Village master code. Profile: 1/31 rows are null or blank. Representative values masked (sensitive or identifying field).

Relationships

- Logically references StateList, DistrictList, BlockList and VillageList by stored geographic codes; no database FKs enforce these links.

Data Analysis

Business-critical or frequently joined/filterable columns: Id, CentreCode, StateId, DistrictId, BlockId, VillageId.

- Highest null/blank counts: VillageId 1/31, StateId 1/31, DistrictId 1/31, BlockId 1/31.
- The primary key prevents duplicate full rows and duplicate key values.
- 7 column(s) use nvarchar(max), limiting type precision and potentially increasing storage/indexing cost.

Data Quality Observations

4 of 8 columns have no null/blank values in the current data. Representative values in the column table are frequency-based and masked for sensitive fields.

Important Findings

- Application-level relationships exist without FK enforcement.

15. dbo.CentreTypeList

Table Overview

Purpose inferred from table and column names. Code/value or geographic reference data for centre type.

Role classification: Reference / classification.

Table Statistics

Measure	Value
Total records	3
Columns	2
Primary key	None
Enforced foreign-key columns	0
Created	2025-09-15T10:48:18
Last schema modification	2025-09-15T10:48:18

Column Details

Column Name	Data Type	Nullable	Key / Constraint	Default	Description
Code	nvarchar(max)	Yes	None	None	Stored category or classification code. Profile: 3 distinct non-null values. Representative values: DEATH-REGISTRAR (1); HOSPITAL (1); LABORATORY (1).
Value	nvarchar(max)	Yes	None	None	Display label or decoded meaning for the associated code. Profile: 3 distinct non-null values. Representative values: DEATH-REGISTRAR (1); HOSPITAL (1); LABORATORY (1).

Relationships

- Probable semantic code/value lookup for Centres.CentreType, based on matching domain names; not enforced by a foreign key.

Data Analysis

Business-critical or frequently joined/filterable columns: Code.

- No null or blank values were found in profiled columns.
- Code values are unique in the current data, but no PK/UNIQUE constraint enforces that condition.
- 2 column(s) use nvarchar(max), limiting type precision and potentially increasing storage/indexing cost.

Data Quality Observations

2 of 2 columns have no null/blank values in the current data. Representative values in the column table are frequency-based and masked for sensitive fields.

Important Findings

- No primary key is defined.
- Application-level relationships exist without FK enforcement.

16. dbo.ClinicalStageList

Table Overview

Purpose inferred from table and column names. Code/value or geographic reference data for clinical stage.

Role classification: Reference / classification.

Table Statistics

Measure	Value
Total records	8
Columns	2
Primary key	None
Enforced foreign-key columns	0
Created	2025-09-15T10:48:18
Last schema modification	2025-09-15T10:48:18

Column Details

Column Name	Data Type	Nullable	Key / Constraint	Default	Description
Code	nvarchar(max)	Yes	None	None	Stored category or classification code. Profile: 8 distinct non-null values. Representative values: 1 (1); 2 (1); 3 (1).
Value	nvarchar(max)	Yes	None	None	Display label or decoded meaning for the associated code. Profile: 8 distinct non-null values. Representative values: Direct Extension (1); Direct extension with regional node involvement (1); Distance metastasis (1).

Relationships

- Probable semantic code/value lookup for TumourTable.ClinicalStage, based on matching domain names; not enforced by a foreign key.

Data Analysis

Business-critical or frequently joined/filterable columns: Code.

- No null or blank values were found in profiled columns.
- Code values are unique in the current data, but no PK/UNIQUE constraint enforces that condition.
- 2 column(s) use nvarchar(max), limiting type precision and potentially increasing storage/indexing cost.

Data Quality Observations

2 of 2 columns have no null/blank values in the current data. Representative values in the column table are frequency-based and masked for sensitive fields.

Important Findings

- No primary key is defined.
- Application-level relationships exist without FK enforcement.

17. dbo.DeletedPatientTable

Table Overview

Purpose inferred from table and column names. Archives deleted patient rows together with deletion and audit metadata.

Role classification: Archive / deletion audit.

Table Statistics

Measure	Value
Total records	25
Columns	37
Primary key	Id
Enforced foreign-key columns	0
Created	2025-09-18T11:46:31
Last schema modification	2025-09-18T11:46:31

Column Details

Column Name	Data Type	Nullable	Key / Constraint	Default	Description
Id	int	No	PK#1; IDENTITY(1,1)	None	Internal row identifier. Profile: range 47 to 1054. Representative values masked (sensitive or identifying field).
REGNO	nvarchar(max)	Yes	None	None	Registry number used as the logical patient link. Representative values masked (sensitive or identifying field).
OBSOLETEFLAGPATIENTTABLE	nvarchar(max)	Yes	None	None	Inferred: stores obsoleteflagpatienttable data. Profile: 25/25 rows are null or blank; 0 distinct non-null values.
PATIENTRECORDID	nvarchar(max)	Yes	None	None	Inferred: stores patientrecordid data. Representative values masked (sensitive or identifying field).
PATIENTUPDATEDBY	nvarchar(max)	Yes	None	None	Inferred: stores patientupdatedby data. Representative values masked (sensitive or identifying field).

Column Name	Data Type	Nullable	Key / Constraint	Default	Description
PATIENTUPDATEDATE	nvarchar(max)	Yes	None	None	Inferred: stores patientupdatedate data. Profile: 10 distinct non-null values. Representative values: 20260530 (10); 20260513 (5); 20260325 (2).
PATIENTRECORDSTATUS	nvarchar(max)	Yes	None	None	Inferred: stores patientrecordstatus data. Profile: 25/25 rows are null or blank; 0 distinct non-null values.
PATIENTCHECKSTATUS	nvarchar(max)	Yes	None	None	Inferred: stores patientcheckstatus data. Profile: 25/25 rows are null or blank; 0 distinct non-null values.
CentreCode	nvarchar(max)	Yes	None	None	Code identifying the participating registry centre. Profile: 9 distinct non-null values. Representative values: C005 (10); C023 (5); C010 (3).
RegistrationNumber	nvarchar(max)	Yes	None	None	Inferred: stores registration number data. Profile: 11/25 rows are null or blank; 15 distinct non-null values. Representative values: 03458999 (1); 12706 (1).
Name	nvarchar(max)	Yes	None	None	Inferred: stores name data. Representative values masked (sensitive or identifying field).
Sex	int	Yes	None	None	Inferred: stores sex data. Profile: 2 distinct non-null values; range 1 to 2. Representative values: 1 (14); 2 (11).
ContactNumber	float	Yes	None	None	Inferred: stores contact number data. Profile: range 458577 to 999999999999. Representative values masked (sensitive or identifying field).
NationalIDCardNumber	nvarchar(max)	Yes	None	None	Inferred: stores national id card number data. Representative values masked (sensitive or identifying field).
State	nvarchar(max)	Yes	None	None	Inferred: stores state data. Profile: 1 distinct non-null values. Representative values: 1 (25).
District	nvarchar(max)	Yes	None	None	Inferred: stores district data. Profile: 1/25 rows are null or blank; 11 distinct non-null values. Representative values: 123 (10); 117 (3); 121 (3).
Block	nvarchar(max)	Yes	None	None	Inferred: stores block data. Profile: 1/25 rows are null or blank; 18 distinct non-null values. Representative values: 12309 (3); 10905 (2); 11705 (2).
Village	nvarchar(max)	Yes	None	None	Inferred: stores village data. Profile: 3/25 rows are null or blank. Representative values masked (sensitive or identifying field).
Address	nvarchar(max)	Yes	None	None	Inferred: stores address data. Profile: 4/25 rows are null or blank. Representative values masked (sensitive or identifying field).
Area	nvarchar(max)	Yes	None	None	Inferred: stores area data. Profile: 3 distinct non-null values. Representative values: 2 (17); 1 (7); 3 (1).
DateOfBirth	nvarchar(max)	Yes	None	None	Inferred: stores date of birth data. Profile: 3/25 rows are null or blank. Representative values masked (sensitive or identifying field).
DayDateOfBirth	nvarchar(max)	Yes	None	None	Inferred: stores day date of birth data. Profile: 3/25 rows are null or blank. Representative values masked (sensitive or identifying field).
MonthDateOfBirth	nvarchar(max)	Yes	None	None	Inferred: stores month date of birth data. Profile: 3/25 rows are null or blank. Representative values masked (sensitive or identifying field).

Column Name	Data Type	Nullable	Key / Constraint	Default	Description
YearDateOfBirth	nvarchar(max)	Yes	None	None	Inferred: stores year date of birth data. Profile: 3/25 rows are null or blank. Representative values masked (sensitive or identifying field).
VitalStatus	nvarchar(max)	Yes	None	None	Inferred: stores vital status data. Profile: 2 distinct non-null values. Representative values: 1 (19); 2 (6).
DateOfDeath	nvarchar(max)	Yes	None	None	Inferred: stores date of death data. Profile: 19/25 rows are null or blank. Representative values masked (sensitive or identifying field).
DayDateOfDeath	nvarchar(max)	Yes	None	None	Inferred: stores day date of death data. Profile: 19/25 rows are null or blank. Representative values masked (sensitive or identifying field).
MonthDateOfDeath	nvarchar(max)	Yes	None	None	Inferred: stores month date of death data. Profile: 19/25 rows are null or blank. Representative values masked (sensitive or identifying field).
YearDateOfDeath	nvarchar(max)	Yes	None	None	Inferred: stores year date of death data. Profile: 19/25 rows are null or blank. Representative values masked (sensitive or identifying field).
AgeAtDeath	int	Yes	None	None	Inferred: stores age at death data. Profile: 19/25 rows are null or blank; 5 distinct non-null values; range 5 to 61. Representative values: 36 (2); 31 (1); 38 (1).
CauseOfDeath	nvarchar(max)	Yes	None	None	Inferred: stores cause of death data. Profile: 19/25 rows are null or blank; 2 distinct non-null values. Representative values: 1 (6).
Remarks	nvarchar(max)	Yes	None	None	Inferred: stores remarks data. Profile: 23/25 rows are null or blank. Representative values masked (sensitive or identifying field).
DEOName	nvarchar(max)	Yes	None	None	Inferred: stores deo name data. Representative values masked (sensitive or identifying field).
DEODate	datetime2(7)	Yes	None	None	Inferred: stores deo date data. Profile: 25 distinct non-null values; range 2026-03-17T12:07:30 to 2026-06-01T10:39:59. Representative values: 2026-03-17 12:07:30.3266667 (1); 2026-03-25 11:41:49.9466667 (1); 2026-03-25 11:55:18.5866667 (1).
LastModifiedByName	nvarchar(max)	Yes	None	None	Inferred: stores last modified by name data. Profile: 24/25 rows are null or blank. Representative values masked (sensitive or identifying field).
LastModifiedDate	datetime2(7)	Yes	None	None	Latest recorded modification timestamp. Profile: 24/25 rows are null or blank; 1 distinct non-null values; range 2026-03-25T11:56:13 to 2026-03-25T11:56:13. Representative values: 2026-03-25 11:56:13.0966667 (1).
DeletedDate	datetime2(7)	Yes	None	None	Deletion/archive timestamp. Profile: 25 distinct non-null values; range 2026-03-25T11:44:40 to 2026-06-18T11:11:27. Representative values: 2026-03-25 11:44:40.9400000 (1); 2026-03-25 11:56:50.8633333 (1); 2026-04-24 16:07:51.6400000 (1).

Relationships

- No enforced or validated logical relationships were identified for this table.

Data Analysis

Business-critical or frequently joined/filterable columns: Id, REGNO, PATIENTRECORDID, PATIENTUPDATEDBY, PATIENTUPDATEDATE, PATIENTRECORDSTATUS, PATIENTCHECKSTATUS, CentreCode, DateOfBirth, DayDateOfBirth, MonthDateOfBirth, YearDateOfBirth.

- Highest null/blank counts: PATIENTRECORDSTATUS 25/25, PATIENTCHECKSTATUS 25/25, OBSOLETEFLAGPATIENTTABLE 25/25, LastModifiedDate 24/25, LastModifiedByName 24/25.
- The primary key prevents duplicate full rows and duplicate key values.
- 30 column(s) use nvarchar(max), limiting type precision and potentially increasing storage/indexing cost.

Data Quality Observations

16 of 37 columns have no null/blank values in the current data. Representative values in the column table are frequency-based and masked for sensitive fields.

Important Findings

- Application-level relationships exist without FK enforcement.

18. dbo.DeletedSourceTable

Table Overview

Purpose inferred from table and column names. Archives deleted source rows together with deletion and audit metadata.

Role classification: Archive / deletion audit.

Table Statistics

Measure	Value
Total records	25
Columns	13
Primary key	Id
Enforced foreign-key columns	0
Created	2025-09-15T10:48:19
Last schema modification	2025-09-15T11:47:24

Column Details

Column Name	Data Type	Nullable	Key / Constraint	Default	Description
-------------	-----------	----------	------------------	---------	-------------

Column Name	Data Type	Nullable	Key / Constraint	Default	Description
Id	int	No	PK#1; IDENTITY(1,1)	None	Internal row identifier. Profile: 25 distinct non-null values; range 328 to 1335. Representative values: 1332 (1); 1333 (1); 1334 (1).
REGNO	nvarchar(max)	Yes	None	None	Registry number used as the logical patient link. Representative values masked (sensitive or identifying field).
TUMOURID	nvarchar(max)	Yes	None	None	Logical tumour identifier. Representative values masked (sensitive or identifying field).
SOURCEID	nvarchar(max)	Yes	None	None	Logical source-record identifier. Representative values masked (sensitive or identifying field).
TUMOURIDSOURCETABLE	nvarchar(max)	Yes	None	None	Tumour key used to link source rows to TumourTable.TUMOURID. Representative values masked (sensitive or identifying field).
SOURCERECORDID	nvarchar(max)	Yes	None	None	Inferred: stores sourcerecordid data. Representative values masked (sensitive or identifying field).
TypeOfSource	nvarchar(max)	Yes	None	None	Inferred: stores type of source data. Profile: 1 distinct non-null values. Representative values: HOSPITAL (25).
SourceCentre	nvarchar(max)	Yes	None	None	Inferred: stores source centre data. Profile: 9 distinct non-null values. Representative values: C005 (10); C023 (5); C010 (3).
CaseFileNumber	nvarchar(max)	Yes	None	None	Inferred: stores case file number data. Profile: 7/25 rows are null or blank. Representative values masked (sensitive or identifying field).
SourceRemarks	nvarchar(max)	Yes	None	None	Inferred: stores source remarks data. Profile: 10/25 rows are null or blank. Representative values masked (sensitive or identifying field).
TumourNumber	nvarchar(max)	Yes	None	None	Inferred: stores tumour number data. Profile: 1 distinct non-null values. Representative values: 1 (25).
SourceNumber	nvarchar(max)	Yes	None	None	Inferred: stores source number data. Profile: 1 distinct non-null values. Representative values: 1 (25).
DeletedDate	datetime2(7)	Yes	None	None	Deletion/archive timestamp. Profile: 25 distinct non-null values; range 2026-03-25T11:44:40 to 2026-06-18T11:11:27. Representative values: 2026-03-25 11:44:40.9233333 (1); 2026-03-25 11:56:50.8466667 (1); 2026-04-24 16:07:51.6233333 (1).

Relationships

- No enforced or validated logical relationships were identified for this table.

Data Analysis

Business-critical or frequently joined/filterable columns: Id, REGNO, TUMOURID, SOURCEID, TUMOURIDSOURCETABLE, SOURCERECORDID, DeletedDate.

- Highest null/blank counts: SourceRemarks 10/25, CaseFileNumber 7/25.
- The primary key prevents duplicate full rows and duplicate key values.

- 11 column(s) use nvarchar(max), limiting type precision and potentially increasing storage/indexing cost.

Data Quality Observations

11 of 13 columns have no null/blank values in the current data. Representative values in the column table are frequency-based and masked for sensitive fields.

Important Findings

- Application-level relationships exist without FK enforcement.

19. dbo.DeletedTumourTable

Table Overview

Purpose inferred from table and column names. Archives deleted tumour rows together with deletion and audit metadata.

Role classification: Archive / deletion audit.

Table Statistics

Measure	Value
Total records	25
Columns	34
Primary key	Id
Enforced foreign-key columns	0
Created	2025-09-15T10:48:20
Last schema modification	2025-11-04T14:59:00

Column Details

Column Name	Data Type	Nullable	Key / Constraint	Default	Description
Id	int	No	PK#1; IDENTITY(1,1)	None	Internal row identifier. Profile: 25 distinct non-null values; range 78 to 1085. Representative values: 1082 (1); 1083 (1); 1084 (1).
REGNO	nvarchar(max)	Yes	None	None	Registry number used as the logical patient link. Representative values masked (sensitive or identifying field).
TUMOURID	nvarchar(max)	Yes	None	None	Logical tumour identifier. Representative values masked (sensitive or identifying field).
RECS	nvarchar(max)	Yes	None	None	Inferred: stores recs data. Profile: 2 distinct non-null values. Representative values: true (17); false (8).

Column Name	Data Type	Nullable	Key / Constraint	Default	Description
CHECKS	nvarchar(max)	Yes	None	None	Inferred: stores checks data. Profile: 2 distinct non-null values. Representative values: true (17); false (8).
MPCODE	nvarchar(max)	Yes	None	None	Inferred: stores mpcode data. Profile: 25/25 rows are null or blank; 1 distinct non-null values.
MPSEQ	nvarchar(max)	Yes	None	None	Inferred: stores mpseq data. Profile: 1 distinct non-null values. Representative values: 0 (25).
MPTOT	nvarchar(max)	Yes	None	None	Inferred: stores mptot data. Profile: 1 distinct non-null values. Representative values: 1 (25).
UPDATE	nvarchar(max)	Yes	None	None	Inferred: stores update data. Profile: 10 distinct non-null values. Representative values: 20260530 (10); 20260513 (5); 20260325 (2).
OBSOLETEFLAGTUMOURTABLE	nvarchar(max)	Yes	None	None	Inferred: stores obsoleteflagtumourtable data. Profile: 1 distinct non-null values. Representative values: 0 (25).
PATIENTIDTUMOURTABLE	nvarchar(max)	Yes	None	None	Patient registry key used by the application to link tumour rows to PatientTable.REGNO. Representative values masked (sensitive or identifying field).
PATIENTRECORDIDTUMOURTABLE	nvarchar(max)	Yes	None	None	Inferred: stores patientrecordidtumourtable data. Representative values masked (sensitive or identifying field).
TUMOURUPDATEDBY	nvarchar(max)	Yes	None	None	Inferred: stores tumourupdatedby data. Representative values masked (sensitive or identifying field).
TUMOURUNDUPLICATIONSTATUS	nvarchar(max)	Yes	None	None	Inferred: stores tumourunduplicationstatus data. Profile: 25/25 rows are null or blank; 1 distinct non-null values.
Age	int	Yes	None	None	Inferred: stores age data. Profile: 6/25 rows are null or blank; 18 distinct non-null values; range 4 to 74. Representative values: 35 (2); 27 (1); 28 (1).
DateOfDiagnosis	nvarchar(max)	Yes	None	None	Inferred: stores date of diagnosis data. Profile: 6/25 rows are null or blank; 17 distinct non-null values. Representative values: 20240101 (2); 20250327 (2); 20171220 (1).
DayDateOfDiagnosis	nvarchar(max)	Yes	None	None	Inferred: stores day date of diagnosis data. Profile: 6/25 rows are null or blank; 13 distinct non-null values. Representative values: 9 (3); 1 (2).
MonthDateOfDiagnosis	nvarchar(max)	Yes	None	None	Inferred: stores month date of diagnosis data. Profile: 6/25 rows are null or blank; 11 distinct non-null values. Representative values: 1 (5); 12 (4).
YearDateOfDiagnosis	nvarchar(max)	Yes	None	None	Inferred: stores year date of diagnosis data. Profile: 6/25 rows are null or blank; 8 distinct non-null values. Representative values: 2025 (8); 2024 (4).
BasisOfDiagnosis	nvarchar(max)	Yes	None	None	Inferred: stores basis of diagnosis data. Profile: 6/25 rows are null or blank; 6 distinct non-null values. Representative values: 1 (6); 7 (6).
Site	nvarchar(max)	Yes	None	None	Inferred: stores site data. Profile: 6/25 rows are null or blank; 11 distinct non-null values. Representative values: 16 (4); 42 (4).
PrimarySite	nvarchar(max)	Yes	None	None	Inferred: stores primary site data. Profile: 6/25 rows are null or blank; 14 distinct non-null values. Representative values: 169 (3); 421 (3).

Column Name	Data Type	Nullable	Key / Constraint	Default	Description
SubSite	nvarchar(max)	Yes	None	None	Inferred: stores sub site data. Profile: 6/25 rows are null or blank; 14 distinct non-null values. Representative values: 169 (3); 421 (3).
Histology	nvarchar(max)	Yes	None	None	Inferred: stores histology data. Profile: 6/25 rows are null or blank; 13 distinct non-null values. Representative values: 8010 - Carcinoma, NOS (5); 9863 - Chronic myeloid leukemia, NOS (3).
GradeCellType	nvarchar(max)	Yes	None	None	Inferred: stores grade cell type data. Profile: 11/25 rows are null or blank; 5 distinct non-null values. Representative values: 9 (6); 3 (4).
Behaviour	nvarchar(max)	Yes	None	None	Inferred: stores behaviour data. Profile: 6/25 rows are null or blank; 3 distinct non-null values. Representative values: 3 (18); 0 (1).
ICD10	nvarchar(max)	Yes	None	None	ICD-10 cancer diagnosis/site code. Profile: 6/25 rows are null or blank; 15 distinct non-null values. Representative values: C921 (3); C169 (2).
ICCCCode	nvarchar(max)	Yes	None	None	Inferred: stores iccc code data. Profile: 6/25 rows are null or blank; 8 distinct non-null values. Representative values: 11f (11); 1c (3).
Notes	nvarchar(max)	Yes	None	None	Inferred: stores notes data. Profile: 21/25 rows are null or blank. Representative values masked (sensitive or identifying field).
Treatment	nvarchar(max)	Yes	None	None	Inferred: stores treatment data. Profile: 6/25 rows are null or blank; 8 distinct non-null values. Representative values: 3 (11); 6 (3).
TreatmentStatus	nvarchar(max)	Yes	None	None	Inferred: stores treatment status data. Profile: 6/25 rows are null or blank; 3 distinct non-null values. Representative values: 2 (14); 1 (5).
TumourNumber	nvarchar(max)	Yes	None	None	Inferred: stores tumour number data. Profile: 1 distinct non-null values. Representative values: 1 (25).
DeletedDate	datetime2(7)	Yes	None	None	Deletion/archive timestamp. Profile: 25 distinct non-null values; range 2026-03-25T11:44:40 to 2026-06-18T11:11:27. Representative values: 2026-03-25 11:44:40.9233333 (1); 2026-03-25 11:56:50.8633333 (1); 2026-04-24 16:07:51.6400000 (1).
ClinicalStage	nvarchar(max)	Yes	None	None	Inferred: stores clinical stage data. Profile: 7/25 rows are null or blank; 8 distinct non-null values. Representative values: 6 (5); 3 (4).

Relationships

- No enforced or validated logical relationships were identified for this table.

Data Analysis

Business-critical or frequently joined/filterable columns: Id, REGNO, TUMOURID, MPCODE, UPDATE, TUMOURUPDATEDBY, TUMOURUNDUPLICATIONSTATUS, DateOfDiagnosis, DayDateOfDiagnosis, MonthDateOfDiagnosis, YearDateOfDiagnosis, ICCCCode.

- Highest null/blank counts: TUMOURUNDUPLICATIONSTATUS 25/25, MPCODE 25/25, Notes 21/25, GradeCellType 11/25, ClinicalStage 7/25.

- The primary key prevents duplicate full rows and duplicate key values.
- 31 column(s) use nvarchar(max), limiting type precision and potentially increasing storage/indexing cost.

Data Quality Observations

14 of 34 columns have no null/blank values in the current data. Representative values in the column table are frequency-based and masked for sensitive fields.

Important Findings

- Application-level relationships exist without FK enforcement.

20. dbo.DiagnosisAtRegistrationList

Table Overview

Purpose inferred from table and column names. Code/value or geographic reference data for diagnosis at registration.

Role classification: Reference / classification.

Table Statistics

Measure	Value
Total records	0
Columns	2
Primary key	None
Enforced foreign-key columns	0
Created	2025-09-15T10:48:22
Last schema modification	2025-09-15T10:48:22

Column Details

Column Name	Data Type	Nullable	Key / Constraint	Default	Description
Code	nvarchar(max)	Yes	None	None	Stored category or classification code.
Value	nvarchar(max)	Yes	None	None	Display label or decoded meaning for the associated code.

Relationships

- No enforced or validated logical relationships were identified for this table.

Data Analysis

Business-critical or frequently joined/filterable columns: Code.

- The table is empty at the profiling timestamp; value distributions and duplicates cannot be assessed.
- 2 column(s) use nvarchar(max), limiting type precision and potentially increasing storage/indexing cost.

Data Quality Observations

Confirmed: no rows are present; completeness, consistency and representative-value checks are not applicable.

Important Findings

- No primary key is defined.
- Application-level relationships exist without FK enforcement.
- The table is inactive/empty at the profiling timestamp; confirm whether it is planned, legacy or awaiting data.

21. dbo.DistrictList

Table Overview

Purpose inferred from table and column names. District-level geographic master keyed to state codes.

Role classification: Reference / classification.

Table Statistics

Measure	Value
Total records	30
Columns	4
Primary key	Id
Enforced foreign-key columns	0
Created	2025-09-15T10:48:22
Last schema modification	2025-09-15T10:48:22

Column Details

Column Name	Data Type	Nullable	Key / Constraint	Default	Description
-------------	-----------	----------	------------------	---------	-------------

Column Name	Data Type	Nullable	Key / Constraint	Default	Description
Id	int	No	PK#1; IDENTITY(1,1)	None	Internal row identifier. Profile: 30 distinct non-null values; range 2 to 31. Representative values: 10 (1); 11 (1); 12 (1).
StateId	nvarchar(max)	Yes	None	None	State master code. Profile: 1 distinct non-null values. Representative values: 1 (30).
DistrictId	nvarchar(max)	Yes	None	None	District master code. Profile: 30 distinct non-null values. Representative values: 101 (1); 102 (1); 103 (1).
DistrictName	nvarchar(max)	Yes	None	None	Inferred: stores district name data. Profile: 30 distinct non-null values. Representative values: Angul (1); Balangir (1); Balasore (1).

Relationships

- Logical child of StateList and parent of BlockList; all current block district codes matched.

Data Analysis

Business-critical or frequently joined/filterable columns: Id, StateId, DistrictId.

- No null or blank values were found in profiled columns.
- The primary key prevents duplicate full rows and duplicate key values.
- 3 column(s) use nvarchar(max), limiting type precision and potentially increasing storage/indexing cost.

Data Quality Observations

4 of 4 columns have no null/blank values in the current data. Representative values in the column table are frequency-based and masked for sensitive fields.

Important Findings

- Application-level relationships exist without FK enforcement.

22. dbo.DurationDateOfDiagnosisToDateOfDeathList

Table Overview

Purpose inferred from table and column names. Code/value or geographic reference data for duration date of diagnosis to date of death.

Role classification: Reference / classification.

Table Statistics

Measure	Value
Total records	0

Measure	Value
Columns	2
Primary key	None
Enforced foreign-key columns	0
Created	2025-09-15T10:48:23
Last schema modification	2025-09-15T10:48:23

Column Details

Column Name	Data Type	Nullable	Key / Constraint	Default	Description
Code	nvarchar(max)	Yes	None	None	Stored category or classification code.
Value	nvarchar(max)	Yes	None	None	Display label or decoded meaning for the associated code.

Relationships

- No enforced or validated logical relationships were identified for this table.

Data Analysis

Business-critical or frequently joined/filterable columns: Code.

- The table is empty at the profiling timestamp; value distributions and duplicates cannot be assessed.
- 2 column(s) use nvarchar(max), limiting type precision and potentially increasing storage/indexing cost.

Data Quality Observations

Confirmed: no rows are present; completeness, consistency and representative-value checks are not applicable.

Important Findings

- No primary key is defined.
- Application-level relationships exist without FK enforcement.
- The table is inactive/empty at the profiling timestamp; confirm whether it is planned, legacy or awaiting data.

23. dbo.EthnicGroupList

Table Overview

Purpose inferred from table and column names. Code/value or geographic reference data for ethnic group.

Role classification: Reference / classification.

Table Statistics

Measure	Value
Total records	0
Columns	2
Primary key	None
Enforced foreign-key columns	0
Created	2025-09-15T10:48:23
Last schema modification	2025-09-15T10:48:23

Column Details

Column Name	Data Type	Nullable	Key / Constraint	Default	Description
Code	nvarchar(max)	Yes	None	None	Stored category or classification code.
Value	nvarchar(max)	Yes	None	None	Display label or decoded meaning for the associated code.

Relationships

- No enforced or validated logical relationships were identified for this table.

Data Analysis

Business-critical or frequently joined/filterable columns: Code.

- The table is empty at the profiling timestamp; value distributions and duplicates cannot be assessed.
- 2 column(s) use nvarchar(max), limiting type precision and potentially increasing storage/indexing cost.

Data Quality Observations

Confirmed: no rows are present; completeness, consistency and representative-value checks are not applicable.

Important Findings

- No primary key is defined.
- Application-level relationships exist without FK enforcement.
- The table is inactive/empty at the profiling timestamp; confirm whether it is planned, legacy or awaiting data.

24. dbo.FamilyHistoryOfCancerList

Table Overview

Purpose inferred from table and column names. Code/value or geographic reference data for family history of cancer.

Role classification: Reference / classification.

Table Statistics

Measure	Value
Total records	0
Columns	2
Primary key	None
Enforced foreign-key columns	0
Created	2025-09-15T10:48:23
Last schema modification	2025-09-15T10:48:23

Column Details

Column Name	Data Type	Nullable	Key / Constraint	Default	Description
Code	nvarchar(max)	Yes	None	None	Stored category or classification code.
Value	nvarchar(max)	Yes	None	None	Display label or decoded meaning for the associated code.

Relationships

- No enforced or validated logical relationships were identified for this table.

Data Analysis

Business-critical or frequently joined/filterable columns: Code.

- The table is empty at the profiling timestamp; value distributions and duplicates cannot be assessed.

- 2 column(s) use nvarchar(max), limiting type precision and potentially increasing storage/indexing cost.

Data Quality Observations

Confirmed: no rows are present; completeness, consistency and representative-value checks are not applicable.

Important Findings

- No primary key is defined.
- Application-level relationships exist without FK enforcement.
- The table is inactive/empty at the profiling timestamp; confirm whether it is planned, legacy or awaiting data.

25. dbo.GradeList

Table Overview

Purpose inferred from table and column names. Code/value or geographic reference data for grade.

Role classification: Reference / classification.

Table Statistics

Measure	Value
Total records	9
Columns	2
Primary key	None
Enforced foreign-key columns	0
Created	2025-09-15T10:48:23
Last schema modification	2025-09-15T10:48:23

Column Details

Column Name	Data Type	Nullable	Key / Constraint	Default	Description
Code	nvarchar(max)	Yes	None	None	Stored category or classification code. Profile: 9 distinct non-null values. Representative values: 1 (1); 2 (1); 3 (1).
Value	nvarchar(max)	Yes	None	None	Display label or decoded meaning for the associated code. Profile: 9 distinct non-null values. Representative values: B-cell (1); Grade I - Well diff. (1); Grade II - Mod. diff. (1).

Relationships

- Probable semantic code/value lookup for TumourTable.GradeCellType, based on matching domain names; not enforced by a foreign key.

Data Analysis

Business-critical or frequently joined/filterable columns: Code.

- No null or blank values were found in profiled columns.
- Code values are unique in the current data, but no PK/UNIQUE constraint enforces that condition.
- 2 column(s) use nvarchar(max), limiting type precision and potentially increasing storage/indexing cost.

Data Quality Observations

2 of 2 columns have no null/blank values in the current data. Representative values in the column table are frequency-based and masked for sensitive fields.

Important Findings

- No primary key is defined.
- Application-level relationships exist without FK enforcement.

26. dbo.HistologyList

Table Overview

Purpose inferred from table and column names. Code/value or geographic reference data for histology.

Role classification: Reference / classification.

Table Statistics

Measure	Value
Total records	557
Columns	2
Primary key	None
Enforced foreign-key columns	0
Created	2025-09-15T10:48:23
Last schema modification	2025-09-15T10:48:23

Column Details

Column Name	Data Type	Nullable	Key / Constraint	Default	Description
Code	nvarchar(max)	Yes	None	None	Stored category or classification code. Profile: 557 distinct non-null values. Representative values: 8000 (1); 8001 (1); 8002 (1).
Value	nvarchar(max)	Yes	None	None	Display label or decoded meaning for the associated code. Profile: 557 distinct non-null values. Representative values: 8000 - Neoplasm, malignant (1); 8001 - Tumor cells, malignant (1); 8002 - Malignant tumor, small cell type (1).

Relationships

- Probable semantic code/value lookup for TumourTable.Histology, based on matching domain names; not enforced by a foreign key.

Data Analysis

Business-critical or frequently joined/filterable columns: Code.

- No null or blank values were found in profiled columns.
- Code values are unique in the current data, but no PK/UNIQUE constraint enforces that condition.
- 2 column(s) use nvarchar(max), limiting type precision and potentially increasing storage/indexing cost.

Data Quality Observations

2 of 2 columns have no null/blank values in the current data. Representative values in the column table are frequency-based and masked for sensitive fields.

Important Findings

- No primary key is defined.
- Application-level relationships exist without FK enforcement.

27. dbo.ICCCMaster

Table Overview

Purpose inferred from table and column names. Intended International Classification of Childhood Cancer reference structure; currently empty.

Role classification: Reference / classification.

Table Statistics

Measure	Value
---------	-------

Measure	Value
Total records	0
Columns	10
Primary key	Id
Enforced foreign-key columns	0
Created	2025-09-15T10:48:23
Last schema modification	2025-09-15T10:48:23

Column Details

Column Name	Data Type	Nullable	Key / Constraint	Default	Description
Id	int	No	PK#1; IDENTITY(1,1)	None	Internal row identifier.
Code1	nvarchar(max)	Yes	None	None	Inferred: stores code1 data.
Code1Description	nvarchar(max)	Yes	None	None	Inferred: stores code1 description data.
Code2	nvarchar(max)	Yes	None	None	Inferred: stores code2 data.
Code2Description	nvarchar(max)	Yes	None	None	Inferred: stores code2 description data.
Code3	nvarchar(max)	Yes	None	None	Inferred: stores code3 data.
Code3Description	nvarchar(max)	Yes	None	None	Inferred: stores code3 description data.
Histology	nvarchar(max)	Yes	None	None	Inferred: stores histology data.
Topography	nvarchar(max)	Yes	None	None	Inferred: stores topography data.
ExtendedClassification	nvarchar(max)	Yes	None	None	Inferred: stores extended classification data.

Relationships

- No enforced or validated logical relationships were identified for this table.

Data Analysis

Business-critical or frequently joined/filterable columns: Id.

- The table is empty at the profiling timestamp; value distributions and duplicates cannot be assessed.
- The primary key prevents duplicate full rows and duplicate key values.
- 9 column(s) use nvarchar(max), limiting type precision and potentially increasing storage/indexing cost.

Data Quality Observations

Confirmed: no rows are present; completeness, consistency and representative-value checks are not applicable.

Important Findings

- Application-level relationships exist without FK enforcement.
- The table is inactive/empty at the profiling timestamp; confirm whether it is planned, legacy or awaiting data.

28. dbo.ICD10Group

Table Overview

Confirmed by schema/application use. Maps normalized ICD-10 codes to grouped cancer-site labels used by incidence and mortality queries.

Role classification: Reference / classification.

Table Statistics

Measure	Value
Total records	87
Columns	2
Primary key	None
Enforced foreign-key columns	0
Created	2025-09-15T10:48:23
Last schema modification	2025-09-15T10:48:23

Column Details

Column Name	Data Type	Nullable	Key / Constraint	Default	Description
Code	nvarchar(max)	No	None	None	Stored category or classification code. Profile: 87 distinct non-null values. Representative values: C00 (1); C01 (1); C02 (1).
Value	nvarchar(max)	No	None	None	Display label or decoded meaning for the associated code. Profile: 59 distinct non-null values. Representative values: Others and unspecified (7); Non-Hodgkin lymphoma (6); Mouth (4).

Relationships

- Application query lookup for normalized TumourTable.ICD10 values; 11 populated tumour codes were unmapped and 2 failed the expected Cnn pattern.

Data Analysis

Business-critical or frequently joined/filterable columns: Code.

- No null or blank values were found in profiled columns.
- Code values are unique in the current data, but no PK/UNIQUE constraint enforces that condition.
- Code is unique across 87 rows; Value has 59 distinct labels, consistent with multiple codes mapping to common grouped sites.
- 2 column(s) use nvarchar(max), limiting type precision and potentially increasing storage/indexing cost.

Data Quality Observations

2 of 2 columns have no null/blank values in the current data. Representative values in the column table are frequency-based and masked for sensitive fields.

Important Findings

- No primary key is defined.

29. dbo.LateralityList

Table Overview

Purpose inferred from table and column names. Code/value or geographic reference data for laterality.

Role classification: Reference / classification.

Table Statistics

Measure	Value
Total records	0
Columns	2
Primary key	None
Enforced foreign-key columns	0
Created	2025-09-15T10:48:25
Last schema modification	2025-09-15T10:48:25

Column Details

Column Name	Data Type	Nullable	Key / Constraint	Default	Description
Code	nvarchar(max)	Yes	None	None	Stored category or classification code.
Value	nvarchar(max)	Yes	None	None	Display label or decoded meaning for the associated code.

Relationships

- No enforced or validated logical relationships were identified for this table.

Data Analysis

Business-critical or frequently joined/filterable columns: Code.

- The table is empty at the profiling timestamp; value distributions and duplicates cannot be assessed.
- 2 column(s) use nvarchar(max), limiting type precision and potentially increasing storage/indexing cost.

Data Quality Observations

Confirmed: no rows are present; completeness, consistency and representative-value checks are not applicable.

Important Findings

- No primary key is defined.
- Application-level relationships exist without FK enforcement.
- The table is inactive/empty at the profiling timestamp; confirm whether it is planned, legacy or awaiting data.

30. dbo.Lymph_Leuk

Table Overview

Purpose inferred from table and column names. Intended lymphoma/leukaemia classification lookup; currently empty.

Role classification: Reference / classification.

Table Statistics

Measure	Value
Total records	0
Columns	2
Primary key	None
Enforced foreign-key columns	0
Created	2025-09-15T10:48:25
Last schema modification	2025-09-15T10:48:25

Column Details

Column Name	Data Type	Nullable	Key / Constraint	Default	Description
Histology	nvarchar(max)	No	None	None	Inferred: stores histology data.
ICD10	nvarchar(max)	No	None	None	ICD-10 cancer diagnosis/site code.

Relationships

- No enforced or validated logical relationships were identified for this table.

Data Analysis

Business-critical or frequently joined/filterable columns: No specific critical column was identifiable from keys and names..

- The table is empty at the profiling timestamp; value distributions and duplicates cannot be assessed.
- 2 column(s) use nvarchar(max), limiting type precision and potentially increasing storage/indexing cost.

Data Quality Observations

Confirmed: no rows are present; completeness, consistency and representative-value checks are not applicable.

Important Findings

- No primary key is defined.
- Application-level relationships exist without FK enforcement.
- The table is inactive/empty at the profiling timestamp; confirm whether it is planned, legacy or awaiting data.

31. dbo.MaritalStatusList

Table Overview

Purpose inferred from table and column names. Code/value or geographic reference data for marital status.

Role classification: Reference / classification.

Table Statistics

Measure	Value
Total records	0

Measure	Value
Columns	2
Primary key	None
Enforced foreign-key columns	0
Created	2025-09-15T10:48:25
Last schema modification	2025-09-15T10:48:25

Column Details

Column Name	Data Type	Nullable	Key / Constraint	Default	Description
Code	nvarchar(max)	Yes	None	None	Stored category or classification code.
Value	nvarchar(max)	Yes	None	None	Display label or decoded meaning for the associated code.

Relationships

- No enforced or validated logical relationships were identified for this table.

Data Analysis

Business-critical or frequently joined/filterable columns: Code.

- The table is empty at the profiling timestamp; value distributions and duplicates cannot be assessed.
- 2 column(s) use nvarchar(max), limiting type precision and potentially increasing storage/indexing cost.

Data Quality Observations

Confirmed: no rows are present; completeness, consistency and representative-value checks are not applicable.

Important Findings

- No primary key is defined.
- Application-level relationships exist without FK enforcement.
- The table is inactive/empty at the profiling timestamp; confirm whether it is planned, legacy or awaiting data.

32. dbo.Meso_Mela

Table Overview

Purpose inferred from table and column names. Intended mesothelioma/melanoma classification lookup; currently empty.

Role classification: Reference / classification.

Table Statistics

Measure	Value
Total records	0
Columns	3
Primary key	None
Enforced foreign-key columns	0
Created	2025-09-15T10:48:25
Last schema modification	2025-09-15T10:48:25

Column Details

Column Name	Data Type	Nullable	Key / Constraint	Default	Description
Site	nvarchar(max)	No	None	None	Inferred: stores site data.
Histology	nvarchar(max)	Yes	None	None	Inferred: stores histology data.
ICD10	nvarchar(max)	No	None	None	ICD-10 cancer diagnosis/site code.

Relationships

- No enforced or validated logical relationships were identified for this table.

Data Analysis

Business-critical or frequently joined/filterable columns: No specific critical column was identifiable from keys and names..

- The table is empty at the profiling timestamp; value distributions and duplicates cannot be assessed.
- 3 column(s) use nvarchar(max), limiting type precision and potentially increasing storage/indexing cost.

Data Quality Observations

Confirmed: no rows are present; completeness, consistency and representative-value checks are not applicable.

Important Findings

- No primary key is defined.
- Application-level relationships exist without FK enforcement.
- The table is inactive/empty at the profiling timestamp; confirm whether it is planned, legacy or awaiting data.

33. dbo.MList

Table Overview

Purpose inferred from table and column names. Code/value or geographic reference data for m.

Role classification: Reference / classification.

Table Statistics

Measure	Value
Total records	0
Columns	2
Primary key	None
Enforced foreign-key columns	0
Created	2025-09-15T10:48:25
Last schema modification	2025-09-15T10:48:25

Column Details

Column Name	Data Type	Nullable	Key / Constraint	Default	Description
Code	nvarchar(max)	Yes	None	None	Stored category or classification code.
Value	nvarchar(max)	Yes	None	None	Display label or decoded meaning for the associated code.

Relationships

- No enforced or validated logical relationships were identified for this table.

Data Analysis

Business-critical or frequently joined/filterable columns: Code.

- The table is empty at the profiling timestamp; value distributions and duplicates cannot be assessed.
- 2 column(s) use nvarchar(max), limiting type precision and potentially increasing storage/indexing cost.

Data Quality Observations

Confirmed: no rows are present; completeness, consistency and representative-value checks are not applicable.

Important Findings

- No primary key is defined.
- Application-level relationships exist without FK enforcement.
- The table is inactive/empty at the profiling timestamp; confirm whether it is planned, legacy or awaiting data.

34. dbo.NList

Table Overview

Purpose inferred from table and column names. Code/value or geographic reference data for n.

Role classification: Reference / classification.

Table Statistics

Measure	Value
Total records	0
Columns	2
Primary key	None
Enforced foreign-key columns	0
Created	2025-09-15T10:48:25
Last schema modification	2025-09-15T10:48:25

Column Details

Column Name	Data Type	Nullable	Key / Constraint	Default	Description
Code	nvarchar(max)	Yes	None	None	Stored category or classification code.

Column Name	Data Type	Nullable	Key / Constraint	Default	Description
Value	nvarchar(max)	Yes	None	None	Display label or decoded meaning for the associated code.

Relationships

- No enforced or validated logical relationships were identified for this table.

Data Analysis

Business-critical or frequently joined/filterable columns: Code.

- The table is empty at the profiling timestamp; value distributions and duplicates cannot be assessed.
- 2 column(s) use nvarchar(max), limiting type precision and potentially increasing storage/indexing cost.

Data Quality Observations

Confirmed: no rows are present; completeness, consistency and representative-value checks are not applicable.

Important Findings

- No primary key is defined.
- Application-level relationships exist without FK enforcement.
- The table is inactive/empty at the profiling timestamp; confirm whether it is planned, legacy or awaiting data.

35. dbo.OccupationList

Table Overview

Purpose inferred from table and column names. Code/value or geographic reference data for occupation.

Role classification: Reference / classification.

Table Statistics

Measure	Value
Total records	0
Columns	2
Primary key	None

Measure	Value
Enforced foreign-key columns	0
Created	2025-09-15T10:48:25
Last schema modification	2025-09-15T10:48:25

Column Details

Column Name	Data Type	Nullable	Key / Constraint	Default	Description
Code	nvarchar(max)	Yes	None	None	Stored category or classification code.
Value	nvarchar(max)	Yes	None	None	Display label or decoded meaning for the associated code.

Relationships

- No enforced or validated logical relationships were identified for this table.

Data Analysis

Business-critical or frequently joined/filterable columns: Code.

- The table is empty at the profiling timestamp; value distributions and duplicates cannot be assessed.
- 2 column(s) use nvarchar(max), limiting type precision and potentially increasing storage/indexing cost.

Data Quality Observations

Confirmed: no rows are present; completeness, consistency and representative-value checks are not applicable.

Important Findings

- No primary key is defined.
- Application-level relationships exist without FK enforcement.
- The table is inactive/empty at the profiling timestamp; confirm whether it is planned, legacy or awaiting data.

36. dbo.PatientFile

Table Overview

Confirmed by schema/application use. Stores file metadata for documents attached logically to tumour records; file contents are not stored in this table.

Role classification: Core / transactional.

Table Statistics

Measure	Value
Total records	1,349
Columns	8
Primary key	Id
Enforced foreign-key columns	0
Created	2025-10-06T16:47:54
Last schema modification	2025-10-07T16:02:52

Column Details

Column Name	Data Type	Nullable	Key / Constraint	Default	Description
Id	int	No	PK#1; IDENTITY(1,1)	None	Internal row identifier. Profile: range 465 to 6289. Representative values masked (sensitive or identifying field).
TumourId	nvarchar(max)	Yes	None	None	Inferred: stores tumour id data. Representative values masked (sensitive or identifying field).
FileName	nvarchar(max)	Yes	None	None	Inferred: stores file name data. Profile: 1,294 distinct non-null values. Representative values: Godabari Sahu (Udala).pdf (3); Jugala Kishore Das.pdf (3); AHALYA MAHANI.2025.BLS.jpeg (2).
FilePath	nvarchar(max)	Yes	None	None	Inferred: stores file path data. Representative values masked (sensitive or identifying field).
ContentType	nvarchar(max)	Yes	None	None	MIME media type for the referenced file. Profile: 3 distinct non-null values. Representative values: application/pdf (997); image/jpeg (271); image/png (81).
FileSize	bigint	No	None	None	Recorded file size in bytes. Profile: 1,290 distinct non-null values; range 44502 to 20560072. Representative values: 3963569 (3); 767389 (3); 10556273 (2).
UploadedDate	datetime2(7)	No	None	None	File metadata upload timestamp. Profile: 1,349 distinct non-null values; range 2026-03-07T10:52:42 to 2026-07-10T23:56:29. Representative values: 2026-03-07 10:52:42.7459680 (1); 2026-03-12 11:26:07.4227227 (1); 2026-03-12 12:17:02.0284383 (1).
FileNumber	nvarchar(max)	Yes	None	None	Inferred: stores file number data. Representative values masked (sensitive or identifying field).

Relationships

- Validated logical child of TumourTable through TumourId; all 1,349 current rows matched.

Data Analysis

Business-critical or frequently joined/filterable columns: Id, TumourId, UploadedDate.

- No null or blank values were found in profiled columns.
- The primary key prevents duplicate full rows and duplicate key values.
- All 1,349 TumourId values matched a TumourTable.TUMOURID.
- 5 column(s) use nvarchar(max), limiting type precision and potentially increasing storage/indexing cost.

Data Quality Observations

8 of 8 columns have no null/blank values in the current data. Representative values in the column table are frequency-based and masked for sensitive fields.

Important Findings

- Application-level relationships exist without FK enforcement.

37. dbo.PatientTable

Table Overview

Confirmed by schema/application use. Stores the active patient-level cancer registry record and demographic/vital-status attributes.

Role classification: Core / transactional.

Table Statistics

Measure	Value
Total records	1,450
Columns	36
Primary key	Id
Enforced foreign-key columns	0
Created	2025-09-16T15:48:38
Last schema modification	2025-09-16T15:48:38

Column Details

Column Name	Data Type	Nullable	Key / Constraint	Default	Description
Id	int	No	PK#1; IDENTITY(1,1)	None	Internal row identifier. Profile: range 1135 to 7975. Representative values masked (sensitive or identifying field).

Column Name	Data Type	Nullable	Key / Constraint	Default	Description
REGNO	nvarchar(max)	Yes	None	None	Registry number used as the logical patient link. Representative values masked (sensitive or identifying field).
OBSOLETEFLAGPATIENTTABLE	nvarchar(max)	Yes	None	None	Inferred: stores obsoleteflagpatienttable data. Profile: 1,450/1,450 rows are null or blank; 0 distinct non-null values.
PATIENTRECORDID	nvarchar(max)	Yes	None	None	Inferred: stores patientrecordid data. Representative values masked (sensitive or identifying field).
PATIENTUPDATEDBY	nvarchar(max)	Yes	None	None	Inferred: stores patientupdatedby data. Representative values masked (sensitive or identifying field).
PATIENTUPDATEDDATE	nvarchar(max)	Yes	None	None	Inferred: stores patientupdateddate data. Profile: 101 distinct non-null values. Representative values: 20260317 (57); 20260618 (54); 20260704 (53).
PATIENTRECORDSTATUS	nvarchar(max)	Yes	None	None	Inferred: stores patientrecordstatus data. Profile: 1,450/1,450 rows are null or blank; 0 distinct non-null values.
PATIENTCHECKSTATUS	nvarchar(max)	Yes	None	None	Inferred: stores patientcheckstatus data. Profile: 1,450/1,450 rows are null or blank; 0 distinct non-null values.
CentreCode	nvarchar(max)	Yes	None	None	Code identifying the participating registry centre. Profile: 30 distinct non-null values. Representative values: C002 (264); C026 (203); C006 (121).
RegistrationNumber	nvarchar(max)	Yes	None	None	Inferred: stores registration number data. Profile: 1,202/1,450 rows are null or blank; 246 distinct non-null values. Representative values: 2025013032 (2); 2506130128 (2).
Name	nvarchar(max)	Yes	None	None	Inferred: stores name data. Representative values masked (sensitive or identifying field).
Sex	int	Yes	None	None	Inferred: stores sex data. Profile: 2 distinct non-null values; range 1 to 2. Representative values: 2 (794); 1 (656).
ContactNumber	float	Yes	None	None	Inferred: stores contact number data. Profile: range 8667476 to 999999999999. Representative values masked (sensitive or identifying field).
NationalIDCardNumber	nvarchar(max)	Yes	None	None	Inferred: stores national id card number data. Representative values masked (sensitive or identifying field).
State	nvarchar(max)	Yes	None	None	Inferred: stores state data. Profile: 1 distinct non-null values. Representative values: 1 (1,450).
District	nvarchar(max)	Yes	None	None	Inferred: stores district data. Profile: 30 distinct non-null values. Representative values: 122 (265); 115 (203); 105 (121).
Block	nvarchar(max)	Yes	None	None	Inferred: stores block data. Profile: 1/1,450 rows are null or blank; 254 distinct non-null values. Representative values: 11505 (47); 10302 (45); 12204 (33).
Village	nvarchar(max)	Yes	None	None	Inferred: stores village data. Profile: 79/1,450 rows are null or blank. Representative values masked (sensitive or identifying field).
Address	nvarchar(max)	Yes	None	None	Inferred: stores address data. Profile: 248/1,450 rows are null or blank. Representative values masked (sensitive or identifying field).

Column Name	Data Type	Nullable	Key / Constraint	Default	Description
Area	nvarchar(max)	Yes	None	None	Inferred: stores area data. Profile: 3 distinct non-null values. Representative values: 2 (1,059); 1 (365); 3 (26).
DateOfBirth	nvarchar(max)	Yes	None	None	Inferred: stores date of birth data. Profile: 37/1,450 rows are null or blank. Representative values masked (sensitive or identifying field).
DayDateOfBirth	nvarchar(max)	Yes	None	None	Inferred: stores day date of birth data. Profile: 37/1,450 rows are null or blank. Representative values masked (sensitive or identifying field).
MonthDateOfBirth	nvarchar(max)	Yes	None	None	Inferred: stores month date of birth data. Profile: 36/1,450 rows are null or blank. Representative values masked (sensitive or identifying field).
YearDateOfBirth	nvarchar(max)	Yes	None	None	Inferred: stores year date of birth data. Profile: 36/1,450 rows are null or blank. Representative values masked (sensitive or identifying field).
VitalStatus	nvarchar(max)	Yes	None	None	Inferred: stores vital status data. Profile: 3 distinct non-null values. Representative values: 1 (1,123); 2 (239); 9 (88).
DateOfDeath	nvarchar(max)	Yes	None	None	Inferred: stores date of death data. Profile: 1,211/1,450 rows are null or blank. Representative values masked (sensitive or identifying field).
DayDateOfDeath	nvarchar(max)	Yes	None	None	Inferred: stores day date of death data. Profile: 1,211/1,450 rows are null or blank. Representative values masked (sensitive or identifying field).
MonthDateOfDeath	nvarchar(max)	Yes	None	None	Inferred: stores month date of death data. Profile: 1,211/1,450 rows are null or blank. Representative values masked (sensitive or identifying field).
YearDateOfDeath	nvarchar(max)	Yes	None	None	Inferred: stores year date of death data. Profile: 1,211/1,450 rows are null or blank. Representative values masked (sensitive or identifying field).
AgeAtDeath	int	Yes	None	None	Inferred: stores age at death data. Profile: 1,210/1,450 rows are null or blank; 62 distinct non-null values; range 1 to 89. Representative values: 56 (14); 61 (11); 54 (10).
CauseOfDeath	nvarchar(max)	Yes	None	None	Inferred: stores cause of death data. Profile: 1,212/1,450 rows are null or blank; 4 distinct non-null values. Representative values: 1 (224); 4 (11).
Remarks	nvarchar(max)	Yes	None	None	Inferred: stores remarks data. Profile: 1,100/1,450 rows are null or blank. Representative values masked (sensitive or identifying field).
DEOName	nvarchar(max)	Yes	None	None	Inferred: stores deo name data. Representative values masked (sensitive or identifying field).
DEODate	datetime2(7)	Yes	None	None	Inferred: stores deo date data. Profile: 1,450 distinct non-null values; range 2026-03-05T12:43:09 to 2026-07-10T23:56:25. Representative values: 2026-03-05 12:43:09.2600000 (1); 2026-03-05 13:29:46.5733333 (1); 2026-03-05 14:08:08.6633333 (1).
LastModifiedByName	nvarchar(max)	Yes	None	None	Inferred: stores last modified by name data. Profile: 1,009/1,450 rows are null or blank. Representative values masked (sensitive or identifying field).

Column Name	Data Type	Nullable	Key / Constraint	Default	Description
LastModifiedDate	datetime2(7)	Yes	None	None	Latest recorded modification timestamp. Profile: 1,009/1,450 rows are null or blank; 441 distinct non-null values; range 2026-03-07T10:52:42 to 2026-07-10T23:53:17. Representative values: 2026-03-07 10:52:42.2200000 (1); 2026-03-12 11:25:52.7333333 (1); 2026-03-12 12:16:30.2133333 (1).

Relationships

- Validated logical parent of TumourTable through PatientTable.REGNO = TumourTable.PATIENTIDTUMOURTABLE; 1,455/1,455 tumour rows matched.
- Validated logical parent of SourceTable through REGNO; 1,455/1,455 source rows matched.

Data Analysis

Business-critical or frequently joined/filterable columns: Id, REGNO, PATIENTRECORDID, PATIENTUPDATEDBY, PATIENTUPDATEDATE, PATIENTRECORDSTATUS, PATIENTCHECKSTATUS, CentreCode, DateOfBirth, DayDateOfBirth, MonthDateOfBirth, YearDateOfBirth.

- Highest null/blank counts: PATIENTRECORDSTATUS 1,450/1,450, PATIENTCHECKSTATUS 1,450/1,450, OBSOLETEFLAGPATIENTTABLE 1,450/1,450, CauseOfDeath 1,212/1,450, YearDateOfDeath 1,211/1,450.
- The primary key prevents duplicate full rows and duplicate key values.
- REGNO has 0 duplicate groups; all 1,450 values are represented in logical tumour/source links as expected.
- DateOfBirth and DateOfDeath are nvarchar(max), but all populated current values converted to date in the read-only check.
- ContactNumber is stored as float, which is not a safe type for exact telephone identifiers.
- 30 column(s) use nvarchar(max), limiting type precision and potentially increasing storage/indexing cost.

Data Quality Observations

16 of 36 columns have no null/blank values in the current data. Representative values in the column table are frequency-based and masked for sensitive fields.

Important Findings

- Application-level relationships exist without FK enforcement.

38. dbo.PossibleDuplicates

Table Overview

Confirmed by schema/application use. Tracks suspected duplicate record pairs, match scores, decisions and review workflow metadata.

Role classification: Core / transactional.

Table Statistics

Measure	Value
Total records	37
Columns	15
Primary key	Id
Enforced foreign-key columns	0
Created	2025-09-15T10:48:26
Last schema modification	2025-09-15T10:48:26

Column Details

Column Name	Data Type	Nullable	Key / Constraint	Default	Description
Id	int	No	PK#1; IDENTITY(1,1)	None	Internal row identifier. Profile: range 877 to 913. Representative values masked (sensitive or identifying field).
Record1	nvarchar(max)	Yes	None	None	Inferred: stores record1 data. Representative values masked (sensitive or identifying field).
Record2	nvarchar(max)	Yes	None	None	Inferred: stores record2 data. Representative values masked (sensitive or identifying field).
MatchPercent	nvarchar(max)	Yes	None	None	Inferred: stores match percent data. Profile: 14 distinct non-null values. Representative values: 76% (9); 77% (7); 75% (3).
DuplicateFoundDate	datetime2(7)	No	None	None	Inferred: stores duplicate found date data. Profile: 30 distinct non-null values; range 2026-03-24T14:50:06 to 2026-06-08T15:47:54. Representative values: 2026-06-08 15:46:15.1666667 (4); 2026-06-08 15:45:31.2733333 (3); 2026-06-08 15:45:31.4366667 (2).
Decision	nvarchar(max)	Yes	None	None	Inferred: stores decision data. Profile: 1 distinct non-null values. Representative values: PENDING (37).
OriginalRecordId	nvarchar(max)	Yes	None	None	Inferred: stores original record id data. Profile: 37/37 rows are null or blank. Representative values masked (sensitive or identifying field).
RecordToBeDeleted	nvarchar(max)	Yes	None	None	Inferred: stores record to be deleted data. Profile: 37/37 rows are null or blank; 0 distinct non-null values.
NewUniqueRecordId	nvarchar(max)	Yes	None	None	Inferred: stores new unique record id data. Profile: 37/37 rows are null or blank. Representative values masked (sensitive or identifying field).

Column Name	Data Type	Nullable	Key / Constraint	Default	Description
AssociatedDuplicate CreateNewRecord	nvarchar(max)	Yes	None	None	Inferred: stores associated duplicate create new record data. Profile: 37/37 rows are null or blank; 0 distinct non-null values.
RecentlyUpdated	nvarchar(max)	Yes	None	None	Inferred: stores recently updated data. Profile: 2 distinct non-null values. Representative values: 0 (26); 1 (11).
ReviewedBy	nvarchar(max)	Yes	None	None	Inferred: stores reviewed by data. Profile: 37/37 rows are null or blank. Representative values masked (sensitive or identifying field).
RecentReviewDate	datetime2(7)	No	None	None	Inferred: stores recent review date data. Profile: 1 distinct non-null values; range 1900-01-01T00:00:00 to 1900-01-01T00:00:00. Representative values: 1900-01-01 00:00:00.0000000 (37).
ReviewHistory	nvarchar(max)	Yes	None	None	Inferred: stores review history data. Profile: 37/37 rows are null or blank. Representative values masked (sensitive or identifying field).
Remarks	nvarchar(max)	Yes	None	None	Inferred: stores remarks data. Profile: 37/37 rows are null or blank. Representative values masked (sensitive or identifying field).

Relationships

- No enforced or validated logical relationships were identified for this table.

Data Analysis

Business-critical or frequently joined/filterable columns: Id, DuplicateFoundDate, OriginalRecordId, NewUniqueRecordId, RecentlyUpdated, RecentReviewDate.

- Highest null/blank counts: ReviewedBy 37/37, ReviewHistory 37/37, Remarks 37/37, RecordToBeDeleted 37/37, OriginalRecordId 37/37.
- The primary key prevents duplicate full rows and duplicate key values.
- All 37 rows contain a decision, but ReviewedBy is null/blank in all 37 rows; review accountability is incomplete.
- 12 column(s) use nvarchar(max), limiting type precision and potentially increasing storage/indexing cost.

Data Quality Observations

8 of 15 columns have no null/blank values in the current data. Representative values in the column table are frequency-based and masked for sensitive fields.

Important Findings

- Application-level relationships exist without FK enforcement.

39. dbo.PrimarySiteList

Table Overview

Purpose inferred from table and column names. Code/value or geographic reference data for primary site.

Role classification: Reference / classification.

Table Statistics

Measure	Value
Total records	401
Columns	2
Primary key	None
Enforced foreign-key columns	0
Created	2025-09-15T10:48:28
Last schema modification	2025-09-15T10:48:28

Column Details

Column Name	Data Type	Nullable	Key / Constraint	Default	Description
Code	nvarchar(max)	Yes	None	None	Stored category or classification code. Profile: 401 distinct non-null values. Representative values: 00 (1); 000 (1); 001 (1).
Value	nvarchar(max)	Yes	None	None	Display label or decoded meaning for the associated code. Profile: 401 distinct non-null values. Representative values: ACCESSORY SINUSES (1); ADRENAL GLAND (1); ANUS (1).

Relationships

- Probable semantic code/value lookup for TumourTable.PrimarySite, based on matching domain names; not enforced by a foreign key.

Data Analysis

Business-critical or frequently joined/filterable columns: Code.

- No null or blank values were found in profiled columns.
- Code values are unique in the current data, but no PK/UNIQUE constraint enforces that condition.
- 2 column(s) use nvarchar(max), limiting type precision and potentially increasing storage/indexing cost.

Data Quality Observations

2 of 2 columns have no null/blank values in the current data. Representative values in the column table are frequency-based and masked for sensitive fields.

Important Findings

- No primary key is defined.
- Application-level relationships exist without FK enforcement.

40. dbo.ReligionList

Table Overview

Purpose inferred from table and column names. Code/value or geographic reference data for religion.
Role classification: Reference / classification.

Table Statistics

Measure	Value
Total records	0
Columns	2
Primary key	None
Enforced foreign-key columns	0
Created	2025-09-15T10:48:28
Last schema modification	2025-09-15T10:48:28

Column Details

Column Name	Data Type	Nullable	Key / Constraint	Default	Description
Code	nvarchar(max)	Yes	None	None	Stored category or classification code.
Value	nvarchar(max)	Yes	None	None	Display label or decoded meaning for the associated code.

Relationships

- No enforced or validated logical relationships were identified for this table.

Data Analysis

Business-critical or frequently joined/filterable columns: Code.

- The table is empty at the profiling timestamp; value distributions and duplicates cannot be assessed.
- 2 column(s) use nvarchar(max), limiting type precision and potentially increasing storage/indexing cost.

Data Quality Observations

Confirmed: no rows are present; completeness, consistency and representative-value checks are not applicable.

Important Findings

- No primary key is defined.
- Application-level relationships exist without FK enforcement.
- The table is inactive/empty at the profiling timestamp; confirm whether it is planned, legacy or awaiting data.

41. dbo.SEERList

Table Overview

Purpose inferred from table and column names. Code/value or geographic reference data for seer.

Role classification: Reference / classification.

Table Statistics

Measure	Value
Total records	0
Columns	2
Primary key	None
Enforced foreign-key columns	0
Created	2025-09-15T10:48:28
Last schema modification	2025-09-15T10:48:28

Column Details

Column Name	Data Type	Nullable	Key / Constraint	Default	Description
Code	nvarchar(max)	Yes	None	None	Stored category or classification code.
Value	nvarchar(max)	Yes	None	None	Display label or decoded meaning for the associated code.

Relationships

- No enforced or validated logical relationships were identified for this table.

Data Analysis

Business-critical or frequently joined/filterable columns: Code.

- The table is empty at the profiling timestamp; value distributions and duplicates cannot be assessed.
- 2 column(s) use nvarchar(max), limiting type precision and potentially increasing storage/indexing cost.

Data Quality Observations

Confirmed: no rows are present; completeness, consistency and representative-value checks are not applicable.

Important Findings

- No primary key is defined.
- Application-level relationships exist without FK enforcement.
- The table is inactive/empty at the profiling timestamp; confirm whether it is planned, legacy or awaiting data.

42. dbo.SexList

Table Overview

Purpose inferred from table and column names. Code/value or geographic reference data for sex.

Role classification: Reference / classification.

Table Statistics

Measure	Value
Total records	2
Columns	2
Primary key	None
Enforced foreign-key columns	0
Created	2025-09-15T10:48:29
Last schema modification	2025-09-15T10:48:29

Column Details

Column Name	Data Type	Nullable	Key / Constraint	Default	Description
Code	nvarchar(max)	Yes	None	None	Stored category or classification code. Profile: 2 distinct non-null values. Representative values: 1 (1); 2 (1).
Value	nvarchar(max)	Yes	None	None	Display label or decoded meaning for the associated code. Profile: 2 distinct non-null values. Representative values: Female (1); Male (1).

Relationships

- Probable semantic code/value lookup for PatientTable.Sex, based on matching domain names; not enforced by a foreign key.

Data Analysis

Business-critical or frequently joined/filterable columns: Code.

- No null or blank values were found in profiled columns.
- Code values are unique in the current data, but no PK/UNIQUE constraint enforces that condition.
- 2 column(s) use nvarchar(max), limiting type precision and potentially increasing storage/indexing cost.

Data Quality Observations

2 of 2 columns have no null/blank values in the current data. Representative values in the column table are frequency-based and masked for sensitive fields.

Important Findings

- No primary key is defined.
- Application-level relationships exist without FK enforcement.

43. dbo.SourceCentreList

Table Overview

Purpose inferred from table and column names. Code/value or geographic reference data for source centre.

Role classification: Reference / classification.

Table Statistics

Measure	Value
Total records	0

Measure	Value
Columns	3
Primary key	Id
Enforced foreign-key columns	0
Created	2025-09-15T10:48:29
Last schema modification	2025-09-15T10:48:29

Column Details

Column Name	Data Type	Nullable	Key / Constraint	Default	Description
Id	int	No	PK#1; IDENTITY(1,1)	None	Internal row identifier.
Code	nvarchar(max)	Yes	None	None	Stored category or classification code.
Value	nvarchar(max)	Yes	None	None	Display label or decoded meaning for the associated code.

Relationships

- No enforced or validated logical relationships were identified for this table.

Data Analysis

Business-critical or frequently joined/filterable columns: Id, Code.

- The table is empty at the profiling timestamp; value distributions and duplicates cannot be assessed.
- The primary key prevents duplicate full rows and duplicate key values.
- 2 column(s) use nvarchar(max), limiting type precision and potentially increasing storage/indexing cost.

Data Quality Observations

Confirmed: no rows are present; completeness, consistency and representative-value checks are not applicable.

Important Findings

- Application-level relationships exist without FK enforcement.
- The table is inactive/empty at the profiling timestamp; confirm whether it is planned, legacy or awaiting data.

44. dbo.SourceTable

Table Overview

Confirmed by schema/application use. Stores source-of-information records linked logically to a tumour and patient.

Role classification: Core / transactional.

Table Statistics

Measure	Value
Total records	1,455
Columns	12
Primary key	Id
Enforced foreign-key columns	0
Created	2025-09-15T10:48:29
Last schema modification	2025-09-15T11:47:17

Column Details

Column Name	Data Type	Nullable	Key / Constraint	Default	Description
Id	int	No	PK#1; IDENTITY(1,1)	None	Internal row identifier. Profile: 1,455 distinct non-null values; range 2170 to 9397. Representative values: 2170 (1); 2187 (1); 2201 (1).
REGNO	nvarchar(max)	Yes	None	None	Registry number used as the logical patient link. Representative values masked (sensitive or identifying field).
TUMOURID	nvarchar(max)	Yes	None	None	Logical tumour identifier. Representative values masked (sensitive or identifying field).
SOURCEID	nvarchar(max)	Yes	None	None	Logical source-record identifier. Representative values masked (sensitive or identifying field).
TUMOURIDSOURCETABLE	nvarchar(max)	Yes	None	None	Tumour key used to link source rows to TumourTable.TUMOURID. Representative values masked (sensitive or identifying field).
SOURCERECORDID	nvarchar(max)	Yes	None	None	Inferred: stores source record id data. Representative values masked (sensitive or identifying field).
TypeOfSource	nvarchar(max)	Yes	None	None	Inferred: stores type of source data. Profile: 1 distinct non-null values. Representative values: HOSPITAL (1,455).
SourceCentre	nvarchar(max)	Yes	None	None	Inferred: stores source centre data. Profile: 30 distinct non-null values. Representative values: C002 (265); C026 (202); C006 (121).
CaseFileNumber	nvarchar(max)	Yes	None	None	Inferred: stores case file number data. Profile: 654/1,455 rows are null or blank. Representative values masked (sensitive or identifying field).

Column Name	Data Type	Nullable	Key / Constraint	Default	Description
SourceRemarks	nvarchar(max)	Yes	None	None	Inferred: stores source remarks data. Profile: 1,063/1,455 rows are null or blank. Representative values masked (sensitive or identifying field).
TumourNumber	nvarchar(max)	Yes	None	None	Inferred: stores tumour number data. Profile: 2 distinct non-null values. Representative values: 1 (1,449); 2 (6).
SourceNumber	nvarchar(max)	Yes	None	None	Inferred: stores source number data. Profile: 1 distinct non-null values. Representative values: 1 (1,455).

Relationships

- Validated logical child of TumourTable through TUMOURIDSOURCETABLE and of PatientTable through REGNO; all current rows matched.

Data Analysis

Business-critical or frequently joined/filterable columns: Id, REGNO, TUMOURID, SOURCEID, TUMOURIDSOURCETABLE, SOURCERECORDID.

- Highest null/blank counts: SourceRemarks 1,063/1,455, CaseFileNumber 654/1,455.
- The primary key prevents duplicate full rows and duplicate key values.
- SOURCEID has 0 duplicate groups; all patient and tumour logical links match.
- 11 column(s) use nvarchar(max), limiting type precision and potentially increasing storage/indexing cost.

Data Quality Observations

10 of 12 columns have no null/blank values in the current data. Representative values in the column table are frequency-based and masked for sensitive fields.

Important Findings

- Application-level relationships exist without FK enforcement.

45. dbo.StaffDetails

Table Overview

Purpose inferred from table and column names. Intended to store staff master and contact/assignment metadata; currently empty.

Role classification: Operational master.

Table Statistics

Measure	Value
Total records	0
Columns	6
Primary key	Id
Enforced foreign-key columns	0
Created	2025-09-15T10:48:29
Last schema modification	2025-09-15T10:48:29

Column Details

Column Name	Data Type	Nullable	Key / Constraint	Default	Description
Id	int	No	PK#1; IDENTITY(1,1)	None	Internal row identifier.
EmployeeCode	nvarchar(max)	Yes	None	None	Inferred: stores employee code data.
Name	nvarchar(max)	Yes	None	None	Inferred: stores name data.
DateOfBirth	datetime2(7)	No	None	None	Inferred: stores date of birth data. Representative values masked (sensitive or identifying field).
Sex	int	Yes	None	None	Inferred: stores sex data.
ContactNumber	float	No	None	None	Inferred: stores contact number data. Representative values masked (sensitive or identifying field).

Relationships

- No enforced or validated logical relationships were identified for this table.

Data Analysis

Business-critical or frequently joined/filterable columns: Id, EmployeeCode, DateOfBirth.

- The table is empty at the profiling timestamp; value distributions and duplicates cannot be assessed.
- The primary key prevents duplicate full rows and duplicate key values.
- 2 column(s) use nvarchar(max), limiting type precision and potentially increasing storage/indexing cost.

Data Quality Observations

Confirmed: no rows are present; completeness, consistency and representative-value checks are not applicable.

Important Findings

- Application-level relationships exist without FK enforcement.
- The table is inactive/empty at the profiling timestamp; confirm whether it is planned, legacy or awaiting data.

46. dbo.StateList

Table Overview

Purpose inferred from table and column names. State-level geographic master.

Role classification: Reference / classification.

Table Statistics

Measure	Value
Total records	1
Columns	3
Primary key	Id
Enforced foreign-key columns	0
Created	2025-09-15T10:48:29
Last schema modification	2025-09-15T10:48:29

Column Details

Column Name	Data Type	Nullable	Key / Constraint	Default	Description
Id	int	No	PK#1; IDENTITY(1,1)	None	Internal row identifier. Profile: 1 distinct non-null values; range 1 to 1. Representative values: 1 (1).
StateId	nvarchar(max)	Yes	None	None	State master code. Profile: 1 distinct non-null values. Representative values: 1 (1).
StateName	nvarchar(max)	Yes	None	None	Inferred: stores state name data. Profile: 1 distinct non-null values. Representative values: Odisha (1).

Relationships

- Logical one-to-many geographic parent of DistrictList; all current district state codes matched.

Data Analysis

Business-critical or frequently joined/filterable columns: Id, StateId.

- No null or blank values were found in profiled columns.
- The primary key prevents duplicate full rows and duplicate key values.

- 2 column(s) use nvarchar(max), limiting type precision and potentially increasing storage/indexing cost.

Data Quality Observations

3 of 3 columns have no null/blank values in the current data. Representative values in the column table are frequency-based and masked for sensitive fields.

Important Findings

- Application-level relationships exist without FK enforcement.

47. dbo.sysdiagrams

Table Overview

Confirmed by schema/application use. SQL Server Management Studio database-diagram metadata table.

Role classification: Platform / administration.

Table Statistics

Measure	Value
Total records	0
Columns	5
Primary key	diagram_id
Enforced foreign-key columns	0
Created	2026-07-20T12:01:23
Last schema modification	2026-07-20T12:01:23

Column Details

Column Name	Data Type	Nullable	Key / Constraint	Default	Description
name	sysname	No	UNIQUE INDEX	None	Inferred: stores name data.
principal_id	int	No	UNIQUE INDEX	None	Inferred: stores principal id data.
diagram_id	int	No	PK#1; IDENTITY(1,1)	None	Inferred: stores diagram id data.
version	int	Yes	None	None	Inferred: stores version data.
definition	varbinary(max)	Yes	None	None	Inferred: stores definition data.

Relationships

- No enforced or validated logical relationships were identified for this table.

Data Analysis

Business-critical or frequently joined/filterable columns: principal_id, diagram_id.

- The table is empty at the profiling timestamp; value distributions and duplicates cannot be assessed.
- The primary key prevents duplicate full rows and duplicate key values.

Data Quality Observations

Confirmed: no rows are present; completeness, consistency and representative-value checks are not applicable.

Important Findings

- Application-level relationships exist without FK enforcement.
- The table is inactive/empty at the profiling timestamp; confirm whether it is planned, legacy or awaiting data.

48. dbo.TList

Table Overview

Purpose inferred from table and column names. Code/value or geographic reference data for t.

Role classification: Reference / classification.

Table Statistics

Measure	Value
Total records	0
Columns	2
Primary key	None
Enforced foreign-key columns	0
Created	2025-09-15T10:48:31
Last schema modification	2025-09-15T10:48:31

Column Details

Column Name	Data Type	Nullable	Key / Constraint	Default	Description
-------------	-----------	----------	------------------	---------	-------------

Column Name	Data Type	Nullable	Key / Constraint	Default	Description
Code	nvarchar(max)	Yes	None	None	Stored category or classification code.
Value	nvarchar(max)	Yes	None	None	Display label or decoded meaning for the associated code.

Relationships

- No enforced or validated logical relationships were identified for this table.

Data Analysis

Business-critical or frequently joined/filterable columns: Code.

- The table is empty at the profiling timestamp; value distributions and duplicates cannot be assessed.
- 2 column(s) use nvarchar(max), limiting type precision and potentially increasing storage/indexing cost.

Data Quality Observations

Confirmed: no rows are present; completeness, consistency and representative-value checks are not applicable.

Important Findings

- No primary key is defined.
- Application-level relationships exist without FK enforcement.
- The table is inactive/empty at the profiling timestamp; confirm whether it is planned, legacy or awaiting data.

49. dbo.TreatmentList

Table Overview

Purpose inferred from table and column names. Code/value or geographic reference data for treatment.

Role classification: Reference / classification.

Table Statistics

Measure	Value
Total records	19
Columns	2

Measure	Value
Primary key	None
Enforced foreign-key columns	0
Created	2025-09-16T12:22:06
Last schema modification	2025-09-16T12:22:06

Column Details

Column Name	Data Type	Nullable	Key / Constraint	Default	Description
Code	nvarchar(max)	Yes	None	None	Stored category or classification code. Profile: 19 distinct non-null values. Representative values: 1 (1); 10 (1); 11 (1).
Value	nvarchar(max)	Yes	None	None	Display label or decoded meaning for the associated code. Profile: 19 distinct non-null values. Representative values: Chemotherapy (CT) (1); CT+H (1); CT+RT (1).

Relationships

- Probable semantic code/value lookup for TumourTable.Treatment, based on matching domain names; not enforced by a foreign key.

Data Analysis

Business-critical or frequently joined/filterable columns: Code.

- No null or blank values were found in profiled columns.
- Code values are unique in the current data, but no PK/UNIQUE constraint enforces that condition.
- 2 column(s) use nvarchar(max), limiting type precision and potentially increasing storage/indexing cost.

Data Quality Observations

2 of 2 columns have no null/blank values in the current data. Representative values in the column table are frequency-based and masked for sensitive fields.

Important Findings

- No primary key is defined.
- Application-level relationships exist without FK enforcement.

50. dbo.TreatmentStatusList

Table Overview

Purpose inferred from table and column names. Code/value or geographic reference data for treatment status.

Role classification: Reference / classification.

Table Statistics

Measure	Value
Total records	4
Columns	2
Primary key	None
Enforced foreign-key columns	0
Created	2025-09-15T15:09:00
Last schema modification	2025-09-15T15:09:00

Column Details

Column Name	Data Type	Nullable	Key / Constraint	Default	Description
Code	nvarchar(max)	Yes	None	None	Stored category or classification code. Profile: 4 distinct non-null values. Representative values: 1 (1); 2 (1); 3 (1).
Value	nvarchar(max)	Yes	None	None	Display label or decoded meaning for the associated code. Profile: 4 distinct non-null values. Representative values: Complete (1); Incomplete (1); Not applicable (1).

Relationships

- Probable semantic code/value lookup for TumourTable.TreatmentStatus, based on matching domain names; not enforced by a foreign key.

Data Analysis

Business-critical or frequently joined/filterable columns: Code.

- No null or blank values were found in profiled columns.
- Code values are unique in the current data, but no PK/UNIQUE constraint enforces that condition.
- 2 column(s) use nvarchar(max), limiting type precision and potentially increasing storage/indexing cost.

Data Quality Observations

2 of 2 columns have no null/blank values in the current data. Representative values in the column table are frequency-based and masked for sensitive fields.

Important Findings

- No primary key is defined.
- Application-level relationships exist without FK enforcement.

51. dbo.TumourTable

Table Overview

Confirmed by schema/application use. Stores tumour/case attributes linked logically to a patient, including diagnosis, site, histology and treatment coding.

Role classification: Core / transactional.

Table Statistics

Measure	Value
Total records	1,455
Columns	33
Primary key	Id
Enforced foreign-key columns	0
Created	2025-09-15T10:48:31
Last schema modification	2025-11-04T14:59:00

Column Details

Column Name	Data Type	Nullable	Key / Constraint	Default	Description
Id	int	No	PK#1; IDENTITY(1,1)	None	Internal row identifier. Profile: 1,455 distinct non-null values; range 2400 to 9627. Representative values: 2400 (1); 2417 (1); 2431 (1).
REGNO	nvarchar(max)	Yes	None	None	Registry number used as the logical patient link. Representative values masked (sensitive or identifying field).
TUMOURID	nvarchar(max)	Yes	None	None	Logical tumour identifier. Representative values masked (sensitive or identifying field).
RECS	nvarchar(max)	Yes	None	None	Inferred: stores recs data. Profile: 2 distinct non-null values. Representative values: true (1,376); false (79).
CHECKS	nvarchar(max)	Yes	None	None	Inferred: stores checks data. Profile: 2 distinct non-null values. Representative values: true (1,389); false (66).

Column Name	Data Type	Nullable	Key / Constraint	Default	Description
MPCODE	nvarchar(max)	Yes	None	None	Inferred: stores mpcode data. Profile: 1,455/1,455 rows are null or blank; 1 distinct non-null values.
MPSEQ	nvarchar(max)	Yes	None	None	Inferred: stores mpseq data. Profile: 1 distinct non-null values. Representative values: 0 (1,455).
MPTOT	nvarchar(max)	Yes	None	None	Inferred: stores mptot data. Profile: 1 distinct non-null values. Representative values: 1 (1,455).
UPDATE	nvarchar(max)	Yes	None	None	Inferred: stores update data. Profile: 101 distinct non-null values. Representative values: 20260317 (57); 20260618 (54); 20260704 (54).
OBSOLETEFLAGTUMOURTABLE	nvarchar(max)	Yes	None	None	Inferred: stores obsoleteflagtumourtable data. Profile: 1 distinct non-null values. Representative values: 0 (1,455).
PATIENTIDTUMOURTABLE	nvarchar(max)	Yes	None	None	Patient registry key used by the application to link tumour rows to PatientTable.REGNO. Representative values masked (sensitive or identifying field).
PATIENTRECORDIDTUMOURTABLE	nvarchar(max)	Yes	None	None	Inferred: stores patientrecordidtumourtable data. Representative values masked (sensitive or identifying field).
TUMOURUPDATEDBY	nvarchar(max)	Yes	None	None	Inferred: stores tumourupdatedby data. Representative values masked (sensitive or identifying field).
TUMOURUNDUPLICATIONSTATUS	nvarchar(max)	Yes	None	None	Inferred: stores tumourunduplicationstatus data. Profile: 1,455/1,455 rows are null or blank; 1 distinct non-null values.
Age	int	Yes	None	None	Inferred: stores age data. Profile: 45/1,455 rows are null or blank; 87 distinct non-null values; range 0 to 91. Representative values: 55 (58); 59 (57); 54 (44).
DateOfDiagnosis	nvarchar(max)	Yes	None	None	Inferred: stores date of diagnosis data. Profile: 43/1,455 rows are null or blank; 669 distinct non-null values. Representative values: 20250404 (9); 20250901 (9); 20250131 (8).
DayDateOfDiagnosis	nvarchar(max)	Yes	None	None	Inferred: stores day date of diagnosis data. Profile: 43/1,455 rows are null or blank; 32 distinct non-null values. Representative values: 4 (70); 1 (69); 15 (64).
MonthDateOfDiagnosis	nvarchar(max)	Yes	None	None	Inferred: stores month date of diagnosis data. Profile: 43/1,455 rows are null or blank; 13 distinct non-null values. Representative values: 1 (160); 2 (147); 3 (138).
YearDateOfDiagnosis	nvarchar(max)	Yes	None	None	Inferred: stores year date of diagnosis data. Profile: 43/1,455 rows are null or blank; 25 distinct non-null values. Representative values: 2025 (1,005); 2024 (145); 2023 (67).
BasisOfDiagnosis	nvarchar(max)	Yes	None	None	Inferred: stores basis of diagnosis data. Profile: 43/1,455 rows are null or blank; 9 distinct non-null values. Representative values: 7 (1,028); 1 (135); 5 (100).
Site	nvarchar(max)	Yes	None	None	Inferred: stores site data. Profile: 42/1,455 rows are null or blank; 60 distinct non-null values. Representative values: 50 (302); 06 (156); 16 (98).
PrimarySite	nvarchar(max)	Yes	None	None	Inferred: stores primary site data. Profile: 43/1,455 rows are null or blank; 159 distinct non-null values. Representative values: 509 (196); 060 (112); 569 (85).

Column Name	Data Type	Nullable	Key / Constraint	Default	Description
SubSite	nvarchar(max)	Yes	None	None	Inferred: stores sub site data. Profile: 43/1,455 rows are null or blank; 159 distinct non-null values. Representative values: 509 (196); 060 (112); 569 (85).
Histology	nvarchar(max)	Yes	None	None	Inferred: stores histology data. Profile: 43/1,455 rows are null or blank; 140 distinct non-null values. Representative values: 8070 - Squamous cell carcinoma, NOS (253); 8140 - Adenocarcinoma, NOS (212); 8500 - Infiltrating duct carcinoma, NOS (C50...) (187).
GradeCellType	nvarchar(max)	Yes	None	None	Inferred: stores grade cell type data. Profile: 101/1,455 rows are null or blank; 9 distinct non-null values. Representative values: 9 (672); 2 (241); 3 (222).
Behaviour	nvarchar(max)	Yes	None	None	Inferred: stores behaviour data. Profile: 43/1,455 rows are null or blank; 3 distinct non-null values. Representative values: 3 (1,410); 2 (2).
ICD10	nvarchar(max)	Yes	None	None	ICD-10 cancer diagnosis/site code. Profile: 46/1,455 rows are null or blank; 167 distinct non-null values. Representative values: C509 (194); C060 (112); C56 (83).
ICCCCode	nvarchar(max)	Yes	None	None	Inferred: stores iccc code data. Profile: 46/1,455 rows are null or blank; 38 distinct non-null values. Representative values: 11f (955); 12b (138); 10d (72).
Notes	nvarchar(max)	Yes	None	None	Inferred: stores notes data. Profile: 1,165/1,455 rows are null or blank. Representative values masked (sensitive or identifying field).
Treatment	nvarchar(max)	Yes	None	None	Inferred: stores treatment data. Profile: 52/1,455 rows are null or blank; 20 distinct non-null values. Representative values: 3 (337); 5 (297); 7 (158).
TreatmentStatus	nvarchar(max)	Yes	None	None	Inferred: stores treatment status data. Profile: 57/1,455 rows are null or blank; 5 distinct non-null values. Representative values: 2 (587); 1 (546); 9 (187).
TumourNumber	nvarchar(max)	Yes	None	None	Inferred: stores tumour number data. Profile: 2 distinct non-null values. Representative values: 1 (1,449); 2 (6).
ClinicalStage	nvarchar(max)	Yes	None	None	Inferred: stores clinical stage data. Profile: 66/1,455 rows are null or blank; 9 distinct non-null values. Representative values: 9 (494); 5 (208); 6 (183).

Relationships

- Validated logical child of PatientTable and parent of SourceTable.
- Validated logical parent of PatientFile through TumourTable.TUMOURID = PatientFile.TumourId; 1,349/1,349 file rows matched.

Data Analysis

Business-critical or frequently joined/filterable columns: Id, REGNO, TUMOURID, MPCODE, UPDATE, TUMOURUPDATEDBY, TUMOURUNDUPLICATIONSTATUS, DateOfDiagnosis, DayDateOfDiagnosis, MonthDateOfDiagnosis, YearDateOfDiagnosis, ICCCCode.

- Highest null/blank counts: TUMOURUNDUPLICATIONSTATUS 1,455/1,455, MPCODE 1,455/1,455, Notes 1,165/1,455, GradeCellType 101/1,455, ClinicalStage 66/1,455.
- The primary key prevents duplicate full rows and duplicate key values.
- TUMOURID has 0 duplicate groups and all patient links match, despite the absence of an FK/UNIQUE constraint.
- ICD10 contains 2 values outside the expected normalized Cnn pattern and 11 values with no ICD10Group match.
- DateOfDiagnosis is nvarchar(max); all 1,412 populated values converted to date in the read-only check.
- 31 column(s) use nvarchar(max), limiting type precision and potentially increasing storage/indexing cost.

Data Quality Observations

13 of 33 columns have no null/blank values in the current data. Representative values in the column table are frequency-based and masked for sensitive fields.

Important Findings

- Application-level relationships exist without FK enforcement.

52. dbo.TypeOfSourceList

Table Overview

Purpose inferred from table and column names. Code/value or geographic reference data for type of source.

Role classification: Reference / classification.

Table Statistics

Measure	Value
Total records	3
Columns	2
Primary key	None
Enforced foreign-key columns	0
Created	2025-09-15T10:48:32
Last schema modification	2025-09-15T10:48:32

Column Details

Column Name	Data Type	Nullable	Key / Constraint	Default	Description
Code	nvarchar(max)	Yes	None	None	Stored category or classification code. Profile: 3 distinct non-null values. Representative values: DEATH-REGISTRAR (1); HOSPITAL (1); LABORATORY (1).
Value	nvarchar(max)	Yes	None	None	Display label or decoded meaning for the associated code. Profile: 3 distinct non-null values. Representative values: DEATH-REGISTRAR (1); HOSPITAL (1); LABORATORY (1).

Relationships

- Probable semantic code/value lookup for SourceTable.TypeOfSource, based on matching domain names; not enforced by a foreign key.

Data Analysis

Business-critical or frequently joined/filterable columns: Code.

- No null or blank values were found in profiled columns.
- Code values are unique in the current data, but no PK/UNIQUE constraint enforces that condition.
- 2 column(s) use nvarchar(max), limiting type precision and potentially increasing storage/indexing cost.

Data Quality Observations

2 of 2 columns have no null/blank values in the current data. Representative values in the column table are frequency-based and masked for sensitive fields.

Important Findings

- No primary key is defined.
- Application-level relationships exist without FK enforcement.

53. dbo.Unknown

Table Overview

Purpose inferred from table and column names. Generic code/value placeholder reference table; currently empty.

Role classification: Reference / classification.

Table Statistics

Measure	Value
---------	-------

Measure	Value
Total records	0
Columns	2
Primary key	None
Enforced foreign-key columns	0
Created	2025-09-15T10:48:32
Last schema modification	2025-09-15T10:48:32

Column Details

Column Name	Data Type	Nullable	Key / Constraint	Default	Description
Site	nvarchar(max)	No	None	None	Inferred: stores site data.
ICD10	nvarchar(max)	No	None	None	ICD-10 cancer diagnosis/site code.

Relationships

- No enforced or validated logical relationships were identified for this table.

Data Analysis

Business-critical or frequently joined/filterable columns: No specific critical column was identifiable from keys and names..

- The table is empty at the profiling timestamp; value distributions and duplicates cannot be assessed.
- 2 column(s) use nvarchar(max), limiting type precision and potentially increasing storage/indexing cost.

Data Quality Observations

Confirmed: no rows are present; completeness, consistency and representative-value checks are not applicable.

Important Findings

- No primary key is defined.
- Application-level relationships exist without FK enforcement.
- The table is inactive/empty at the profiling timestamp; confirm whether it is planned, legacy or awaiting data.

54. dbo.VillageList

Table Overview

Purpose inferred from table and column names. Village-level geographic master keyed to state, district and block codes.

Role classification: Reference / classification.

Table Statistics

Measure	Value
Total records	53,782
Columns	6
Primary key	Id
Enforced foreign-key columns	0
Created	2025-09-15T10:48:32
Last schema modification	2025-09-15T10:48:32

Column Details

Column Name	Data Type	Nullable	Key / Constraint	Default	Description
Id	int	No	PK#1; IDENTITY(1,1)	None	Internal row identifier. Profile: 53,782 distinct non-null values; range 16 to 53797. Representative values: 100 (1); 1000 (1); 10000 (1).
StateId	nvarchar(max)	Yes	None	None	State master code. Profile: 1 distinct non-null values. Representative values: 1 (53,782).
DistrictId	nvarchar(max)	Yes	None	None	District master code. Profile: 30 distinct non-null values. Representative values: 122 (4,125); 110 (3,385); 105 (3,121).
BlockId	nvarchar(max)	Yes	None	None	Block master code. Profile: 318 distinct non-null values. Representative values: 11103 (514); 11710 (488); 12706 (452).
VillageId	nvarchar(max)	Yes	None	None	Village master code. Representative values masked (sensitive or identifying field).
VillageName	nvarchar(max)	Yes	None	None	Inferred: stores village name data. Representative values masked (sensitive or identifying field).

Relationships

- Logical child of BlockList and geographic parent of Centres; all current centre village codes matched.

Data Analysis

Business-critical or frequently joined/filterable columns: Id, StateId, DistrictId, BlockId, VillageId.

- No null or blank values were found in profiled columns.
- The primary key prevents duplicate full rows and duplicate key values.
- VillageId has 66 duplicate groups (66 excess rows) and is not protected by a unique constraint.
- 310 village rows reference a BlockId absent from BlockList.
- 5 column(s) use nvarchar(max), limiting type precision and potentially increasing storage/indexing cost.

Data Quality Observations

6 of 6 columns have no null/blank values in the current data. Representative values in the column table are frequency-based and masked for sensitive fields.

Important Findings

- Application-level relationships exist without FK enforcement.

55. dbo.VitalStatusList

Table Overview

Purpose inferred from table and column names. Code/value or geographic reference data for vital status.

Role classification: Reference / classification.

Table Statistics

Measure	Value
Total records	3
Columns	2
Primary key	None
Enforced foreign-key columns	0
Created	2025-09-15T10:48:32
Last schema modification	2025-09-15T10:48:32

Column Details

Column Name	Data Type	Nullable	Key / Constraint	Default	Description
Code	nvarchar(max)	Yes	None	None	Stored category or classification code. Profile: 3 distinct non-null values. Representative values: 1 (1); 2 (1); 9 (1).

Column Name	Data Type	Nullable	Key / Constraint	Default	Description
Value	nvarchar(max)	Yes	None	None	Display label or decoded meaning for the associated code. Profile: 3 distinct non-null values. Representative values: Alive (1); Dead (1); Unknown (1).

Relationships

- Probable semantic code/value lookup for PatientTable.VitalStatus, based on matching domain names; not enforced by a foreign key.

Data Analysis

Business-critical or frequently joined/filterable columns: Code.

- No null or blank values were found in profiled columns.
- Code values are unique in the current data, but no PK/UNIQUE constraint enforces that condition.
- 2 column(s) use nvarchar(max), limiting type precision and potentially increasing storage/indexing cost.

Data Quality Observations

2 of 2 columns have no null/blank values in the current data. Representative values in the column table are frequency-based and masked for sensitive fields.

Important Findings

- No primary key is defined.
- Application-level relationships exist without FK enforcement.

56. dbo.YesNoList

Table Overview

Purpose inferred from table and column names. Code/value or geographic reference data for yes no.

Role classification: Reference / classification.

Table Statistics

Measure	Value
Total records	3
Columns	2
Primary key	None
Enforced foreign-key columns	0

Measure	Value
Created	2025-09-15T10:48:33
Last schema modification	2025-09-15T10:48:33

Column Details

Column Name	Data Type	Nullable	Key / Constraint	Default	Description
Code	nvarchar(max)	Yes	None	None	Stored category or classification code. Profile: 3 distinct non-null values. Representative values: 1 (1); 2 (1); 9 (1).
Value	nvarchar(max)	Yes	None	None	Display label or decoded meaning for the associated code. Profile: 3 distinct non-null values. Representative values: No (1); Unknown (1); Yes (1).

Relationships

- No enforced or validated logical relationships were identified for this table.

Data Analysis

Business-critical or frequently joined/filterable columns: Code.

- No null or blank values were found in profiled columns.
- Code values are unique in the current data, but no PK/UNIQUE constraint enforces that condition.
- 2 column(s) use nvarchar(max), limiting type precision and potentially increasing storage/indexing cost.

Data Quality Observations

2 of 2 columns have no null/blank values in the current data. Representative values in the column table are frequency-based and masked for sensitive fields.

Important Findings

- No primary key is defined.
- Application-level relationships exist without FK enforcement.

Concise Final Risk and Recommendation Summary

- High: Repair the 310 VillageList rows with unknown BlockId and resolve the 66 duplicate VillageId groups before introducing constraints.
- High: Add staged UNIQUE constraints for PatientTable.REGNO, TumourTable.TUMOURID and SourceTable.SOURCEID after regression testing.

- High: Add staged FKs for the validated patient-tumour-source-file chain and geographic hierarchy; use WITH CHECK so trust is verified.
- High: Remediate the 2 malformed and 11 unmapped ICD10 values, then enforce normalized code validation or a controlled lookup.
- Medium: Migrate date strings to date/datetime2 columns and ContactNumber away from float; preserve source text during a controlled transition.
- Medium: Replace unnecessary nvarchar(max) columns with bounded lengths derived from real maxima, prioritizing keys and frequently filtered fields.
- Medium: Add CHECK/default rules for status flags, required workflow fields and audit timestamps; define nullability from business rules.
- Medium: Require reviewer identity for duplicate decisions or explicitly record an automated decision source.
- Medium: Review the 24 empty tables and retire, populate or document them so inactive schema does not obscure intended functionality.
- Security: Verify the intended authorization model: 154 AspNetUsers rows exist while role/claim membership tables are empty and the web app also uses Windows authentication.