

TECHNICAL DATABASE REPORT

# Comprehensive Database Summary

## Setu\_Odisha

*Schema, relationships, database objects, record counts, column dictionary and data-quality analysis*

Profile generated 24 July 2026, 22:03 India Standard Time

Read-only catalog and aggregate-data analysis; sensitive values masked

## Detailed Summary of Overall Database

### Database Overview

Setu\_Odisha is an online, multi-user Microsoft SQL Server database hosted on ACER-LP01-MR-CC. It was created on 2026-07-20T12:01:06, uses compatibility level 140, collation SQL\_Latin1\_General\_CP1\_CI\_AS, and the FULL recovery model. The database is writable and has 144.00 MB allocated.

Purpose (confirmed from the application query paths and schema): it supports the Odisha population-based cancer registry portal, including patient, tumour, source, file, duplicate-review, geographic, classification and user-account data.

**Evidence boundary:** Catalog facts, exact record counts and aggregate checks are confirmed directly from the database. Business descriptions without database extended properties are explicitly labeled as inferred from names, columns or application use. No patient/user-identifiable sample values are reproduced.

### Database Statistics

| Metric                      | Confirmed value                      |
|-----------------------------|--------------------------------------|
| Database                    | Setu_Odisha                          |
| Base tables                 | 56                                   |
| Total exact records         | 61,266                               |
| Total columns               | 344                                  |
| Populated / empty tables    | 31 / 25                              |
| Tables with a primary key   | 25                                   |
| Indexes                     | 33 (including PK and unique indexes) |
| Enforced foreign keys       | 6                                    |
| CHECK / DEFAULT constraints | 0 / 0                                |
| Views / stored procedures   | 0 / 15                               |
| Functions / triggers        | 1 / 0                                |
| Allocated size              | 144.00 MB                            |

### Data-Type Distribution

| Data type | Columns | Share |
|-----------|---------|-------|
| nvarchar  | 291     | 84.6% |

| Data type      | Columns | Share |
|----------------|---------|-------|
| int            | 30      | 8.7%  |
| datetime2      | 11      | 3.2%  |
| bit            | 5       | 1.5%  |
| float          | 3       | 0.9%  |
| datetimeoffset | 1       | 0.3%  |
| bigint         | 1       | 0.3%  |
| sysname        | 1       | 0.3%  |
| varbinary      | 1       | 0.3%  |

Confirmed profile: 291 of 344 columns are nvarchar, and 271 are nvarchar(max). This schema is strongly text-oriented.

## Database Architecture

The database is a single-schema (dbo) relational design with four functional layers:

- Core registry transactions: PatientTable, TumourTable, SourceTable, PatientFile and PossibleDuplicates.
- Reference/master data: geography, centres, cancer classifications, clinical codes and other Code/Value lookup tables.
- Archive/audit data: DeletedPatientTable, DeletedTumourTable and DeletedSourceTable.
- Platform/security data: ASP.NET Core Identity tables, Entity Framework migration history and SQL Server diagram metadata.

Core data flow (validated): PatientTable.REGNO -> TumourTable.PATIENTIDTUMOURTABLE -> SourceTable.TUMOURIDSOURCETABLE, with PatientFile.TumourId also pointing logically to TumourTable.TUMOURID. All current rows in those four logical child links matched a parent. These relationships are not enforced by database foreign keys.

## Tables and Their Roles

| Table                     | Role                       | Rows | Purpose                                                                             |
|---------------------------|----------------------------|------|-------------------------------------------------------------------------------------|
| dbo.__EFMigrationsHistory | Platform / administration  | 13   | Records applied Entity Framework Core migrations for application schema versioning. |
| dbo.AreaList              | Reference / classification | 3    | Code/value or geographic reference data for area.                                   |
| dbo.AspNetRoleClaims      | Security / identity        | 0    | Standard ASP.NET Core Identity table for role claims data.                          |
| dbo.AspNetRoles           | Security / identity        | 0    | Standard ASP.NET Core Identity table for roles data.                                |

| Table                                        | Role                       | Rows | Purpose                                                                                             |
|----------------------------------------------|----------------------------|------|-----------------------------------------------------------------------------------------------------|
| dbo.AspNetUserClaims                         | Security / identity        | 0    | Standard ASP.NET Core Identity table for user claims data.                                          |
| dbo.AspNetUserLogins                         | Security / identity        | 0    | Standard ASP.NET Core Identity table for user logins data.                                          |
| dbo.AspNetUserRoles                          | Security / identity        | 0    | Standard ASP.NET Core Identity table for user roles data.                                           |
| dbo.AspNetUsers                              | Security / identity        | 154  | Standard ASP.NET Core Identity table for users data.                                                |
| dbo.AspNetUserTokens                         | Security / identity        | 0    | Standard ASP.NET Core Identity table for user tokens data.                                          |
| dbo.BasisOfDiagnosisList                     | Reference / classification | 8    | Code/value or geographic reference data for basis of diagnosis.                                     |
| dbo.BehaviourList                            | Reference / classification | 4    | Code/value or geographic reference data for behaviour.                                              |
| dbo.BlockList                                | Reference / classification | 317  | Block-level geographic master keyed to state and district codes.                                    |
| dbo.CauseOfDeathList                         | Reference / classification | 3    | Code/value or geographic reference data for cause of death.                                         |
| dbo.Centres                                  | Operational master         | 31   | Master list of participating centres and their geographic codes.                                    |
| dbo.CentreTypeList                           | Reference / classification | 3    | Code/value or geographic reference data for centre type.                                            |
| dbo.ClinicalStageList                        | Reference / classification | 8    | Code/value or geographic reference data for clinical stage.                                         |
| dbo.DeletedPatientTable                      | Archive / deletion audit   | 25   | Archives deleted patient rows together with deletion and audit metadata.                            |
| dbo.DeletedSourceTable                       | Archive / deletion audit   | 25   | Archives deleted source rows together with deletion and audit metadata.                             |
| dbo.DeletedTumourTable                       | Archive / deletion audit   | 25   | Archives deleted tumour rows together with deletion and audit metadata.                             |
| dbo.DiagnosisAtRegistrationList              | Reference / classification | 0    | Code/value or geographic reference data for diagnosis at registration.                              |
| dbo.DistrictList                             | Reference / classification | 30   | District-level geographic master keyed to state codes.                                              |
| dbo.DurationDateOfDiagnosisToDateOfDeathList | Reference / classification | 0    | Code/value or geographic reference data for duration date of diagnosis to date of death.            |
| dbo.EthnicGroupList                          | Reference / classification | 0    | Code/value or geographic reference data for ethnic group.                                           |
| dbo.FamilyHistoryOfCancerList                | Reference / classification | 0    | Code/value or geographic reference data for family history of cancer.                               |
| dbo.GradeList                                | Reference / classification | 9    | Code/value or geographic reference data for grade.                                                  |
| dbo.HistologyList                            | Reference / classification | 557  | Code/value or geographic reference data for histology.                                              |
| dbo.ICCCMaster                               | Reference / classification | 0    | Intended International Classification of Childhood Cancer reference structure; currently empty.     |
| dbo.ICD10Group                               | Reference / classification | 87   | Maps normalized ICD-10 codes to grouped cancer-site labels used by incidence and mortality queries. |

| Table                   | Role                       | Rows  | Purpose                                                                                                              |
|-------------------------|----------------------------|-------|----------------------------------------------------------------------------------------------------------------------|
| dbo.LateralityList      | Reference / classification | 0     | Code/value or geographic reference data for laterality.                                                              |
| dbo.Lymph_Leuk          | Reference / classification | 0     | Intended lymphoma/leukaemia classification lookup; currently empty.                                                  |
| dbo.MaritalStatusList   | Reference / classification | 0     | Code/value or geographic reference data for marital status.                                                          |
| dbo.Meso_Mela           | Reference / classification | 0     | Intended mesothelioma/melanoma classification lookup; currently empty.                                               |
| dbo.MList               | Reference / classification | 0     | Code/value or geographic reference data for m.                                                                       |
| dbo.NList               | Reference / classification | 0     | Code/value or geographic reference data for n.                                                                       |
| dbo.OccupationList      | Reference / classification | 0     | Code/value or geographic reference data for occupation.                                                              |
| dbo.PatientFile         | Core / transactional       | 1,349 | Stores file metadata for documents attached logically to tumour records; file contents are not stored in this table. |
| dbo.PatientTable        | Core / transactional       | 1,450 | Stores the active patient-level cancer registry record and demographic/vital-status attributes.                      |
| dbo.PossibleDuplicates  | Core / transactional       | 37    | Tracks suspected duplicate record pairs, match scores, decisions and review workflow metadata.                       |
| dbo.PrimarySiteList     | Reference / classification | 401   | Code/value or geographic reference data for primary site.                                                            |
| dbo.ReligionList        | Reference / classification | 0     | Code/value or geographic reference data for religion.                                                                |
| dbo.SEERList            | Reference / classification | 0     | Code/value or geographic reference data for seer.                                                                    |
| dbo.SexList             | Reference / classification | 2     | Code/value or geographic reference data for sex.                                                                     |
| dbo.SourceCentreList    | Reference / classification | 0     | Code/value or geographic reference data for source centre.                                                           |
| dbo.SourceTable         | Core / transactional       | 1,455 | Stores source-of-information records linked logically to a tumour and patient.                                       |
| dbo.StaffDetails        | Operational master         | 0     | Intended to store staff master and contact/assignment metadata; currently empty.                                     |
| dbo.StateList           | Reference / classification | 1     | State-level geographic master.                                                                                       |
| dbo.sysdiagrams         | Platform / administration  | 0     | SQL Server Management Studio database-diagram metadata table.                                                        |
| dbo.TList               | Reference / classification | 0     | Code/value or geographic reference data for t.                                                                       |
| dbo.TreatmentList       | Reference / classification | 19    | Code/value or geographic reference data for treatment.                                                               |
| dbo.TreatmentStatusList | Reference / classification | 4     | Code/value or geographic reference data for treatment status.                                                        |

| Table                | Role                       | Rows   | Purpose                                                                                                                 |
|----------------------|----------------------------|--------|-------------------------------------------------------------------------------------------------------------------------|
| dbo.TumourTable      | Core / transactional       | 1,455  | Stores tumour/case attributes linked logically to a patient, including diagnosis, site, histology and treatment coding. |
| dbo.TypeOfSourceList | Reference / classification | 3      | Code/value or geographic reference data for type of source.                                                             |
| dbo.Unknown          | Reference / classification | 0      | Generic code/value placeholder reference table; currently empty.                                                        |
| dbo.VillageList      | Reference / classification | 53,782 | Village-level geographic master keyed to state, district and block codes.                                               |
| dbo.VitalStatusList  | Reference / classification | 3      | Code/value or geographic reference data for vital status.                                                               |
| dbo.YesNoList        | Reference / classification | 3      | Code/value or geographic reference data for yes no.                                                                     |

## Relationships and Dependencies

### Enforced foreign keys

| Constraint                             | Child                   | Parent         | Delete  | Status  |
|----------------------------------------|-------------------------|----------------|---------|---------|
| FK_AspNetRoleClaims_AspNetRoles_RoleId | AspNetRoleClaims.RoleId | AspNetRoles.Id | CASCADE | Trusted |
| FK_AspNetUserClaims_AspNetUsers_UserId | AspNetUserClaims.UserId | AspNetUsers.Id | CASCADE | Trusted |
| FK_AspNetUserLogins_AspNetUsers_UserId | AspNetUserLogins.UserId | AspNetUsers.Id | CASCADE | Trusted |
| FK_AspNetUserRoles_AspNetRoles_RoleId  | AspNetUserRoles.RoleId  | AspNetRoles.Id | CASCADE | Trusted |
| FK_AspNetUserRoles_AspNetUsers_UserId  | AspNetUserRoles.UserId  | AspNetUsers.Id | CASCADE | Trusted |
| FK_AspNetUserTokens_AspNetUsers_UserId | AspNetUserTokens.UserId | AspNetUsers.Id | CASCADE | Trusted |

Confirmed: all six enforced foreign keys belong to the ASP.NET Identity subsystem. No cancer-registry, file, centre, geography or clinical lookup relationship is enforced by an FK.

### Validated logical relationships

| Logical relationship                                    | Child rows | Matched | Orphans |
|---------------------------------------------------------|------------|---------|---------|
| TumourTable.PATIENTIDTUMOURTABLE -> PatientTable.REGNO  | 1,455      | 1,455   | 0       |
| TumourTable.REGNO -> PatientTable.REGNO                 | 1,455      | 1,455   | 0       |
| SourceTable.TUMOURIDSOURCETABLE -> TumourTable.TUMOURID | 1,455      | 1,455   | 0       |
| SourceTable.REGNO -> PatientTable.REGNO                 | 1,455      | 1,455   | 0       |
| PatientFile.TumourId -> TumourTable.TUMOURID            | 1,349      | 1,349   | 0       |

## Observed cardinality

| Relationship                | Parents | No child | One   | Many | Max |
|-----------------------------|---------|----------|-------|------|-----|
| PatientTable -> TumourTable | 1,450   | 1        | 1,443 | 6    | 2   |
| TumourTable -> SourceTable  | 1,455   | 0        | 1,455 | 0    | 1   |
| TumourTable -> PatientFile  | 1,455   | 310      | 1,009 | 136  | 9   |

## Keys, Constraints, and Indexes

The catalog contains 33 indexes across 25 tables. 25 tables have primary keys; 31 do not. There are no user-defined CHECK constraints, no column DEFAULT constraints and no computed columns.

| Table                 | Index                      | Type      | Columns                                       |
|-----------------------|----------------------------|-----------|-----------------------------------------------|
| __EFMigrationsHistory | PK__EFMigrationsHistory    | PK        | [MigrationId] ASC                             |
| AspNetRoleClaims      | PK_AspNetRoleClaims        | PK        | [Id] ASC                                      |
| AspNetRoleClaims      | IX_AspNetRoleClaims_RoleId | Nonunique | [RoleId] ASC                                  |
| AspNetRoles           | PK_AspNetRoles             | PK        | [Id] ASC                                      |
| AspNetRoles           | RoleNameIndex              | Unique    | [NormalizedName] ASC                          |
| AspNetUserClaims      | PK_AspNetUserClaims        | PK        | [Id] ASC                                      |
| AspNetUserClaims      | IX_AspNetUserClaims_UserId | Nonunique | [UserId] ASC                                  |
| AspNetUserLogins      | PK_AspNetUserLogins        | PK        | [LoginProvider] ASC, [ProviderKey] ASC        |
| AspNetUserLogins      | IX_AspNetUserLogins_UserId | Nonunique | [UserId] ASC                                  |
| AspNetUserRoles       | PK_AspNetUserRoles         | PK        | [UserId] ASC, [RoleId] ASC                    |
| AspNetUserRoles       | IX_AspNetUserRoles_RoleId  | Nonunique | [RoleId] ASC                                  |
| AspNetUsers           | PK_AspNetUsers             | PK        | [Id] ASC                                      |
| AspNetUsers           | UserNameIndex              | Unique    | [NormalizedUserName] ASC                      |
| AspNetUsers           | EmailIndex                 | Nonunique | [NormalizedEmail] ASC                         |
| AspNetUserTokens      | PK_AspNetUserTokens        | PK        | [UserId] ASC, [LoginProvider] ASC, [Name] ASC |
| BlockList             | PK_BlockList               | PK        | [Id] ASC                                      |
| Centres               | PK_Centres                 | PK        | [Id] ASC                                      |
| DeletedPatientTable   | PK_DeletedPatientTable     | PK        | [Id] ASC                                      |
| DeletedSourceTable    | PK_DeletedSourceTable      | PK        | [Id] ASC                                      |
| DeletedTumourTable    | PK_DeletedTumourTable      | PK        | [Id] ASC                                      |
| DistrictList          | PK_DistrictList            | PK        | [Id] ASC                                      |
| ICCCMaster            | PK_ICCCMaster              | PK        | [Id] ASC                                      |
| PatientFile           | PK_PatientFile             | PK        | [Id] ASC                                      |

| Table              | Index                          | Type   | Columns                        |
|--------------------|--------------------------------|--------|--------------------------------|
| PatientTable       | PK_PatientTable                | PK     | [Id] ASC                       |
| PossibleDuplicates | PK_PossibleDuplicates          | PK     | [Id] ASC                       |
| SourceCentreList   | PK_SourceCentreList            | PK     | [Id] ASC                       |
| SourceTable        | PK_SourceTable                 | PK     | [Id] ASC                       |
| StaffDetails       | PK_StaffDetails                | PK     | [Id] ASC                       |
| StateList          | PK_StateList                   | PK     | [Id] ASC                       |
| sysdiagrams        | PK__sysdiagr__C2B05B61DAFDC6EC | PK     | [diagram_id] ASC               |
| sysdiagrams        | UK_principal_name              | Unique | [principal_id] ASC, [name] ASC |
| TumourTable        | PK_TumourTable                 | PK     | [Id] ASC                       |
| VillageList        | PK_VillageList                 | PK     | [Id] ASC                       |

## Views, Stored Procedures, Functions, and Triggers

Confirmed catalog totals: 0 views; 15 stored procedures; 1 function; 0 triggers.

| Type             | Object                                            | Parameters                                                                     | Dependencies    | Purpose                                                                 |
|------------------|---------------------------------------------------|--------------------------------------------------------------------------------|-----------------|-------------------------------------------------------------------------|
| Scalar Function  | dbo.fn_diagramobjects                             | int                                                                            | None recorded   | SQL Server diagram-management support object.                           |
| Stored Procedure | dbo.sp_alterdiagram                               | @diagramname sysname,<br>@owner_id int, @version int,<br>@definition varbinary | dbo.sysdiagrams | SQL Server diagram-management support object.                           |
| Stored Procedure | dbo.sp_creatediagram                              | @diagramname sysname,<br>@owner_id int, @version int,<br>@definition varbinary | dbo.sysdiagrams | SQL Server diagram-management support object.                           |
| Stored Procedure | dbo.sp_dropdiagram                                | @diagramname sysname,<br>@owner_id int                                         | dbo.sysdiagrams | SQL Server diagram-management support object.                           |
| Stored Procedure | dbo.SP_GET_NIRMITI_INCI_MORT_FORMAT               | @clauses varchar                                                               | None recorded   | Application export/report procedure; purpose inferred from object name. |
| Stored Procedure | dbo.SP_GET_NIRMITI_PAEDIATRIC_FORMAT              | @clauses varchar                                                               | None recorded   | Application export/report procedure; purpose inferred from object name. |
| Stored Procedure | dbo.SP_GET_PATIENT_DATA_CANREG5_FORMAT            | @clauses varchar                                                               | None recorded   | Application export/report procedure; purpose inferred from object name. |
| Stored Procedure | dbo.SP_GET_PATIENTTUMOUR_DATA_CANREG5_FORMAT      | @clauses varchar                                                               | None recorded   | Application export/report procedure; purpose inferred from object name. |
| Stored Procedure | dbo.SP_GET_PATIENTTUMOURSOURCEDATA_CANREG5_FORMAT | @clauses varchar                                                               | None recorded   | Application export/report procedure; purpose inferred from object name. |
| Stored Procedure | dbo.SP_GET_SOURCE_DATA_CANREG5_FORMAT             | @clauses varchar                                                               | None recorded   | Application export/report procedure; purpose inferred from object name. |
| Stored Procedure | dbo.SP_GET_TUMOUR_DATA_CANREG5_FORMAT             | @clauses varchar                                                               | None recorded   | Application export/report procedure; purpose inferred from object name. |



| Type             | Object                                      | Parameters                                                          | Dependencies                        | Purpose                                                                 |
|------------------|---------------------------------------------|---------------------------------------------------------------------|-------------------------------------|-------------------------------------------------------------------------|
| Stored Procedure | dbo.SP_GET_TUMOURSOURCE_DATA_CANREG5_FORMAT | @clauses varchar                                                    | None recorded                       | Application export/report procedure; purpose inferred from object name. |
| Stored Procedure | dbo.sp_helpdiagramdefinition                | @diagramname sysname,<br>@owner_id int                              | dbo.sysdiagrams                     | SQL Server diagram-management support object.                           |
| Stored Procedure | dbo.sp_helpdiagrams                         | @diagramname sysname,<br>@owner_id int                              | sysdiagrams                         | SQL Server diagram-management support object.                           |
| Stored Procedure | dbo.sp_renamediagram                        | @diagramname sysname,<br>@owner_id int,<br>@new_diagramname sysname | dbo.sysdiagrams                     | SQL Server diagram-management support object.                           |
| Stored Procedure | dbo.sp_upgraddiagrams                       | None                                                                | dbo.dproperties,<br>dbo.sysdiagrams | SQL Server diagram-management support object.                           |

## Data Quality and Integrity Analysis

- Core logical integrity is currently strong: all 1,455 tumour-to-patient, 1,455 source-to-tumour, 1,455 source-to-patient and 1,349 file-to-tumour links matched.
- Business identifiers REGNO, TUMOURID and SOURCEID have no duplicate groups in current data, but uniqueness is not enforced.
- VillageList contains 66 duplicate Villageld groups (66 excess rows) and 310 rows whose BlockId is absent from BlockList.
- TumourTable.ICD10 has 2 populated values outside the expected normalized Cnn pattern and 11 populated values not mapped by ICD10Group.
- PossibleDuplicates contains 37 decisions; ReviewedBy is missing in all 37 rows.
- 25 of 56 tables are empty, including several classification/reference tables and all standard Identity role/claim/link tables.
- 286 of 344 columns are nullable; 271 are nvarchar(max).
- No user-defined CHECK constraints or DEFAULT constraints exist.
- All populated DateOfBirth, DateOfDeath and DateOfDiagnosis values converted successfully in the current read-only check; the fields remain stored as text.

## Important Findings and Recommendations

| Priority | Recommendation                                                                                                                     |
|----------|------------------------------------------------------------------------------------------------------------------------------------|
| High     | Repair the 310 VillageList rows with unknown BlockId and resolve the 66 duplicate Villageld groups before introducing constraints. |
| High     | Add staged UNIQUE constraints for PatientTable.REGNO, TumourTable.TUMOURID and SourceTable.SOURCEID after regression testing.      |
| High     | Add staged FKs for the validated patient-tumour-source-file chain and geographic hierarchy; use WITH CHECK so trust is verified.   |

| Priority | Recommendation                                                                                                                                                     |
|----------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| High     | Remediate the 2 malformed and 11 unmapped ICD10 values, then enforce normalized code validation or a controlled lookup.                                            |
| Medium   | Migrate date strings to date/datetime2 columns and ContactNumber away from float; preserve source text during a controlled transition.                             |
| Medium   | Replace unnecessary nvarchar(max) columns with bounded lengths derived from real maxima, prioritizing keys and frequently filtered fields.                         |
| Medium   | Add CHECK/default rules for status flags, required workflow fields and audit timestamps; define nullability from business rules.                                   |
| Medium   | Require reviewer identity for duplicate decisions or explicitly record an automated decision source.                                                               |
| Medium   | Review the 25 empty tables and retire, populate or document them so inactive schema does not obscure intended functionality.                                       |
| Security | Verify the intended authorization model: 154 AspNetUsers rows exist while role/claim membership tables are empty and the web app also uses Windows authentication. |

## Detailed Summary of Individual Tables

Each section below reports the exact record count, catalog metadata, every column, enforced and logical relationships, aggregate profile facts and privacy-safe representative values. Descriptions prefixed “Inferred” are observations, not catalog documentation.

### 1. dbo.\_\_EFMigrationsHistory

#### Table Overview

**Confirmed by schema/application use.** Records applied Entity Framework Core migrations for application schema versioning.

Role classification: Platform / administration.

#### Table Statistics

| Measure                      | Value               |
|------------------------------|---------------------|
| Total records                | 13                  |
| Columns                      | 2                   |
| Primary key                  | MigrationId         |
| Enforced foreign-key columns | 0                   |
| Created                      | 2025-09-15T10:48:17 |
| Last schema modification     | 2025-09-15T10:48:17 |

#### Column Details

| Column Name    | Data Type     | Nullable | Key / Constraint | Default | Description                                                                                                                      |
|----------------|---------------|----------|------------------|---------|----------------------------------------------------------------------------------------------------------------------------------|
| MigrationId    | nvarchar(150) | No       | PK#1             | None    | Entity Framework migration identifier. Representative values masked (sensitive or identifying field).                            |
| ProductVersion | nvarchar(32)  | No       | None             | None    | Entity Framework product version used for the migration. Profile: 1 distinct non-null values. Representative values: 6.0.1 (13). |

#### Relationships

- No enforced or validated logical relationships were identified for this table.

#### Data Analysis

Business-critical or frequently joined/filterable columns: MigrationId.

- No null or blank values were found in profiled columns.

- The primary key prevents duplicate full rows and duplicate key values.

Data Quality Observations

2 of 2 columns have no null/blank values in the current data. Representative values in the column table are frequency-based and masked for sensitive fields.

Important Findings

- Application-level relationships exist without FK enforcement.

2. dbo.AreaList

Table Overview

**Purpose inferred from table and column names.** Code/value or geographic reference data for area.

Role classification: Reference / classification.

Table Statistics

| Measure                      | Value               |
|------------------------------|---------------------|
| Total records                | 3                   |
| Columns                      | 2                   |
| Primary key                  | None                |
| Enforced foreign-key columns | 0                   |
| Created                      | 2025-09-16T13:05:09 |
| Last schema modification     | 2025-09-16T13:05:09 |

Column Details

| Column Name | Data Type     | Nullable | Key / Constraint | Default | Description                                                                                                                                             |
|-------------|---------------|----------|------------------|---------|---------------------------------------------------------------------------------------------------------------------------------------------------------|
| Code        | nvarchar(max) | Yes      | None             | None    | Stored category or classification code. Profile: 3 distinct non-null values. Representative values: 1 (1); 2 (1); 3 (1).                                |
| Value       | nvarchar(max) | Yes      | None             | None    | Display label or decoded meaning for the associated code. Profile: 3 distinct non-null values. Representative values: Rural (1); Tribal (1); Urban (1). |

Relationships

- Probable semantic code/value lookup for PatientTable.Area, based on matching domain names; not enforced by a foreign key.

## Data Analysis

Business-critical or frequently joined/filterable columns: Code.

- No null or blank values were found in profiled columns.
- Code values are unique in the current data, but no PK/UNIQUE constraint enforces that condition.
- 2 column(s) use nvarchar(max), limiting type precision and potentially increasing storage/indexing cost.

## Data Quality Observations

2 of 2 columns have no null/blank values in the current data. Representative values in the column table are frequency-based and masked for sensitive fields.

## Important Findings

- No primary key is defined.
- Application-level relationships exist without FK enforcement.

## 3. dbo.AspNetRoleClaims

### Table Overview

**Confirmed standard framework schema.** Standard ASP.NET Core Identity table for role claims data.

Role classification: Security / identity.

### Table Statistics

| Measure                      | Value               |
|------------------------------|---------------------|
| Total records                | 0                   |
| Columns                      | 4                   |
| Primary key                  | Id                  |
| Enforced foreign-key columns | 1                   |
| Created                      | 2025-09-15T10:48:33 |
| Last schema modification     | 2025-09-15T10:48:36 |

## Column Details

| Column Name | Data Type     | Nullable | Key / Constraint         | Default | Description                        |
|-------------|---------------|----------|--------------------------|---------|------------------------------------|
| Id          | int           | No       | PK#1; IDENTITY(1,1)      | None    | Internal row identifier.           |
| RoleId      | nvarchar(450) | No       | FK -> dbo.AspNetRoles.Id | None    | Inferred: stores role id data.     |
| ClaimType   | nvarchar(max) | Yes      | None                     | None    | Inferred: stores claim type data.  |
| ClaimValue  | nvarchar(max) | Yes      | None                     | None    | Inferred: stores claim value data. |

## Relationships

- Enforced many-to-one: dbo.AspNetRoleClaims.RoleId -> dbo.AspNetRoles.Id (ON DELETE CASCADE; ON UPDATE NO\_ACTION).

## Data Analysis

Business-critical or frequently joined/filterable columns: Id, RoleId.

- The table is empty at the profiling timestamp; value distributions and duplicates cannot be assessed.
- The primary key prevents duplicate full rows and duplicate key values.
- 2 column(s) use nvarchar(max), limiting type precision and potentially increasing storage/indexing cost.

## Data Quality Observations

Confirmed: no rows are present; completeness, consistency and representative-value checks are not applicable.

## Important Findings

- The table is inactive/empty at the profiling timestamp; confirm whether it is planned, legacy or awaiting data.

## 4. dbo.AspNetRoles

### Table Overview

**Confirmed standard framework schema.** Standard ASP.NET Core Identity table for roles data.

Role classification: Security / identity.

## Table Statistics

| Measure                      | Value               |
|------------------------------|---------------------|
| Total records                | 0                   |
| Columns                      | 4                   |
| Primary key                  | Id                  |
| Enforced foreign-key columns | 0                   |
| Created                      | 2025-09-15T10:48:17 |
| Last schema modification     | 2025-09-15T10:48:36 |

## Column Details

| Column Name      | Data Type     | Nullable | Key / Constraint | Default | Description                                                                                             |
|------------------|---------------|----------|------------------|---------|---------------------------------------------------------------------------------------------------------|
| Id               | nvarchar(450) | No       | PK#1             | None    | Internal row identifier.                                                                                |
| Name             | nvarchar(256) | Yes      | None             | None    | Inferred: stores name data.                                                                             |
| NormalizedName   | nvarchar(256) | Yes      | UNIQUE INDEX     | None    | Inferred: stores normalized name data.                                                                  |
| ConcurrencyStamp | nvarchar(max) | Yes      | None             | None    | Inferred: stores concurrency stamp data. Representative values masked (sensitive or identifying field). |

## Relationships

- Enforced one-to-many parent for dbo.AspNetRoleClaims through FK\_AspNetRoleClaims\_AspNetRoles\_RoleId.
- Enforced one-to-many parent for dbo.AspNetUserRoles through FK\_AspNetUserRoles\_AspNetRoles\_RoleId.

## Data Analysis

Business-critical or frequently joined/filterable columns: Id.

- The table is empty at the profiling timestamp; value distributions and duplicates cannot be assessed.
- The primary key prevents duplicate full rows and duplicate key values.
- 1 column(s) use nvarchar(max), limiting type precision and potentially increasing storage/indexing cost.

## Data Quality Observations

Confirmed: no rows are present; completeness, consistency and representative-value checks are not applicable.

## Important Findings

- The table is inactive/empty at the profiling timestamp; confirm whether it is planned, legacy or awaiting data.

## 5. dbo.AspNetUserClaims

### Table Overview

**Confirmed standard framework schema.** Standard ASP.NET Core Identity table for user claims data.

Role classification: Security / identity.

### Table Statistics

| Measure                      | Value               |
|------------------------------|---------------------|
| Total records                | 0                   |
| Columns                      | 4                   |
| Primary key                  | Id                  |
| Enforced foreign-key columns | 1                   |
| Created                      | 2025-09-15T10:48:33 |
| Last schema modification     | 2025-09-15T10:48:36 |

### Column Details

| Column Name | Data Type     | Nullable | Key / Constraint         | Default | Description                        |
|-------------|---------------|----------|--------------------------|---------|------------------------------------|
| Id          | int           | No       | PK#1; IDENTITY(1,1)      | None    | Internal row identifier.           |
| UserId      | nvarchar(450) | No       | FK -> dbo.AspNetUsers.Id | None    | Inferred: stores user id data.     |
| ClaimType   | nvarchar(max) | Yes      | None                     | None    | Inferred: stores claim type data.  |
| ClaimValue  | nvarchar(max) | Yes      | None                     | None    | Inferred: stores claim value data. |

### Relationships

- Enforced many-to-one: dbo.AspNetUserClaims.UserId -> dbo.AspNetUsers.Id (ON DELETE CASCADE; ON UPDATE NO\_ACTION).

### Data Analysis

Business-critical or frequently joined/filterable columns: Id, UserId.

- The table is empty at the profiling timestamp; value distributions and duplicates cannot be assessed.



- The primary key prevents duplicate full rows and duplicate key values.
- 2 column(s) use nvarchar(max), limiting type precision and potentially increasing storage/indexing cost.

## Data Quality Observations

Confirmed: no rows are present; completeness, consistency and representative-value checks are not applicable.

## Important Findings

- The table is inactive/empty at the profiling timestamp; confirm whether it is planned, legacy or awaiting data.

## 6. dbo.AspNetUserLogins

### Table Overview

**Confirmed standard framework schema.** Standard ASP.NET Core Identity table for user logins data.

Role classification: Security / identity.

### Table Statistics

| Measure                      | Value                      |
|------------------------------|----------------------------|
| Total records                | 0                          |
| Columns                      | 4                          |
| Primary key                  | LoginProvider, ProviderKey |
| Enforced foreign-key columns | 1                          |
| Created                      | 2025-09-15T10:48:33        |
| Last schema modification     | 2025-09-15T10:48:37        |

### Column Details

| Column Name         | Data Type     | Nullable | Key / Constraint         | Default | Description                                  |
|---------------------|---------------|----------|--------------------------|---------|----------------------------------------------|
| LoginProvider       | nvarchar(450) | No       | PK#1                     | None    | Inferred: stores login provider data.        |
| ProviderKey         | nvarchar(450) | No       | PK#2                     | None    | Inferred: stores provider key data.          |
| ProviderDisplayName | nvarchar(max) | Yes      | None                     | None    | Inferred: stores provider display name data. |
| UserId              | nvarchar(450) | No       | FK -> dbo.AspNetUsers.Id | None    | Inferred: stores user id data.               |

## Relationships

- Enforced many-to-one: dbo.AspNetUserLogins.UserId -> dbo.AspNetUsers.Id (ON DELETE CASCADE; ON UPDATE NO\_ACTION).

## Data Analysis

Business-critical or frequently joined/filterable columns: LoginProvider, ProviderKey, UserId.

- The table is empty at the profiling timestamp; value distributions and duplicates cannot be assessed.
- The primary key prevents duplicate full rows and duplicate key values.
- 1 column(s) use nvarchar(max), limiting type precision and potentially increasing storage/indexing cost.

## Data Quality Observations

Confirmed: no rows are present; completeness, consistency and representative-value checks are not applicable.

## Important Findings

- The table is inactive/empty at the profiling timestamp; confirm whether it is planned, legacy or awaiting data.

## 7. dbo.AspNetUserRoles

### Table Overview

**Confirmed standard framework schema.** Standard ASP.NET Core Identity table for user roles data.

Role classification: Security / identity.

### Table Statistics

| Measure                      | Value               |
|------------------------------|---------------------|
| Total records                | 0                   |
| Columns                      | 2                   |
| Primary key                  | UserId, RoleId      |
| Enforced foreign-key columns | 2                   |
| Created                      | 2025-09-15T10:48:35 |
| Last schema modification     | 2025-09-15T10:48:37 |

## Column Details

| Column Name | Data Type     | Nullable | Key / Constraint               | Default | Description                    |
|-------------|---------------|----------|--------------------------------|---------|--------------------------------|
| UserId      | nvarchar(450) | No       | PK#1; FK -> dbo.AspNetUsers.Id | None    | Inferred: stores user id data. |
| RoleId      | nvarchar(450) | No       | PK#2; FK -> dbo.AspNetRoles.Id | None    | Inferred: stores role id data. |

## Relationships

- Enforced many-to-one: dbo.AspNetUserRoles.RoleId -> dbo.AspNetRoles.Id (ON DELETE CASCADE; ON UPDATE NO\_ACTION).
- Enforced many-to-one: dbo.AspNetUserRoles.UserId -> dbo.AspNetUsers.Id (ON DELETE CASCADE; ON UPDATE NO\_ACTION).

## Data Analysis

Business-critical or frequently joined/filterable columns: UserId, RoleId.

- The table is empty at the profiling timestamp; value distributions and duplicates cannot be assessed.
- The primary key prevents duplicate full rows and duplicate key values.

## Data Quality Observations

Confirmed: no rows are present; completeness, consistency and representative-value checks are not applicable.

## Important Findings

- The table is inactive/empty at the profiling timestamp; confirm whether it is planned, legacy or awaiting data.

## 8. dbo.AspNetUsers

### Table Overview

**Confirmed standard framework schema.** Standard ASP.NET Core Identity table for users data.

Role classification: Security / identity.

Table Statistics

| Measure                      | Value               |
|------------------------------|---------------------|
| Total records                | 154                 |
| Columns                      | 19                  |
| Primary key                  | Id                  |
| Enforced foreign-key columns | 0                   |
| Created                      | 2025-09-15T10:48:17 |
| Last schema modification     | 2025-09-15T10:48:37 |

Column Details

| Column Name        | Data Type     | Nullable | Key / Constraint | Default | Description                                                                                                                                    |
|--------------------|---------------|----------|------------------|---------|------------------------------------------------------------------------------------------------------------------------------------------------|
| Id                 | nvarchar(450) | No       | PK#1             | None    | Internal row identifier. Representative values masked (sensitive or identifying field).                                                        |
| PersonName         | nvarchar(max) | No       | None             | None    | Inferred: stores person name data. Representative values masked (sensitive or identifying field).                                              |
| UserType           | int           | No       | None             | None    | Inferred: stores user type data. Profile: 3 distinct non-null values; range 1 to 3. Representative values: 3 (85); 1 (66); 2 (3).              |
| CentreCode         | nvarchar(max) | No       | None             | None    | Code identifying the participating registry centre. Profile: 31 distinct non-null values. Representative values: C023 (9); C002 (7); C017 (7). |
| IsActive           | bit           | No       | None             | None    | Inferred: stores is active data. Profile: 2 distinct non-null values. Representative values: 1 (151); 0 (3).                                   |
| UserName           | nvarchar(256) | Yes      | None             | None    | Inferred: stores user name data. Representative values masked (sensitive or identifying field).                                                |
| NormalizedUserName | nvarchar(256) | Yes      | UNIQUE INDEX     | None    | Inferred: stores normalized user name data. Representative values masked (sensitive or identifying field).                                     |
| Email              | nvarchar(256) | Yes      | None             | None    | Inferred: stores email data. Representative values masked (sensitive or identifying field).                                                    |
| NormalizedEmail    | nvarchar(256) | Yes      | None             | None    | Inferred: stores normalized email data. Representative values masked (sensitive or identifying field).                                         |
| EmailConfirmed     | bit           | No       | None             | None    | Inferred: stores email confirmed data. Representative values masked (sensitive or identifying field).                                          |
| PasswordHash       | nvarchar(max) | Yes      | None             | None    | Inferred: stores password hash data. Representative values masked (sensitive or identifying field).                                            |
| SecurityStamp      | nvarchar(max) | Yes      | None             | None    | Inferred: stores security stamp data. Representative values masked (sensitive or identifying field).                                           |
| ConcurrencyStamp   | nvarchar(max) | Yes      | None             | None    | Inferred: stores concurrency stamp data. Representative values masked (sensitive or identifying field).                                        |
| PhoneNumber        | nvarchar(max) | Yes      | None             | None    | Inferred: stores phone number data. Profile: 154/154 rows are null or blank. Representative values masked (sensitive or identifying field).    |

| Column Name          | Data Type         | Nullable | Key / Constraint | Default | Description                                                                                                                   |
|----------------------|-------------------|----------|------------------|---------|-------------------------------------------------------------------------------------------------------------------------------|
| PhoneNumberConfirmed | bit               | No       | None             | None    | Inferred: stores phone number confirmed data. Representative values masked (sensitive or identifying field).                  |
| TwoFactorEnabled     | bit               | No       | None             | None    | Inferred: stores two factor enabled data. Profile: 1 distinct non-null values. Representative values: 0 (154).                |
| LockoutEnd           | datetimeoffset(7) | Yes      | None             | None    | Inferred: stores lockout end data. Profile: 154/154 rows are null or blank; 0 distinct non-null values.                       |
| LockoutEnabled       | bit               | No       | None             | None    | Inferred: stores lockout enabled data. Profile: 1 distinct non-null values. Representative values: 1 (154).                   |
| AccessFailedCount    | int               | No       | None             | None    | Inferred: stores access failed count data. Profile: 1 distinct non-null values; range 0 to 0. Representative values: 0 (154). |

## Relationships

- Enforced one-to-many parent for dbo.AspNetUserClaims through FK\_AspNetUserClaims\_AspNetUsers\_UserId.
- Enforced one-to-many parent for dbo.AspNetUserLogins through FK\_AspNetUserLogins\_AspNetUsers\_UserId.
- Enforced one-to-many parent for dbo.AspNetUserRoles through FK\_AspNetUserRoles\_AspNetUsers\_UserId.
- Enforced one-to-many parent for dbo.AspNetUserTokens through FK\_AspNetUserTokens\_AspNetUsers\_UserId.

## Data Analysis

Business-critical or frequently joined/filterable columns: Id, CentreCode.

- Highest null/blank counts: PhoneNumber 154/154, LockoutEnd 154/154.
- The primary key prevents duplicate full rows and duplicate key values.
- 154 users exist while the standard role, role-claim, user-role, user-claim, login and token tables are empty.
- Authorization appears to rely on the custom UserType/CentreCode fields or external Windows authentication; verify intended policy.
- 6 column(s) use nvarchar(max), limiting type precision and potentially increasing storage/indexing cost.

## Data Quality Observations

17 of 19 columns have no null/blank values in the current data. Representative values in the column table are frequency-based and masked for sensitive fields.

## Important Findings

- No additional table-specific structural risk was identified beyond the database-wide recommendations.

## 9. dbo.AspNetUserTokens

### Table Overview

**Confirmed standard framework schema.** Standard ASP.NET Core Identity table for user tokens data.

Role classification: Security / identity.

### Table Statistics

| Measure                      | Value                       |
|------------------------------|-----------------------------|
| Total records                | 0                           |
| Columns                      | 4                           |
| Primary key                  | UserId, LoginProvider, Name |
| Enforced foreign-key columns | 1                           |
| Created                      | 2025-09-15T10:48:35         |
| Last schema modification     | 2025-09-15T10:48:35         |

### Column Details

| Column Name   | Data Type     | Nullable | Key / Constraint               | Default | Description                                               |
|---------------|---------------|----------|--------------------------------|---------|-----------------------------------------------------------|
| UserId        | nvarchar(450) | No       | PK#1; FK -> dbo.AspNetUsers.Id | None    | Inferred: stores user id data.                            |
| LoginProvider | nvarchar(450) | No       | PK#2                           | None    | Inferred: stores login provider data.                     |
| Name          | nvarchar(450) | No       | PK#3                           | None    | Inferred: stores name data.                               |
| Value         | nvarchar(max) | Yes      | None                           | None    | Display label or decoded meaning for the associated code. |

### Relationships

- Enforced many-to-one: dbo.AspNetUserTokens.UserId -> dbo.AspNetUsers.Id (ON DELETE CASCADE; ON UPDATE NO\_ACTION).

### Data Analysis

Business-critical or frequently joined/filterable columns: UserId, LoginProvider, Name.

- The table is empty at the profiling timestamp; value distributions and duplicates cannot be assessed.

- The primary key prevents duplicate full rows and duplicate key values.
- 1 column(s) use nvarchar(max), limiting type precision and potentially increasing storage/indexing cost.

### Data Quality Observations

Confirmed: no rows are present; completeness, consistency and representative-value checks are not applicable.

### Important Findings

- The table is inactive/empty at the profiling timestamp; confirm whether it is planned, legacy or awaiting data.

## 10. dbo.BasisOfDiagnosisList

### Table Overview

**Purpose inferred from table and column names.** Code/value or geographic reference data for basis of diagnosis.

Role classification: Reference / classification.

### Table Statistics

| Measure                      | Value               |
|------------------------------|---------------------|
| Total records                | 8                   |
| Columns                      | 2                   |
| Primary key                  | None                |
| Enforced foreign-key columns | 0                   |
| Created                      | 2025-09-15T10:48:17 |
| Last schema modification     | 2025-09-15T10:48:17 |

### Column Details

| Column Name | Data Type     | Nullable | Key / Constraint | Default | Description                                                                                                                                                                                                 |
|-------------|---------------|----------|------------------|---------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Code        | nvarchar(max) | Yes      | None             | None    | Stored category or classification code. Profile: 8 distinct non-null values. Representative values: 0 (1); 1 (1); 2 (1).                                                                                    |
| Value       | nvarchar(max) | Yes      | None             | None    | Display label or decoded meaning for the associated code. Profile: 8 distinct non-null values. Representative values: Clinical (1); Cytology (Peripheral blood/Bone marrow (1); Death Certificate only (1). |

## Relationships

- Probable semantic code/value lookup for TumourTable.BasisOfDiagnosis, based on matching domain names; not enforced by a foreign key.

## Data Analysis

Business-critical or frequently joined/filterable columns: Code.

- No null or blank values were found in profiled columns.
- Code values are unique in the current data, but no PK/UNIQUE constraint enforces that condition.
- 2 column(s) use nvarchar(max), limiting type precision and potentially increasing storage/indexing cost.

## Data Quality Observations

2 of 2 columns have no null/blank values in the current data. Representative values in the column table are frequency-based and masked for sensitive fields.

## Important Findings

- No primary key is defined.
- Application-level relationships exist without FK enforcement.

## 11. dbo.BehaviourList

### Table Overview

**Purpose inferred from table and column names.** Code/value or geographic reference data for behaviour.

Role classification: Reference / classification.

### Table Statistics

| Measure                      | Value               |
|------------------------------|---------------------|
| Total records                | 4                   |
| Columns                      | 2                   |
| Primary key                  | None                |
| Enforced foreign-key columns | 0                   |
| Created                      | 2025-09-15T10:48:17 |
| Last schema modification     | 2025-09-15T10:48:17 |



## Column Details

| Column Name | Data Type     | Nullable | Key / Constraint | Default | Description                                                                                                                                                   |
|-------------|---------------|----------|------------------|---------|---------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Code        | nvarchar(max) | Yes      | None             | None    | Stored category or classification code. Profile: 4 distinct non-null values. Representative values: 0 (1); 1 (1); 2 (1).                                      |
| Value       | nvarchar(max) | Yes      | None             | None    | Display label or decoded meaning for the associated code. Profile: 4 distinct non-null values. Representative values: Benign (1); In situ (1); Malignant (1). |

## Relationships

- Probable semantic code/value lookup for TumourTable.Behaviour, based on matching domain names; not enforced by a foreign key.

## Data Analysis

Business-critical or frequently joined/filterable columns: Code.

- No null or blank values were found in profiled columns.
- Code values are unique in the current data, but no PK/UNIQUE constraint enforces that condition.
- 2 column(s) use nvarchar(max), limiting type precision and potentially increasing storage/indexing cost.

## Data Quality Observations

2 of 2 columns have no null/blank values in the current data. Representative values in the column table are frequency-based and masked for sensitive fields.

## Important Findings

- No primary key is defined.
- Application-level relationships exist without FK enforcement.

## 12. dbo.BlockList

### Table Overview

**Purpose inferred from table and column names.** Block-level geographic master keyed to state and district codes.

Role classification: Reference / classification.

## Table Statistics

| Measure                      | Value               |
|------------------------------|---------------------|
| Total records                | 317                 |
| Columns                      | 5                   |
| Primary key                  | Id                  |
| Enforced foreign-key columns | 0                   |
| Created                      | 2025-09-15T10:48:17 |
| Last schema modification     | 2025-09-15T10:48:17 |

## Column Details

| Column Name | Data Type     | Nullable | Key / Constraint    | Default | Description                                                                                                                           |
|-------------|---------------|----------|---------------------|---------|---------------------------------------------------------------------------------------------------------------------------------------|
| Id          | int           | No       | PK#1; IDENTITY(1,1) | None    | Internal row identifier. Profile: 317 distinct non-null values; range 4 to 320. Representative values: 10 (1); 100 (1); 101 (1).      |
| StateId     | nvarchar(max) | Yes      | None                | None    | State master code. Profile: 1 distinct non-null values. Representative values: 1 (317).                                               |
| DistrictId  | nvarchar(max) | Yes      | None                | None    | District master code. Profile: 30 distinct non-null values. Representative values: 122 (26); 110 (23); 130 (18).                      |
| BlockId     | nvarchar(max) | Yes      | None                | None    | Block master code. Profile: 317 distinct non-null values. Representative values: 10101 (1); 10102 (1); 10103 (1).                     |
| BlockName   | nvarchar(max) | Yes      | None                | None    | Inferred: stores block name data. Profile: 317 distinct non-null values. Representative values: Aali (1); Agalpur (1); Ambabhona (1). |

## Relationships

- Logical child of DistrictList and parent of VillageList; 310 VillageList rows reference a BlockId absent from BlockList.

## Data Analysis

Business-critical or frequently joined/filterable columns: Id, StateId, DistrictId, BlockId.

- No null or blank values were found in profiled columns.
- The primary key prevents duplicate full rows and duplicate key values.
- 4 column(s) use nvarchar(max), limiting type precision and potentially increasing storage/indexing cost.

Data Quality Observations

5 of 5 columns have no null/blank values in the current data. Representative values in the column table are frequency-based and masked for sensitive fields.

Important Findings

- Application-level relationships exist without FK enforcement.

13. dbo.CauseOfDeathList

Table Overview

**Purpose inferred from table and column names.** Code/value or geographic reference data for cause of death.

Role classification: Reference / classification.

Table Statistics

| Measure                      | Value               |
|------------------------------|---------------------|
| Total records                | 3                   |
| Columns                      | 2                   |
| Primary key                  | None                |
| Enforced foreign-key columns | 0                   |
| Created                      | 2025-09-15T10:48:18 |
| Last schema modification     | 2025-09-15T10:48:18 |

Column Details

| Column Name | Data Type     | Nullable | Key / Constraint | Default | Description                                                                                                                                                |
|-------------|---------------|----------|------------------|---------|------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Code        | nvarchar(max) | Yes      | None             | None    | Stored category or classification code. Profile: 3 distinct non-null values. Representative values: 1 (1); 2 (1); 4 (1).                                   |
| Value       | nvarchar(max) | Yes      | None             | None    | Display label or decoded meaning for the associated code. Profile: 3 distinct non-null values. Representative values: Cancer (1); Others (1); Unknown (1). |

Relationships

- Probable semantic code/value lookup for PatientTable.CauseOfDeath, based on matching domain names; not enforced by a foreign key.

## Data Analysis

Business-critical or frequently joined/filterable columns: Code.

- No null or blank values were found in profiled columns.
- Code values are unique in the current data, but no PK/UNIQUE constraint enforces that condition.
- 2 column(s) use nvarchar(max), limiting type precision and potentially increasing storage/indexing cost.

## Data Quality Observations

2 of 2 columns have no null/blank values in the current data. Representative values in the column table are frequency-based and masked for sensitive fields.

## Important Findings

- No primary key is defined.
- Application-level relationships exist without FK enforcement.

## 14. dbo.Centres

### Table Overview

**Purpose inferred from table and column names.** Master list of participating centres and their geographic codes.

Role classification: Operational master.

### Table Statistics

| Measure                      | Value               |
|------------------------------|---------------------|
| Total records                | 31                  |
| Columns                      | 8                   |
| Primary key                  | Id                  |
| Enforced foreign-key columns | 0                   |
| Created                      | 2025-09-15T10:48:18 |
| Last schema modification     | 2025-09-15T10:48:18 |

### Column Details

| Column Name | Data Type | Nullable | Key / Constraint    | Default | Description                                                                                                                 |
|-------------|-----------|----------|---------------------|---------|-----------------------------------------------------------------------------------------------------------------------------|
| Id          | int       | No       | PK#1; IDENTITY(1,1) | None    | Internal row identifier. Profile: 31 distinct non-null values; range 1 to 73. Representative values: 1 (1); 44 (1); 45 (1). |

| Column Name | Data Type     | Nullable | Key / Constraint | Default | Description                                                                                                                                        |
|-------------|---------------|----------|------------------|---------|----------------------------------------------------------------------------------------------------------------------------------------------------|
| CentreCode  | nvarchar(max) | Yes      | None             | None    | Code identifying the participating registry centre. Profile: 31 distinct non-null values. Representative values: C000 (1); C001 (1); C002 (1).     |
| CentreName  | nvarchar(max) | Yes      | None             | None    | Inferred: stores centre name data. Profile: 31 distinct non-null values. Representative values: DHH Angul (1); DHH Balangir (1); DHH Balasore (1). |
| CentreType  | nvarchar(max) | Yes      | None             | None    | Inferred: stores centre type data. Profile: 1 distinct non-null values. Representative values: HOSPITAL (31).                                      |
| StateId     | nvarchar(max) | Yes      | None             | None    | State master code. Profile: 1/31 rows are null or blank; 1 distinct non-null values. Representative values: 1 (30).                                |
| DistrictId  | nvarchar(max) | Yes      | None             | None    | District master code. Profile: 1/31 rows are null or blank; 30 distinct non-null values. Representative values: 101 (1); 102 (1); 103 (1).         |
| BlockId     | nvarchar(max) | Yes      | None             | None    | Block master code. Profile: 1/31 rows are null or blank; 30 distinct non-null values. Representative values: 10101 (1); 10201 (1); 10302 (1).      |
| VillageId   | nvarchar(max) | Yes      | None             | None    | Village master code. Profile: 1/31 rows are null or blank. Representative values masked (sensitive or identifying field).                          |

## Relationships

- Logically references StateList, DistrictList, BlockList and VillageList by stored geographic codes; no database FKs enforce these links.

## Data Analysis

Business-critical or frequently joined/filterable columns: Id, CentreCode, StateId, DistrictId, BlockId, VillageId.

- Highest null/blank counts: VillageId 1/31, StateId 1/31, DistrictId 1/31, BlockId 1/31.
- The primary key prevents duplicate full rows and duplicate key values.
- 7 column(s) use nvarchar(max), limiting type precision and potentially increasing storage/indexing cost.

## Data Quality Observations

4 of 8 columns have no null/blank values in the current data. Representative values in the column table are frequency-based and masked for sensitive fields.

## Important Findings

- Application-level relationships exist without FK enforcement.

## 15. dbo.CentreTypeList

### Table Overview

**Purpose inferred from table and column names.** Code/value or geographic reference data for centre type.

Role classification: Reference / classification.

### Table Statistics

| Measure                      | Value               |
|------------------------------|---------------------|
| Total records                | 3                   |
| Columns                      | 2                   |
| Primary key                  | None                |
| Enforced foreign-key columns | 0                   |
| Created                      | 2025-09-15T10:48:18 |
| Last schema modification     | 2025-09-15T10:48:18 |

### Column Details

| Column Name | Data Type     | Nullable | Key / Constraint | Default | Description                                                                                                                                                              |
|-------------|---------------|----------|------------------|---------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Code        | nvarchar(max) | Yes      | None             | None    | Stored category or classification code. Profile: 3 distinct non-null values. Representative values: DEATH-REGISTRAR (1); HOSPITAL (1); LABORATORY (1).                   |
| Value       | nvarchar(max) | Yes      | None             | None    | Display label or decoded meaning for the associated code. Profile: 3 distinct non-null values. Representative values: DEATH-REGISTRAR (1); HOSPITAL (1); LABORATORY (1). |

### Relationships

- Probable semantic code/value lookup for Centres.CentreType, based on matching domain names; not enforced by a foreign key.

### Data Analysis

Business-critical or frequently joined/filterable columns: Code.

- No null or blank values were found in profiled columns.
- Code values are unique in the current data, but no PK/UNIQUE constraint enforces that condition.
- 2 column(s) use nvarchar(max), limiting type precision and potentially increasing storage/indexing cost.

Data Quality Observations

2 of 2 columns have no null/blank values in the current data. Representative values in the column table are frequency-based and masked for sensitive fields.

Important Findings

- No primary key is defined.
- Application-level relationships exist without FK enforcement.

16. dbo.ClinicalStageList

Table Overview

**Purpose inferred from table and column names.** Code/value or geographic reference data for clinical stage.

Role classification: Reference / classification.

Table Statistics

| Measure                      | Value               |
|------------------------------|---------------------|
| Total records                | 8                   |
| Columns                      | 2                   |
| Primary key                  | None                |
| Enforced foreign-key columns | 0                   |
| Created                      | 2025-09-15T10:48:18 |
| Last schema modification     | 2025-09-15T10:48:18 |

Column Details

| Column Name | Data Type     | Nullable | Key / Constraint | Default | Description                                                                                                                                                                                                               |
|-------------|---------------|----------|------------------|---------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Code        | nvarchar(max) | Yes      | None             | None    | Stored category or classification code. Profile: 8 distinct non-null values. Representative values: 1 (1); 2 (1); 3 (1).                                                                                                  |
| Value       | nvarchar(max) | Yes      | None             | None    | Display label or decoded meaning for the associated code. Profile: 8 distinct non-null values. Representative values: Direct Extension (1); Direct extension with regional node involvement (1); Distance metastasis (1). |

Relationships

- Probable semantic code/value lookup for TumourTable.ClinicalStage, based on matching domain names; not enforced by a foreign key.

## Data Analysis

Business-critical or frequently joined/filterable columns: Code.

- No null or blank values were found in profiled columns.
- Code values are unique in the current data, but no PK/UNIQUE constraint enforces that condition.
- 2 column(s) use nvarchar(max), limiting type precision and potentially increasing storage/indexing cost.

## Data Quality Observations

2 of 2 columns have no null/blank values in the current data. Representative values in the column table are frequency-based and masked for sensitive fields.

## Important Findings

- No primary key is defined.
- Application-level relationships exist without FK enforcement.

## 17. dbo.DeletedPatientTable

### Table Overview

**Purpose inferred from table and column names.** Archives deleted patient rows together with deletion and audit metadata.

Role classification: Archive / deletion audit.

### Table Statistics

| Measure                      | Value               |
|------------------------------|---------------------|
| Total records                | 25                  |
| Columns                      | 37                  |
| Primary key                  | Id                  |
| Enforced foreign-key columns | 0                   |
| Created                      | 2025-09-18T11:46:31 |
| Last schema modification     | 2025-09-18T11:46:31 |

### Column Details

| Column Name | Data Type | Nullable | Key / Constraint    | Default | Description                                                                                                        |
|-------------|-----------|----------|---------------------|---------|--------------------------------------------------------------------------------------------------------------------|
| Id          | int       | No       | PK#1; IDENTITY(1,1) | None    | Internal row identifier. Profile: range 47 to 1054. Representative values masked (sensitive or identifying field). |



| Column Name              | Data Type     | Nullable | Key / Constraint | Default | Description                                                                                                                                                    |
|--------------------------|---------------|----------|------------------|---------|----------------------------------------------------------------------------------------------------------------------------------------------------------------|
| REGNO                    | nvarchar(max) | Yes      | None             | None    | Registry number used as the logical patient link. Representative values masked (sensitive or identifying field).                                               |
| OBSOLETEFLAGPATIENTTABLE | nvarchar(max) | Yes      | None             | None    | Inferred: stores obsoleteflagpatienttable data. Profile: 25/25 rows are null or blank; 0 distinct non-null values.                                             |
| PATIENTRECORDID          | nvarchar(max) | Yes      | None             | None    | Inferred: stores patientrecordid data. Representative values masked (sensitive or identifying field).                                                          |
| PATIENTUPDATEDBY         | nvarchar(max) | Yes      | None             | None    | Inferred: stores patientupdatedby data. Representative values masked (sensitive or identifying field).                                                         |
| PATIENTUPDATEDDATE       | nvarchar(max) | Yes      | None             | None    | Inferred: stores patientupdateddate data. Profile: 10 distinct non-null values. Representative values: 20260530 (10); 20260513 (5); 20260325 (2).              |
| PATIENTRECORDSTATUS      | nvarchar(max) | Yes      | None             | None    | Inferred: stores patientrecordstatus data. Profile: 25/25 rows are null or blank; 0 distinct non-null values.                                                  |
| PATIENTCHECKSTATUS       | nvarchar(max) | Yes      | None             | None    | Inferred: stores patientcheckstatus data. Profile: 25/25 rows are null or blank; 0 distinct non-null values.                                                   |
| CentreCode               | nvarchar(max) | Yes      | None             | None    | Code identifying the participating registry centre. Profile: 9 distinct non-null values. Representative values: C005 (10); C023 (5); C010 (3).                 |
| RegistrationNumber       | nvarchar(max) | Yes      | None             | None    | Inferred: stores registration number data. Profile: 11/25 rows are null or blank; 15 distinct non-null values. Representative values: 03458999 (1); 12706 (1). |
| Name                     | nvarchar(max) | Yes      | None             | None    | Inferred: stores name data. Representative values masked (sensitive or identifying field).                                                                     |
| Sex                      | int           | Yes      | None             | None    | Inferred: stores sex data. Profile: 2 distinct non-null values; range 1 to 2. Representative values: 1 (14); 2 (11).                                           |
| ContactNumber            | float         | Yes      | None             | None    | Inferred: stores contact number data. Profile: range 458577 to 999999999999. Representative values masked (sensitive or identifying field).                    |
| NationalIDCardNumber     | nvarchar(max) | Yes      | None             | None    | Inferred: stores national id card number data. Representative values masked (sensitive or identifying field).                                                  |
| State                    | nvarchar(max) | Yes      | None             | None    | Inferred: stores state data. Profile: 1 distinct non-null values. Representative values: 1 (25).                                                               |
| District                 | nvarchar(max) | Yes      | None             | None    | Inferred: stores district data. Profile: 1/25 rows are null or blank; 11 distinct non-null values. Representative values: 123 (10); 117 (3); 121 (3).          |
| Block                    | nvarchar(max) | Yes      | None             | None    | Inferred: stores block data. Profile: 1/25 rows are null or blank; 18 distinct non-null values. Representative values: 12309 (3); 10905 (2); 11705 (2).        |
| Village                  | nvarchar(max) | Yes      | None             | None    | Inferred: stores village data. Profile: 3/25 rows are null or blank. Representative values masked (sensitive or identifying field).                            |
| Address                  | nvarchar(max) | Yes      | None             | None    | Inferred: stores address data. Profile: 4/25 rows are null or blank. Representative values masked (sensitive or identifying field).                            |

| Column Name        | Data Type     | Nullable | Key / Constraint | Default | Description                                                                                                                                                                                                                                       |
|--------------------|---------------|----------|------------------|---------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Area               | nvarchar(max) | Yes      | None             | None    | Inferred: stores area data. Profile: 3 distinct non-null values. Representative values: 2 (17); 1 (7); 3 (1).                                                                                                                                     |
| DateOfBirth        | nvarchar(max) | Yes      | None             | None    | Inferred: stores date of birth data. Profile: 3/25 rows are null or blank. Representative values masked (sensitive or identifying field).                                                                                                         |
| DayDateOfBirth     | nvarchar(max) | Yes      | None             | None    | Inferred: stores day date of birth data. Profile: 3/25 rows are null or blank. Representative values masked (sensitive or identifying field).                                                                                                     |
| MonthDateOfBirth   | nvarchar(max) | Yes      | None             | None    | Inferred: stores month date of birth data. Profile: 3/25 rows are null or blank. Representative values masked (sensitive or identifying field).                                                                                                   |
| YearDateOfBirth    | nvarchar(max) | Yes      | None             | None    | Inferred: stores year date of birth data. Profile: 3/25 rows are null or blank. Representative values masked (sensitive or identifying field).                                                                                                    |
| VitalStatus        | nvarchar(max) | Yes      | None             | None    | Inferred: stores vital status data. Profile: 2 distinct non-null values. Representative values: 1 (19); 2 (6).                                                                                                                                    |
| DateOfDeath        | nvarchar(max) | Yes      | None             | None    | Inferred: stores date of death data. Profile: 19/25 rows are null or blank. Representative values masked (sensitive or identifying field).                                                                                                        |
| DayDateOfDeath     | nvarchar(max) | Yes      | None             | None    | Inferred: stores day date of death data. Profile: 19/25 rows are null or blank. Representative values masked (sensitive or identifying field).                                                                                                    |
| MonthDateOfDeath   | nvarchar(max) | Yes      | None             | None    | Inferred: stores month date of death data. Profile: 19/25 rows are null or blank. Representative values masked (sensitive or identifying field).                                                                                                  |
| YearDateOfDeath    | nvarchar(max) | Yes      | None             | None    | Inferred: stores year date of death data. Profile: 19/25 rows are null or blank. Representative values masked (sensitive or identifying field).                                                                                                   |
| AgeAtDeath         | int           | Yes      | None             | None    | Inferred: stores age at death data. Profile: 19/25 rows are null or blank; 5 distinct non-null values; range 5 to 61. Representative values: 36 (2); 31 (1); 38 (1).                                                                              |
| CauseOfDeath       | nvarchar(max) | Yes      | None             | None    | Inferred: stores cause of death data. Profile: 19/25 rows are null or blank; 2 distinct non-null values. Representative values: 1 (6).                                                                                                            |
| Remarks            | nvarchar(max) | Yes      | None             | None    | Inferred: stores remarks data. Profile: 23/25 rows are null or blank. Representative values masked (sensitive or identifying field).                                                                                                              |
| DEOName            | nvarchar(max) | Yes      | None             | None    | Inferred: stores deo name data. Representative values masked (sensitive or identifying field).                                                                                                                                                    |
| DEODate            | datetime2(7)  | Yes      | None             | None    | Inferred: stores deo date data. Profile: 25 distinct non-null values; range 2026-03-17T12:07:30 to 2026-06-01T10:39:59. Representative values: 2026-03-17 12:07:30.3266667 (1); 2026-03-25 11:41:49.9466667 (1); 2026-03-25 11:55:18.5866667 (1). |
| LastModifiedByName | nvarchar(max) | Yes      | None             | None    | Inferred: stores last modified by name data. Profile: 24/25 rows are null or blank. Representative values masked (sensitive or identifying field).                                                                                                |
| LastModifiedDate   | datetime2(7)  | Yes      | None             | None    | Latest recorded modification timestamp. Profile: 24/25 rows are null or blank; 1 distinct non-null values; range 2026-03-25T11:56:13 to 2026-03-25T11:56:13. Representative values: 2026-03-25 11:56:13.0966667 (1).                              |

| Column Name | Data Type    | Nullable | Key / Constraint | Default | Description                                                                                                                                                                                                                                   |
|-------------|--------------|----------|------------------|---------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| DeletedDate | datetime2(7) | Yes      | None             | None    | Deletion/archive timestamp. Profile: 25 distinct non-null values; range 2026-03-25T11:44:40 to 2026-06-18T11:11:27. Representative values: 2026-03-25 11:44:40.9400000 (1); 2026-03-25 11:56:50.8633333 (1); 2026-04-24 16:07:51.6400000 (1). |

## Relationships

- No enforced or validated logical relationships were identified for this table.

## Data Analysis

Business-critical or frequently joined/filterable columns: Id, REGNO, PATIENTRECORDID, PATIENTUPDATEDBY, PATIENTUPDATEDATE, PATIENTRECORDSTATUS, PATIENTCHECKSTATUS, CentreCode, DateOfBirth, DayDateOfBirth, MonthDateOfBirth, YearDateOfBirth.

- Highest null/blank counts: PATIENTRECORDSTATUS 25/25, PATIENTCHECKSTATUS 25/25, OBSOLETEFLAGPATIENTTABLE 25/25, LastModifiedDate 24/25, LastModifiedByName 24/25.
- The primary key prevents duplicate full rows and duplicate key values.
- 30 column(s) use nvarchar(max), limiting type precision and potentially increasing storage/indexing cost.

## Data Quality Observations

16 of 37 columns have no null/blank values in the current data. Representative values in the column table are frequency-based and masked for sensitive fields.

## Important Findings

- Application-level relationships exist without FK enforcement.

## 18. dbo.DeletedSourceTable

### Table Overview

**Purpose inferred from table and column names.** Archives deleted source rows together with deletion and audit metadata.

Role classification: Archive / deletion audit.

## Table Statistics

| Measure                      | Value               |
|------------------------------|---------------------|
| Total records                | 25                  |
| Columns                      | 13                  |
| Primary key                  | Id                  |
| Enforced foreign-key columns | 0                   |
| Created                      | 2025-09-15T10:48:19 |
| Last schema modification     | 2025-09-15T11:47:24 |

## Column Details

| Column Name         | Data Type     | Nullable | Key / Constraint    | Default | Description                                                                                                                                  |
|---------------------|---------------|----------|---------------------|---------|----------------------------------------------------------------------------------------------------------------------------------------------|
| Id                  | int           | No       | PK#1; IDENTITY(1,1) | None    | Internal row identifier. Profile: 25 distinct non-null values; range 328 to 1335. Representative values: 1332 (1); 1333 (1); 1334 (1).       |
| REGNO               | nvarchar(max) | Yes      | None                | None    | Registry number used as the logical patient link. Representative values masked (sensitive or identifying field).                             |
| TUMOURID            | nvarchar(max) | Yes      | None                | None    | Logical tumour identifier. Representative values masked (sensitive or identifying field).                                                    |
| SOURCEID            | nvarchar(max) | Yes      | None                | None    | Logical source-record identifier. Representative values masked (sensitive or identifying field).                                             |
| TUMOURIDSOURCETABLE | nvarchar(max) | Yes      | None                | None    | Tumour key used to link source rows to TumourTable.TUMOURID. Representative values masked (sensitive or identifying field).                  |
| SOURCERECORDID      | nvarchar(max) | Yes      | None                | None    | Inferred: stores source record id data. Representative values masked (sensitive or identifying field).                                       |
| TypeOfSource        | nvarchar(max) | Yes      | None                | None    | Inferred: stores type of source data. Profile: 1 distinct non-null values. Representative values: HOSPITAL (25).                             |
| SourceCentre        | nvarchar(max) | Yes      | None                | None    | Inferred: stores source centre data. Profile: 9 distinct non-null values. Representative values: C005 (10); C023 (5); C010 (3).              |
| CaseFileNumber      | nvarchar(max) | Yes      | None                | None    | Inferred: stores case file number data. Profile: 7/25 rows are null or blank. Representative values masked (sensitive or identifying field). |
| SourceRemarks       | nvarchar(max) | Yes      | None                | None    | Inferred: stores source remarks data. Profile: 10/25 rows are null or blank. Representative values masked (sensitive or identifying field).  |
| TumourNumber        | nvarchar(max) | Yes      | None                | None    | Inferred: stores tumour number data. Profile: 1 distinct non-null values. Representative values: 1 (25).                                     |
| SourceNumber        | nvarchar(max) | Yes      | None                | None    | Inferred: stores source number data. Profile: 1 distinct non-null values. Representative values: 1 (25).                                     |

| Column Name | Data Type    | Nullable | Key / Constraint | Default | Description                                                                                                                                                                                                                                   |
|-------------|--------------|----------|------------------|---------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| DeletedDate | datetime2(7) | Yes      | None             | None    | Deletion/archive timestamp. Profile: 25 distinct non-null values; range 2026-03-25T11:44:40 to 2026-06-18T11:11:27. Representative values: 2026-03-25 11:44:40.9233333 (1); 2026-03-25 11:56:50.8466667 (1); 2026-04-24 16:07:51.6233333 (1). |

## Relationships

- No enforced or validated logical relationships were identified for this table.

## Data Analysis

Business-critical or frequently joined/filterable columns: Id, REGNO, TUMOURID, SOURCEID, TUMOURIDSOURCETABLE, SOURCERECORDID, DeletedDate.

- Highest null/blank counts: SourceRemarks 10/25, CaseFileNumber 7/25.
- The primary key prevents duplicate full rows and duplicate key values.
- 11 column(s) use nvarchar(max), limiting type precision and potentially increasing storage/indexing cost.

## Data Quality Observations

11 of 13 columns have no null/blank values in the current data. Representative values in the column table are frequency-based and masked for sensitive fields.

## Important Findings

- Application-level relationships exist without FK enforcement.

## 19. dbo.DeletedTumourTable

### Table Overview

**Purpose inferred from table and column names.** Archives deleted tumour rows together with deletion and audit metadata.

Role classification: Archive / deletion audit.

## Table Statistics

| Measure                      | Value               |
|------------------------------|---------------------|
| Total records                | 25                  |
| Columns                      | 34                  |
| Primary key                  | Id                  |
| Enforced foreign-key columns | 0                   |
| Created                      | 2025-09-15T10:48:20 |
| Last schema modification     | 2025-11-04T14:59:00 |

## Column Details

| Column Name                | Data Type     | Nullable | Key / Constraint    | Default | Description                                                                                                                                            |
|----------------------------|---------------|----------|---------------------|---------|--------------------------------------------------------------------------------------------------------------------------------------------------------|
| Id                         | int           | No       | PK#1; IDENTITY(1,1) | None    | Internal row identifier. Profile: 25 distinct non-null values; range 78 to 1085. Representative values: 1082 (1); 1083 (1); 1084 (1).                  |
| REGNO                      | nvarchar(max) | Yes      | None                | None    | Registry number used as the logical patient link. Representative values masked (sensitive or identifying field).                                       |
| TUMOURID                   | nvarchar(max) | Yes      | None                | None    | Logical tumour identifier. Representative values masked (sensitive or identifying field).                                                              |
| RECS                       | nvarchar(max) | Yes      | None                | None    | Inferred: stores recs data. Profile: 2 distinct non-null values. Representative values: true (17); false (8).                                          |
| CHECKS                     | nvarchar(max) | Yes      | None                | None    | Inferred: stores checks data. Profile: 2 distinct non-null values. Representative values: true (17); false (8).                                        |
| MPCODE                     | nvarchar(max) | Yes      | None                | None    | Inferred: stores mpcode data. Profile: 25/25 rows are null or blank; 1 distinct non-null values.                                                       |
| MPSEQ                      | nvarchar(max) | Yes      | None                | None    | Inferred: stores mpseq data. Profile: 1 distinct non-null values. Representative values: 0 (25).                                                       |
| MPTOT                      | nvarchar(max) | Yes      | None                | None    | Inferred: stores mptot data. Profile: 1 distinct non-null values. Representative values: 1 (25).                                                       |
| UPDATE                     | nvarchar(max) | Yes      | None                | None    | Inferred: stores update data. Profile: 10 distinct non-null values. Representative values: 20260530 (10); 20260513 (5); 20260325 (2).                  |
| OBSOLETEFLAGTUMOURTABLE    | nvarchar(max) | Yes      | None                | None    | Inferred: stores obsoleteflagtumourtable data. Profile: 1 distinct non-null values. Representative values: 0 (25).                                     |
| PATIENTIDTUMOURTABLE       | nvarchar(max) | Yes      | None                | None    | Patient registry key used by the application to link tumour rows to PatientTable.REGNO. Representative values masked (sensitive or identifying field). |
| PATIENTRECORDIDTUMOURTABLE | nvarchar(max) | Yes      | None                | None    | Inferred: stores patientrecordidtumourtable data. Representative values masked (sensitive or identifying field).                                       |
| TUMOURUPDATEDBY            | nvarchar(max) | Yes      | None                | None    | Inferred: stores tumourupdatedby data. Representative values masked (sensitive or identifying field).                                                  |

| Column Name               | Data Type     | Nullable | Key / Constraint | Default | Description                                                                                                                                                                                     |
|---------------------------|---------------|----------|------------------|---------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| TUMOURUNDUPLICATIONSTATUS | nvarchar(max) | Yes      | None             | None    | Inferred: stores tumourunduplicationstatus data. Profile: 25/25 rows are null or blank; 1 distinct non-null values.                                                                             |
| Age                       | int           | Yes      | None             | None    | Inferred: stores age data. Profile: 6/25 rows are null or blank; 18 distinct non-null values; range 4 to 74. Representative values: 35 (2); 27 (1); 28 (1).                                     |
| DateOfDiagnosis           | nvarchar(max) | Yes      | None             | None    | Inferred: stores date of diagnosis data. Profile: 6/25 rows are null or blank; 17 distinct non-null values. Representative values: 20240101 (2); 20250327 (2); 20171220 (1).                    |
| DayDateOfDiagnosis        | nvarchar(max) | Yes      | None             | None    | Inferred: stores day date of diagnosis data. Profile: 6/25 rows are null or blank; 13 distinct non-null values. Representative values: 9 (3); 1 (2).                                            |
| MonthDateOfDiagnosis      | nvarchar(max) | Yes      | None             | None    | Inferred: stores month date of diagnosis data. Profile: 6/25 rows are null or blank; 11 distinct non-null values. Representative values: 1 (5); 12 (4).                                         |
| YearDateOfDiagnosis       | nvarchar(max) | Yes      | None             | None    | Inferred: stores year date of diagnosis data. Profile: 6/25 rows are null or blank; 8 distinct non-null values. Representative values: 2025 (8); 2024 (4).                                      |
| BasisOfDiagnosis          | nvarchar(max) | Yes      | None             | None    | Inferred: stores basis of diagnosis data. Profile: 6/25 rows are null or blank; 6 distinct non-null values. Representative values: 1 (6); 7 (6).                                                |
| Site                      | nvarchar(max) | Yes      | None             | None    | Inferred: stores site data. Profile: 6/25 rows are null or blank; 11 distinct non-null values. Representative values: 16 (4); 42 (4).                                                           |
| PrimarySite               | nvarchar(max) | Yes      | None             | None    | Inferred: stores primary site data. Profile: 6/25 rows are null or blank; 14 distinct non-null values. Representative values: 169 (3); 421 (3).                                                 |
| SubSite                   | nvarchar(max) | Yes      | None             | None    | Inferred: stores sub site data. Profile: 6/25 rows are null or blank; 14 distinct non-null values. Representative values: 169 (3); 421 (3).                                                     |
| Histology                 | nvarchar(max) | Yes      | None             | None    | Inferred: stores histology data. Profile: 6/25 rows are null or blank; 13 distinct non-null values. Representative values: 8010 - Carcinoma, NOS (5); 9863 - Chronic myeloid leukemia, NOS (3). |
| GradeCellType             | nvarchar(max) | Yes      | None             | None    | Inferred: stores grade cell type data. Profile: 11/25 rows are null or blank; 5 distinct non-null values. Representative values: 9 (6); 3 (4).                                                  |
| Behaviour                 | nvarchar(max) | Yes      | None             | None    | Inferred: stores behaviour data. Profile: 6/25 rows are null or blank; 3 distinct non-null values. Representative values: 3 (18); 0 (1).                                                        |
| ICD10                     | nvarchar(max) | Yes      | None             | None    | ICD-10 cancer diagnosis/site code. Profile: 6/25 rows are null or blank; 15 distinct non-null values. Representative values: C921 (3); C169 (2).                                                |
| ICCCCode                  | nvarchar(max) | Yes      | None             | None    | Inferred: stores iccc code data. Profile: 6/25 rows are null or blank; 8 distinct non-null values. Representative values: 11f (11); 1c (3).                                                     |
| Notes                     | nvarchar(max) | Yes      | None             | None    | Inferred: stores notes data. Profile: 21/25 rows are null or blank. Representative values masked (sensitive or identifying field).                                                              |
| Treatment                 | nvarchar(max) | Yes      | None             | None    | Inferred: stores treatment data. Profile: 6/25 rows are null or blank; 8 distinct non-null values. Representative values: 3 (11); 6 (3).                                                        |

| Column Name     | Data Type     | Nullable | Key / Constraint | Default | Description                                                                                                                                                                                                                                   |
|-----------------|---------------|----------|------------------|---------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| TreatmentStatus | nvarchar(max) | Yes      | None             | None    | Inferred: stores treatment status data. Profile: 6/25 rows are null or blank; 3 distinct non-null values. Representative values: 2 (14); 1 (5).                                                                                               |
| TumourNumber    | nvarchar(max) | Yes      | None             | None    | Inferred: stores tumour number data. Profile: 1 distinct non-null values. Representative values: 1 (25).                                                                                                                                      |
| DeletedDate     | datetime2(7)  | Yes      | None             | None    | Deletion/archive timestamp. Profile: 25 distinct non-null values; range 2026-03-25T11:44:40 to 2026-06-18T11:11:27. Representative values: 2026-03-25 11:44:40.9233333 (1); 2026-03-25 11:56:50.8633333 (1); 2026-04-24 16:07:51.6400000 (1). |
| ClinicalStage   | nvarchar(max) | Yes      | None             | None    | Inferred: stores clinical stage data. Profile: 7/25 rows are null or blank; 8 distinct non-null values. Representative values: 6 (5); 3 (4).                                                                                                  |

## Relationships

- No enforced or validated logical relationships were identified for this table.

## Data Analysis

Business-critical or frequently joined/filterable columns: Id, REGNO, TUMOURID, MPCODE, UPDATE, TUMOURUPDATEDBY, TUMOURUNDUPLICATIONSTATUS, DateOfDiagnosis, DayDateOfDiagnosis, MonthDateOfDiagnosis, YearDateOfDiagnosis, ICCCCode.

- Highest null/blank counts: TUMOURUNDUPLICATIONSTATUS 25/25, MPCODE 25/25, Notes 21/25, GradeCellType 11/25, ClinicalStage 7/25.
- The primary key prevents duplicate full rows and duplicate key values.
- 31 column(s) use nvarchar(max), limiting type precision and potentially increasing storage/indexing cost.

## Data Quality Observations

14 of 34 columns have no null/blank values in the current data. Representative values in the column table are frequency-based and masked for sensitive fields.

## Important Findings

- Application-level relationships exist without FK enforcement.

## 20. dbo.DiagnosisAtRegistrationList

### Table Overview

**Purpose inferred from table and column names.** Code/value or geographic reference data for diagnosis at registration.



Role classification: Reference / classification.

### Table Statistics

| Measure                      | Value               |
|------------------------------|---------------------|
| Total records                | 0                   |
| Columns                      | 2                   |
| Primary key                  | None                |
| Enforced foreign-key columns | 0                   |
| Created                      | 2025-09-15T10:48:22 |
| Last schema modification     | 2025-09-15T10:48:22 |

### Column Details

| Column Name | Data Type     | Nullable | Key / Constraint | Default | Description                                               |
|-------------|---------------|----------|------------------|---------|-----------------------------------------------------------|
| Code        | nvarchar(max) | Yes      | None             | None    | Stored category or classification code.                   |
| Value       | nvarchar(max) | Yes      | None             | None    | Display label or decoded meaning for the associated code. |

### Relationships

- No enforced or validated logical relationships were identified for this table.

### Data Analysis

Business-critical or frequently joined/filterable columns: Code.

- The table is empty at the profiling timestamp; value distributions and duplicates cannot be assessed.
- 2 column(s) use nvarchar(max), limiting type precision and potentially increasing storage/indexing cost.

### Data Quality Observations

Confirmed: no rows are present; completeness, consistency and representative-value checks are not applicable.

### Important Findings

- No primary key is defined.
- Application-level relationships exist without FK enforcement.
- The table is inactive/empty at the profiling timestamp; confirm whether it is planned, legacy or awaiting data.

## 21. dbo.DistrictList

### Table Overview

**Purpose inferred from table and column names.** District-level geographic master keyed to state codes.

Role classification: Reference / classification.

### Table Statistics

| Measure                      | Value               |
|------------------------------|---------------------|
| Total records                | 30                  |
| Columns                      | 4                   |
| Primary key                  | Id                  |
| Enforced foreign-key columns | 0                   |
| Created                      | 2025-09-15T10:48:22 |
| Last schema modification     | 2025-09-15T10:48:22 |

### Column Details

| Column Name  | Data Type     | Nullable | Key / Constraint    | Default | Description                                                                                                                              |
|--------------|---------------|----------|---------------------|---------|------------------------------------------------------------------------------------------------------------------------------------------|
| Id           | int           | No       | PK#1; IDENTITY(1,1) | None    | Internal row identifier. Profile: 30 distinct non-null values; range 2 to 31. Representative values: 10 (1); 11 (1); 12 (1).             |
| StateId      | nvarchar(max) | Yes      | None                | None    | State master code. Profile: 1 distinct non-null values. Representative values: 1 (30).                                                   |
| DistrictId   | nvarchar(max) | Yes      | None                | None    | District master code. Profile: 30 distinct non-null values. Representative values: 101 (1); 102 (1); 103 (1).                            |
| DistrictName | nvarchar(max) | Yes      | None                | None    | Inferred: stores district name data. Profile: 30 distinct non-null values. Representative values: Angul (1); Balangir (1); Balasore (1). |

### Relationships

- Logical child of StateList and parent of BlockList; all current block district codes matched.

### Data Analysis

Business-critical or frequently joined/filterable columns: Id, StateId, DistrictId.

- No null or blank values were found in profiled columns.
- The primary key prevents duplicate full rows and duplicate key values.
- 3 column(s) use nvarchar(max), limiting type precision and potentially increasing storage/indexing cost.

Data Quality Observations

4 of 4 columns have no null/blank values in the current data. Representative values in the column table are frequency-based and masked for sensitive fields.

Important Findings

- Application-level relationships exist without FK enforcement.

22. dbo.DurationDateOfDiagnosisToDateOfDeathList

Table Overview

**Purpose inferred from table and column names.** Code/value or geographic reference data for duration date of diagnosis to date of death.

Role classification: Reference / classification.

Table Statistics

| Measure                      | Value               |
|------------------------------|---------------------|
| Total records                | 0                   |
| Columns                      | 2                   |
| Primary key                  | None                |
| Enforced foreign-key columns | 0                   |
| Created                      | 2025-09-15T10:48:23 |
| Last schema modification     | 2025-09-15T10:48:23 |

Column Details

| Column Name | Data Type     | Nullable | Key / Constraint | Default | Description                                               |
|-------------|---------------|----------|------------------|---------|-----------------------------------------------------------|
| Code        | nvarchar(max) | Yes      | None             | None    | Stored category or classification code.                   |
| Value       | nvarchar(max) | Yes      | None             | None    | Display label or decoded meaning for the associated code. |

Relationships

- No enforced or validated logical relationships were identified for this table.

Data Analysis

Business-critical or frequently joined/filterable columns: Code.

- The table is empty at the profiling timestamp; value distributions and duplicates cannot be assessed.
- 2 column(s) use nvarchar(max), limiting type precision and potentially increasing storage/indexing cost.

Data Quality Observations

Confirmed: no rows are present; completeness, consistency and representative-value checks are not applicable.

Important Findings

- No primary key is defined.
- Application-level relationships exist without FK enforcement.
- The table is inactive/empty at the profiling timestamp; confirm whether it is planned, legacy or awaiting data.

23. dbo.EthnicGroupList

Table Overview

**Purpose inferred from table and column names.** Code/value or geographic reference data for ethnic group.

Role classification: Reference / classification.

Table Statistics

| Measure                      | Value               |
|------------------------------|---------------------|
| Total records                | 0                   |
| Columns                      | 2                   |
| Primary key                  | None                |
| Enforced foreign-key columns | 0                   |
| Created                      | 2025-09-15T10:48:23 |
| Last schema modification     | 2025-09-15T10:48:23 |

Column Details

| Column Name | Data Type     | Nullable | Key / Constraint | Default | Description                                               |
|-------------|---------------|----------|------------------|---------|-----------------------------------------------------------|
| Code        | nvarchar(max) | Yes      | None             | None    | Stored category or classification code.                   |
| Value       | nvarchar(max) | Yes      | None             | None    | Display label or decoded meaning for the associated code. |

Relationships

- No enforced or validated logical relationships were identified for this table.

Data Analysis

Business-critical or frequently joined/filterable columns: Code.

- The table is empty at the profiling timestamp; value distributions and duplicates cannot be assessed.
- 2 column(s) use nvarchar(max), limiting type precision and potentially increasing storage/indexing cost.

Data Quality Observations

Confirmed: no rows are present; completeness, consistency and representative-value checks are not applicable.

Important Findings

- No primary key is defined.
- Application-level relationships exist without FK enforcement.
- The table is inactive/empty at the profiling timestamp; confirm whether it is planned, legacy or awaiting data.

24. dbo.FamilyHistoryOfCancerList

Table Overview

**Purpose inferred from table and column names.** Code/value or geographic reference data for family history of cancer.

Role classification: Reference / classification.

Table Statistics

| Measure                      | Value               |
|------------------------------|---------------------|
| Total records                | 0                   |
| Columns                      | 2                   |
| Primary key                  | None                |
| Enforced foreign-key columns | 0                   |
| Created                      | 2025-09-15T10:48:23 |
| Last schema modification     | 2025-09-15T10:48:23 |

## Column Details

| Column Name | Data Type     | Nullable | Key / Constraint | Default | Description                                               |
|-------------|---------------|----------|------------------|---------|-----------------------------------------------------------|
| Code        | nvarchar(max) | Yes      | None             | None    | Stored category or classification code.                   |
| Value       | nvarchar(max) | Yes      | None             | None    | Display label or decoded meaning for the associated code. |

## Relationships

- No enforced or validated logical relationships were identified for this table.

## Data Analysis

Business-critical or frequently joined/filterable columns: Code.

- The table is empty at the profiling timestamp; value distributions and duplicates cannot be assessed.
- 2 column(s) use nvarchar(max), limiting type precision and potentially increasing storage/indexing cost.

## Data Quality Observations

Confirmed: no rows are present; completeness, consistency and representative-value checks are not applicable.

## Important Findings

- No primary key is defined.
- Application-level relationships exist without FK enforcement.
- The table is inactive/empty at the profiling timestamp; confirm whether it is planned, legacy or awaiting data.

## 25. dbo.GradeList

### Table Overview

**Purpose inferred from table and column names.** Code/value or geographic reference data for grade.

Role classification: Reference / classification.

Table Statistics

| Measure                      | Value               |
|------------------------------|---------------------|
| Total records                | 9                   |
| Columns                      | 2                   |
| Primary key                  | None                |
| Enforced foreign-key columns | 0                   |
| Created                      | 2025-09-15T10:48:23 |
| Last schema modification     | 2025-09-15T10:48:23 |

Column Details

| Column Name | Data Type     | Nullable | Key / Constraint | Default | Description                                                                                                                                                                            |
|-------------|---------------|----------|------------------|---------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Code        | nvarchar(max) | Yes      | None             | None    | Stored category or classification code. Profile: 9 distinct non-null values. Representative values: 1 (1); 2 (1); 3 (1).                                                               |
| Value       | nvarchar(max) | Yes      | None             | None    | Display label or decoded meaning for the associated code. Profile: 9 distinct non-null values. Representative values: B-cell (1); Grade I - Well diff. (1); Grade II - Mod. diff. (1). |

Relationships

- Probable semantic code/value lookup for TumourTable.GradeCellType, based on matching domain names; not enforced by a foreign key.

Data Analysis

Business-critical or frequently joined/filterable columns: Code.

- No null or blank values were found in profiled columns.
- Code values are unique in the current data, but no PK/UNIQUE constraint enforces that condition.
- 2 column(s) use nvarchar(max), limiting type precision and potentially increasing storage/indexing cost.

Data Quality Observations

2 of 2 columns have no null/blank values in the current data. Representative values in the column table are frequency-based and masked for sensitive fields.

Important Findings

- No primary key is defined.
- Application-level relationships exist without FK enforcement.

## 26. dbo.HistologyList

### Table Overview

**Purpose inferred from table and column names.** Code/value or geographic reference data for histology.

Role classification: Reference / classification.

### Table Statistics

| Measure                      | Value               |
|------------------------------|---------------------|
| Total records                | 557                 |
| Columns                      | 2                   |
| Primary key                  | None                |
| Enforced foreign-key columns | 0                   |
| Created                      | 2025-09-15T10:48:23 |
| Last schema modification     | 2025-09-15T10:48:23 |

### Column Details

| Column Name | Data Type     | Nullable | Key / Constraint | Default | Description                                                                                                                                                                                                                             |
|-------------|---------------|----------|------------------|---------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Code        | nvarchar(max) | Yes      | None             | None    | Stored category or classification code. Profile: 557 distinct non-null values. Representative values: 8000 (1); 8001 (1); 8002 (1).                                                                                                     |
| Value       | nvarchar(max) | Yes      | None             | None    | Display label or decoded meaning for the associated code. Profile: 557 distinct non-null values. Representative values: 8000 - Neoplasm, malignant (1); 8001 - Tumor cells, malignant (1); 8002 - Malignant tumor, small cell type (1). |

### Relationships

- Probable semantic code/value lookup for TumourTable.Histology, based on matching domain names; not enforced by a foreign key.

### Data Analysis

Business-critical or frequently joined/filterable columns: Code.

- No null or blank values were found in profiled columns.
- Code values are unique in the current data, but no PK/UNIQUE constraint enforces that condition.
- 2 column(s) use nvarchar(max), limiting type precision and potentially increasing storage/indexing cost.



Data Quality Observations

2 of 2 columns have no null/blank values in the current data. Representative values in the column table are frequency-based and masked for sensitive fields.

Important Findings

- No primary key is defined.
- Application-level relationships exist without FK enforcement.

27. dbo.ICCCMaster

Table Overview

**Purpose inferred from table and column names.** Intended International Classification of Childhood Cancer reference structure; currently empty.

Role classification: Reference / classification.

Table Statistics

| Measure                      | Value               |
|------------------------------|---------------------|
| Total records                | 0                   |
| Columns                      | 10                  |
| Primary key                  | Id                  |
| Enforced foreign-key columns | 0                   |
| Created                      | 2025-09-15T10:48:23 |
| Last schema modification     | 2025-09-15T10:48:23 |

Column Details

| Column Name      | Data Type     | Nullable | Key / Constraint    | Default | Description                              |
|------------------|---------------|----------|---------------------|---------|------------------------------------------|
| Id               | int           | No       | PK#1; IDENTITY(1,1) | None    | Internal row identifier.                 |
| Code1            | nvarchar(max) | Yes      | None                | None    | Inferred: stores code1 data.             |
| Code1Description | nvarchar(max) | Yes      | None                | None    | Inferred: stores code1 description data. |
| Code2            | nvarchar(max) | Yes      | None                | None    | Inferred: stores code2 data.             |
| Code2Description | nvarchar(max) | Yes      | None                | None    | Inferred: stores code2 description data. |
| Code3            | nvarchar(max) | Yes      | None                | None    | Inferred: stores code3 data.             |
| Code3Description | nvarchar(max) | Yes      | None                | None    | Inferred: stores code3 description data. |
| Histology        | nvarchar(max) | Yes      | None                | None    | Inferred: stores histology data.         |
| Topography       | nvarchar(max) | Yes      | None                | None    | Inferred: stores topography data.        |

| Column Name            | Data Type     | Nullable | Key / Constraint | Default | Description                                    |
|------------------------|---------------|----------|------------------|---------|------------------------------------------------|
| ExtendedClassification | nvarchar(max) | Yes      | None             | None    | Inferred: stores extended classification data. |

## Relationships

- No enforced or validated logical relationships were identified for this table.

## Data Analysis

Business-critical or frequently joined/filterable columns: Id.

- The table is empty at the profiling timestamp; value distributions and duplicates cannot be assessed.
- The primary key prevents duplicate full rows and duplicate key values.
- 9 column(s) use nvarchar(max), limiting type precision and potentially increasing storage/indexing cost.

## Data Quality Observations

Confirmed: no rows are present; completeness, consistency and representative-value checks are not applicable.

## Important Findings

- Application-level relationships exist without FK enforcement.
- The table is inactive/empty at the profiling timestamp; confirm whether it is planned, legacy or awaiting data.

## 28. dbo.ICD10Group

### Table Overview

**Confirmed by schema/application use.** Maps normalized ICD-10 codes to grouped cancer-site labels used by incidence and mortality queries.

Role classification: Reference / classification.

## Table Statistics

| Measure                      | Value               |
|------------------------------|---------------------|
| Total records                | 87                  |
| Columns                      | 2                   |
| Primary key                  | None                |
| Enforced foreign-key columns | 0                   |
| Created                      | 2025-09-15T10:48:23 |
| Last schema modification     | 2025-09-15T10:48:23 |

## Column Details

| Column Name | Data Type     | Nullable | Key / Constraint | Default | Description                                                                                                                                                                             |
|-------------|---------------|----------|------------------|---------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Code        | nvarchar(max) | No       | None             | None    | Stored category or classification code. Profile: 87 distinct non-null values. Representative values: C00 (1); C01 (1); C02 (1).                                                         |
| Value       | nvarchar(max) | No       | None             | None    | Display label or decoded meaning for the associated code. Profile: 59 distinct non-null values. Representative values: Others and unspecified (7); Non-Hodgkin lymphoma (6); Mouth (4). |

## Relationships

- Application query lookup for normalized TumourTable.ICD10 values; 11 populated tumour codes were unmapped and 2 failed the expected Cnn pattern.

## Data Analysis

Business-critical or frequently joined/filterable columns: Code.

- No null or blank values were found in profiled columns.
- Code values are unique in the current data, but no PK/UNIQUE constraint enforces that condition.
- Code is unique across 87 rows; Value has 59 distinct labels, consistent with multiple codes mapping to common grouped sites.
- 2 column(s) use nvarchar(max), limiting type precision and potentially increasing storage/indexing cost.

## Data Quality Observations

2 of 2 columns have no null/blank values in the current data. Representative values in the column table are frequency-based and masked for sensitive fields.

Important Findings

- No primary key is defined.

29. dbo.LateralityList

Table Overview

Purpose inferred from table and column names. Code/value or geographic reference data for laterality.

Role classification: Reference / classification.

Table Statistics

| Measure                      | Value               |
|------------------------------|---------------------|
| Total records                | 0                   |
| Columns                      | 2                   |
| Primary key                  | None                |
| Enforced foreign-key columns | 0                   |
| Created                      | 2025-09-15T10:48:25 |
| Last schema modification     | 2025-09-15T10:48:25 |

Column Details

| Column Name | Data Type     | Nullable | Key / Constraint | Default | Description                                               |
|-------------|---------------|----------|------------------|---------|-----------------------------------------------------------|
| Code        | nvarchar(max) | Yes      | None             | None    | Stored category or classification code.                   |
| Value       | nvarchar(max) | Yes      | None             | None    | Display label or decoded meaning for the associated code. |

Relationships

- No enforced or validated logical relationships were identified for this table.

Data Analysis

Business-critical or frequently joined/filterable columns: Code.

- The table is empty at the profiling timestamp; value distributions and duplicates cannot be assessed.
- 2 column(s) use nvarchar(max), limiting type precision and potentially increasing storage/indexing cost.

Data Quality Observations

Confirmed: no rows are present; completeness, consistency and representative-value checks are not applicable.

Important Findings

- No primary key is defined.
- Application-level relationships exist without FK enforcement.
- The table is inactive/empty at the profiling timestamp; confirm whether it is planned, legacy or awaiting data.

30. dbo.Lymph\_Leuk

Table Overview

**Purpose inferred from table and column names.** Intended lymphoma/leukaemia classification lookup; currently empty.

Role classification: Reference / classification.

Table Statistics

| Measure                      | Value               |
|------------------------------|---------------------|
| Total records                | 0                   |
| Columns                      | 2                   |
| Primary key                  | None                |
| Enforced foreign-key columns | 0                   |
| Created                      | 2025-09-15T10:48:25 |
| Last schema modification     | 2025-09-15T10:48:25 |

Column Details

| Column Name | Data Type     | Nullable | Key / Constraint | Default | Description                        |
|-------------|---------------|----------|------------------|---------|------------------------------------|
| Histology   | nvarchar(max) | No       | None             | None    | Inferred: stores histology data.   |
| ICD10       | nvarchar(max) | No       | None             | None    | ICD-10 cancer diagnosis/site code. |

Relationships

- No enforced or validated logical relationships were identified for this table.

## Data Analysis

Business-critical or frequently joined/filterable columns: No specific critical column was identifiable from keys and names..

- The table is empty at the profiling timestamp; value distributions and duplicates cannot be assessed.
- 2 column(s) use nvarchar(max), limiting type precision and potentially increasing storage/indexing cost.

## Data Quality Observations

Confirmed: no rows are present; completeness, consistency and representative-value checks are not applicable.

## Important Findings

- No primary key is defined.
- Application-level relationships exist without FK enforcement.
- The table is inactive/empty at the profiling timestamp; confirm whether it is planned, legacy or awaiting data.

## 31. dbo.MaritalStatusList

### Table Overview

**Purpose inferred from table and column names.** Code/value or geographic reference data for marital status.

Role classification: Reference / classification.

### Table Statistics

| Measure                      | Value               |
|------------------------------|---------------------|
| Total records                | 0                   |
| Columns                      | 2                   |
| Primary key                  | None                |
| Enforced foreign-key columns | 0                   |
| Created                      | 2025-09-15T10:48:25 |
| Last schema modification     | 2025-09-15T10:48:25 |

## Column Details

| Column Name | Data Type     | Nullable | Key / Constraint | Default | Description                                               |
|-------------|---------------|----------|------------------|---------|-----------------------------------------------------------|
| Code        | nvarchar(max) | Yes      | None             | None    | Stored category or classification code.                   |
| Value       | nvarchar(max) | Yes      | None             | None    | Display label or decoded meaning for the associated code. |

## Relationships

- No enforced or validated logical relationships were identified for this table.

## Data Analysis

Business-critical or frequently joined/filterable columns: Code.

- The table is empty at the profiling timestamp; value distributions and duplicates cannot be assessed.
- 2 column(s) use nvarchar(max), limiting type precision and potentially increasing storage/indexing cost.

## Data Quality Observations

Confirmed: no rows are present; completeness, consistency and representative-value checks are not applicable.

## Important Findings

- No primary key is defined.
- Application-level relationships exist without FK enforcement.
- The table is inactive/empty at the profiling timestamp; confirm whether it is planned, legacy or awaiting data.

## 32. dbo.Meso\_Mela

### Table Overview

**Purpose inferred from table and column names.** Intended mesothelioma/melanoma classification lookup; currently empty.

Role classification: Reference / classification.

Table Statistics

| Measure                      | Value               |
|------------------------------|---------------------|
| Total records                | 0                   |
| Columns                      | 3                   |
| Primary key                  | None                |
| Enforced foreign-key columns | 0                   |
| Created                      | 2025-09-15T10:48:25 |
| Last schema modification     | 2025-09-15T10:48:25 |

Column Details

| Column Name | Data Type     | Nullable | Key / Constraint | Default | Description                        |
|-------------|---------------|----------|------------------|---------|------------------------------------|
| Site        | nvarchar(max) | No       | None             | None    | Inferred: stores site data.        |
| Histology   | nvarchar(max) | Yes      | None             | None    | Inferred: stores histology data.   |
| ICD10       | nvarchar(max) | No       | None             | None    | ICD-10 cancer diagnosis/site code. |

Relationships

- No enforced or validated logical relationships were identified for this table.

Data Analysis

Business-critical or frequently joined/filterable columns: No specific critical column was identifiable from keys and names..

- The table is empty at the profiling timestamp; value distributions and duplicates cannot be assessed.
- 3 column(s) use nvarchar(max), limiting type precision and potentially increasing storage/indexing cost.

Data Quality Observations

Confirmed: no rows are present; completeness, consistency and representative-value checks are not applicable.

Important Findings

- No primary key is defined.
- Application-level relationships exist without FK enforcement.
- The table is inactive/empty at the profiling timestamp; confirm whether it is planned, legacy or awaiting data.



### 33. dbo.MList

#### Table Overview

**Purpose inferred from table and column names.** Code/value or geographic reference data for m.

Role classification: Reference / classification.

#### Table Statistics

| Measure                      | Value               |
|------------------------------|---------------------|
| Total records                | 0                   |
| Columns                      | 2                   |
| Primary key                  | None                |
| Enforced foreign-key columns | 0                   |
| Created                      | 2025-09-15T10:48:25 |
| Last schema modification     | 2025-09-15T10:48:25 |

#### Column Details

| Column Name | Data Type     | Nullable | Key / Constraint | Default | Description                                               |
|-------------|---------------|----------|------------------|---------|-----------------------------------------------------------|
| Code        | nvarchar(max) | Yes      | None             | None    | Stored category or classification code.                   |
| Value       | nvarchar(max) | Yes      | None             | None    | Display label or decoded meaning for the associated code. |

#### Relationships

- No enforced or validated logical relationships were identified for this table.

#### Data Analysis

Business-critical or frequently joined/filterable columns: Code.

- The table is empty at the profiling timestamp; value distributions and duplicates cannot be assessed.
- 2 column(s) use nvarchar(max), limiting type precision and potentially increasing storage/indexing cost.

#### Data Quality Observations

Confirmed: no rows are present; completeness, consistency and representative-value checks are not applicable.

## Important Findings

- No primary key is defined.
- Application-level relationships exist without FK enforcement.
- The table is inactive/empty at the profiling timestamp; confirm whether it is planned, legacy or awaiting data.

## 34. dbo.NList

### Table Overview

**Purpose inferred from table and column names.** Code/value or geographic reference data for n.

Role classification: Reference / classification.

### Table Statistics

| Measure                      | Value               |
|------------------------------|---------------------|
| Total records                | 0                   |
| Columns                      | 2                   |
| Primary key                  | None                |
| Enforced foreign-key columns | 0                   |
| Created                      | 2025-09-15T10:48:25 |
| Last schema modification     | 2025-09-15T10:48:25 |

### Column Details

| Column Name | Data Type     | Nullable | Key / Constraint | Default | Description                                               |
|-------------|---------------|----------|------------------|---------|-----------------------------------------------------------|
| Code        | nvarchar(max) | Yes      | None             | None    | Stored category or classification code.                   |
| Value       | nvarchar(max) | Yes      | None             | None    | Display label or decoded meaning for the associated code. |

### Relationships

- No enforced or validated logical relationships were identified for this table.

### Data Analysis

Business-critical or frequently joined/filterable columns: Code.

- The table is empty at the profiling timestamp; value distributions and duplicates cannot be assessed.

- 2 column(s) use nvarchar(max), limiting type precision and potentially increasing storage/indexing cost.

Data Quality Observations

Confirmed: no rows are present; completeness, consistency and representative-value checks are not applicable.

Important Findings

- No primary key is defined.
- Application-level relationships exist without FK enforcement.
- The table is inactive/empty at the profiling timestamp; confirm whether it is planned, legacy or awaiting data.

35. dbo.OccupationList

Table Overview

**Purpose inferred from table and column names.** Code/value or geographic reference data for occupation.

Role classification: Reference / classification.

Table Statistics

| Measure                      | Value               |
|------------------------------|---------------------|
| Total records                | 0                   |
| Columns                      | 2                   |
| Primary key                  | None                |
| Enforced foreign-key columns | 0                   |
| Created                      | 2025-09-15T10:48:25 |
| Last schema modification     | 2025-09-15T10:48:25 |

Column Details

| Column Name | Data Type     | Nullable | Key / Constraint | Default | Description                                               |
|-------------|---------------|----------|------------------|---------|-----------------------------------------------------------|
| Code        | nvarchar(max) | Yes      | None             | None    | Stored category or classification code.                   |
| Value       | nvarchar(max) | Yes      | None             | None    | Display label or decoded meaning for the associated code. |

## Relationships

- No enforced or validated logical relationships were identified for this table.

## Data Analysis

Business-critical or frequently joined/filterable columns: Code.

- The table is empty at the profiling timestamp; value distributions and duplicates cannot be assessed.
- 2 column(s) use nvarchar(max), limiting type precision and potentially increasing storage/indexing cost.

## Data Quality Observations

Confirmed: no rows are present; completeness, consistency and representative-value checks are not applicable.

## Important Findings

- No primary key is defined.
- Application-level relationships exist without FK enforcement.
- The table is inactive/empty at the profiling timestamp; confirm whether it is planned, legacy or awaiting data.

## 36. dbo.PatientFile

### Table Overview

**Confirmed by schema/application use.** Stores file metadata for documents attached logically to tumour records; file contents are not stored in this table.

Role classification: Core / transactional.

### Table Statistics

| Measure                      | Value               |
|------------------------------|---------------------|
| Total records                | 1,349               |
| Columns                      | 8                   |
| Primary key                  | Id                  |
| Enforced foreign-key columns | 0                   |
| Created                      | 2025-10-06T16:47:54 |
| Last schema modification     | 2025-10-07T16:02:52 |

## Column Details

| Column Name  | Data Type     | Nullable | Key / Constraint    | Default | Description                                                                                                                                                                                                                                          |
|--------------|---------------|----------|---------------------|---------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Id           | int           | No       | PK#1; IDENTITY(1,1) | None    | Internal row identifier. Profile: range 465 to 6289. Representative values masked (sensitive or identifying field).                                                                                                                                  |
| TumourId     | nvarchar(max) | Yes      | None                | None    | Inferred: stores tumour id data. Representative values masked (sensitive or identifying field).                                                                                                                                                      |
| FileName     | nvarchar(max) | Yes      | None                | None    | Inferred: stores file name data. Profile: 1,294 distinct non-null values. Representative values: Godabari Sahu (Udala).pdf (3); Jugala Kishore Das.pdf (3); AHALYA MAHANI.2025.BLS.jpeg (2).                                                         |
| FilePath     | nvarchar(max) | Yes      | None                | None    | Inferred: stores file path data. Representative values masked (sensitive or identifying field).                                                                                                                                                      |
| ContentType  | nvarchar(max) | Yes      | None                | None    | MIME media type for the referenced file. Profile: 3 distinct non-null values. Representative values: application/pdf (997); image/jpeg (271); image/png (81).                                                                                        |
| FileSize     | bigint        | No       | None                | None    | Recorded file size in bytes. Profile: 1,290 distinct non-null values; range 44502 to 20560072. Representative values: 3963569 (3); 767389 (3); 10556273 (2).                                                                                         |
| UploadedDate | datetime2(7)  | No       | None                | None    | File metadata upload timestamp. Profile: 1,349 distinct non-null values; range 2026-03-07T10:52:42 to 2026-07-10T23:56:29. Representative values: 2026-03-07 10:52:42.7459680 (1); 2026-03-12 11:26:07.4227227 (1); 2026-03-12 12:17:02.0284383 (1). |
| FileNumber   | nvarchar(max) | Yes      | None                | None    | Inferred: stores file number data. Representative values masked (sensitive or identifying field).                                                                                                                                                    |

## Relationships

- Validated logical child of TumourTable through TumourId; all 1,349 current rows matched.

## Data Analysis

Business-critical or frequently joined/filterable columns: Id, TumourId, UploadedDate.

- No null or blank values were found in profiled columns.
- The primary key prevents duplicate full rows and duplicate key values.
- All 1,349 TumourId values matched a TumourTable.TUMOURID.
- 5 column(s) use nvarchar(max), limiting type precision and potentially increasing storage/indexing cost.

## Data Quality Observations

8 of 8 columns have no null/blank values in the current data. Representative values in the column table are frequency-based and masked for sensitive fields.

## Important Findings

- Application-level relationships exist without FK enforcement.

## 37. dbo.PatientTable

### Table Overview

**Confirmed by schema/application use.** Stores the active patient-level cancer registry record and demographic/vital-status attributes.

Role classification: Core / transactional.

### Table Statistics

| Measure                      | Value               |
|------------------------------|---------------------|
| Total records                | 1,450               |
| Columns                      | 36                  |
| Primary key                  | Id                  |
| Enforced foreign-key columns | 0                   |
| Created                      | 2025-09-16T15:48:38 |
| Last schema modification     | 2025-09-16T15:48:38 |

### Column Details

| Column Name              | Data Type     | Nullable | Key / Constraint    | Default | Description                                                                                                                                          |
|--------------------------|---------------|----------|---------------------|---------|------------------------------------------------------------------------------------------------------------------------------------------------------|
| Id                       | int           | No       | PK#1; IDENTITY(1,1) | None    | Internal row identifier. Profile: range 1135 to 7975. Representative values masked (sensitive or identifying field).                                 |
| REGNO                    | nvarchar(max) | Yes      | None                | None    | Registry number used as the logical patient link. Representative values masked (sensitive or identifying field).                                     |
| OBSOLETEFLAGPATIENTTABLE | nvarchar(max) | Yes      | None                | None    | Inferred: stores obsoleteflagpatienttable data. Profile: 1,450/1,450 rows are null or blank; 0 distinct non-null values.                             |
| PATIENTRECORDID          | nvarchar(max) | Yes      | None                | None    | Inferred: stores patientrecordid data. Representative values masked (sensitive or identifying field).                                                |
| PATIENTUPDATEDBY         | nvarchar(max) | Yes      | None                | None    | Inferred: stores patientupdatedby data. Representative values masked (sensitive or identifying field).                                               |
| PATIENTUPDATEDDATE       | nvarchar(max) | Yes      | None                | None    | Inferred: stores patientupdateddate data. Profile: 101 distinct non-null values. Representative values: 20260317 (57); 20260618 (54); 20260704 (53). |
| PATIENTRECORDSTATUS      | nvarchar(max) | Yes      | None                | None    | Inferred: stores patientrecordstatus data. Profile: 1,450/1,450 rows are null or blank; 0 distinct non-null values.                                  |

| Column Name          | Data Type     | Nullable | Key / Constraint | Default | Description                                                                                                                                                                  |
|----------------------|---------------|----------|------------------|---------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| PATIENTCHECKSTATUS   | nvarchar(max) | Yes      | None             | None    | Inferred: stores patientcheckstatus data. Profile: 1,450/1,450 rows are null or blank; 0 distinct non-null values.                                                           |
| CentreCode           | nvarchar(max) | Yes      | None             | None    | Code identifying the participating registry centre. Profile: 30 distinct non-null values. Representative values: C002 (264); C026 (203); C006 (121).                         |
| RegistrationNumber   | nvarchar(max) | Yes      | None             | None    | Inferred: stores registration number data. Profile: 1,202/1,450 rows are null or blank; 246 distinct non-null values. Representative values: 2025013032 (2); 2506130128 (2). |
| Name                 | nvarchar(max) | Yes      | None             | None    | Inferred: stores name data. Representative values masked (sensitive or identifying field).                                                                                   |
| Sex                  | int           | Yes      | None             | None    | Inferred: stores sex data. Profile: 2 distinct non-null values; range 1 to 2. Representative values: 2 (794); 1 (656).                                                       |
| ContactNumber        | float         | Yes      | None             | None    | Inferred: stores contact number data. Profile: range 8667476 to 999999999999. Representative values masked (sensitive or identifying field).                                 |
| NationalIDCardNumber | nvarchar(max) | Yes      | None             | None    | Inferred: stores national id card number data. Representative values masked (sensitive or identifying field).                                                                |
| State                | nvarchar(max) | Yes      | None             | None    | Inferred: stores state data. Profile: 1 distinct non-null values. Representative values: 1 (1,450).                                                                          |
| District             | nvarchar(max) | Yes      | None             | None    | Inferred: stores district data. Profile: 30 distinct non-null values. Representative values: 122 (265); 115 (203); 105 (121).                                                |
| Block                | nvarchar(max) | Yes      | None             | None    | Inferred: stores block data. Profile: 1/1,450 rows are null or blank; 254 distinct non-null values. Representative values: 11505 (47); 10302 (45); 12204 (33).               |
| Village              | nvarchar(max) | Yes      | None             | None    | Inferred: stores village data. Profile: 79/1,450 rows are null or blank. Representative values masked (sensitive or identifying field).                                      |
| Address              | nvarchar(max) | Yes      | None             | None    | Inferred: stores address data. Profile: 248/1,450 rows are null or blank. Representative values masked (sensitive or identifying field).                                     |
| Area                 | nvarchar(max) | Yes      | None             | None    | Inferred: stores area data. Profile: 3 distinct non-null values. Representative values: 2 (1,059); 1 (365); 3 (26).                                                          |
| DateOfBirth          | nvarchar(max) | Yes      | None             | None    | Inferred: stores date of birth data. Profile: 37/1,450 rows are null or blank. Representative values masked (sensitive or identifying field).                                |
| DayDateOfBirth       | nvarchar(max) | Yes      | None             | None    | Inferred: stores day date of birth data. Profile: 37/1,450 rows are null or blank. Representative values masked (sensitive or identifying field).                            |
| MonthDateOfBirth     | nvarchar(max) | Yes      | None             | None    | Inferred: stores month date of birth data. Profile: 36/1,450 rows are null or blank. Representative values masked (sensitive or identifying field).                          |
| YearDateOfBirth      | nvarchar(max) | Yes      | None             | None    | Inferred: stores year date of birth data. Profile: 36/1,450 rows are null or blank. Representative values masked (sensitive or identifying field).                           |
| VitalStatus          | nvarchar(max) | Yes      | None             | None    | Inferred: stores vital status data. Profile: 3 distinct non-null values. Representative values: 1 (1,123); 2 (239); 9 (88).                                                  |

| Column Name        | Data Type     | Nullable | Key / Constraint | Default | Description                                                                                                                                                                                                                                                                                    |
|--------------------|---------------|----------|------------------|---------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| DateOfDeath        | nvarchar(max) | Yes      | None             | None    | Inferred: stores date of death data. Profile: 1,211/1,450 rows are null or blank. Representative values masked (sensitive or identifying field).                                                                                                                                               |
| DayDateOfDeath     | nvarchar(max) | Yes      | None             | None    | Inferred: stores day date of death data. Profile: 1,211/1,450 rows are null or blank. Representative values masked (sensitive or identifying field).                                                                                                                                           |
| MonthDateOfDeath   | nvarchar(max) | Yes      | None             | None    | Inferred: stores month date of death data. Profile: 1,211/1,450 rows are null or blank. Representative values masked (sensitive or identifying field).                                                                                                                                         |
| YearDateOfDeath    | nvarchar(max) | Yes      | None             | None    | Inferred: stores year date of death data. Profile: 1,211/1,450 rows are null or blank. Representative values masked (sensitive or identifying field).                                                                                                                                          |
| AgeAtDeath         | int           | Yes      | None             | None    | Inferred: stores age at death data. Profile: 1,210/1,450 rows are null or blank; 62 distinct non-null values; range 1 to 89. Representative values: 56 (14); 61 (11); 54 (10).                                                                                                                 |
| CauseOfDeath       | nvarchar(max) | Yes      | None             | None    | Inferred: stores cause of death data. Profile: 1,212/1,450 rows are null or blank; 4 distinct non-null values. Representative values: 1 (224); 4 (11).                                                                                                                                         |
| Remarks            | nvarchar(max) | Yes      | None             | None    | Inferred: stores remarks data. Profile: 1,100/1,450 rows are null or blank. Representative values masked (sensitive or identifying field).                                                                                                                                                     |
| DEOName            | nvarchar(max) | Yes      | None             | None    | Inferred: stores deo name data. Representative values masked (sensitive or identifying field).                                                                                                                                                                                                 |
| DEODate            | datetime2(7)  | Yes      | None             | None    | Inferred: stores deo date data. Profile: 1,450 distinct non-null values; range 2026-03-05T12:43:09 to 2026-07-10T23:56:25. Representative values: 2026-03-05 12:43:09.2600000 (1); 2026-03-05 13:29:46.5733333 (1); 2026-03-05 14:08:08.6633333 (1).                                           |
| LastModifiedByName | nvarchar(max) | Yes      | None             | None    | Inferred: stores last modified by name data. Profile: 1,009/1,450 rows are null or blank. Representative values masked (sensitive or identifying field).                                                                                                                                       |
| LastModifiedDate   | datetime2(7)  | Yes      | None             | None    | Latest recorded modification timestamp. Profile: 1,009/1,450 rows are null or blank; 441 distinct non-null values; range 2026-03-07T10:52:42 to 2026-07-10T23:53:17. Representative values: 2026-03-07 10:52:42.2200000 (1); 2026-03-12 11:25:52.7333333 (1); 2026-03-12 12:16:30.2133333 (1). |

## Relationships

- Validated logical parent of TumourTable through PatientTable.REGNO = TumourTable.PATIENTIDTUMOURTABLE; 1,455/1,455 tumour rows matched.
- Validated logical parent of SourceTable through REGNO; 1,455/1,455 source rows matched.

## Data Analysis

Business-critical or frequently joined/filterable columns: Id, REGNO, PATIENTRECORDID, PATIENTUPDATEDBY, PATIENTUPDATEDDATE, PATIENTRECORDSTATUS, PATIENTCHECKSTATUS, CentreCode, DateOfBirth, DayDateOfBirth, MonthDateOfBirth, YearDateOfBirth.



- Highest null/blank counts: PATIENTRECORDSTATUS 1,450/1,450, PATIENTCHECKSTATUS 1,450/1,450, OBSOLETEFLAGPATIENTTABLE 1,450/1,450, CauseOfDeath 1,212/1,450, YearDateOfDeath 1,211/1,450.
- The primary key prevents duplicate full rows and duplicate key values.
- REGNO has 0 duplicate groups; all 1,450 values are represented in logical tumour/source links as expected.
- DateOfBirth and DateOfDeath are nvarchar(max), but all populated current values converted to date in the read-only check.
- ContactNumber is stored as float, which is not a safe type for exact telephone identifiers.
- 30 column(s) use nvarchar(max), limiting type precision and potentially increasing storage/indexing cost.

### Data Quality Observations

16 of 36 columns have no null/blank values in the current data. Representative values in the column table are frequency-based and masked for sensitive fields.

### Important Findings

- Application-level relationships exist without FK enforcement.

## 38. dbo.PossibleDuplicates

### Table Overview

**Confirmed by schema/application use.** Tracks suspected duplicate record pairs, match scores, decisions and review workflow metadata.

Role classification: Core / transactional.

### Table Statistics

| Measure                      | Value               |
|------------------------------|---------------------|
| Total records                | 37                  |
| Columns                      | 15                  |
| Primary key                  | Id                  |
| Enforced foreign-key columns | 0                   |
| Created                      | 2025-09-15T10:48:26 |
| Last schema modification     | 2025-09-15T10:48:26 |

## Column Details

| Column Name                        | Data Type     | Nullable | Key / Constraint    | Default | Description                                                                                                                                                                                                                                                   |
|------------------------------------|---------------|----------|---------------------|---------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Id                                 | int           | No       | PK#1; IDENTITY(1,1) | None    | Internal row identifier. Profile: range 877 to 913. Representative values masked (sensitive or identifying field).                                                                                                                                            |
| Record1                            | nvarchar(max) | Yes      | None                | None    | Inferred: stores record1 data. Representative values masked (sensitive or identifying field).                                                                                                                                                                 |
| Record2                            | nvarchar(max) | Yes      | None                | None    | Inferred: stores record2 data. Representative values masked (sensitive or identifying field).                                                                                                                                                                 |
| MatchPercent                       | nvarchar(max) | Yes      | None                | None    | Inferred: stores match percent data. Profile: 14 distinct non-null values. Representative values: 76% (9); 77% (7); 75% (3).                                                                                                                                  |
| DuplicateFoundDate                 | datetime2(7)  | No       | None                | None    | Inferred: stores duplicate found date data. Profile: 30 distinct non-null values; range 2026-03-24T14:50:06 to 2026-06-08T15:47:54. Representative values: 2026-06-08 15:46:15.1666667 (4); 2026-06-08 15:45:31.2733333 (3); 2026-06-08 15:45:31.4366667 (2). |
| Decision                           | nvarchar(max) | Yes      | None                | None    | Inferred: stores decision data. Profile: 1 distinct non-null values. Representative values: PENDING (37).                                                                                                                                                     |
| OriginalRecordId                   | nvarchar(max) | Yes      | None                | None    | Inferred: stores original record id data. Profile: 37/37 rows are null or blank. Representative values masked (sensitive or identifying field).                                                                                                               |
| RecordToBeDeleted                  | nvarchar(max) | Yes      | None                | None    | Inferred: stores record to be deleted data. Profile: 37/37 rows are null or blank; 0 distinct non-null values.                                                                                                                                                |
| NewUniqueRecordId                  | nvarchar(max) | Yes      | None                | None    | Inferred: stores new unique record id data. Profile: 37/37 rows are null or blank. Representative values masked (sensitive or identifying field).                                                                                                             |
| AssociatedDuplicateCreateNewRecord | nvarchar(max) | Yes      | None                | None    | Inferred: stores associated duplicate create new record data. Profile: 37/37 rows are null or blank; 0 distinct non-null values.                                                                                                                              |
| RecentlyUpdated                    | nvarchar(max) | Yes      | None                | None    | Inferred: stores recently updated data. Profile: 2 distinct non-null values. Representative values: 0 (26); 1 (11).                                                                                                                                           |
| ReviewedBy                         | nvarchar(max) | Yes      | None                | None    | Inferred: stores reviewed by data. Profile: 37/37 rows are null or blank. Representative values masked (sensitive or identifying field).                                                                                                                      |
| RecentReviewDate                   | datetime2(7)  | No       | None                | None    | Inferred: stores recent review date data. Profile: 1 distinct non-null values; range 1900-01-01T00:00:00 to 1900-01-01T00:00:00. Representative values: 1900-01-01 00:00:00.0000000 (37).                                                                     |
| ReviewHistory                      | nvarchar(max) | Yes      | None                | None    | Inferred: stores review history data. Profile: 37/37 rows are null or blank. Representative values masked (sensitive or identifying field).                                                                                                                   |
| Remarks                            | nvarchar(max) | Yes      | None                | None    | Inferred: stores remarks data. Profile: 37/37 rows are null or blank. Representative values masked (sensitive or identifying field).                                                                                                                          |

## Relationships

- No enforced or validated logical relationships were identified for this table.

Data Analysis

Business-critical or frequently joined/filterable columns: Id, DuplicateFoundDate, OriginalRecordId, NewUniqueRecordId, RecentlyUpdated, RecentReviewDate.

- Highest null/blank counts: ReviewedBy 37/37, ReviewHistory 37/37, Remarks 37/37, RecordToBeDeleted 37/37, OriginalRecordId 37/37.
- The primary key prevents duplicate full rows and duplicate key values.
- All 37 rows contain a decision, but ReviewedBy is null/blank in all 37 rows; review accountability is incomplete.
- 12 column(s) use nvarchar(max), limiting type precision and potentially increasing storage/indexing cost.

Data Quality Observations

8 of 15 columns have no null/blank values in the current data. Representative values in the column table are frequency-based and masked for sensitive fields.

Important Findings

- Application-level relationships exist without FK enforcement.

39. dbo.PrimarySiteList

Table Overview

**Purpose inferred from table and column names.** Code/value or geographic reference data for primary site.

Role classification: Reference / classification.

Table Statistics

| Measure                      | Value               |
|------------------------------|---------------------|
| Total records                | 401                 |
| Columns                      | 2                   |
| Primary key                  | None                |
| Enforced foreign-key columns | 0                   |
| Created                      | 2025-09-15T10:48:28 |
| Last schema modification     | 2025-09-15T10:48:28 |

## Column Details

| Column Name | Data Type     | Nullable | Key / Constraint | Default | Description                                                                                                                                                                 |
|-------------|---------------|----------|------------------|---------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Code        | nvarchar(max) | Yes      | None             | None    | Stored category or classification code. Profile: 401 distinct non-null values. Representative values: 00 (1); 000 (1); 001 (1).                                             |
| Value       | nvarchar(max) | Yes      | None             | None    | Display label or decoded meaning for the associated code. Profile: 401 distinct non-null values. Representative values: ACCESSORY SINUSES (1); ADRENAL GLAND (1); ANUS (1). |

## Relationships

- Probable semantic code/value lookup for TumourTable.PrimarySite, based on matching domain names; not enforced by a foreign key.

## Data Analysis

Business-critical or frequently joined/filterable columns: Code.

- No null or blank values were found in profiled columns.
- Code values are unique in the current data, but no PK/UNIQUE constraint enforces that condition.
- 2 column(s) use nvarchar(max), limiting type precision and potentially increasing storage/indexing cost.

## Data Quality Observations

2 of 2 columns have no null/blank values in the current data. Representative values in the column table are frequency-based and masked for sensitive fields.

## Important Findings

- No primary key is defined.
- Application-level relationships exist without FK enforcement.

## 40. dbo.ReligionList

### Table Overview

**Purpose inferred from table and column names.** Code/value or geographic reference data for religion.

Role classification: Reference / classification.

## Table Statistics

| Measure                      | Value               |
|------------------------------|---------------------|
| Total records                | 0                   |
| Columns                      | 2                   |
| Primary key                  | None                |
| Enforced foreign-key columns | 0                   |
| Created                      | 2025-09-15T10:48:28 |
| Last schema modification     | 2025-09-15T10:48:28 |

## Column Details

| Column Name | Data Type     | Nullable | Key / Constraint | Default | Description                                               |
|-------------|---------------|----------|------------------|---------|-----------------------------------------------------------|
| Code        | nvarchar(max) | Yes      | None             | None    | Stored category or classification code.                   |
| Value       | nvarchar(max) | Yes      | None             | None    | Display label or decoded meaning for the associated code. |

## Relationships

- No enforced or validated logical relationships were identified for this table.

## Data Analysis

Business-critical or frequently joined/filterable columns: Code.

- The table is empty at the profiling timestamp; value distributions and duplicates cannot be assessed.
- 2 column(s) use nvarchar(max), limiting type precision and potentially increasing storage/indexing cost.

## Data Quality Observations

Confirmed: no rows are present; completeness, consistency and representative-value checks are not applicable.

## Important Findings

- No primary key is defined.
- Application-level relationships exist without FK enforcement.
- The table is inactive/empty at the profiling timestamp; confirm whether it is planned, legacy or awaiting data.

## 41. dbo.SEERList

### Table Overview

**Purpose inferred from table and column names.** Code/value or geographic reference data for seer.

Role classification: Reference / classification.

### Table Statistics

| Measure                      | Value               |
|------------------------------|---------------------|
| Total records                | 0                   |
| Columns                      | 2                   |
| Primary key                  | None                |
| Enforced foreign-key columns | 0                   |
| Created                      | 2025-09-15T10:48:28 |
| Last schema modification     | 2025-09-15T10:48:28 |

### Column Details

| Column Name | Data Type     | Nullable | Key / Constraint | Default | Description                                               |
|-------------|---------------|----------|------------------|---------|-----------------------------------------------------------|
| Code        | nvarchar(max) | Yes      | None             | None    | Stored category or classification code.                   |
| Value       | nvarchar(max) | Yes      | None             | None    | Display label or decoded meaning for the associated code. |

### Relationships

- No enforced or validated logical relationships were identified for this table.

### Data Analysis

Business-critical or frequently joined/filterable columns: Code.

- The table is empty at the profiling timestamp; value distributions and duplicates cannot be assessed.
- 2 column(s) use nvarchar(max), limiting type precision and potentially increasing storage/indexing cost.

### Data Quality Observations

Confirmed: no rows are present; completeness, consistency and representative-value checks are not applicable.

## Important Findings

- No primary key is defined.
- Application-level relationships exist without FK enforcement.
- The table is inactive/empty at the profiling timestamp; confirm whether it is planned, legacy or awaiting data.

## 42. dbo.SexList

### Table Overview

**Purpose inferred from table and column names.** Code/value or geographic reference data for sex.

Role classification: Reference / classification.

### Table Statistics

| Measure                      | Value               |
|------------------------------|---------------------|
| Total records                | 2                   |
| Columns                      | 2                   |
| Primary key                  | None                |
| Enforced foreign-key columns | 0                   |
| Created                      | 2025-09-15T10:48:29 |
| Last schema modification     | 2025-09-15T10:48:29 |

### Column Details

| Column Name | Data Type     | Nullable | Key / Constraint | Default | Description                                                                                                                                 |
|-------------|---------------|----------|------------------|---------|---------------------------------------------------------------------------------------------------------------------------------------------|
| Code        | nvarchar(max) | Yes      | None             | None    | Stored category or classification code. Profile: 2 distinct non-null values. Representative values: 1 (1); 2 (1).                           |
| Value       | nvarchar(max) | Yes      | None             | None    | Display label or decoded meaning for the associated code. Profile: 2 distinct non-null values. Representative values: Female (1); Male (1). |

### Relationships

- Probable semantic code/value lookup for PatientTable.Sex, based on matching domain names; not enforced by a foreign key.

### Data Analysis

Business-critical or frequently joined/filterable columns: Code.

- No null or blank values were found in profiled columns.
- Code values are unique in the current data, but no PK/UNIQUE constraint enforces that condition.
- 2 column(s) use nvarchar(max), limiting type precision and potentially increasing storage/indexing cost.

## Data Quality Observations

2 of 2 columns have no null/blank values in the current data. Representative values in the column table are frequency-based and masked for sensitive fields.

## Important Findings

- No primary key is defined.
- Application-level relationships exist without FK enforcement.

## 43. dbo.SourceCentreList

### Table Overview

**Purpose inferred from table and column names.** Code/value or geographic reference data for source centre.

Role classification: Reference / classification.

### Table Statistics

| Measure                      | Value               |
|------------------------------|---------------------|
| Total records                | 0                   |
| Columns                      | 3                   |
| Primary key                  | Id                  |
| Enforced foreign-key columns | 0                   |
| Created                      | 2025-09-15T10:48:29 |
| Last schema modification     | 2025-09-15T10:48:29 |

### Column Details

| Column Name | Data Type     | Nullable | Key / Constraint    | Default | Description                                               |
|-------------|---------------|----------|---------------------|---------|-----------------------------------------------------------|
| Id          | int           | No       | PK#1; IDENTITY(1,1) | None    | Internal row identifier.                                  |
| Code        | nvarchar(max) | Yes      | None                | None    | Stored category or classification code.                   |
| Value       | nvarchar(max) | Yes      | None                | None    | Display label or decoded meaning for the associated code. |



## Relationships

- No enforced or validated logical relationships were identified for this table.

## Data Analysis

Business-critical or frequently joined/filterable columns: Id, Code.

- The table is empty at the profiling timestamp; value distributions and duplicates cannot be assessed.
- The primary key prevents duplicate full rows and duplicate key values.
- 2 column(s) use nvarchar(max), limiting type precision and potentially increasing storage/indexing cost.

## Data Quality Observations

Confirmed: no rows are present; completeness, consistency and representative-value checks are not applicable.

## Important Findings

- Application-level relationships exist without FK enforcement.
- The table is inactive/empty at the profiling timestamp; confirm whether it is planned, legacy or awaiting data.

## 44. dbo.SourceTable

### Table Overview

**Confirmed by schema/application use.** Stores source-of-information records linked logically to a tumour and patient.

Role classification: Core / transactional.

### Table Statistics

| Measure                      | Value               |
|------------------------------|---------------------|
| Total records                | 1,455               |
| Columns                      | 12                  |
| Primary key                  | Id                  |
| Enforced foreign-key columns | 0                   |
| Created                      | 2025-09-15T10:48:29 |
| Last schema modification     | 2025-09-15T11:47:17 |

## Column Details

| Column Name         | Data Type     | Nullable | Key / Constraint    | Default | Description                                                                                                                                       |
|---------------------|---------------|----------|---------------------|---------|---------------------------------------------------------------------------------------------------------------------------------------------------|
| Id                  | int           | No       | PK#1; IDENTITY(1,1) | None    | Internal row identifier. Profile: 1,455 distinct non-null values; range 2170 to 9397. Representative values: 2170 (1); 2187 (1); 2201 (1).        |
| REGNO               | nvarchar(max) | Yes      | None                | None    | Registry number used as the logical patient link. Representative values masked (sensitive or identifying field).                                  |
| TUMOURID            | nvarchar(max) | Yes      | None                | None    | Logical tumour identifier. Representative values masked (sensitive or identifying field).                                                         |
| SOURCEID            | nvarchar(max) | Yes      | None                | None    | Logical source-record identifier. Representative values masked (sensitive or identifying field).                                                  |
| TUMOURIDSOURCETABLE | nvarchar(max) | Yes      | None                | None    | Tumour key used to link source rows to TumourTable.TUMOURID. Representative values masked (sensitive or identifying field).                       |
| SOURCERECORDID      | nvarchar(max) | Yes      | None                | None    | Inferred: stores source recordid data. Representative values masked (sensitive or identifying field).                                             |
| TypeOfSource        | nvarchar(max) | Yes      | None                | None    | Inferred: stores type of source data. Profile: 1 distinct non-null values. Representative values: HOSPITAL (1,455).                               |
| SourceCentre        | nvarchar(max) | Yes      | None                | None    | Inferred: stores source centre data. Profile: 30 distinct non-null values. Representative values: C002 (265); C026 (202); C006 (121).             |
| CaseFileNumber      | nvarchar(max) | Yes      | None                | None    | Inferred: stores case file number data. Profile: 654/1,455 rows are null or blank. Representative values masked (sensitive or identifying field). |
| SourceRemarks       | nvarchar(max) | Yes      | None                | None    | Inferred: stores source remarks data. Profile: 1,063/1,455 rows are null or blank. Representative values masked (sensitive or identifying field). |
| TumourNumber        | nvarchar(max) | Yes      | None                | None    | Inferred: stores tumour number data. Profile: 2 distinct non-null values. Representative values: 1 (1,449); 2 (6).                                |
| SourceNumber        | nvarchar(max) | Yes      | None                | None    | Inferred: stores source number data. Profile: 1 distinct non-null values. Representative values: 1 (1,455).                                       |

## Relationships

- Validated logical child of TumourTable through TUMOURIDSOURCETABLE and of PatientTable through REGNO; all current rows matched.

## Data Analysis

Business-critical or frequently joined/filterable columns: Id, REGNO, TUMOURID, SOURCEID, TUMOURIDSOURCETABLE, SOURCERECORDID.

- Highest null/blank counts: SourceRemarks 1,063/1,455, CaseFileNumber 654/1,455.
- The primary key prevents duplicate full rows and duplicate key values.
- SOURCEID has 0 duplicate groups; all patient and tumour logical links match.

- 11 column(s) use nvarchar(max), limiting type precision and potentially increasing storage/indexing cost.

Data Quality Observations

10 of 12 columns have no null/blank values in the current data. Representative values in the column table are frequency-based and masked for sensitive fields.

Important Findings

- Application-level relationships exist without FK enforcement.

45. dbo.StaffDetails

Table Overview

**Purpose inferred from table and column names.** Intended to store staff master and contact/assignment metadata; currently empty.

Role classification: Operational master.

Table Statistics

| Measure                      | Value               |
|------------------------------|---------------------|
| Total records                | 0                   |
| Columns                      | 6                   |
| Primary key                  | Id                  |
| Enforced foreign-key columns | 0                   |
| Created                      | 2025-09-15T10:48:29 |
| Last schema modification     | 2025-09-15T10:48:29 |

Column Details

| Column Name   | Data Type     | Nullable | Key / Constraint    | Default | Description                                                                                          |
|---------------|---------------|----------|---------------------|---------|------------------------------------------------------------------------------------------------------|
| Id            | int           | No       | PK#1; IDENTITY(1,1) | None    | Internal row identifier.                                                                             |
| EmployeeCode  | nvarchar(max) | Yes      | None                | None    | Inferred: stores employee code data.                                                                 |
| Name          | nvarchar(max) | Yes      | None                | None    | Inferred: stores name data.                                                                          |
| DateOfBirth   | datetime2(7)  | No       | None                | None    | Inferred: stores date of birth data. Representative values masked (sensitive or identifying field).  |
| Sex           | int           | Yes      | None                | None    | Inferred: stores sex data.                                                                           |
| ContactNumber | float         | No       | None                | None    | Inferred: stores contact number data. Representative values masked (sensitive or identifying field). |

## Relationships

- No enforced or validated logical relationships were identified for this table.

## Data Analysis

Business-critical or frequently joined/filterable columns: Id, EmployeeCode, DateOfBirth.

- The table is empty at the profiling timestamp; value distributions and duplicates cannot be assessed.
- The primary key prevents duplicate full rows and duplicate key values.
- 2 column(s) use nvarchar(max), limiting type precision and potentially increasing storage/indexing cost.

## Data Quality Observations

Confirmed: no rows are present; completeness, consistency and representative-value checks are not applicable.

## Important Findings

- Application-level relationships exist without FK enforcement.
- The table is inactive/empty at the profiling timestamp; confirm whether it is planned, legacy or awaiting data.

## 46. dbo.StateList

### Table Overview

**Purpose inferred from table and column names.** State-level geographic master.

Role classification: Reference / classification.

### Table Statistics

| Measure                      | Value               |
|------------------------------|---------------------|
| Total records                | 1                   |
| Columns                      | 3                   |
| Primary key                  | Id                  |
| Enforced foreign-key columns | 0                   |
| Created                      | 2025-09-15T10:48:29 |
| Last schema modification     | 2025-09-15T10:48:29 |

## Column Details

| Column Name | Data Type     | Nullable | Key / Constraint    | Default | Description                                                                                               |
|-------------|---------------|----------|---------------------|---------|-----------------------------------------------------------------------------------------------------------|
| Id          | int           | No       | PK#1; IDENTITY(1,1) | None    | Internal row identifier. Profile: 1 distinct non-null values; range 1 to 1. Representative values: 1 (1). |
| StateId     | nvarchar(max) | Yes      | None                | None    | State master code. Profile: 1 distinct non-null values. Representative values: 1 (1).                     |
| StateName   | nvarchar(max) | Yes      | None                | None    | Inferred: stores state name data. Profile: 1 distinct non-null values. Representative values: Odisha (1). |

## Relationships

- Logical one-to-many geographic parent of DistrictList; all current district state codes matched.

## Data Analysis

Business-critical or frequently joined/filterable columns: Id, StateId.

- No null or blank values were found in profiled columns.
- The primary key prevents duplicate full rows and duplicate key values.
- 2 column(s) use nvarchar(max), limiting type precision and potentially increasing storage/indexing cost.

## Data Quality Observations

3 of 3 columns have no null/blank values in the current data. Representative values in the column table are frequency-based and masked for sensitive fields.

## Important Findings

- Application-level relationships exist without FK enforcement.

## 47. dbo.sysdiagrams

### Table Overview

**Confirmed by schema/application use.** SQL Server Management Studio database-diagram metadata table.

Role classification: Platform / administration.

Table Statistics

| Measure                      | Value               |
|------------------------------|---------------------|
| Total records                | 0                   |
| Columns                      | 5                   |
| Primary key                  | diagram_id          |
| Enforced foreign-key columns | 0                   |
| Created                      | 2026-07-20T12:01:23 |
| Last schema modification     | 2026-07-20T12:01:23 |

Column Details

| Column Name  | Data Type      | Nullable | Key / Constraint    | Default | Description                         |
|--------------|----------------|----------|---------------------|---------|-------------------------------------|
| name         | sysname        | No       | UNIQUE INDEX        | None    | Inferred: stores name data.         |
| principal_id | int            | No       | UNIQUE INDEX        | None    | Inferred: stores principal id data. |
| diagram_id   | int            | No       | PK#1; IDENTITY(1,1) | None    | Inferred: stores diagram id data.   |
| version      | int            | Yes      | None                | None    | Inferred: stores version data.      |
| definition   | varbinary(max) | Yes      | None                | None    | Inferred: stores definition data.   |

Relationships

- No enforced or validated logical relationships were identified for this table.

Data Analysis

Business-critical or frequently joined/filterable columns: principal\_id, diagram\_id.

- The table is empty at the profiling timestamp; value distributions and duplicates cannot be assessed.
- The primary key prevents duplicate full rows and duplicate key values.

Data Quality Observations

Confirmed: no rows are present; completeness, consistency and representative-value checks are not applicable.

Important Findings

- Application-level relationships exist without FK enforcement.
- The table is inactive/empty at the profiling timestamp; confirm whether it is planned, legacy or awaiting data.

## 48. dbo.TList

### Table Overview

**Purpose inferred from table and column names.** Code/value or geographic reference data for t.

Role classification: Reference / classification.

### Table Statistics

| Measure                      | Value               |
|------------------------------|---------------------|
| Total records                | 0                   |
| Columns                      | 2                   |
| Primary key                  | None                |
| Enforced foreign-key columns | 0                   |
| Created                      | 2025-09-15T10:48:31 |
| Last schema modification     | 2025-09-15T10:48:31 |

### Column Details

| Column Name | Data Type     | Nullable | Key / Constraint | Default | Description                                               |
|-------------|---------------|----------|------------------|---------|-----------------------------------------------------------|
| Code        | nvarchar(max) | Yes      | None             | None    | Stored category or classification code.                   |
| Value       | nvarchar(max) | Yes      | None             | None    | Display label or decoded meaning for the associated code. |

### Relationships

- No enforced or validated logical relationships were identified for this table.

### Data Analysis

Business-critical or frequently joined/filterable columns: Code.

- The table is empty at the profiling timestamp; value distributions and duplicates cannot be assessed.
- 2 column(s) use nvarchar(max), limiting type precision and potentially increasing storage/indexing cost.

### Data Quality Observations

Confirmed: no rows are present; completeness, consistency and representative-value checks are not applicable.

## Important Findings

- No primary key is defined.
- Application-level relationships exist without FK enforcement.
- The table is inactive/empty at the profiling timestamp; confirm whether it is planned, legacy or awaiting data.

## 49. dbo.TreatmentList

### Table Overview

**Purpose inferred from table and column names.** Code/value or geographic reference data for treatment.

Role classification: Reference / classification.

### Table Statistics

| Measure                      | Value               |
|------------------------------|---------------------|
| Total records                | 19                  |
| Columns                      | 2                   |
| Primary key                  | None                |
| Enforced foreign-key columns | 0                   |
| Created                      | 2025-09-16T12:22:06 |
| Last schema modification     | 2025-09-16T12:22:06 |

### Column Details

| Column Name | Data Type     | Nullable | Key / Constraint | Default | Description                                                                                                                                                        |
|-------------|---------------|----------|------------------|---------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Code        | nvarchar(max) | Yes      | None             | None    | Stored category or classification code. Profile: 19 distinct non-null values. Representative values: 1 (1); 10 (1); 11 (1).                                        |
| Value       | nvarchar(max) | Yes      | None             | None    | Display label or decoded meaning for the associated code. Profile: 19 distinct non-null values. Representative values: Chemotherapy (CT) (1); CT+H (1); CT+RT (1). |

### Relationships

- Probable semantic code/value lookup for TumourTable.Treatment, based on matching domain names; not enforced by a foreign key.



## Data Analysis

Business-critical or frequently joined/filterable columns: Code.

- No null or blank values were found in profiled columns.
- Code values are unique in the current data, but no PK/UNIQUE constraint enforces that condition.
- 2 column(s) use nvarchar(max), limiting type precision and potentially increasing storage/indexing cost.

## Data Quality Observations

2 of 2 columns have no null/blank values in the current data. Representative values in the column table are frequency-based and masked for sensitive fields.

## Important Findings

- No primary key is defined.
- Application-level relationships exist without FK enforcement.

## 50. dbo.TreatmentStatusList

### Table Overview

**Purpose inferred from table and column names.** Code/value or geographic reference data for treatment status.

Role classification: Reference / classification.

### Table Statistics

| Measure                      | Value               |
|------------------------------|---------------------|
| Total records                | 4                   |
| Columns                      | 2                   |
| Primary key                  | None                |
| Enforced foreign-key columns | 0                   |
| Created                      | 2025-09-15T15:09:00 |
| Last schema modification     | 2025-09-15T15:09:00 |

## Column Details

| Column Name | Data Type     | Nullable | Key / Constraint | Default | Description                                                                                                                                                             |
|-------------|---------------|----------|------------------|---------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Code        | nvarchar(max) | Yes      | None             | None    | Stored category or classification code. Profile: 4 distinct non-null values. Representative values: 1 (1); 2 (1); 3 (1).                                                |
| Value       | nvarchar(max) | Yes      | None             | None    | Display label or decoded meaning for the associated code. Profile: 4 distinct non-null values. Representative values: Complete (1); Incomplete (1); Not applicable (1). |

## Relationships

- Probable semantic code/value lookup for TumourTable.TreatmentStatus, based on matching domain names; not enforced by a foreign key.

## Data Analysis

Business-critical or frequently joined/filterable columns: Code.

- No null or blank values were found in profiled columns.
- Code values are unique in the current data, but no PK/UNIQUE constraint enforces that condition.
- 2 column(s) use nvarchar(max), limiting type precision and potentially increasing storage/indexing cost.

## Data Quality Observations

2 of 2 columns have no null/blank values in the current data. Representative values in the column table are frequency-based and masked for sensitive fields.

## Important Findings

- No primary key is defined.
- Application-level relationships exist without FK enforcement.

## 51. dbo.TumourTable

### Table Overview

**Confirmed by schema/application use.** Stores tumour/case attributes linked logically to a patient, including diagnosis, site, histology and treatment coding.

Role classification: Core / transactional.

## Table Statistics

| Measure                      | Value               |
|------------------------------|---------------------|
| Total records                | 1,455               |
| Columns                      | 33                  |
| Primary key                  | Id                  |
| Enforced foreign-key columns | 0                   |
| Created                      | 2025-09-15T10:48:31 |
| Last schema modification     | 2025-11-04T14:59:00 |

## Column Details

| Column Name                | Data Type     | Nullable | Key / Constraint    | Default | Description                                                                                                                                            |
|----------------------------|---------------|----------|---------------------|---------|--------------------------------------------------------------------------------------------------------------------------------------------------------|
| Id                         | int           | No       | PK#1; IDENTITY(1,1) | None    | Internal row identifier. Profile: 1,455 distinct non-null values; range 2400 to 9627. Representative values: 2400 (1); 2417 (1); 2431 (1).             |
| REGNO                      | nvarchar(max) | Yes      | None                | None    | Registry number used as the logical patient link. Representative values masked (sensitive or identifying field).                                       |
| TUMOURID                   | nvarchar(max) | Yes      | None                | None    | Logical tumour identifier. Representative values masked (sensitive or identifying field).                                                              |
| RECS                       | nvarchar(max) | Yes      | None                | None    | Inferred: stores recs data. Profile: 2 distinct non-null values. Representative values: true (1,376); false (79).                                      |
| CHECKS                     | nvarchar(max) | Yes      | None                | None    | Inferred: stores checks data. Profile: 2 distinct non-null values. Representative values: true (1,389); false (66).                                    |
| MPCODE                     | nvarchar(max) | Yes      | None                | None    | Inferred: stores mpcode data. Profile: 1,455/1,455 rows are null or blank; 1 distinct non-null values.                                                 |
| MPSEQ                      | nvarchar(max) | Yes      | None                | None    | Inferred: stores mpseq data. Profile: 1 distinct non-null values. Representative values: 0 (1,455).                                                    |
| MPTOT                      | nvarchar(max) | Yes      | None                | None    | Inferred: stores mptot data. Profile: 1 distinct non-null values. Representative values: 1 (1,455).                                                    |
| UPDATE                     | nvarchar(max) | Yes      | None                | None    | Inferred: stores update data. Profile: 101 distinct non-null values. Representative values: 20260317 (57); 20260618 (54); 20260704 (54).               |
| OBSOLETEFLAGTUMOURTABLE    | nvarchar(max) | Yes      | None                | None    | Inferred: stores obsoleteflagtumourtable data. Profile: 1 distinct non-null values. Representative values: 0 (1,455).                                  |
| PATIENTIDTUMOURTABLE       | nvarchar(max) | Yes      | None                | None    | Patient registry key used by the application to link tumour rows to PatientTable.REGNO. Representative values masked (sensitive or identifying field). |
| PATIENTRECORDIDTUMOURTABLE | nvarchar(max) | Yes      | None                | None    | Inferred: stores patientrecordidtumourtable data. Representative values masked (sensitive or identifying field).                                       |
| TUMOURUPDATEDBY            | nvarchar(max) | Yes      | None                | None    | Inferred: stores tumourupdatedby data. Representative values masked (sensitive or identifying field).                                                  |

| Column Name               | Data Type     | Nullable | Key / Constraint | Default | Description                                                                                                                                                                                                                                                        |
|---------------------------|---------------|----------|------------------|---------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| TUMOURUNDUPLICATIONSTATUS | nvarchar(max) | Yes      | None             | None    | Inferred: stores tumourunduplicationstatus data. Profile: 1,455/1,455 rows are null or blank; 1 distinct non-null values.                                                                                                                                          |
| Age                       | int           | Yes      | None             | None    | Inferred: stores age data. Profile: 45/1,455 rows are null or blank; 87 distinct non-null values; range 0 to 91. Representative values: 55 (58); 59 (57); 54 (44).                                                                                                 |
| DateOfDiagnosis           | nvarchar(max) | Yes      | None             | None    | Inferred: stores date of diagnosis data. Profile: 43/1,455 rows are null or blank; 669 distinct non-null values. Representative values: 20250404 (9); 20250901 (9); 20250131 (8).                                                                                  |
| DayDateOfDiagnosis        | nvarchar(max) | Yes      | None             | None    | Inferred: stores day date of diagnosis data. Profile: 43/1,455 rows are null or blank; 32 distinct non-null values. Representative values: 4 (70); 1 (69); 15 (64).                                                                                                |
| MonthDateOfDiagnosis      | nvarchar(max) | Yes      | None             | None    | Inferred: stores month date of diagnosis data. Profile: 43/1,455 rows are null or blank; 13 distinct non-null values. Representative values: 1 (160); 2 (147); 3 (138).                                                                                            |
| YearDateOfDiagnosis       | nvarchar(max) | Yes      | None             | None    | Inferred: stores year date of diagnosis data. Profile: 43/1,455 rows are null or blank; 25 distinct non-null values. Representative values: 2025 (1,005); 2024 (145); 2023 (67).                                                                                   |
| BasisOfDiagnosis          | nvarchar(max) | Yes      | None             | None    | Inferred: stores basis of diagnosis data. Profile: 43/1,455 rows are null or blank; 9 distinct non-null values. Representative values: 7 (1,028); 1 (135); 5 (100).                                                                                                |
| Site                      | nvarchar(max) | Yes      | None             | None    | Inferred: stores site data. Profile: 42/1,455 rows are null or blank; 60 distinct non-null values. Representative values: 50 (302); 06 (156); 16 (98).                                                                                                             |
| PrimarySite               | nvarchar(max) | Yes      | None             | None    | Inferred: stores primary site data. Profile: 43/1,455 rows are null or blank; 159 distinct non-null values. Representative values: 509 (196); 060 (112); 569 (85).                                                                                                 |
| SubSite                   | nvarchar(max) | Yes      | None             | None    | Inferred: stores sub site data. Profile: 43/1,455 rows are null or blank; 159 distinct non-null values. Representative values: 509 (196); 060 (112); 569 (85).                                                                                                     |
| Histology                 | nvarchar(max) | Yes      | None             | None    | Inferred: stores histology data. Profile: 43/1,455 rows are null or blank; 140 distinct non-null values. Representative values: 8070 - Squamous cell carcinoma, NOS (253); 8140 - Adenocarcinoma, NOS (212); 8500 - Infiltrating duct carcinoma, NOS (C50_) (187). |
| GradeCellType             | nvarchar(max) | Yes      | None             | None    | Inferred: stores grade cell type data. Profile: 101/1,455 rows are null or blank; 9 distinct non-null values. Representative values: 9 (672); 2 (241); 3 (222).                                                                                                    |
| Behaviour                 | nvarchar(max) | Yes      | None             | None    | Inferred: stores behaviour data. Profile: 43/1,455 rows are null or blank; 3 distinct non-null values. Representative values: 3 (1,410); 2 (2).                                                                                                                    |
| ICD10                     | nvarchar(max) | Yes      | None             | None    | ICD-10 cancer diagnosis/site code. Profile: 46/1,455 rows are null or blank; 167 distinct non-null values. Representative values: C509 (194); C060 (112); C56 (83).                                                                                                |
| ICCCCode                  | nvarchar(max) | Yes      | None             | None    | Inferred: stores iccc code data. Profile: 46/1,455 rows are null or blank; 38 distinct non-null values. Representative values: 11f (955); 12b (138); 10d (72).                                                                                                     |

| Column Name     | Data Type     | Nullable | Key / Constraint | Default | Description                                                                                                                                                     |
|-----------------|---------------|----------|------------------|---------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Notes           | nvarchar(max) | Yes      | None             | None    | Inferred: stores notes data. Profile: 1,165/1,455 rows are null or blank. Representative values masked (sensitive or identifying field).                        |
| Treatment       | nvarchar(max) | Yes      | None             | None    | Inferred: stores treatment data. Profile: 52/1,455 rows are null or blank; 20 distinct non-null values. Representative values: 3 (337); 5 (297); 7 (158).       |
| TreatmentStatus | nvarchar(max) | Yes      | None             | None    | Inferred: stores treatment status data. Profile: 57/1,455 rows are null or blank; 5 distinct non-null values. Representative values: 2 (587); 1 (546); 9 (187). |
| TumourNumber    | nvarchar(max) | Yes      | None             | None    | Inferred: stores tumour number data. Profile: 2 distinct non-null values. Representative values: 1 (1,449); 2 (6).                                              |
| ClinicalStage   | nvarchar(max) | Yes      | None             | None    | Inferred: stores clinical stage data. Profile: 66/1,455 rows are null or blank; 9 distinct non-null values. Representative values: 9 (494); 5 (208); 6 (183).   |

## Relationships

- Validated logical child of PatientTable and parent of SourceTable.
- Validated logical parent of PatientFile through TumourTable.TUMOURID = PatientFile.TumourId; 1,349/1,349 file rows matched.

## Data Analysis

Business-critical or frequently joined/filterable columns: Id, REGNO, TUMOURID, MPCODE, UPDATE, TUMOURUPDATEDBY, TUMOURUNDUPLICATIONSTATUS, DateOfDiagnosis, DayDateOfDiagnosis, MonthDateOfDiagnosis, YearDateOfDiagnosis, ICCCCode.

- Highest null/blank counts: TUMOURUNDUPLICATIONSTATUS 1,455/1,455, MPCODE 1,455/1,455, Notes 1,165/1,455, GradeCellType 101/1,455, ClinicalStage 66/1,455.
- The primary key prevents duplicate full rows and duplicate key values.
- TUMOURID has 0 duplicate groups and all patient links match, despite the absence of an FK/UNIQUE constraint.
- ICD10 contains 2 values outside the expected normalized Cnn pattern and 11 values with no ICD10Group match.
- DateOfDiagnosis is nvarchar(max); all 1,412 populated values converted to date in the read-only check.
- 31 column(s) use nvarchar(max), limiting type precision and potentially increasing storage/indexing cost.

## Data Quality Observations

13 of 33 columns have no null/blank values in the current data. Representative values in the column table are frequency-based and masked for sensitive fields.

Important Findings

- Application-level relationships exist without FK enforcement.

52. dbo.TypeOfSourceList

Table Overview

**Purpose inferred from table and column names.** Code/value or geographic reference data for type of source.

Role classification: Reference / classification.

Table Statistics

| Measure                      | Value               |
|------------------------------|---------------------|
| Total records                | 3                   |
| Columns                      | 2                   |
| Primary key                  | None                |
| Enforced foreign-key columns | 0                   |
| Created                      | 2025-09-15T10:48:32 |
| Last schema modification     | 2025-09-15T10:48:32 |

Column Details

| Column Name | Data Type     | Nullable | Key / Constraint | Default | Description                                                                                                                                                              |
|-------------|---------------|----------|------------------|---------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Code        | nvarchar(max) | Yes      | None             | None    | Stored category or classification code. Profile: 3 distinct non-null values. Representative values: DEATH-REGISTRAR (1); HOSPITAL (1); LABORATORY (1).                   |
| Value       | nvarchar(max) | Yes      | None             | None    | Display label or decoded meaning for the associated code. Profile: 3 distinct non-null values. Representative values: DEATH-REGISTRAR (1); HOSPITAL (1); LABORATORY (1). |

Relationships

- Probable semantic code/value lookup for SourceTable.TypeOfSource, based on matching domain names; not enforced by a foreign key.

Data Analysis

Business-critical or frequently joined/filterable columns: Code.

- No null or blank values were found in profiled columns.

- Code values are unique in the current data, but no PK/UNIQUE constraint enforces that condition.
- 2 column(s) use nvarchar(max), limiting type precision and potentially increasing storage/indexing cost.

### Data Quality Observations

2 of 2 columns have no null/blank values in the current data. Representative values in the column table are frequency-based and masked for sensitive fields.

### Important Findings

- No primary key is defined.
- Application-level relationships exist without FK enforcement.

## 53. dbo.Unknown

### Table Overview

**Purpose inferred from table and column names.** Generic code/value placeholder reference table; currently empty.

Role classification: Reference / classification.

### Table Statistics

| Measure                      | Value               |
|------------------------------|---------------------|
| Total records                | 0                   |
| Columns                      | 2                   |
| Primary key                  | None                |
| Enforced foreign-key columns | 0                   |
| Created                      | 2025-09-15T10:48:32 |
| Last schema modification     | 2025-09-15T10:48:32 |

### Column Details

| Column Name | Data Type     | Nullable | Key / Constraint | Default | Description                        |
|-------------|---------------|----------|------------------|---------|------------------------------------|
| Site        | nvarchar(max) | No       | None             | None    | Inferred: stores site data.        |
| ICD10       | nvarchar(max) | No       | None             | None    | ICD-10 cancer diagnosis/site code. |

### Relationships

- No enforced or validated logical relationships were identified for this table.

Data Analysis

Business-critical or frequently joined/filterable columns: No specific critical column was identifiable from keys and names..

- The table is empty at the profiling timestamp; value distributions and duplicates cannot be assessed.
- 2 column(s) use nvarchar(max), limiting type precision and potentially increasing storage/indexing cost.

Data Quality Observations

Confirmed: no rows are present; completeness, consistency and representative-value checks are not applicable.

Important Findings

- No primary key is defined.
- Application-level relationships exist without FK enforcement.
- The table is inactive/empty at the profiling timestamp; confirm whether it is planned, legacy or awaiting data.

54. dbo.VillageList

Table Overview

**Purpose inferred from table and column names.** Village-level geographic master keyed to state, district and block codes.

Role classification: Reference / classification.

Table Statistics

| Measure                      | Value               |
|------------------------------|---------------------|
| Total records                | 53,782              |
| Columns                      | 6                   |
| Primary key                  | Id                  |
| Enforced foreign-key columns | 0                   |
| Created                      | 2025-09-15T10:48:32 |
| Last schema modification     | 2025-09-15T10:48:32 |



## Column Details

| Column Name | Data Type     | Nullable | Key / Constraint    | Default | Description                                                                                                                                |
|-------------|---------------|----------|---------------------|---------|--------------------------------------------------------------------------------------------------------------------------------------------|
| Id          | int           | No       | PK#1; IDENTITY(1,1) | None    | Internal row identifier. Profile: 53,782 distinct non-null values; range 16 to 53797. Representative values: 100 (1); 1000 (1); 10000 (1). |
| StateId     | nvarchar(max) | Yes      | None                | None    | State master code. Profile: 1 distinct non-null values. Representative values: 1 (53,782).                                                 |
| DistrictId  | nvarchar(max) | Yes      | None                | None    | District master code. Profile: 30 distinct non-null values. Representative values: 122 (4,125); 110 (3,385); 105 (3,121).                  |
| BlockId     | nvarchar(max) | Yes      | None                | None    | Block master code. Profile: 318 distinct non-null values. Representative values: 11103 (514); 11710 (488); 12706 (452).                    |
| VillageId   | nvarchar(max) | Yes      | None                | None    | Village master code. Representative values masked (sensitive or identifying field).                                                        |
| VillageName | nvarchar(max) | Yes      | None                | None    | Inferred: stores village name data. Representative values masked (sensitive or identifying field).                                         |

## Relationships

- Logical child of BlockList and geographic parent of Centres; all current centre village codes matched.

## Data Analysis

Business-critical or frequently joined/filterable columns: Id, StateId, DistrictId, BlockId, VillageId.

- No null or blank values were found in profiled columns.
- The primary key prevents duplicate full rows and duplicate key values.
- VillageId has 66 duplicate groups (66 excess rows) and is not protected by a unique constraint.
- 310 village rows reference a BlockId absent from BlockList.
- 5 column(s) use nvarchar(max), limiting type precision and potentially increasing storage/indexing cost.

## Data Quality Observations

6 of 6 columns have no null/blank values in the current data. Representative values in the column table are frequency-based and masked for sensitive fields.

## Important Findings

- Application-level relationships exist without FK enforcement.

## 55. dbo.VitalStatusList

### Table Overview

**Purpose inferred from table and column names.** Code/value or geographic reference data for vital status.

Role classification: Reference / classification.

### Table Statistics

| Measure                      | Value               |
|------------------------------|---------------------|
| Total records                | 3                   |
| Columns                      | 2                   |
| Primary key                  | None                |
| Enforced foreign-key columns | 0                   |
| Created                      | 2025-09-15T10:48:32 |
| Last schema modification     | 2025-09-15T10:48:32 |

### Column Details

| Column Name | Data Type     | Nullable | Key / Constraint | Default | Description                                                                                                                                             |
|-------------|---------------|----------|------------------|---------|---------------------------------------------------------------------------------------------------------------------------------------------------------|
| Code        | nvarchar(max) | Yes      | None             | None    | Stored category or classification code. Profile: 3 distinct non-null values. Representative values: 1 (1); 2 (1); 9 (1).                                |
| Value       | nvarchar(max) | Yes      | None             | None    | Display label or decoded meaning for the associated code. Profile: 3 distinct non-null values. Representative values: Alive (1); Dead (1); Unknown (1). |

### Relationships

- Probable semantic code/value lookup for PatientTable.VitalStatus, based on matching domain names; not enforced by a foreign key.

### Data Analysis

Business-critical or frequently joined/filterable columns: Code.

- No null or blank values were found in profiled columns.
- Code values are unique in the current data, but no PK/UNIQUE constraint enforces that condition.
- 2 column(s) use nvarchar(max), limiting type precision and potentially increasing storage/indexing cost.

Data Quality Observations

2 of 2 columns have no null/blank values in the current data. Representative values in the column table are frequency-based and masked for sensitive fields.

Important Findings

- No primary key is defined.
- Application-level relationships exist without FK enforcement.

56. dbo.YesNoList

Table Overview

**Purpose inferred from table and column names.** Code/value or geographic reference data for yes no.  
Role classification: Reference / classification.

Table Statistics

| Measure                      | Value               |
|------------------------------|---------------------|
| Total records                | 3                   |
| Columns                      | 2                   |
| Primary key                  | None                |
| Enforced foreign-key columns | 0                   |
| Created                      | 2025-09-15T10:48:33 |
| Last schema modification     | 2025-09-15T10:48:33 |

Column Details

| Column Name | Data Type     | Nullable | Key / Constraint | Default | Description                                                                                                                                         |
|-------------|---------------|----------|------------------|---------|-----------------------------------------------------------------------------------------------------------------------------------------------------|
| Code        | nvarchar(max) | Yes      | None             | None    | Stored category or classification code. Profile: 3 distinct non-null values. Representative values: 1 (1); 2 (1); 9 (1).                            |
| Value       | nvarchar(max) | Yes      | None             | None    | Display label or decoded meaning for the associated code. Profile: 3 distinct non-null values. Representative values: No (1); Unknown (1); Yes (1). |

Relationships

- No enforced or validated logical relationships were identified for this table.

Data Analysis

Business-critical or frequently joined/filterable columns: Code.

- No null or blank values were found in profiled columns.
- Code values are unique in the current data, but no PK/UNIQUE constraint enforces that condition.
- 2 column(s) use nvarchar(max), limiting type precision and potentially increasing storage/indexing cost.

### **Data Quality Observations**

2 of 2 columns have no null/blank values in the current data. Representative values in the column table are frequency-based and masked for sensitive fields.

### **Important Findings**

- No primary key is defined.
- Application-level relationships exist without FK enforcement.

## Concise Final Risk and Recommendation Summary

- High: Repair the 310 VillageList rows with unknown BlockId and resolve the 66 duplicate VillageId groups before introducing constraints.
- High: Add staged UNIQUE constraints for PatientTable.REGNO, TumourTable.TUMOURID and SourceTable.SOURCEID after regression testing.
- High: Add staged FKs for the validated patient-tumour-source-file chain and geographic hierarchy; use WITH CHECK so trust is verified.
- High: Remediate the 2 malformed and 11 unmapped ICD10 values, then enforce normalized code validation or a controlled lookup.
- Medium: Migrate date strings to date/datetime2 columns and ContactNumber away from float; preserve source text during a controlled transition.
- Medium: Replace unnecessary nvarchar(max) columns with bounded lengths derived from real maxima, prioritizing keys and frequently filtered fields.
- Medium: Add CHECK/default rules for status flags, required workflow fields and audit timestamps; define nullability from business rules.
- Medium: Require reviewer identity for duplicate decisions or explicitly record an automated decision source.
- Medium: Review the 25 empty tables and retire, populate or document them so inactive schema does not obscure intended functionality.
- Security: Verify the intended authorization model: 154 AspNetUsers rows exist while role/claim membership tables are empty and the web app also uses Windows authentication.