

Improving bus arrival-time estimates

using real-time vehicle positions to estimate road state

Tom Elliott and Thomas Lumley

Department of Statistics, University of Auckland, New Zealand

tom.elliott@auckland.ac.nz

1. Introduction

- real time information (RTI) is a vital component of public transit systems, most importantly providing estimated times of arrival (ETAs) of vehicles
- transit vehicle tracking has been well studied in order to improve ETA accuracy [1–4], though these typically focus on individual vehicle or route modeling
- the major cause of unreliability, particularly in networks with poor infrastructure for vehicles (e.g., priority lanes), is congestion
- it has been shown that using buses from multiple routes for prediction improves estimates [5], however this was not generalised to all roads throughout the network
- **we are proposing a generalised approach to modeling transit vehicles that simultaneously models traffic along roads independently of route, allowing for more accurate arrival time prediction by accounting for real-time traffic conditions**

2. GTFS network construction

- **GTFS** is an API specification for transit data [6]
 - available in over 500 locations worldwide
 - we construct a transit network (intersections and connecting road segments) by from the raw GTFS data
1. raw GTFS data provides **one shape per route**
 2. **identify points of intersection** between one or more routes using algorithm adapted from [7]
 3. **split shapes at intersections** to obtain shapes for each individual road segment
 4. express each route as a sequence of road segments




Figure 1: An example transit network produced from five routes. Left: the raw GTFS shapes; Right: the generated transit network with intersections shown as dots.

- Implementation in progress: the `gtfsnetwork` R package, github.com/tmelliott/gtfsnetwork

References

- [1] Z. Wall and D.J. Dailey. An algorithm for predicting the arrival time of mass transit vehicles using automatic vehicle location data. In *Proceedings of the Transportation Research Board Annual Meeting*, 1999.
- [2] D. Dailey, S. Maclean, F. Cathey, and Z. Wall. Transit vehicle arrival prediction: Algorithm and large-scale implementation. *Transportation Research Record: Journal of the Transportation Research Board*, 1771:46–51, jan 2001.
- [3] F. W. Cathey and D. J. Dailey. A prescription for transit arrival/departure prediction using automatic vehicle location data. *Transportation Research Part C: Emerging Technologies*, 11(3-4):241–264, jun 2003.
- [4] Etienne Hans, Nicolas Chabaut, Ludovic Leclercq, and Robert L. Bertini. Real-time bus route state forecasting using particle filter and mesoscopic modeling. *Transportation Research Part C: Emerging Technologies*, 61:121–140, dec 2015.
- [5] Bin Yu, William H. K. Lam, and Mei Lam Tam. Bus arrival time prediction at bus stop with multiple routes. *Transportation Research Part C: Emerging Technologies*, 19(6):1157–1170, dec 2011.
- [6] Google Developers. What is GTFS? <https://developers.google.com/transit/gtfs/>, 2006.
- [7] Yongchuan Zhang, Jiping Liu, Xinlin Qian, Aigen Qiu, and Fuhao Zhang. An automatic road network construction method using massive gps trajectory data. *ISPRS International Journal of Geo-Information*, 6(12), 2017.

3. Vehicle state model

- sequential Bayesian methods well suited to **real-time vehicle tracking**
- in Auckland, GTFS realtime positions obtained approximately every 30 seconds, but high variability
- **particle filter**: general, flexible estimation method that uses sample of particles $\tilde{X}_k = (\mathbf{X}_k^{(i)})_{i=1}^N$, each transitioned independently so features such as multimodality (e.g., at bus stops) are easily handled
- measurement function $h: \mathbb{R} \mapsto \mathbb{R}^2$ calculates particle's map position from distance traveled along shape

1. predict trajectory of each particle using transition function f and system noise parameter Q_k

$$\mathbf{X}_k^{(i)} = f(\mathbf{X}_{k-1}^{(i)}, w_k), \quad w_k \sim N(0, Q_{k-1})$$

2. assume Y_k is a noisy measurement of true position with GPS error σ_y^2 , and define $g: \mathbb{R}^2 \mapsto \mathbb{R}^2$ such that $\text{dist}(g(Y_1), g(Y_2))$ is the ground distance between the points, then the measurement model is

$$g(Y_k) \sim N\left(g(h(\mathbf{X}_k)), \begin{bmatrix} \sigma_y^2 & 0 \\ 0 & \sigma_y^2 \end{bmatrix}\right)$$

and $(\delta_k^{(i)})^2 = \text{dist}(g(h(\mathbf{X}_k^{(i)})), g(Y_k))^2$ is the sum of two independent normal r.v.'s with mean 0 and variance σ_y^2

$$((\delta_k^{(i)})^2 / \sigma_y^2) \sim \chi^2(2) \sim \text{Exp}(0.5)$$

3. evaluated the likelihood for each particle

$$p(Y_k | \mathbf{X}_k^{(i)}) = 0.5e^{-(\delta_k^{(i)})^2 / 2\sigma_y^2}$$

4. update state by resampling particles with replacement, using likelihood weights

$$w^{(i)} = p(Y_k | \mathbf{X}_k^{(i)}) / \sum_{j=1}^N p(Y_k | \mathbf{X}_k^{(j)})$$

5. use resulting trajectories to estimate vehicle speed along road segments to update network in section 4




Figure 2: Left: simulated particle trajectories. Right: particle positions $h(\mathbf{X}_k^{(i)})$; observation Y_k in red.




Figure 3: Y_k (red cross) is a bivariate normal r.v. with mean and variance represented by the black dot and concentric rings, respectively.




Figure 4: After resampling, a posterior sample of trajectories is obtained (orange).

4. Network state model

- network model to estimate and predict network state
- segment j has state β_r^j (vehicle speed) at time t_r with variance P_r^j
- estimate state using an adapted extended Kalman filter (EKF) algorithm
- Step 1: predict future state
 - define **transition function** a such that the state converges to the prior (fig. 5)
 - prior mean speed $\mu_j(t)$ and variance $\psi_j(t)$ at time t from **historical data** (blue lines in fig. 5)
 - use EKF equations to recursively predict state in 1 second intervals
 - define **system noise** so P_r^j converges to $\psi_j(t_r)$
- Step 2: update state when observations received from step 5 in section 3 (red point fig. 6)
 - **measurement error**: variance of particle speeds
 - use EKF update equations to update state at time of observation




Figure 5: Road state β^j (with variance P_r^j , dashed black lines) converge to the prior (blue lines).




Figure 6: After receiving a vehicle speed estimate (red dot), the state is updated.

5. Predicting arrival time

- for each particle, simulate journey along remainder of route
- **simulate speed** $v_t^j \sim N(\beta_t^j, P_t^j)$ for each upcoming segment j
- simulate intersection and bus stop wait times and compute arrival time at each upcoming stop
- resulting ETA distribution can be conveyed to passengers
 - a point estimate
 - and/or a prediction interval (for commuters, this would be understood as a min and “max” wait time)
- ETAs are typically reported in discrete minutes. For the example in figure 7, the distribution might be summarised with
 - a **point estimate** of 5 minutes
 - a **prediction interval** of 4–8 minutes
- summary statistics need to be chosen such that, as the bus approaches, the estimates decrease




Figure 7: Top: travel time predictions for a bus, showing locations of stops (left axis) and intersections (right axis). Bottom: posterior density of ETAs for stop 3.

6. Conclusion and future work

- segmenting routes into route-independent segments allows vehicle observations to update the road network
- real-time network state used to predict arrival time

Next steps:

- improve the network state model: variable speeds along a roads (i.e., $\mu_j(t, d)$ depends on time and distance along segment), include covariates in state transition (adjacent segments, yesterday's traffic, weather, etc.)
- develop a stop-time and intersection-wait time model to more accurately predict wait times
- investigate ideal summary statistics for ETAs (both point and interval prediction)