Notes/Comments for HW #2

This assignment will be using the `read()` function and therefore must accommodate for a possible input error and code for an exception. The following two functions will be defined as given:

```
public static void main(String[] args) throws java.io.IOException

static int NextWordLength() throws java.io.IOException
```

Will use the ~ tilde character to signify end of file, EOF, for keyboard input. This check can then be coded into your program so you can run code from within NetBeans environment. Once it is working correctly, you can then run from command line and do input redirection. The tilde must be by itself. **There must be a space after the last character then the tilde.**

When doing input with the `read()` function, if the buffer is empty or end-of-file, the value of -1 is often returned. When doing the input from the command prompt and entering CTRL-Z to input end-of-file, the ASCII value returned is 26, which signifies the end-of-file. When entering end-of-file, or CTRL-Z, from command line, **make sure to proceed it with punctuation or space.**

There is a function call `isPunct()` that is found in program file call `isPunct.java`. You can use this to help determine if a character is a punctuation mark or not.

You may have noticed that Windows has a different way of storing newlines than Mac and Linux. A newline on Windows is encoded as `\r\n`, which symbolizes a Carriage Return (CR) followed by a Line Feed (LF). By contrast, Mac and Linux simply use a \n.

The words file can be found on Canvas, except for `words.3`. This is an empty file and Canvas does not allow an empty file to be copied. Will need to just open up any text editor and create empty file and save it as `words.3`.

In the comment section at top of program, make sure to tell and explain what you are classifying as a word. Specify your rules, which should be very close to mine.