

### **Protection Switching**

The object model represented here is captured in attributes. The switchData Object is implemented as a data structure.

The protection groups are created on the managedElement directl by an OS or the craft interface and not via this interface. The interface however will notify the OS of such a creation (or deletion) of the protection group.

The 1+1 APS and 1:N APS groups provide the basic line layer protection. The examples that follow refer to SDH/SONET usage, but the principles and approaches explained here could be applied to any Trail protection scheme.

The 2- fiber ring protection group contains the east and the west TPs. The implementation of the 4-fiber rings is that there are three component groups. One for each span as these TPs provide protection to each other within a span first and then the third group encompasses these two groups. By convention for 2-Fiber the first TP is for East and second is for West (mandated), for 4-fiber, the first 2 are East and the last two TPs are for West. The list of TPs within a group is an ordered list, with the protecting TP at the end of the list (except in a non-revertive 1+1 MSP systems, where there is no notion of worker and protection TPs).

In this document and the related IDL, the terms «worker TP» and «protection TP» are used to identify the role of a TP in a protection group. A «worker TP» is sometimes referred to as a «working TP», «protected TP», «primary TP», or «main TP». A «protection TP» is sometimes referred to as a «protecting TP», «secondary TP», or «backup TP».



# 1 Pictorial Depiction of the MS (Line) Layer Protection groups

# 1.1 Application of the Protection groups




Figure: 1+1 MSP




Figure: 1:N MSP Groups.






Figure: 2 Fiber MSSPRING






Figure: Protection Groups in a 4-Fiber MSSPRING.

In the figures, the shaded portions represents the different protection groups and their component TPs at one end.

| PGP Config | Number of groups | Ordered List of TPs.                   |
|------------|------------------|--|
| 1+1 MSP    | 1                | G1 = { P1, P1p} <i>(PGP_TYPE=1+1)</i>  |
| 1:N MSP    | 1                | G1 = { P1Pn, Pp} <i>(PGP_TYPE=1:N)</i> |
| 2F BLSR    | 1                | G1 = {P1,P2} <i>(PGP_TYPE=2FBLSR)</i>  |



| 4FBLSR | G1= $\{P1,P1p\}$ , G2 = $\{P2,P2p\}$ , $(PGP\_TYPE= 1:N groups)$<br>G3 = $\{P1,P1p,P2,P2p\}$ $(PGP\_TYPE=4FBLSR)$ |
|--------|---|

### 1.2 Examples of Protection Switch Notifications

In the following examples, the following apply:

- 1. 1+1 MSP consists of
  - TP<sub>w</sub> and TP<sub>p</sub>
- 2. 1:N consists of
  - TP<sub>w1</sub>.....TP<sub>wi</sub>..... TP<sub>wn</sub> and TP<sub>p</sub>
  - When used in the context of a 4-Fiber ring groups these are 1:1 groups {EW, EP} and {WW, WP} denoting the direction East and West and the worker/protection relationship.
- 3. 2F Ring consists of
  - E and W
- 4. 4F Ring consists of
  - EW, EP, WW, and WP.

| Scenario<br>Description  | protectedTP | switchAwayFromTP | switchToTP | Comments  |
|--|-------------|------------------|------------|---|
| 1+1 MSP, switch from worker to protection.                         | TPw         | TPw              | ТРр        |   |
| 1+1 MSP,<br>switch from<br>protection to<br>worker.                | TPw         | ТРр              | TPw        | When the lockout occurs and the traffic position is changed, no notification is raised. |
| 1:N MSP,<br>switch from<br>one of the<br>workers to<br>Protection. | TPwi        | TPwi             | TPp        |   |
| 1:N MSP,<br>switch from<br>protection back<br>to one of the        | TPwi        | TPp              | TPwi       |   |




| workers.  |                   |     |      |  |
|---|-------------------|-----|------|--|
| 1:N MSP, priority switch: (1) the lower priority traffic switches from protection back to its failed worker; (2) the higher priority traffic switches from its failed worker to the protection. | (1) TPwi (2) TPwj | TPp | TPwi | Low priority traffic  High priority traffic  Two notifications are generated in this case. |
| 2 Fiber Ring, fault detected on the east and redirect the traffic to west.  | E                 | E   | W    | Similar examples apply for the other direction.  |
| 2 Fiber Ring,<br>traffic reverts to<br>East   | Е                 | W   | Е    | Similar examples apply for the other direction.  |
| 4-Fiber Ring,<br>Span Switch in<br>the East span.   | EW                | EW  | EP   | Similar examples apply for the other direction.  |
| 4-Fiber Ring,<br>Span Switch in<br>the East span.,<br>reversion.  | EW                | EP  | EW   | Similar examples apply for the other direction.  |
| 4 Fiber Ring,<br>Ring Switch<br>from the East<br>to the West  | EW                | EW  | WP   | Similar examples apply for the other direction.  |
| 4 Fiber Ring, reversion of the ring switch, in the previous case.   | EW                | WP  | EW   | Similar examples apply for the other direction.  |

## 1.3 Examples Of Protection Switch Data Retrieval

| Scenario    | protectedTP | switchToTP | Comments |
|-------------|-------------|------------|----------|
| Description | protecteure | SWILCHTOTP | Comments |



| 1+1 MSP,after a switch from worker to protection.   | TPw         | ТРр  |   |
|---|-------------|------|---|
| 1+1 MSP, after<br>switch back<br>from protection<br>to worker or<br>when no switch.                     | TPw         | TPw  |   |
| 1:N MSP, after<br>a switch from<br>one of the<br>workers to<br>Protection.                              | TPwi {i=1n} | ТРр  | Retrieve Switch data returns data structure, one per worker TP.         |
| 1:N MSP, after<br>a switch from<br>protection back<br>to one of the<br>workers or in a<br>steady state. | TPwi {i=1n} | TPwi | Retrieve Switch data<br>returns data<br>structure, one per<br>worker TP |
| 2 Fiber Ring  | Е           | W    |   |
| after redirection of the traffic to west.   | W           | W    |   |
| 2 Fiber Ring,   | Е           | E    |   |
| after traffic<br>reverts to East<br>or in steady<br>state   | W           | W    |   |
| 4-Fiber Ring,   | EW          | EP   | .This examples  |
| after a Span<br>Switch in the<br>East span.   | ww          | ww   | assumes that the span switch has not occurred in the West direction.    |
| 4-Fiber Ring,   | EW          | EW   |   |
| after a Span<br>Switch in the<br>East span.,<br>reversion or in<br>steady state                         | WW          | ww   |   |
| 4 Fiber Ring,   | EW          | WP   |   |
| after a Ring<br>Switch from the<br>East to the<br>West  | WW          | ww   |   |
| 4 Fiber Ring,   | EW          | EW   |   |





| after reversion of the ring switch, in the | ww | ww |  |
|--|----|----|--|
| previous case<br>or in steady              |    |    |  |
| state                                      |    |    |  |



### 2 Administrative Appendix

#### 2.1 Document History

| Version | Date       | Description of Change |
|---------|------------|-----------------------|
| 3.0     | April 2005 |                       |

#### 2.2 Acknowledgments

| First Name | Last Name | Company |
|------------|-----------|---------|
|            |           |         |

### 2.3 How to comment on this document

Comments and requests for information must be in written form and addressed to the contact identified below:

| Keith   | Dorking            | CIENA |
|---------|--------------------|-------|
| Phone:  | +1 678 867 5007    |       |
| Fax:    | +1 678 867 5010    |       |
| e-mail: | Kdorking@ciena.com |       |

Please be specific, since your comments will be dealt with by the team evaluating numerous inputs and trying to produce a single text. Thus we appreciate significant specific input. We are looking for more input than wordsmith" items, however editing and structural help are greatly appreciated where better clarity is the result.