



Red Hat Training and Certification

Managing and Building Container Images and Containers)

Travis Michette

Version 1.0

Table of Contents

Introduction	1
Lab Machine Requirements	1
Using the Lab Guide	2
1. RHEL 8 Changes	3
1.1. TMUX Usage	3
1.2. SystemD Overview	4
1.2.1. Understanding SystemD Unit Files and Creating a Service	4
1.3. FirewallD	7
1.3.1. FirewallD Service Definitions	7
1.3.2. The firewall-cmd Utility	7
1.3.3. FirewallD Files and Locations	9
1.3.4. Defining a Custom Service File	10
1.3.5. FirewallD Configuration Files	10
1.4. Cockpit	11
1.4.1. Installing Additional Cockpit Packages	12
1.4.1.1. Cockpit to Manage Multiple Systems	12
2. Managing Containers with the New Runtime	16
2.1. Deploying Containers with the New Container Runtime	16
2.1.1. The Podman Container Engine	16
2.2. Podman Configuration Files	18
2.3. Container Image Storage	18
2.4. Managing Containers using the Red Hat Web Console	18
3. Podman Pods	19
3.1. Using and Leveraging Pods with Podman	19
3.2. Podman Image and Container Pruning	19
4. Building Containers with Buildah	20
4.1. Building an Image Using Buildah Rootless	22
5. Containers as System Services	23
6. Container Management with Ansible	24
6.1. Ansible Podman Collection	24
6.1.1. Obtaining Podman Collections	24
6.1.2. Installing and Using the containers.podman Collection	24
7. Quay Image Registry	26
7.1. Installing the Quay Image Registry	26
7.2. Using the Quay Image Registry	26
7.3. Inspecting Images with Skopeo on Remote Registries	26
Appendix A: System Security Policy and Compliance	27
A.1. Customizing SCAP Content	27
A.2. Running a SCAP Scan with Custom Content	30
A.3. Creating an Ansible Remediation Playbook Based on SCAP Scan Results	37

Introduction

This guide will cover additional and supplemental materials for the DO180 custom container course. As part of this guide, students will be learning the following concepts:

Course Objectives

- Exploring RHEL 8.x Differences
- Exploring SystemD and Creating SystemD Services
- Exploring FirewallD and FirewallD Custom Services
- Exploring Cockpit and the Red Hat Web Console
- Rootless Podman
- Leveraging Podman's Pod Capabilities
- Managing Containers with the Red Hat Web Console (Cockpit)
- Running Containers as a Service (SystemD)
- Building Container Images with Buildah (from scratch)
- Building Container Images from Containerfile/Dockerfile Files
- Installing/Configuring/Using Quay Container Registry
- Using ClairV4 and Quay Mirroring with Quay
- Exploring Skopeo to Interact with Container Images

Courses for Reference

- DO180
- RH134
- RH354

This course will use a DO180 course for the hands-on lab environment. The environment has been modified to have an additional machine to perform custom exercises and have the Quay registry installed locally.

Lab Machine Requirements

In addition to the DO180 lab environment, a new VM has been added to that environment. This machine can be setup and configured locally with the following requirements:

VM Requirements

- RHEL 8.4+
- 6 vCPU (8 vCPU Recommended)
- 12GB RAM (16GB Recommended)
- 60GB Storage (Image and Database storage)

Using the Lab Guide

This lab guide and contents within the guide are meant to supplement the course and materials delivered as part of a custom DO180 delivery. It is advisable to download the RH354 course manual and the RH134 course manual prior to the class delivery. The DO180 course guide can be downloaded as part of the course.



Course Materials

All course materials and lab materials for the custom portion of the course can be found here:
https://github.com/tmichett/OCP_Demos

The lab guide for this course can be downloaded from here: https://github.com/tmichett/OCP_Demos/blob/main/Containers/Containers.pdf

1. RHEL 8 Changes

RHEL 8.x brought several significant changes and expanded upon other changes that were introduced as part of the **SystemD** switch in RHEL 7.x. This course will highlight some of the most significant changes and enhancements to RHEL 8.x.

RHEL 8.x Enhancements

- TMUX
- SystemD
- FirewallD

1.1. TMUX Usage

As part of the upgrade process and package replacement process in RHEL8, several packages have not only been deprecated, they've been completely removed. The **screen** package is one package that is no longer available for installation. Instead, a new terminal program **tmux** has been introduced to provide the **screen** functionality as well as other enhancements.



TMUX References

Red Hat Learning Community: <https://learn.redhat.com/t5/Platform-Linux/Using-tmux-to-execute-commands-on-servers-in-parallel/m-p/2200>

Tactical TMUX: <https://danielmiessler.com/study/tmux/>

TMUX Usage

In the example below, we will explore the **screen** functionalities of TMUX with respect to attaching and detaching of sessions.

Installing TMUX

1. Install **tmux** with YUM

Listing 1. Installation of TMUX

```
[root@workstation ~]# yum install tmux
Red Hat Enterprise Linux 8.0 AppStream (dvd) 21 MB/s | 5.3 MB 00:00
Red Hat Enterprise Linux 8.0 BaseOS (dvd) 23 MB/s | 2.2 MB 00:00
Last metadata expiration check: 0:00:01 ago on Mon 13 Apr 2020 10:55:47 AM EDT.
Package tmux-2.7-1.el8.x86_64 is already installed.
Dependencies resolved.
Nothing to do.
Complete!
```

2. Launch **tmux**

Listing 2. Using tmux

```
[student@workstation ~]$ tmux
```

[Chapter1 7d227] | Chapter1-7d227.png

Figure 1. **tmux** Terminal Window

3. Placing **tmux** Window in Background (CTRL+B+D)

Listing 3. Detaching a **tmux** Session

```
[student@workstation ~]$ tmux
[detached (from session 0)]
```

4. Re-attaching to **tmux**

Listing 4. Source Description

```
[student@workstation ~]$ tmux list-sessions
0: 1 windows (created Mon Apr 13 11:01:53 2020) [80x23]

[student@workstation ~]$ tmux attach-session -t 0
```

Naming or Renaming Sessions

It is possible that once you are in a **tmux** session to rename the session.

Listing 5. Renaming a **TMUX** Session

```
[student@workstation ~]$ tmux rename-session --help
usage: rename-session [-t target-session] new-name

[student@workstation ~]$ tmux rename-session -t 0 travis-demo
```



[Chapter1 bf6b1] | Chapter1-bf6b1.png

Figure 2. Renamed **tmux** Session

```
[student@workstation ~]$ tmux new-session
[detached (from session travis-demo)]

[student@workstation ~]$ tmux list-sessions
travis-demo: 1 windows (created Mon Apr 13 11:08:28 2020) [98x23]

[student@workstation ~]$ tmux attach-session -t travis-demo
```

1.2. SystemD Overview

1.2.1. Understanding SystemD Unit Files and Creating a Service

Starting in RHEL 7, **SystemD** replaced the older style Linux SystemV (sysvinit daemon). This change continued through with RHEL 8 and more systemd tools replaced the traditional legacy tools. This small section will provide references and an overview of how **systemd** can be used to replace the older *init* scripts that were placed in **/etc/init.d/** or some of the other directories.



SystemD References

Linus Torvalds and others on Linux's systemd: <https://www.zdnet.com/article/linus-torvalds-and-others-on-linuxs-systemd/>

SysVinit Vs systemd Cheatsheet: <https://www.2daygeek.com/sysvinit-vs-systemd-cheatsheet-systemctl-command-usage/>

1. Create the Init Script

Listing 6. Init Script to Run at Startup

```
[root@servera ~]# vim /usr/bin/ups_test_service.sh
#!/usr/bin/bash

DATE=`date '+%Y-%m-%d %H:%M:%S'`
echo "This is a sample service started at ${DATE} for the UPS RH354 course." | systemd-cat -p info

while :
do
echo "Looping...";
sleep 30;
done
```

2. Make script executable

*Listing 7. Running **chmod** on script*

```
[root@servera ~]# chmod +x /usr/bin/ups_test_service.sh
```

3. Edit SystemD Service (Unit File)

Listing 8. Editing the .service File

```
[root@servera ~]# vim /etc/systemd/system/ups_test_service.service

[Unit]
Description=UPS example systemd service.

[Service]
Type=simple
ExecStart=/bin/bash /usr/bin/ups_test_service.sh

[Install]
WantedBy=multi-user.target
```

4. Fix Permissions on .service File

*Listing 9. Running **chmod** on .service File*

```
[root@servera ~]# chmod 644 /etc/systemd/system/ups_test_service.service
```



SystemD Services

Once a script has been created and made executable and a service file has properly been created and placed in **/etc/systemd/system/** directory it is possible to use the **systemctl** command to interact with the service file and make it active on boot.



Default SystemD Directories

It is important to note that there are several default SystemD directories. When defining your own files, the proper location is to place them in **/etc/systemd**. There is more information available in other Red Hat courses, specifically the RH442 Performance Tuning course.

Default Location: **/lib/systemd/**

1. Starting and Enabling a Custom Service

Listing 10. Controlling a Custom Service with **systemctl**

```
[root@servera ~]# systemctl enable ups_test_service.service --now
Created symlink /etc/systemd/system/multi-user.target.wants/ups_test_service.service → /etc/systemd/system/ups_test_service.service.
```

2. Checking Status of a Custom Service

Listing 11. Using **systemctl** to Check Service Status

```
[root@servera ~]# systemctl status ups_test_service.service
● ups_test_service.service - UPS example systemd service.
   Loaded: loaded (/etc/systemd/system/ups_test_service.service; enabled)
   Active: active (running) since Wed 2020-05-20 18:08:22 EDT; 19s ago
     Main PID: 2136 (bash)
       Tasks: 2 (limit: 23896)
      Memory: 940.0K
        CGroup: /system.slice/ups_test_service.service
                └─2136 /bin/bash /usr/bin/ups_test_service.sh
                  └─2140 sleep 30

May 20 18:08:22 servera.lab.example.com systemd[1]: Started UPS examp>
May 20 18:08:22 servera.lab.example.com bash[2136]: Looping..
```

3. Checking **/var/log/messages** for Custom Service

Listing 12. Searching Log file for Custom Service

```
[root@servera ~]# grep -i ups /var/log/messages
May 20 18:08:22 jegui journal[2139]: This is a sample service started at 2020-05-20 18:08:22 for the UPS RH354 course.
```




SystemD References

Creating a Service at Boot: <https://www.linode.com/docs/quick-answers/linux/start-service-at-boot/>

Overview of SystemD for RHEL7: <https://access.redhat.com/articles/754933>

Converting traditional sysV init scripts to Red Hat Enterprise Linux 7 systemd unit files:
<https://www.redhat.com/en/blog/converting-traditional-sysv-init-scripts-red-hat-enterprise-linux-7-systemd-unit-files>

Creating and Modifying SystemD Unit Files: https://access.redhat.com/documentation/en-us/red_hat_enterprise_linux/7/html/system_administrators_guide/sect-managing_services_with_systemd-unit_files

Creating a Linux service with systemd: <https://medium.com/@benmorel/creating-a-linux-service-with-systemd-611b5c8b91d6>

How to create systemd service unit in Linux: <https://linuxconfig.org/how-to-create-systemd-service-unit-in-linux>

1.3. FirewallD

Beginning in RHEL 8.0, Red Hat moved away from **iptables** as the back-end firewall implementation and instead moved to NTables. However, the introduction of FirewallD and the **firewall-cmd** management commands implemented in RHEL 7.x have evolved and leveraging FirewallD is still the preferred firewall management solution in RHEL 8.x.

1.3.1. FirewallD Service Definitions

FirewallD was introduced in RHEL7 as part of the SystemD transition and a new way to manage firewalls without using the underlying firewall implementation (**iptables**). FirewallD with **firewall-cmd** continues to be used in RHEL8 as the preferred method of managing and maintaining firewall rules.



FirewallD Resources

<https://firewalld.org/>

<https://www.liquidweb.com/kb/an-introduction-to-firewalld/>

<https://cheatography.com/mikael-leberre/cheat-sheets/firewall-cmd/>

1.3.2. The firewall-cmd Utility

The **firewall-cmd** utility is the primary method to manage and interact with firewall rules on RHEL7/8 systems. The **firewall-cmd** utility supports BASH completion and allows firewall rules to be added based on defined services or by specifying ports/protocols.

Listing 13. Allowing HTTP through the Firewall by Port/Protocol

```
[root@servera ~]# firewall-cmd --add-port=80/tcp
success

[root@servera ~]# firewall-cmd --list-all
public (active)
  target: default
  icmp-block-inversion: no
  interfaces: enp1s0
  sources:
  services: cockpit dhcpv6-client ssh
  ports: 80/tcp
  protocols:
  masquerade: no
  forward-ports:
  source-ports:
  icmp-blocks:
  rich rules:

[root@servera ~]# firewall-cmd --remove-port=80/tcp
success
```

Listing 14. Allowing HTTP through the Firewall by Service

```
[root@servera ~]# firewall-cmd --add-service=
Display all 154 possibilities? (y or n)

[root@servera ~]# firewall-cmd --add-service=http
success

[root@servera ~]# firewall-cmd --list-all
public (active)
  target: default
  icmp-block-inversion: no
  interfaces: enp1s0
  sources:
  services: cockpit dhcpv6-client http ssh
  ports:
  protocols:
  masquerade: no
  forward-ports:
  source-ports:
  icmp-blocks:
  rich rules:
```

firewall-cmd Usage Warning

The **firewall-cmd** utility can be used to make changes to the running firewall as shown in the examples above. This does not make changes to the firewall config file. In order to make the changes to the configuration file, it is necessary to use the **--permanent** options to have the changes written to a file.

When using **--permanent**, and you are not making changes to the current firewall runtime, it is also necessary to use: **firewall-cmd --reload** to reload or load new firewall rules from the firewall configuration file.

*Important Header*

It is important to note that presently the Red Hat Web Console (cockpit) only supports management of **firewalld** using defined services.

1.3.3. FirewallD Files and Locations

FirewallD has a few locations for files both for configuration and usage. As with most configuration files on a Linux system, those rely in **/etc/**. The user configurable files for FirewallD also reside in **/etc/**. Default configuration files for services, zones, and other FirewallD functionality resides in **/usr/lib/firewalld**. This location contains all defined services files and default configuration files for FirewallD and used by the **firewall-cmd** utility.

Listing 15. FirewallD Configuration Files

```
[root@servera ~]# tree /etc/firewalld/
/etc/firewalld/
├── firewalld.conf
├── helpers
├── icmptypes
├── ipsets
├── lockdown-whitelist.xml
├── services
├── zones
│   ├── public.xml
│   └── public.xml.old
5 directories, 4 files
```

Listing 16. FirewallD Default Configuration Files

```
[root@servera ~]# tree /usr/lib/firewalld/
/usr/lib/firewalld/
├── helpers
│   ├── amanda.xml
│   ├── ftp.xml
│   ├── h323.xml
│   ├── irc.xml
│   ├── netbios-ns.xml
│   ├── pptp.xml
│   └── proto-gre.xml
... output omitted ...
├── zones
│   ├── block.xml
│   ├── dmz.xml
│   ├── drop.xml
│   ├── external.xml
│   ├── home.xml
│   ├── internal.xml
│   ├── public.xml
│   ├── trusted.xml
│   └── work.xml
5 directories, 222 files
```

1.3.4. Defining a Custom Service File

It is possible to define custom **firewalld** service files. These files can be used for your environments for custom applications or custom firewall rules. These service files can also be checked into a version control system such as **git**.



Creating a Custom Service File using Existing File as Base

It is easiest to take an existing service file, copy it to the **/etc/firewalld/services** directory, rename and edit the file.

1. Copy existing FirewallD service file to **/etc/firewalld/services**

Listing 17. Using SSH Service File as a Starting Point

```
[root@servera ~]# cp /usr/lib/firewalld/services/ssh.xml /etc/firewalld/services/custom_ssh.xml
```

2. Edit the file and specify the new options

Listing 18. Edit the Custom SSH Service Definition

```
[root@servera ~]# vim /etc/firewalld/services/custom_ssh.xml
<?xml version="1.0" encoding="utf-8"?>
<service>
  <short>SSH_Custom</short>
  <description>This is a custom SSH service definition for paranoid people that don't want to run SSH on the default port of 22. This will
  allow SSH to run on the port 8022 to meet our defined security guidance.</description>
  <port protocol="tcp" port="8022"/>
</service>
```

3. Listing FirewallD Services to Verify New Service

Listing 19. Getting Listing of FirewallD Services

```
[root@servera ~]# firewall-cmd --get-services | grep custom_ssh
```



FirewallD Delays in Discovering a Service

Depending on system speed and refreshing of FirewallD daemon, the new service might not be picked up immediately. It will be discovered or if you are in a hurry, you can run **firewall-cmd --reload** command to immediately have the service discovered and available.

1.3.5. FirewallD Configuration Files

As stated above, the main FirewallD configuration files are located in **/etc/firewalld**. To specifically change or view the configuration file on the system, you generally want to look at the firewalls in the **Firewall Zone**. This is found by opening the corresponding zone file in **/etc/firewalld/zones** directory.

1. Viewing Firewall configuration for the Public Zone.

Listing 20. FirewallD Configuration for Public

```
[root@servera ~]# cat /etc/firewalld/zones/public.xml
<?xml version="1.0" encoding="utf-8"?>
<zone>
  <short>Public</short>
  <description>For use in public areas. You do not trust the other computers on networks to not harm your computer. Only selected incoming
connections are accepted.</description>
  <service name="ssh"/>
  <service name="dhcpv6-client"/>
  <service name="cockpit"/>
</zone>
```

2. Adding a custom service

Listing 21. Adding our new Service

```
[root@servera ~]# firewall-cmd --add-service=custom_ssh --permanent
success
```

3. Verifying Firewall configuration for the Public Zone.

Listing 22. FirewallD Configuration for Public with Custom Service

```
[root@servera ~]# cat /etc/firewalld/zones/public.xml
<?xml version="1.0" encoding="utf-8"?>
<zone>
  <short>Public</short>
  <description>For use in public areas. You do not trust the other computers on networks to not harm your computer. Only selected incoming
connections are accepted.</description>
  <service name="ssh"/>
  <service name="dhcpv6-client"/>
  <service name="cockpit"/>
  <service name="custom_ssh"/>
</zone>
```

1.4. Cockpit

Another change with RHEL 8.x was with the graphical server and the desktop manager. The X11 project and XWindows has been replaced largely with Wayland/Gnome3 as the graphical rendering environment of choice. These changes introduced some dependencies on the graphical management of several system services and components. The Wayland change no longer supports the X11 forwarding, so it was necessary to build tools or extend existing tools to be managed differently. The **cockpit** project was utilized and implemented in RHEL 8 as the new Red Hat Web Management Console which brought in numerous plugins allowing these services to be managed graphically within a standard web browser.



Red Hat Web Management Console

Leverage portions of the RH354 text around Cockpit and the Red Hat Web Management Console before looking at the additional Cockpit packages.

1.4.1. Installing Additional Cockpit Packages

Listing 23. Install all Base Cockpit Packages

```
[root@servera ~]# yum install cockpit*
```




Figure 3. Cockpit Dashboard



Cockpit Plugin and Package Availability

Using the installation method above will install all Cockpit packages and plugins that are available in currently subscribed channels. However, not all components will work until additional back-end components are installed. For example, the **Composer** cockpit plugins need composer and other items installed in order to be able to be fully utilized. This installation gives the **Cockpit Dashboard Plugin** which allows connecting to multiple Web Consoles.

1.4.1.1. Cockpit to Manage Multiple Systems

It is possible to use a single **cockpit** Interface to manage multiple servers.

1. Ensure cockpit socket/service is running and configured on all systems.

Listing 24. Test and Enable Cockpit

```
[student@workstation ~]$ ssh root@servera
Activate the web console with: systemctl enable --now cockpit.socket

[root@servera ~]# systemctl enable --now cockpit.socket
Created symlink /etc/systemd/system/sockets.target.wants/cockpit.socket → /usr/lib/systemd/system/cockpit.socket.
```

2. Connect to the Cockpit Web Console




Figure 4. Red Hat Web Console (cockpit)

3. Add another Web Console from the Cockpit Dashboard
 - a. Navigate to the Dashboard
 - b. Click the "+" and complete the information




Figure 5. Adding Additional machines

4. Verify the System Fingerprint and click **Connect** image::Chapter3-87075.png[title="Fingerprint Verification", align="center"]
5. It is now possible to switch systems from the System Drop-down menu




Figure 6. Switching Systems

2. Managing Containers with the New Runtime

2.1. Deploying Containers with the New Container Runtime

2.1.1. The Podman Container Engine

RHEL8 includes the **container-tools** package module. New engine is **podman** replaces **docker** and **moby**. It also contains new tools **buildah** to build container images and **skopeo** to manage images on registries like **runc**. The new toolset allows building/running containers without daemons.




Figure 7. Docker to RHEL8 Container Runtime

Container Runtime Toolset

- Docker replaced with new container runtime
- New toolset supports OCI and reuse of third-party images
- Integrates with **audit** of Docker client-server model
- **container-tools** module provides new container runtime tools and engine.




Figure 8. New Container Runtime

Describing new Container Runtime Tool

- The **podman** engine is daemonless and supporting container execution.
- **podman** syntax is similar to the docker command, supporting **Dockerfile** use
- **Buildah** builds container images, from scratch or a Dockerfile.
- Copy and inspect container images in registries with **Skopeo**
- **Skopeo** supports Docker and private registries, the Atomic registry, and local directories, including those which use OCI



RHEL8 includes **Pacemaker** containers with **podman** as a tech preview. Pacemaker supports execution of the container across multiple hosts.

Listing 25. Installation of Container Tools

```
[student@workstation ~]$ sudo yum module install container-tools
```

2.2. Podman Configuration Files

2.3. Container Image Storage

2.4. Managing Containers using the Red Hat Web Console

3. Podman Pods

This will talk about Podman Pods

3.1. Using and Leveraging Pods with Podman

3.2. Podman Image and Container Pruning



References

Managing Containers and Pods: https://developers.redhat.com/blog/2019/01/15/podman-managing-containers-pods?ts=1634314817672#podman_pods__what_you_need_to_know

Managing Containers using Podman and Skopeo: <https://www.tecmint.com/manage-containers-using-podman-in-rhel/>

Podman: <https://docs.podman.io/en/latest/>

Podman System Prune:

man pages

podman-system-prune, podman-container-cleanup,

4. Building Containers with Buildah

Example 1. EXAMPLE - Creating a Custom Container Image Using Buildah

Listing 26. Creating a Custom Container

```
[root@workstation ~]# buildah from scratch
working-container
```

Listing 27. Naming and Inspecting a Custom Container

```
[root@workstation ~]# buildah config --label name=My-Container working-container
[root@workstation ~]# buildah inspect working-container
```

Listing 28. Installing Packages on Working Container

```
[root@workstation ~]# buildah mount working-container ❶

[root@workstation ~]# yumdownloader --destdir=/tmp redhat-release-server ❷

[root@workstation ~]# rpm -ivh --root
/var/lib/containers/storage/overlay/a6a136063f0ada2b1ed4b01eff9a04b4d6419ae828bc4b49e742bca594e08560/merged /tmp/redhat-release-8.0-
0.39.el8.x86_64.rpm ❸

[root@workstation ~]# cp /etc/yum.repos.d/rhel_dvd.repo
/var/lib/containers/storage/overlay/a6a136063f0ada2b1ed4b01eff9a04b4d6419ae828bc4b49e742bca594e08560/merged/etc/yum.repos.d/ ❹

[root@workstation ~]# yum install --installroot
/var/lib/containers/storage/overlay/a6a136063f0ada2b1ed4b01eff9a04b4d6419ae828bc4b49e742bca594e08560/merged httpd ❺

[root@workstation ~]# echo "This is a custom webserver container for me" >>
/var/lib/containers/storage/overlay/a6a136063f0ada2b1ed4b01eff9a04b4d6419ae828bc4b49e742bca594e08560/merged/var/www/html/index.html ❻

[root@workstation ~]# yum install --installroot
/var/lib/containers/storage/overlay/a6a136063f0ada2b1ed4b01eff9a04b4d6419ae828bc4b49e742bca594e08560/merged httpd-manual ❼

[root@workstation ~]# buildah config --cmd "/usr/sbin/httpd -DFOREGROUND" working-container ❽

[root@workstation ~]# buildah config --port 80/tcp working-container ❾

[root@workstation ~]# yum clean all --installroot
/var/lib/containers/storage/overlay/a6a136063f0ada2b1ed4b01eff9a04b4d6419ae828bc4b49e742bca594e08560/merged ❿

[root@workstation ~]# buildah unmount working-container ⓫

[root@workstation ~]# buildah commit working-container my-container-image ⓬

[root@workstation ~]# buildah images ⓭
```

- ❶ Mount container image filesystem for modification
- ❷ Download Red Hat Release RPM for installation
- ❸ Install Red Hat Release RPM
- ❹ Create repository for container image so files can be installed

- ⑤ Install the HTTP package for a webserver
- ⑥ Create an **index.html** file for the webserver
- ⑦ Install the Apache manual for reference documentation
- ⑧ Configure webserver to run
- ⑨ Configure and open port **80** for the **TCP** protocol for the container
- ⑩ Clean up yum data to minimize required disk space
- ⑪ Unmount the container image filesystem
- ⑫ Commit the container image
- ⑬ List container images

Listing 29. Testing the Container Image

```
[root@workstation ~]# podman run -d -p 8080:80 localhost/my-container-image

[root@workstation ~]# curl localhost:8080
This is a custom webserver container for me

[root@workstation ~]# curl http://localhost:8080/manual/
```




Figure 9. Testing Container

Listing 30. Stopping and Cleanup of Image

```
[root@workstation ~]# podman list ❶
CONTAINER ID   IMAGE                                COMMAND                  CREATED        STATUS        PORTS                NAMES
9bd572633953   localhost/my-container-image:latest /usr/sbin/httpd -...    2 seconds ago Up 1 second ago 0.0.0.0:8080->80/tcp  cranky_stonebraker

[root@workstation ~]# podman stop 9bd572633953 ❷
9bd572633953276ac75417db3ac8e70875a0f2713e8cdfd32253fe343d06153d

[root@workstation ~]# podman stop -a ❸

[root@workstation ~]# podman rm cranky_stonebraker ❹

[root@workstation ~]# podman rm 9bd572633953276ac75417db3ac8e70875a0f2713e8cdfd32253fe343d06153d ❺

[root@workstation ~]# podman rmi localhost/my-container-image ❻

[root@workstation ~]# buildah delete working-container ❼
```

- ❶ Listing Running Containers
- ❷ Stopping Single Container by ID
- ❸ Stopping All Running Containers
- ❹ Remove Container by Name
- ❺ Remove Container by ID
- ❻ Removing Container Image from Registry
- ❼ Delete Working Container from System

4.1. Building an Image Using Buildah Rootless

5. Containers as System Services

6. Container Management with Ansible

Containers can now be managed with the Ansible Podman collection leveraging Ansible Automation Platform (AAP). Red Hat curates and maintains several supported Ansible Collections at Ansible Automation Hub. The community collections are available to be installed from Ansible Galaxy.

6.1. Ansible Podman Collection

The Ansible Podman collection is a required component in order to have the Ansible Modules needed to manage containers using Podman. Currently, the **containers.podman** is only available via Ansible Galaxy.

6.1.1. Obtaining Podman Collections

In order to leverage Ansible to official manage Podman containers, the **containers.podman** collection must be installed on the Ansible Control node. Currently, there are two main sources for installation of Ansible collections.

Ansible Collections

- Red Hat supported collections for Ansible can be downloaded from Ansible Automation Hub (<https://console.redhat.com/ansible/automation-hub>).
- Ansible Community collections can be downloaded from Ansible Galaxy (<https://galaxy.ansible.com/containers/podman>)

Ansible Automation Hub and Ansible Galaxy

It is required that you have a Red Hat Subscription for Ansible Automation Platform (AAP2.0) in order to access Red Hat Supported Ansible collections. The lab and exercises will use the Ansible Galaxy Podman collection.



Listing 31. Installing Ansible Galaxy Podman Collection

```
ansible-galaxy collection install containers.podman
```

containers.podman Documentation

<https://galaxy.ansible.com/containers/podman> <https://docs.ansible.com/ansible/latest/collections/containers/podman/index.html> https://docs.ansible.com/ansible/latest/collections/containers/podman/podman_container_module.html

6.1.2. Installing and Using the containers.podman Collection

There are multiple methods for the Podman collection to be installed, however, for this course and the exercises, the collection will be installed locally to the **.collections** sub-folder using a requirements.yml file. The **ansible.cfg** will point to this as already available in the path and the Ansible playbooks being utilized will reference the **collections** at the top of the playbook similar to Ansible roles so that throughout the playbook tasks, the shorter module name can be referenced.

Using Collections

Referencing the **collection** and using shorter module names. This allows a cleaner and more streamlined approach and is generally consistent with the older Ansible versions. It is 100% fully acceptable to utilize the fully qualified module names, however, for the course and ease of use we will continue referencing Ansible modules by the shortened/condensed name.

Listing 32. Sample Playbook with Collections



```
---
- name: Deploy Quay Mirror
  hosts: quay
  vars:
    QUAY_DIR: /quay
  vars_files:
    - registry_login.yml
  collections: ❶
    - containers.podman

  tasks:

    ## Podman Collections Needed for Login
    - name: Login to Container Registry
      podman_login: ❷
        username: "{{ registry_un }}"
        password: "{{ registry_pass }}"
        registry: "{{ registry_url }}"
```

- ❶ Importing the collection(s) to be used and referenced by short module names in the playbook.
- ❷ Leveraging modules by short module names in the playbook.



References

References for this chapter

7. Quay Image Registry

7.1. Installing the Quay Image Registry

7.2. Using the Quay Image Registry

7.3. Inspecting Images with Skopeo on Remote Registries

Appendix A: System Security Policy and Compliance

System security and compliance is a primary concern for people when thinking about the protection of systems and integrity of data. This set of hands-on procedures will focus on obtaining the content and necessary packages to perform a basic scan and remediate the system based on scan results. As part of the lab, you will be customizing your own SCAP content for a scan, view the results, and generate an Ansible playbook based on the failed results.

A.1. Customizing SCAP Content

Red Hat includes the SCAP Workbench application as a GUI application which allows scanning, customizing, and saving SCAP scans and results. The SCAP Workbench can be used to perform scans of remote systems over an SSH connection or it can be utilized to scan the local system. Since the SCAP Workbench is a GUI application, it must run on a system with X-Windows installed.

Servers to Configure

- workstation

Packages to Install

- scap-workbench



Since we are using an application on a VM that requires a GUI, we can use X11 forwarding with the SSH connection by specifying a **-X** on the command line.

Step 1 - SSH to Workstation

The first step is to connect to the workstation and forward X11 traffic back to the local system.

Example 2. Connecting to the Workstation VM

Listing 33. Connecting to Workstation Using SSH

```
# ssh root@workstation -X
```

Step 2 - Install Packages

After connecting to the Workstation VM, you will need to install the SCAP Workbench and its dependencies.

Example 3. Installing SCAP Workbench

Listing 34. Using Yum to Install SCAP Workbench

```
# yum install scap-workbench

Loaded plugins: langpacks, search-disabled-repos
Resolving Dependencies
--> Running transaction check
--> Package scap-workbench.x86_64 0:1.1.6-1.el7 will be installed
--> Processing Dependency: openscap-utils >= 1.2.0 for package: scap-workbench-1.1.6-1.el7.x86_64
--> Processing Dependency: scap-security-guide for package: scap-workbench-1.1.6-1.el7.x86_64
--> Running transaction check
--> Package openscap-utils.x86_64 0:1.2.16-8.el7_5 will be installed
--> Processing Dependency: openscap-containers = 1.2.16-8.el7_5 for package: openscap-utils-1.2.16-8.el7_5.x86_64
--> Package scap-security-guide.noarch 0:0.1.36-9.el7_5 will be installed
--> Processing Dependency: openscap-scanner >= 1.2.5 for package: scap-security-guide-0.1.36-9.el7_5.noarch
--> Running transaction check
--> Package openscap-containers.noarch 0:1.2.16-8.el7_5 will be installed
--> Package openscap-scanner.x86_64 0:1.2.16-8.el7_5 will be installed
--> Finished Dependency Resolution

Dependencies Resolved

=====
Package                Arch      Version              Repository            Size
=====
Installing:
scap-workbench          x86_64    1.1.6-1.el7          rhel--server-dvd     1.8 M
Installing for dependencies:
openscap-containers     noarch    1.2.16-8.el7_5       rhel_updates          27 k
openscap-scanner        x86_64    1.2.16-8.el7_5       rhel_updates          61 k
openscap-utils          x86_64    1.2.16-8.el7_5       rhel_updates          27 k
scap-security-guide     noarch    0.1.36-9.el7_5       rhel_updates          2.6 M

Transaction Summary
=====
Install 1 Package (+4 Dependent packages)

Total download size: 4.5 M
Installed size: 64 M
Is this ok [y/d/N]:
```



Some things might already be installed for you, if SCAP Workbench is already installed, please move on to the next step. Also note the dependencies for SCAP Workbench as they are automatically installed.

Step 3 - Launching SCAP Workbench

In order to run a scan or customize SCAP content, you will need to launch the SCAP Workbench application.



You **must** use SCAP Workbench from a GUI, so it will need to run either locally or through an SSH connection with X11 forwarded.

Example 4. Launching SCAP Workbench

Listing 35. Using SCAP Workbench

```
# scap-workbench
```

[AppendixA d656e] | *AppendixA-d656e.png**Figure 10. SCAP Workbench Startup*

Step 4 - Creating Custom Content

Once SCAP Workbench has been launched, select the content to load. For this lab, we will be using the RHEL7 content.

Example 5. Creating Custom Content

1. For **Select content to load**: select "**RHEL8**", then click "**Load Content**"
2. Select the **Profile** you want to use to start customization



For this example, we will use the **OSPP - Protection Profile for General Purpose Operating Systems Baseline**

[AppendixA 12524] | *AppendixA-12524.png**Figure 11. SCAP Workbench OSPP Profile*

3. Click "**Customize**" to create custom SCAP content based on the chosen profile, and give it a name.

[AppendixA 7cd7e] | *AppendixA-7cd7e.png**Figure 12. SCAP Custom OSPP Profile Creation*

The name for this is: **xccdf_org.ssgproject.content_profile_ospp_customized**

4. Click "Deselect All" so that you can select the items you wish to include in your custom scan profile. **NOTE:** we are doing this to also limit it to a few checks for the example.

[AppendixA 04ed6] | *AppendixA-04ed6.png**Figure 13. SCAP Custom Profile Selections*

For this lab, we will be setting the minimum password length and PAM Password quality settings

5. Search for Password to set **minimum password length** and set the values in **login.defs**. Check **Set Password Minimum Length in login.defs** and click on the **minimum password length** and set the value to **18**

[AppendixA 1ddf2] | *AppendixA-1ddf2.png*

Figure 14. SCAP Custom Profile Password Settings for Login.Defs

6. Set password quality requirements with PAM. Search for the minlen and set it to **18**. Also, place a checkbox in **Set Password Quality Requirements with pam_quality**. Then click "OK"

[AppendixA 09b9f] | AppendixA-09b9f.png

Figure 15. SCAP Custom Profile PAM Quality Requirements

7. At this point, we have taken the default settings from the OSPP profile with only the tailored pieces that we selected. The next step is to click "File ⇒ Save Customization Only" to save the custom content

[AppendixA 756be] | AppendixA-756be.png

Figure 16. SCAP Custom Profile Selected Settings View

[AppendixA 61450] | AppendixA-61450.png

Figure 17. SCAP Custom Profile Creation Saving

[AppendixA 421c2] | AppendixA-421c2.png

Figure 18. SCAP Custom Profile Final View

8. Copy the custom tailoring file to the server(s) being scanned. In this case, we will want to copy the file to **servera**

Listing 36. Copy custom content

```
[root@workstation ~]# scp ssg-rhel8-ds-tailoring.xml root@servera:
ssg-rhel8-ds-tailoring.xml          100% 28KB 10.7MB/s 00:00
[root@workstation ~]#
```

A.2. Running a SCAP Scan with Custom Content

Servers to Configure

- servera

Packages to Install

- openscap-scanner
- scap-security-guide

Step 1 - SSH to serverc

The first step is to connect to the server.

*Example 6. Connecting to the **servera** VM**Listing 37. Connecting to **servera** Using SSH*

```
# ssh root@servera
```

Step 2 - Install packages on servera

The second step is to install software on the server.

*Example 7. Install software on **servera****Listing 38. Installing Software on **servera***

```
[root@servera ~]# yum install scap-security-guide
Last metadata expiration check: 0:47:44 ago on Thu 16 Apr 2020 08:26:15 AM EDT.
Dependencies resolved.
=====
Package           Arch  Version      Repository                               Size
=====
Installing:
scap-security-guide
noarch 0.1.42-11.el8 rhel-8.0-for-x86_64-appstream-rpms 3.4 M
Installing dependencies:
openscap           x86_64 1.3.0-7.el8  rhel-8.0-for-x86_64-appstream-rpms 3.3 M
openscap-scanner   x86_64 1.3.0-7.el8  rhel-8.0-for-x86_64-appstream-rpms 66 k
xml-common         noarch 0.6.3-50.el8 rhel-8.0-for-x86_64-baseos-rpms 39 k

Transaction Summary
=====
Install 4 Packages

Total download size: 6.9 M
Installed size: 132 M
Is this ok [y/N]: y

... output omitted ...

Verifying      : openscap-1.3.0-7.el8.x86_64                1/4
Verifying      : openscap-scanner-1.3.0-7.el8.x86_64       2/4
Verifying      : scap-security-guide-0.1.42-11.el8.noarch   3/4
Verifying      : xml-common-0.6.3-50.el8.noarch             4/4

Installed:
scap-security-guide-0.1.42-11.el8.noarch  openscap-1.3.0-7.el8.x86_64
openscap-scanner-1.3.0-7.el8.x86_64      xml-common-0.6.3-50.el8.noarch

Complete!
```

Learning about SCAP Commands

The SSG man page is a very good source of information for usage of the **oscap** tool as well as provides examples of how to use the SCAP SSG Guide profiles itself.

Listing 39. Looking at **SCAP Security Guide (SSG)** Man Page

```
# man scap-security-guide

scap-security-guide(8)      System Manager's Manual      scap-security-guide(8)

NAME
    SCAP Security Guide - Delivers security guidance, baselines, and associated validation mechanisms utilizing the Security Content Automation Protocol (SCAP).

... output omitted ...

EXAMPLES
    To scan your system utilizing the OpenSCAP utility against the osp-
    rhel7 profile:

    oscap xccdf eval --profile osp-rhel7 --results /tmp/`hostname`-ssg-
    results.xml --report /tmp/`hostname`-ssg-results.html --oval-results
    /usr/share/xml/scap/ssg/content/ssg-rhel7-xccdf.xml
```

Listing 40. Looking at **oscap** Man Page

```
# man oscap

OSCAP(8)      System Administration Utilities      OSCP(8)

NAME
    oscap - OpenSCAP command line tool

SYNOPSIS
    oscap [general-options] module operation [operation-options-and-argu-
    ments]

DESCRIPTION
    oscap is Security Content Automation Protocol (SCAP) toolkit based on
    OpenSCAP library. It provides various functions for different SCAP
    specifications (modules).

    OpenSCAP tool claims to provide capabilities of Authenticated Configu-
    ration Scanner and Authenticated Vulnerability Scanner as defined by
    The National Institute of Standards and Technology.

... output omitted ...

EXAMPLES
    Evaluate XCCDF content using CPE dictionary and produce html report. In
    this case we use United States Government Configuration Baseline
    (USGCB) for Red Hat Enterprise Linux 5 Desktop.

    oscap xccdf eval --fetch-remote-resources --oval-results \
    --profile united_states_government_configuration_baseline \
    --report usgcb-rhel5desktop.report.html \
    --results usgcb-rhel5desktop-xccdf.xml.result.xml \
    --cpe usgcb-rhel5desktop-cpe-dictionary.xml \
    usgcb-rhel5desktop-xccdf.xml
```

Step 3 - Running oscap scan

We will run the **oscap** utility to generate a report and a results file that can be sent back to the **workstation** system so that we can create an Ansible playbook for remediation and view the results of the report.



Be very careful about the name of the profile as this was selected during the creation of the custom profile/tailoring file portion when doing SCAP Workbench customizations.

*Example 8. Scanning **servera***

Listing 41. Using **oscap** and the tailoring profile to scan **servera**

```
# [root@servera ~]# oscap xccdf eval \
--profile xccdf_org.ssgproject.content_profile_osp_customized \
--tailoring-file ssg-rhel8-ds-tailoring.xml \
--results custom_scan_results.xml \
/usr/share/xml/scap/ssg/content/ssg-rhel8-ds.xml

Title    Set Password Minimum Length in login.defs
Rule     xccdf_org.ssgproject.content_rule_accounts_password_minlen_login_defs
Ident    CCE-80652-1
Result   fail

Title    Set Password Strength Minimum Different Characters
Rule     xccdf_org.ssgproject.content_rule_accounts_password_pam_difok
Ident    CCE-80654-7
Result   fail

Title    Set Password Strength Minimum Uppercase Characters
Rule     xccdf_org.ssgproject.content_rule_accounts_password_pam_ucredit
Ident    CCE-80665-3
Result   fail

Title    Set Password Minimum Length
Rule     xccdf_org.ssgproject.content_rule_accounts_password_pam_minlen
Ident    CCE-80656-2
Result   fail

Title    Set Password Retry Prompts Permitted Per-Session
Rule     xccdf_org.ssgproject.content_rule_accounts_password_pam_retry
Ident    CCE-80664-6
Result   fail

Title    Set Password Strength Minimum Different Categories
Rule     xccdf_org.ssgproject.content_rule_accounts_password_pam_minclass
Result   fail

Title    Set Password Maximum Consecutive Repeating Characters
Rule     xccdf_org.ssgproject.content_rule_accounts_password_pam_maxrepeat
Result   fail

Title    Set Password Strength Minimum Special Characters
Rule     xccdf_org.ssgproject.content_rule_accounts_password_pam_ocredit
Ident    CCE-80663-8
Result   fail

Title    Set Password Strength Minimum Lowercase Characters
Rule     xccdf_org.ssgproject.content_rule_accounts_password_pam_lcredit
Ident    CCE-80655-4
Result   fail

Title    Set Password Strength Minimum Digit Characters
Rule     xccdf_org.ssgproject.content_rule_accounts_password_pam_dcredit
Ident    CCE-80653-9
Result   fail

Title    Set Password to Maximum of Consecutive Repeating Characters from Same Character Class
Rule     xccdf_org.ssgproject.content_rule_accounts_password_pam_maxclassrepeat
Result   fail
```



Getting Custom Profile Name from Tailoring File

If you need to locate the profile used for the custom scanning content from the tailoring file, you can search for it with **grep**.

```
[root@servera ~]# grep "Profile id" ssg-rhel8-ds-tailoring.xml
<xccdf:Profile id="xccdf_org.ssgproject.content_profile_ospp_customized" extends
="xccdf_org.ssgproject.content_profile_ospp">
```

Step 4 - Creating a Results Report

You can create a results report file from the results file so you have a nice HTML file that is easy to read with the results from the SCAP scan.

Example 9. Creating a SCAP Report from a Results File

Listing 42. Generating a Report

```
[root@servera ~]# oscap xccdf generate report \
custom_scan_results.xml > Custom_Scan_Report.html
```

Combining Steps 3 & 4

It is possible to perform a custom content scan which will generate the results file and the report for transfer back to the workstation for review.

Need to Specify

- **--results**
- **--report**

Listing 43. Creating a Results File and Report During Custom Content Scan

```
[root@servera ~]# oscap xccdf eval \
--profile xccdf_org.ssgproject.content_profile_ospp_customized \
--tailoring-file ssg-rhel8-ds-tailoring.xml \
--results custom_scan_results_2.xml \
--report Custom_Scan_Report_2.html \
/usr/share/xml/scap/ssg/content/ssg-rhel8-ds.xml

Title Set Password Minimum Length in login.defs
Rule xccdf_org.ssgproject.content_rule_accounts_password_minlen_login_defs
Ident CCE-80652-1
Result fail

Title Set Password Strength Minimum Different Characters
Rule xccdf_org.ssgproject.content_rule_accounts_password_pam_difok
Ident CCE-80654-7
Result fail

Title Set Password Strength Minimum Uppercase Characters
Rule xccdf_org.ssgproject.content_rule_accounts_password_pam_ucredit
Ident CCE-80665-3
Result fail

Title Set Password Minimum Length
Rule xccdf_org.ssgproject.content_rule_accounts_password_pam_minlen
Ident CCE-80656-2
Result fail

Title Set Password Retry Prompts Permitted Per-Session
Rule xccdf_org.ssgproject.content_rule_accounts_password_pam_retry
Ident CCE-80664-6
Result fail

Title Set Password Strength Minimum Different Categories
Rule xccdf_org.ssgproject.content_rule_accounts_password_pam_minclass
Result fail

Title Set Password Maximum Consecutive Repeating Characters
Rule xccdf_org.ssgproject.content_rule_accounts_password_pam_maxrepeat
Result fail

Title Set Password Strength Minimum Special Characters
Rule xccdf_org.ssgproject.content_rule_accounts_password_pam_ocredit
Ident CCE-80663-8
Result fail

Title Set Password Strength Minimum Lowercase Characters
Rule xccdf_org.ssgproject.content_rule_accounts_password_pam_lcredit
Ident CCE-80655-4
Result fail

Title Set Password Strength Minimum Digit Characters
Rule xccdf_org.ssgproject.content_rule_accounts_password_pam_dcredit
Ident CCE-80653-9
Result fail

Title Set Password to Maximum of Consecutive Repeating Characters from Same Character Class
Rule xccdf_org.ssgproject.content_rule_accounts_password_pam_maxclassrepeat
Result fail
```

Step 5 - Transferring Results File and Report to Workstation

After you have the results files and the report, you should transfer it to your graphical workstation (**workstation**) for further analysis.

Example 10. Transferring Results

Listing 44. Transferring the Results and Report Files

```
[root@servera ~]# scp *.xml *.html root@workstation:
The authenticity of host 'workstation (<no hostip for proxy command>)' can't be established.
ECDSA key fingerprint is SHA256:p0Q10JmyF2PFI+jxyFo0SCfi+1oWNsUruy2DZNjg+N0.
Are you sure you want to continue connecting (yes/no)? yes
Warning: Permanently added 'workstation' (ECDSA) to the list of known hosts.
root@workstation's password:
custom_scan_results_2.xml          100% 4086KB  32.4MB/s   00:00
custom_scan_results.xml           100% 4086KB  60.0MB/s   00:00
ssg-rhel8-ds-tailoring.xml        100%   28KB  16.2MB/s   00:00
Custom_Scan_Report_2.html         100%  332KB  44.3MB/s   00:00
Custom_Scan_Report.html           100%  332KB  37.6MB/s   00:00
[root@servera ~]#
```

Step 6 - Viewing the SCAP scan report

After you have transferred the results file to **workstation** you can open the HTML report in a web browser. In this case we will use **firefox** to open the file.

Example 11. Viewing the SCAP Report

Listing 45. Opening the SCAP HTML Report with Firefox

```
[root@workstation ~]# firefox Custom_Scan_Report.html
```

[AppendixA 9416a] | AppendixA-9416a.png

Figure 19. SCAP Scan Results Report in Firefox



Firefox may not open the file based on SELinux context triggers. In order to get around this you can use the command prompt and do **setenforce 0** to allow you to open the report.

A.3. Creating an Ansible Remediation Playbook Based on SCAP Scan Results

The OpenSCAP project and content created by Red Hat can automatically remediate findings from OpenSCAP scans. The findings can be remediated in many ways (**BASH**, **Ansible**, etc.). While things are mostly complete, there are some automated remediations that have not yet been developed.



There are multiple automatic remediation methods developed, but at this time, there isn't a script to fix everything.

Servers to Configure

- servera



We will continue to use **workstation** as our master SCAP system as it should have Ansible and SCAP Workbench installed.

Step 1 - Creating an Ansible Playbook from Results

The first step will be to generate an Ansible playbook from the SCAP scan results for system remediation.

Example 12. Generating Ansible Playbook

Listing 46. Ansible Playbook Generation

```
[root@workstation ~]# oscap xccdf generate fix \
--profile xccdf_org.ssgproject.content_profile_osp_customized \
--tailoring-file ssg-rhel8-ds-tailoring.xml \
--fix-type ansible \
--result-id "" \
custom_scan_results.xml > Custom_Scan_Fix.yml
```

Viewing Remediation Playbook

It is also a good idea to view the created playbook for the system prior to running it.

```
[root@workstation ~]# cat Custom_Scan_Fix.yml
---
#####
#
# Ansible remediation role for the results of evaluation of profile
# xccdf_org.ssgproject.content_profile_osp_customized
# XCCDF Version: unknown
#
# Evaluation Start Time: 2020-04-16T09:21:32
# Evaluation End Time: 2020-04-16T09:21:33
#
# This file was generated by OpenSCAP 1.3.0 using:
# $ oscap xccdf generate fix --result-id xccdf_org.open-
# scap_testresult_xccdf_org.ssgproject.content_profile_osp_customized --template urn:xccdf:fix:script:ansible
# xccdf-results.xml
#
# This script is generated from the results of a profile evaluation.
# It attempts to remediate all issues from the selected rules that failed the test.
#
# How to apply this remediation role:
# $ ansible-playbook -i "localhost," -c local playbook.yml
# $ ansible-playbook -i "192.168.1.155," playbook.yml
# $ ansible-playbook -i inventory.ini playbook.yml
#
#####

- hosts: all
  vars:
    var_accounts_password_minlen_login_defs: !!str 18
    var_password_pam_difok: !!str 8
    var_password_pam_ucredit: !!str -1
    var_password_pam_minlen: !!str 18
```




```

var_password_pam_retry: !!str 3
var_password_pam_minclass: !!str 3
var_password_pam_maxrepeat: !!str 3
var_password_pam_ocredit: !!str -1
var_password_pam_lcredit: !!str -1
var_password_pam_dcredit: !!str -1
var_password_pam_maxclassrepeat: !!str 4
tasks:

- name: "Set Password Minimum Length in login.defs"
  lineinfile:
    dest: /etc/login.defs
    regexp: "^PASS_MIN_LEN *[0-9]*"
    state: present
    line: "PASS_MIN_LEN      {{ var_accounts_password_minlen_login_defs }}"
  tags:
    - accounts_password_minlen_login_defs
    - medium_severity
    - restrict_strategy
    - low_complexity
    - low_disruption
    - CCE-80652-1
    - NIST-800-53-IA-5(f)
    - NIST-800-53-IA-5(1)(a)
    - NIST-800-171-3.5.7
    - CJIS-5.6.2.1

... Output Omitted ...

- name: Ensure PAM variable maxclassrepeat is set accordingly

  lineinfile:
    create: yes
    dest: "/etc/security/pwquality.conf"
    regexp: '^#\s*maxclassrepeat'
    line: "maxclassrepeat = {{ var_password_pam_maxclassrepeat }}"

  tags:
    - accounts_password_pam_maxclassrepeat
    - medium_severity
    - restrict_strategy
    - low_complexity
    - low_disruption
    - NIST-800-53-IA-5
    - NIST-800-53-IA-5(c)

```

Ansible is not setup for the lab

Before we can do the next steps, we will download an Ansible config file and an inventory file so we can properly run the playbook.

Listing 47. Error Output Message

```
[root@workstation ~]# ansible-playbook Custom_Scan_Fix.yml
[WARNING]: provided hosts list is empty, only localhost is available. Note
that the implicit localhost does not match 'all'

PLAY [all] *****
skipping: no hosts matched

PLAY RECAP *****
[root@workstation ~]#
```

Step 2 - Downloading Ansible Config and Ansible Inventory Files

This step is needed so that our Ansible system can be configured with various configuration options and the inventory files so we can run the given playbook.

*Example 13. Downloading Ansible Files**Listing 48. Downloading Ansible Files*

```
[root@workstation ~]# wget http://people.redhat.com/~tmichett/rh354/inventory
--2020-04-16 09:38:50-- http://people.redhat.com/~tmichett/rh354/inventory
Resolving people.redhat.com (people.redhat.com)... 209.132.183.19
Connecting to people.redhat.com (people.redhat.com)|209.132.183.19|:80... connected.
HTTP request sent, awaiting response... 200 OK
Length: 24
Saving to: 'inventory'

inventory      100%[=====>]      24  --.-KB/s   in 0s

2020-04-16 09:38:50 (2.69 MB/s) - 'inventory' saved [24/24]

[root@workstation ~]# wget http://people.redhat.com/~tmichett/rh354/ansible.cfg
--2020-04-16 09:39:34-- http://people.redhat.com/~tmichett/rh354/ansible.cfg
Resolving people.redhat.com (people.redhat.com)... 209.132.183.19
Connecting to people.redhat.com (people.redhat.com)|209.132.183.19|:80... connected.
HTTP request sent, awaiting response... 200 OK
Length: 159
Saving to: 'ansible.cfg'

ansible.cfg    100%[=====>]    159  --.-KB/s   in 0s

2020-04-16 09:39:35 (13.8 MB/s) - 'ansible.cfg' saved [159/159]
```

Reviewing Ansible Configurations

The **inventory** file provided only has a single host **servera** in there. On real systems, you must be very cautious of running remediation playbooks against an inventory file as it could apply to unintended systems. Additionally the **ansible.cfg** file provided was created for use in this lab environment. Both of these items should be taken into account when doing going through the process on production systems.



```
[root@workstation ~]# cat inventory
servera.lab.example.com

[root@workstation ~]# cat ansible.cfg
[defaults]
roles_path = /etc/ansible/roles:/usr/share/ansible/roles
log_path   = /tmp/ansible.log
inventory  = ./inventory

[privilege_escalation]
become=True
[root@workstation ~]#
```

Step 3 - Run the Ansible Playbook

This step will utilize the **workstation** system which is configured as your Ansible management node and will run the playbook to remediate the results on the **servera** system.

Example 14. Remediation of **serverc** with Ansible Playbook

Listing 49. Running the Ansible Playbook

```
[root@workstation ~]# ansible-playbook Custom_Scan_Fix.yml

PLAY [all] *****

TASK [Gathering Facts] *****
ok: [servera.lab.example.com]

TASK [Set Password Minimum Length in login.defs] *****
changed: [servera.lab.example.com]

TASK [Ensure PAM variable difok is set accordingly] *****
changed: [servera.lab.example.com]

TASK [Ensure PAM variable ucredit is set accordingly] *****
changed: [servera.lab.example.com]

TASK [Ensure PAM variable minlen is set accordingly] *****
changed: [servera.lab.example.com]

TASK [Set Password Retry Prompts Permitted Per-Session - system-auth (change)] ***
ok: [servera.lab.example.com]

TASK [Set Password Retry Prompts Permitted Per-Session - system-auth (add)] ****
changed: [servera.lab.example.com]

TASK [Ensure PAM variable minclass is set accordingly] *****
changed: [servera.lab.example.com]

TASK [Ensure PAM variable maxrepeat is set accordingly] *****
changed: [servera.lab.example.com]

TASK [Ensure PAM variable ocredit is set accordingly] *****
changed: [servera.lab.example.com]

TASK [Ensure PAM variable lcredit is set accordingly] *****
changed: [servera.lab.example.com]

TASK [Ensure PAM variable dcredit is set accordingly] *****
changed: [servera.lab.example.com]

TASK [Ensure PAM variable maxclassrepeat is set accordingly] *****
changed: [servera.lab.example.com]

PLAY RECAP *****
servera.lab.example.com : ok=13  changed=11  unreachable=0  failed=0  skipped=0  rescued=0  ignored=0
```



After running the playbook, you can see that there were 10 changes that were made to the system and exactly which parameters were changed. The next thing to do is perform another scan of the system to ensure that it is now fully compliant.

Step 4 - Rescan System and Review Results

*Example 15. Scanning System after Fixes and Verifying Results**Listing 50. Performing SCAP Verification Scan*

```
[root@servera ~]# oscap xccdf eval \
--profile xccdf_org.ssgproject.content_profile_ospp_customized \
--tailoring-file ssg-rhel8-ds-tailoring.xml \
--results custom_scan_results_fixed.xml \
--report Custom_Scan_Report_Fixed.html \
/usr/share/xml/scap/ssg/content/ssg-rhel8-ds.xml
```

Listing 51. Copying Results to Workstation

```
[root@servera ~]# scp custom_scan_results_fixed.xml Custom_Scan_Report_Fixed.html workstation:
root@workstation's password:
custom_scan_results_fixed.xml          100% 4086KB 60.3MB/s 00:00
Custom_Scan_Report_Fixed.html         100% 282KB 48.4MB/s 00:00
```

Listing 52. Viewing Results on Workstation

```
[root@workstation ~]# firefox Custom_Scan_Report_Fixed.html
```

[AppendixA 1bfad] | AppendixA-1bfad.png

Figure 20. Fixed SCAP Scan Results Report in Firefox