



It remains to check whether there exist points $p_1 \in S_1$ and $p_2 \in S_2$ such that the distance between them is smaller than d . We cannot afford to check all possible such pairs since there are $\frac{n}{2} \cdot \frac{n}{2} = \Theta(n^2)$ of them. To check this faster, we first discard all points from S_1 and S_2 whose x -distance to the middle line is greater than d . That is, we focus on the following strip:



Stop and think: Why can we narrow the search to this strip? Now, let's sort the points of the strip by their y -coordinates and denote the resulting sorted list by $P = [p_1, \dots, p_k]$. It turns out that if $|i - j| > 7$, then the distance between points p_i and p_j is greater than d for sure. This follows from the Exercise Break below.

Exercise break: Partition the strip into $d \times d$ squares as shown below and show that each such square contains at most four input points.



This results in the following algorithm. We first sort the given n points by their x -coordinates and then split the resulting sorted list into two halves S_1 and S_2 of size $\frac{n}{2}$. By making a recursive call for each of the sets S_1 and S_2 , we find the minimum distances d_1 and d_2 in them. Let $d = \min\{d_1, d_2\}$. However, we are not done yet as we also need to find the minimum distance between points from different sets (i.e., a point from S_1 and a point from S_2) and check whether it is smaller than d . To perform such a check, we filter the initial point set and keep only those points whose x -distance to the middle line does not exceed d . Afterwards, we sort the set of points in the resulting strip by their y -coordinates and scan the resulting list of points. For each point, we compute its distance to the seven subsequent points in this list and compute d' , the minimum distance that we encountered during this scan. Afterwards, we return $\min\{d, d'\}$.

The running time of the algorithm satisfies the recurrence relation

$$T(n) = 2 \cdot T\left(\frac{n}{2}\right) + O(n \log n).$$

The $O(n \log n)$ term comes from sorting the points in the strip by their y -coordinates at every iteration.

Exercise break: Prove that $T(n) = O(n \log^2 n)$ by analyzing the recursion tree of the algorithm.

Exercise break: Show how to bring the running time down to $O(n \log n)$ by avoiding sorting at each recursive call.

Need Help?

Ask a question or see the questions asked by other learners at [this forum thread](#).