

# CampusEats Database Schema — Service Boundaries

## IDENTITY SERVICE

### students

PK student\_id  
email  
name  
phone  
status  
created\_at

### vendor\_accounts

PK vendor\_id  
name  
email  
status  
created\_at

## CATALOGUE SERVICE

### vendors

PK vendor\_id  
name  
location  
status

### menu\_items

PK item\_id  
vendor\_id FK  
name  
category  
price  
available

## ORDER SERVICE

### carts

PK cart\_id  
student\_id (opaque)  
status  
updated\_at

### orders

PK order\_id  
student\_id (opaque)  
total\_amount  
status  
created\_at

### order\_items

PK order\_item\_id  
order\_id FK  
item\_id (opaque)  
quantity  
unit\_price

## PAYMENT SERVICE

### payments

PK payment\_id  
order\_id (opaque)  
student\_id (opaque)  
amount  
status  
provider\_ref

### payment\_attempts

PK attempt\_id  
payment\_id FK  
amount  
status  
attempted\_at

## NOTIFICATION SERVICE

### notifications

PK notification\_id  
student\_id (opaque)  
order\_id (opaque)  
event • message • status • created\_at

Opaque cross-service IDs are intentionally not foreign keys. Foreign keys exist only inside a service boundary.